

Code Listing

1 Code examples

```
1 import numpy as np
2
3 def incmatrix(genl1,genl2):
4     m = len(genl1)
5     n = len(genl2)
6     M = None #to become the incidence matrix
7     VT = np.zeros((n*m,1), int) #dummy variable
8
9     #compute the bitwise xor matrix
10    M1 = bitxormatrix(genl1)
11    M2 = np.triu(bitxormatrix(genl2),1)
12
13    for i in range(m-1):
14        for j in range(i+1, m):
15            [r,c] = np.where(M2 == M1[i,j])
16            for k in range(len(r)):
17                VT[(i)*n + r[k]] = 1;
18                VT[(i)*n + c[k]] = 1;
19                VT[(j)*n + r[k]] = 1;
20                VT[(j)*n + c[k]] = 1;
21
22            if M is None:
23                M = np.copy(VT)
24            else:
25                M = np.concatenate((M, VT), 1)
26
27            VT = np.zeros((n*m,1), int)
28
29    return M
```

Listing 1: Python example

The next code will be directly imported from a file:

```
1 function X = BitXorMatrix(A,B)
2 %function to compute the sum without charge of two vectors
3
4 %convert elements into unsigned integers
5 A = uint8(A);
6 B = uint8(B);
7
8 m1 = length(A);
9 m2 = length(B);
10 X = uint8(zeros(m1, m2));
11 for n1=1:m1
12     for n2=1:m2
13         X(n1, n2) = bitxor(A(n1), B(n2));
14     end
15 end
```

Listing 2: Octave sample code

Listings

1	Python example	1
2	Octave sample code	2