

## **FCAI ANU Materials – Semi Seniors – Computer Graphics – Lecture 1**

### **Batch 1 – Questions 1 to 30**

Q1. Which of the following is enough on its own to create the appearance of three dimensions on a 2D screen?

- a) Color
- b) Perspective
- c) Texture mapping
- d) Fog

Answer: b) Perspective

---

Q2. Hiding the back sides of solid geometry mainly helps in:

- a) Saving memory
- b) Enhancing the 3D illusion
- c) Avoiding transparency issues
- d) Increasing color realism

Answer: b) Enhancing the 3D illusion

---

Q3. Adding different colors to objects increases:

- a) Realism
- b) Processing time
- c) The illusion of three dimensions
- d) Anti-aliasing

Answer: c) The illusion of three dimensions

---

Q4. Proper shading creates the illusion of:

- a) Motion
- b) Illumination
- c) Depth buffer
- d) Antialiasing

Answer: b) Illumination

---

Q5. Which effect provides a convincing illusion for wide-open spaces?

- a) Antialiasing
- b) Fog
- c) Shading
- d) Blending

Answer: b) Fog

---

Q6. Blending in 3D graphics is commonly used to achieve:

- a) Polygon filling
- b) Reflection effects
- c) Hidden surface removal
- d) Line stippling

Answer: b) Reflection effects

---

Q7. Antialiasing is mainly used to:

- a) Add shadows
- b) Remove background noise
- c) Smooth jagged edges

d) Improve texture mapping

Answer: c) Smooth jagged edges

---

Q8. Which of the following is NOT a common real-time 3D application?

a) Flight simulator

b) CAD

c) Medical imaging

d) Movie rendering like *Shrek*

Answer: d) Movie rendering like *Shrek*

---

Q9. Non-real-time 3D rendering is typically used for:

a) Games

b) Scientific visualization

c) Movies

d) Flight simulators

Answer: c) Movies

---

Q10. Rendering a single high-quality movie frame may take:

a) Seconds

b) Minutes

c) Hours

d) Days

Answer: c) Hours

---

Q11. What does GPU stand for?

- a) General Processing Unit
- b) Graphics Processing Unit
- c) Graphic Program Utility
- d) General Pixel Utility

Answer: b) Graphics Processing Unit

---

Q12. Shaders allow for:

- a) Slower rendering
- b) Hardware-only lighting
- c) Real-time realism
- d) Only color adjustment

Answer: c) Real-time realism

---

Q13. OpenGL is best described as:

- a) A programming language
- b) A software interface to graphics hardware
- c) A Windows-only API
- d) A 3D rendering engine

Answer: b) A software interface to graphics hardware

---

Q14. OpenGL is designed as:

- a) Hardware-dependent
- b) Hardware-independent
- c) CPU-based only

d) DirectX-based

Answer: b) Hardware-independent

---

Q15. Which of the following is NOT true about OpenGL?

a) It is not a programming language like C++

b) It provides high-level commands for complex shapes

c) Models must be built from primitives like points, lines, and polygons

d) It works across platforms

Answer: b) It provides high-level commands for complex shapes

---

Q16. OpenGL commands usually start with:

a) op

b) gl

c) ogl

d) gx

Answer: b) gl

---

Q17. Which of the following OpenGL auxiliary libraries was the first to exist?

a) freeglut

b) GLUT

c) AUX

d) GLU

Answer: c) AUX

---

Q18. AUX was later replaced by:

- a) GLX
- b) GLUT
- c) Direct3D
- d) OpenGL ES

Answer: b) GLUT

---

Q19. GLUT stands for:

- a) General Light Utility Toolkit
- b) Graphics Layer Unified Tool
- c) OpenGL Utility Toolkit
- d) General Library for Utility Textures

Answer: c) OpenGL Utility Toolkit

---

Q20. Which operating system discontinued GLUT development?

- a) Linux
- b) Windows
- c) MacOS
- d) Solaris

Answer: b) Windows

---

Q21. The modern replacement for GLUT is:

- a) Freeglut
- b) GLU
- c) DirectX

d) AUX2

Answer: a) Freeglut

---

Q22. OpenGL does not directly handle:

- a) Keyboard input
- b) Mouse input
- c) Window management
- d) All of the above

Answer: d) All of the above

---

Q23. Which company originally created OpenGL?

- a) Microsoft
- b) Apple
- c) Silicon Graphics (SGI)
- d) Intel

Answer: c) Silicon Graphics (SGI)

---

Q24. OpenGL's cross-platform mobile subset is called:

- a) OpenGL Mini
- b) OpenGL ES
- c) OpenGL Lite
- d) OpenGL Mobile

Answer: b) OpenGL ES

---

Q25. A hardware OpenGL implementation is often referred to as:

- a) Native implementation
- b) Accelerated implementation
- c) Compact implementation
- d) Local implementation

Answer: b) Accelerated implementation

---

Q26. Which function is used in OpenGL to clear the screen?

- a) glClearWindow()
- b) glClear()
- c) glReset()
- d) glWipe()

Answer: b) glClear()

---

Q27. Which buffer is cleared using GL\_COLOR\_BUFFER\_BIT?

- a) Color buffer
- b) Depth buffer
- c) Stencil buffer
- d) Texture buffer

Answer: a) Color buffer

---

Q28. Which OpenGL command sets the window clearing color?

- a) glSetClear()
- b) glClearColor()
- c) glColorBuffer()

d) glResetColor()

Answer: b) glClearColor()

---

Q29. The glFlush() command is used to:

- a) Stop OpenGL execution
- b) Clear the screen
- c) Force all issued commands to execute
- d) Reset color settings

Answer: c) Force all issued commands to execute

---

Q30. The GLUT function glutMainLoop() is used to:

- a) Initialize OpenGL
- b) Enter the event processing loop
- c) Exit the program
- d) Set the window size

Answer: b) Enter the event processing loop

---

## Batch 2 – Questions 31 to 60

Q31. In OpenGL, the suffix f in a function name usually indicates:

- a) Boolean data type
- b) Integer data type
- c) Float data type
- d) Double data type

Answer: c) Float data type

---

Q32. Which suffix corresponds to a 64-bit floating-point in OpenGL?

- a) f
- b) d
- c) i
- d) s

Answer: b) d

---

Q33. The suffix i in OpenGL corresponds to which data type?

- a) 8-bit integer
- b) 16-bit integer
- c) 32-bit integer
- d) Boolean

Answer: c) 32-bit integer

---

Q34. The command `glVertex2i(1, 3);` is equivalent to:

- a) `glVertex2f(1, 3)`
- b) `glVertex2f(1.0, 3.0)`
- c) `glVertex2d(1, 3)`
- d) `glVertex2s(1, 3)`

Answer: b) `glVertex2f(1.0, 3.0)`

---

Q35. Which OpenGL function sets the viewport size?

- a) `glSetViewport()`
- b) `glViewport()`
- c) `glWindowSize()`

d) glOrtho()

Answer: b) glViewport()

---

Q36. The purpose of redefining the clipping volume in ChangeSize is to:

- a) Adjust window color
- b) Keep the aspect ratio consistent
- c) Enable depth testing
- d) Reduce CPU usage

Answer: b) Keep the aspect ratio consistent

---

Q37. Which function defines the clipping volume in OpenGL?

- a) glClearDepth()
- b) glViewport()
- c) glOrtho()
- d) glPolygonMode()

Answer: c) glOrtho()

---

Q38. In glOrtho(left, right, bottom, top, near, far), the near and far parameters control:

- a) Lighting
- b) The z-axis range
- c) The background color
- d) The polygon fill mode

Answer: b) The z-axis range

---

Q39. If a viewport is rectangular but mapped to a square clipping volume, the image appears:

- a) Enlarged
- b) Distorted
- c) Antialiased
- d) Transparent

Answer: b) Distorted

---

Q40. In the bouncing square example, what is used to reverse direction when reaching an edge?

- a) glClear()
- b) Changing step sign (xstep/ystep)
- c) glOrtho()
- d) glEnable()

Answer: b) Changing step sign (xstep/ystep)

---

Q41. Which GLUT function is used to register a timer callback?

- a) glutIdleFunc()
- b) glutTimerFunc()
- c) glutReshapeFunc()
- d) glutPostRedisplay()

Answer: b) glutTimerFunc()

---

Q42. The parameter msec in glutTimerFunc specifies:

- a) Seconds
- b) Milliseconds

- c) Nanoseconds
  - d) Frames per second
- Answer: b) Milliseconds
- 

Q43. In the timer callback, the function prototype must be:

- a) void TimerFunction();
- b) void TimerFunction(int value);
- c) void TimerFunc(float value);
- d) void TimerFunc();

Answer: b) void TimerFunction(int value);

---

Q44. In OpenGL, the command glutPostRedisplay() is used to:

- a) Force the scene to redraw
- b) Initialize the main loop
- c) Clear the screen
- d) Resize the viewport

Answer: a) Force the scene to redraw

---

Q45. Which display mode flag enables double buffering in GLUT?

- a) GLUT\_SINGLE
- b) GLUT\_DOUBLE
- c) GLUT\_RGBA
- d) GLUT\_DEPTH

Answer: b) GLUT\_DOUBLE

---

Q46. In the bouncing square program, double buffering is needed because:

- a) It improves performance
- b) It avoids flickering
- c) It supports transparency
- d) It reduces memory usage

Answer: b) It avoids flickering

---

Q47. OpenGL is described as a:

- a) Shader compiler
- b) State machine
- c) Rendering engine
- d) Scene graph library

Answer: b) State machine

---

Q48. In OpenGL, the current drawing color is an example of a:

- a) State variable
- b) Function
- c) Shader program
- d) Texture coordinate

Answer: a) State variable

---

Q49. To enable a mode in OpenGL, which function is used?

- a) glEnable()
- b) glActivate()
- c) glSetMode()

d) glRunMode()

Answer: a) glEnable()

---

Q50. Which command disables a specific OpenGL mode?

a) glModeOff()

b) glDisable()

c) glExitMode()

d) glResetMode()

Answer: b) glDisable()

---

Q51. To query the value of an OpenGL float state variable, you use:

a) glGetFloatv()

b) glGetIntegerv()

c) glGetBooleanv()

d) glGetDoublev()

Answer: a) glGetFloatv()

---

Q52. The command glPushAttrib(GL\_TEXTURE\_BIT | GL\_LIGHTING\_BIT) is used to:

a) Enable texture and lighting

b) Save texture and lighting states

c) Reset all attributes

d) Clear the depth buffer

Answer: b) Save texture and lighting states

---

Q53. Which function restores previously saved OpenGL attributes?

- a) glRestore()
- b) glPopAttrib()
- c) glEnable()
- d) glPopState()

Answer: b) glPopAttrib()

---

Q54. The command glColor3f(1.0, 0.0, 0.0) sets the current color to:

- a) Green
- b) Blue
- c) Red
- d) White

Answer: c) Red

---

Q55. The command glColor3f(0.0, 0.0, 0.0) sets the current color to:

- a) White
- b) Black
- c) Cyan
- d) Magenta

Answer: b) Black

---

Q56. If you call glColor3f(0.0, 1.0, 0.0), the color is:

- a) Red
- b) Blue
- c) Green

d) Yellow

Answer: c) Green

---

Q57. The color cyan is represented in OpenGL by:

a) (0.0, 1.0, 0.0)

b) (1.0, 0.0, 1.0)

c) (0.0, 1.0, 1.0)

d) (1.0, 1.0, 0.0)

Answer: c) (0.0, 1.0, 1.0)

---

Q58. The process of ensuring only visible surfaces are drawn is called:

a) Antialiasing

b) Hidden-surface removal

c) Fogging

d) Culling

Answer: b) Hidden-surface removal

---

Q59. OpenGL uses which algorithm for hidden-surface removal?

a) Painter's algorithm

b) Z-buffer algorithm

c) Scanline algorithm

d) Ray tracing

Answer: b) Z-buffer algorithm

---

Q60. In z-buffering, the z-buffer stores:

- a) Colors of each pixel
- b) Depth values of each pixel
- c) Lighting coefficients
- d) Texture coordinates

Answer: b) Depth values of each pixel

---

### Batch 3 – Questions 61 to 90

Q61. The z-buffer algorithm is also known as:

- a) Depth-buffering
- b) Scanline algorithm
- c) Ray tracing
- d) Back-face culling

Answer: a) Depth-buffering

---

Q62. In z-buffering, if a new pixel is closer than the stored value, it:

- a) Is ignored
- b) Replaces the buffered value
- c) Causes an error
- d) Makes the frame flicker

Answer: b) Replaces the buffered value

---

Q63. Which GLUT flag should be set to enable depth buffering?

- a) GLUT\_RGBA
- b) GLUT\_DEPTH
- c) GLUT\_SINGLE

d) GLUT\_ALPHA

Answer: b) GLUT\_DEPTH

---

Q64. The OpenGL command to enable depth testing is:

a) glEnable(GL\_DEPTH\_TEST)

b) glDepthBufferOn()

c) glInitDepth()

d) glCheckDepth()

Answer: a) glEnable(GL\_DEPTH\_TEST)

---

Q65. Which OpenGL error occurs if the enum argument is out of range?

a) GL\_INVALID\_VALUE

b) GL\_INVALID\_ENUM

c) GL\_STACK\_OVERFLOW

d) GL\_OUT\_OF\_MEMORY

Answer: b) GL\_INVALID\_ENUM

---

Q66. The OpenGL error GL\_STACK\_UNDERFLOW occurs when:

a) The color stack is full

b) A stack is popped when empty

c) The memory is low

d) An enum is out of range

Answer: b) A stack is popped when empty

---

Q67. Which error code indicates insufficient memory?

- a) GL\_OUT\_OF\_MEMORY
- b) GL\_NO\_ERROR
- c) GL\_INVALID\_OPERATION
- d) GL\_STACK\_OVERFLOW

Answer: a) GL\_OUT\_OF\_MEMORY

---

Q68. Which function retrieves the latest error in OpenGL?

- a) glError()
- b) glCheckError()
- c) glGetError()
- d) gluError()

Answer: c) glGetError()

---

Q69. To get a human-readable string for an OpenGL error, use:

- a) glErrorString()
- b) gluErrorString()
- c) glGetErrorText()
- d) glMessageError()

Answer: b) gluErrorString()

---

Q70. In OpenGL, geometric shapes are built using:

- a) High-level primitives
- b) Points, lines, and polygons
- c) Meshes only

d) Texture maps

Answer: b) Points, lines, and polygons

---

Q71. To start drawing a primitive, the OpenGL command is:

a) glBegin()

b) glDraw()

c) glPrimitive()

d) glInitShape()

Answer: a) glBegin()

---

Q72. To end the definition of a primitive, use:

a) glStop()

b) glEnd()

c) glFlush()

d) glCloseShape()

Answer: b) glEnd()

---

Q73. The primitive GL\_POINTS is used to:

a) Draw filled polygons

b) Draw vertices as points

c) Draw connected lines

d) Draw triangle strips

Answer: b) Draw vertices as points

---

Q74. The function `glPointSize(size)` sets:

- a) Point size in world units
- b) Point size in pixels
- c) Point size in depth values
- d) Point color intensity

Answer: b) Point size in pixels

---

Q75. By default, points drawn in OpenGL are:

- a) Round
- b) Rectangular
- c) Square pixels
- d) Depth-scaled

Answer: c) Square pixels

---

Q76. To set line width, which command is used?

- a) `glSetLineWidth()`
- b) `glLineSize()`
- c) `glLineWidth()`
- d) `glStrokeWidth()`

Answer: c) `glLineWidth()`

---

Q77. The Microsoft OpenGL implementation allows line widths from:

- a) 0.1 to 5.0
- b) 0.5 to 10.0
- c) 1.0 to 20.0

d) 2.0 to 15.0

Answer: b) 0.5 to 10.0

---

Q78. The function to enable line stippling is:

a) glEnable(GL\_LINE\_STIPPLE)

b) glLineStyle()

c) glEnableLinePattern()

d) glPatternOn()

Answer: a) glEnable(GL\_LINE\_STIPPLE)

---

Q79. The function glLineStipple(factor, pattern) uses:

a) A 32-bit color value

b) A 16-bit pattern of 0s and 1s

c) A float range

d) A boolean argument

Answer: b) A 16-bit pattern of 0s and 1s

---

Q80. In line stippling, a bit 1 means:

a) Skip pixel

b) Draw pixel

c) Draw twice

d) Erase pixel

Answer: b) Draw pixel

---

Q81. Which primitive is used to draw connected lines?

- a) GL\_LINE\_LOOP
- b) GL\_LINE\_STRIP
- c) GL\_LINES
- d) GL\_POINTS

Answer: b) GL\_LINE\_STRIP

---

Q82. Which primitive closes the loop by connecting the last vertex to the first?

- a) GL\_LINE\_STRIP
- b) GL\_LINE\_LOOP
- c) GL\_POLYGON
- d) GL\_TRIANGLES

Answer: b) GL\_LINE\_LOOP

---

Q83. Which OpenGL primitive is preferred for hardware acceleration?

- a) Quads
- b) Polygons
- c) Triangles
- d) Points

Answer: c) Triangles

---

Q84. By default, OpenGL considers which winding order as front-facing?

- a) Clockwise (CW)
- b) Counterclockwise (CCW)
- c) Both CW and CCW

d) Random

Answer: b) Counterclockwise (CCW)

---

Q85. To change front-facing winding to clockwise, call:

a) `glFrontFace(GL_CCW)`

b) `glFrontFace(GL_CW)`

c) `glEnable(GL_CULL_FACE)`

d) `glPolygonMode(GL_CW)`

Answer: b) `glFrontFace(GL_CW)`

---

Q86. Which primitive type draws a connected strip of triangles?

a) `GL_TRIANGLES`

b) `GL_TRIANGLE_STRIP`

c) `GL_TRIANGLE_FAN`

d) `GL_POLYGON`

Answer: b) `GL_TRIANGLE_STRIP`

---

Q87. Which primitive type draws triangles radiating out from a central point?

a) `GL_TRIANGLE_STRIP`

b) `GL_TRIANGLE_FAN`

c) `GL_TRIANGLES`

d) `GL_QUADS`

Answer: b) `GL_TRIANGLE_FAN`

---

Q88. Which OpenGL primitive draws a four-sided polygon?

- a) GL\_QUADS
- b) GL\_QUAD\_STRIP
- c) GL\_POLYGON
- d) GL\_RECT

Answer: a) GL\_QUADS

---

Q89. When using GL\_QUADS, what must be true about the four vertices?

- a) They must be convex
- b) They must be planar
- c) They must be normalized
- d) They must be clockwise

Answer: b) They must be planar

---

Q90. A GL\_QUAD\_STRIP requires how many vertices for the first quad?

- a) 2
- b) 3
- c) 4
- d) 5

Answer: c) 4

---

Batch 4 – Questions 91 to 120

Q91. Polygon stippling uses which size bitmap for its pattern?

- a) 16×16
- b) 32×32
- c) 64×64

d) 8×8

Answer: b) 32×32

---

Q92. To enable polygon stippling in OpenGL, use:

a) glEnable(GL\_LINE\_STIPPLE)

b) glEnable(GL\_POLYGON\_STIPPLE)

c) glEnable(GL\_TEXTURE)

d) glEnable(GL\_FILL\_PATTERN)

Answer: b) glEnable(GL\_POLYGON\_STIPPLE)

---

Q93. A polygon is valid in OpenGL only if:

a) Its vertices are round numbers

b) It is convex and planar

c) It is colored

d) It is stippled

Answer: b) It is convex and planar

---

Q94. If a polygon's edges intersect, the polygon is considered:

a) Convex

b) Concave

c) Invalid

d) Hidden

Answer: c) Invalid

---

Q95. OpenGL can directly draw only:

- a) Concave polygons
- b) Convex polygons
- c) Arbitrary polygons
- d) High-level meshes

Answer: b) Convex polygons

---

Q96. By default, polygons are drawn in OpenGL as:

- a) Wireframe
- b) Points
- c) Filled solids
- d) Transparent

Answer: c) Filled solids

---

Q97. The command `glPolygonMode(GL_BACK, GL_LINE)` makes the back faces appear as:

- a) Filled polygons
- b) Outlined polygons
- c) Transparent
- d) Points

Answer: b) Outlined polygons

---

Q98. The function to discard back-facing polygons is:

- a) `glCullFace()`
- b) `glBackFace()`
- c) `glDiscardFace()`

d) glHiddenFace()

Answer: a) glCullFace()

---

Q99. To enable polygon culling, you must also call:

a) glEnable(GL\_CULL\_FACE)

b) glCullOn()

c) glPolygonMode(GL\_CULL)

d) glEnable(GL\_HIDDEN\_SURFACE)

Answer: a) glEnable(GL\_CULL\_FACE)

---

Q100. By default, OpenGL assumes front-facing polygons are:

a) CW

b) CCW

c) Random

d) Both

Answer: b) CCW

---

Q101. Which command manually controls boundary edges?

a) glPolygonMode()

b) glEdgeFlag()

c) glCullFace()

d) glLineStipple()

Answer: b) glEdgeFlag()

---

Q102. The main purpose of normal vectors in OpenGL is:

- a) Hidden-surface removal
- b) Texture mapping
- c) Lighting calculations
- d) Antialiasing

Answer: c) Lighting calculations

---

Q103. For a polygon, the normal vector can be computed using:

- a) Addition of vertices
- b) Cross product of edges
- c) Dot product of vertices
- d) Average of coordinates

Answer: b) Cross product of edges

---

Q104. If four polygons meet at a point P, the normal for P is usually:

- a) Chosen randomly
- b) The longest normal vector
- c) The average of the four normals
- d) The shortest normal vector

Answer: c) The average of the four normals

---

Q105. The gradient of an implicit surface equation  $F(x,y,z)=0$  gives:

- a) Tangent vector
- b) Normal vector
- c) Vertex coordinates

d) Light direction

Answer: b) Normal vector

---

Q106. The unit normal vector is obtained by:

a) Taking the dot product

b) Normalizing the vector

c) Adding vectors

d) Multiplying by z-buffer

Answer: b) Normalizing the vector

---

Q107. An icosahedron is often used as:

a) A cube substitute

b) An approximation of a sphere

c) A tetrahedron replacement

d) A pyramid model

Answer: b) An approximation of a sphere

---

Q108. The OpenGL primitive used for constructing the icosahedron faces is:

a) GL\_QUADS

b) GL\_TRIANGLES

c) GL\_POLYGON

d) GL\_LINES

Answer: b) GL\_TRIANGLES

---

Q109. When drawing an icosahedron, adding different colors to each face helps to:

- a) Reduce z-buffer usage
- b) Show its 3D quality
- c) Eliminate culling
- d) Smooth edges

Answer: b) Show its 3D quality

---

Q110. Normal vectors for an icosahedron can be calculated using:

- a) Vector addition
- b) Normalized cross product
- c) Scalar multiplication
- d) Dot product

Answer: b) Normalized cross product

---

Q111. The OpenGL command `glNormal3fv()` is used to:

- a) Define texture coordinates
- b) Specify normal vectors
- c) Query state variables
- d) Initialize lighting

Answer: b) Specify normal vectors

---

Q112. In the cube rotation program, which function rotates the cube?

- a) `glTranslatef()`
- b) `glRotatef()`
- c) `glScalef()`

d) glColor3f()

Answer: b) glRotatef()

---

Q113. Which GLUT function handles mouse input in the cube program?

a) glutMouseFunc()

b) glutKeyboardFunc()

c) glutMotionFunc()

d) glutPassiveMouseFunc()

Answer: a) glutMouseFunc()

---

Q114. In the cube program, which key exits the program?

a) W

b) Q

c) E

d) ESC

Answer: b) Q

---

Q115. The cube program uses which projection function to define a 3D box space?

a) glFrustum()

b) glPerspective()

c) glOrtho()

d) gluLookAt()

Answer: c) glOrtho()

---

Q116. Which OpenGL function swaps the front and back buffers?

- a) glFlush()
- b) glutSwapBuffers()
- c) glBufferSwap()
- d) glClearBuffer()

Answer: b) glutSwapBuffers()

---

Q117. Which OpenGL matrix mode is used for setting projection transformations?

- a) GL\_MODELVIEW
- b) GL\_TEXTURE
- c) GL\_PROJECTION
- d) GL\_VIEWPORT

Answer: c) GL\_PROJECTION

---

Q118. Which OpenGL matrix mode is typically used for camera transformations?

- a) GL\_MODELVIEW
- b) GL\_TEXTURE
- c) GL\_PROJECTION
- d) GL\_NORMALS

Answer: a) GL\_MODELVIEW

---

Q119. In the cube program, rotating with the left mouse button does what?

- a) Rotates cube clockwise

- b) Rotates cube counterclockwise
- c) Stops rotation
- d) Resets view

Answer: a) Rotates cube clockwise

---

Q120. The `glClearColor(0.0, 0.0, 0.0, 0.0)` in the cube program sets the background to:

- a) White
- b) Red
- c) Blue
- d) Black

Answer: d) Black

---

**Wish you all the best!**

**Fathy.**