Exp-5:
Write a Dart program to create a class Laptop with properties [id, name, ram] and create 3 objects of it and print all details.
main.dart:

```
import 'package:flutter/material.dart';

void main() => runApp(const LaptopApp());

class Laptop {
 final int id;
 final String name;
 final int ram;

 const Laptop({required this.id, required this.name, required this.ram});
}

class LaptopApp extends StatelessWidget {
 const LaptopApp({super.key});

 @override
 Widget build(BuildContext context) {
  return MaterialApp(
    title: 'Laptop List',
    theme: ThemeData(
      primarySwatch: Colors.teal,
      scaffoldBackgroundColor: Colors.white,
    ),
    home: const LaptopListScreen(),
  );
 }
}

class LaptopListScreen extends StatelessWidget {
 const LaptopListScreen({super.key});

 final List<Laptop> laptops = const [
  Laptop(id: 101, name: 'Dell XPS 13', ram: 16),
  Laptop(id: 102, name: 'MacBook Pro', ram: 32),
  Laptop(id: 103, name: 'Lenovo ThinkPad', ram: 8),
 ];

 @override
 Widget build(BuildContext context) {
  return Scaffold(
    appBar: AppBar(title: const Text('Laptops')),
    body: ListView.builder(
      padding: const EdgeInsets.all(16),
      itemCount: laptops.length,
```

```
      itemBuilder: (context, index) {
        final laptop = laptops[index];
        return Card(
          margin: const EdgeInsets.symmetric(vertical: 8),
          elevation: 3,
          child: ListTile(
            leading: CircleAvatar(
              backgroundColor: Colors.teal.shade700,
              child: Text(
                laptop.id.toString(),
                style: const TextStyle(color: Colors.white),
              ),
            ),
            title: Text(laptop.name, style: const TextStyle(fontWeight: FontWeight.bold)),
            subtitle: Text('RAM: ${laptop.ram} GB'),
          ),
        );
      },
    ),
  );
}
```

Output:

