

What this is. One-page reference for the match-night push notification system (shipped 5 Jul 2026). Two flows: [admin one-off setup](#) (repeat only if a secret rotates), and [player opt-in](#) (each device, once). Bottom: the four errors you're likely to hit while wiring it up, with the fix for each.

How it works. Admin submits a match result → [voting_windows](#) row inserts → Postgres trigger calls the edge function → the function fetches rostered players' push subscriptions, signs a VAPID JWT, encrypts the payload and hands it to Apple / FCM / Mozilla → the browser's service worker renders "Vote for tonight's awards" on the player's device. Same flow when results publish, different payload.

ADMIN — ONE-OFF SETUP

DONE ONCE. ONLY REDO IF A SECRET ROTATES OR THE FUNCTION GOES MISSING.

- 1 **Generate a VAPID keypair.** Any machine with node: `npm run generate-vapid-keys -- --json`. Public key = safe to publish. Private key = secret.
- 2 **Hardcode the public key in the client.** Lives at `src/lib/push.ts` as `VAPID_PUBLIC_KEY`. Browsers use this to sign the subscription request.
- 3 **Set project secrets.** Dashboard → Settings → Edge Functions → Secrets. Add `VAPID_PRIVATE_KEY` and `VAPID_SUBJECT = mailto:pabarham@gmail.com`.
- 4 **Deploy the edge function.** Dashboard → Edge Functions → Deploy → paste `supabase/functions/send-vote-notifications/index.ts`, name it `send-vote-notifications`, turn OFF Verify JWT.
- 5 **Store the function URL in Vault.** One SQL call: `vault.create_secret(<url>, 'vote_notify_url', 'desc')`. The trigger reads it — never hardcoded.
- 6 **Wire the triggers.** Migration `048` creates `voting_windows_notify_open_trg` (INSERT) and `voting_windows_notify_results_trg` (UPDATE OF results_published). Apply and you're done.

PLAYER — PER-DEVICE OPT-IN

EACH PLAYER, EACH DEVICE, ONCE. IOS NEEDS HOME SCREEN INSTALL FIRST.

- 1 **Open the app from the Home Screen icon** — not from Safari. iOS only allows web push from an installed PWA. If you haven't added it: share sheet → Add to Home Screen.
- 2 **Go to Profile.** Tap the avatar in the top-right of any tab.
- 3 **Tap "Enable notifications"** on the Match-night notifications card. Grant permission when the browser prompts. The card flips green ON.
- 4 **Done.** After the next Thursday match, when the admin submits the result, your phone gets pinged. Tap it to jump straight into the ballot.

Change your mind? Same card → "Turn off on this device". Blocked by mistake in Safari? Site Settings → Notifications → Allow, then re-enable in the app.

Where the config lives

CLIENT (PUBLIC)
`src/lib/push.ts` ·
`VAPID_PUBLIC_KEY`

SUPABASE SECRETS
`VAPID_PRIVATE_KEY`,
`VAPID_SUBJECT`

VAULT
`vote_notify_url`

DB / SW
`push_subscriptions`,
`public/sw.js`

Troubleshooting — the four errors you'll hit

404 Requested function was not found

Fix: the edge function isn't deployed. Redeploy via Dashboard. Confirm the vault URL matches the deployed name exactly (hyphens, not underscores).

401 UNAUTHORIZED_NO_AUTH_HEADER

Fix: Verify JWT is still on. Toggle off on the function's Details page. Our pg_net call intentionally sends no auth header.

500 VAPID_PRIVATE_KEY not configured

Fix: add the private key as a project secret. Case-sensitive, no trailing whitespace. Redeploy so the env is picked up.

403 BadAuthorizationHeader (Apple)

Fix: VAPID public key at send-time doesn't match the one the browser signed the subscription with. Either add `VAPID_PUBLIC_KEY` as a project secret, or match the hardcoded fallback to `src/lib/push.ts`.

Diagnostic path

Fire a manual test from SQL — the response includes the exact status code + body for any failure:

```
SELECT public.call_send_vote_notifications(  
  (SELECT id FROM matches WHERE status='completed' ORDER BY match_date DESC LIMIT 1), 'vote_open');  
SELECT pg_sleep(4);  
SELECT status_code, content FROM net._http_response  
WHERE created > NOW() - INTERVAL '30 seconds' ORDER BY id DESC LIMIT 1;
```

Success: `{"sent":1,"total":1,"results":[{"ok":true}]}`. Anything else: `results[].statusCode` + `body` map to one of the four errors above.

Full source · migrations `047` + `048` · edge function · SW handler → all on `main`. This runbook + a fire drill = zero-drama recovery.