

Stacks & Queues



Yi-Shin Chen

Institute of Information Systems and Applications

Department of Computer Science

National Tsing Hua University

yishin@gmail.com



Template

Abstracted Bag Container

```
class Bag
{
public:
    Bag(int bagCapacity = 10); // Constructor
    ~Bag(); // Destructor

    int Size() const; // Return the number of elements
    bool IsEmpty() const; // Check if bag is empty
    int Element() const; // Return an element in the bag

    void Push(const int); // Insert an integer into the bag
    void Pop() // Delete an integer from the bag

private:
    int *array; // Integer array that stores the data
    int capacity; // Capacity of array
    int top; // Position of top element
};
```

3

Bag Implementation

```
Bag::Bag( int bagCapacity):capacity( bagCapacity ) {
    if(capacity < 1) throw "Capacity must be > 0";
    array = new int [ capacity ];
    top = -1;}

Bag::~Bag(){ delete [] array; }

inline int Bag::Size() const { return top + 1; }

inline bool Bag::IsEmpty() const { return Size() == 0; }

inline int Bag::Element() const {
    if(IsEmpty()) throw "Bag is empty";
    return array [0]; // Always return the first element
}

void Bag::Push(const int x) {
    if(capacity == top+1) ChangeSize1D(array,capacity,2* capacity);
    capacity *= 2;
    array[++top]=x;}

void Bag::Pop( ) {
    if(IsEmpty()) throw "Bag is empty, cannot delete";
    int deletePos = top / 2; // Always delete the middle element
    copy (array+deletePos+1, array+top+1, array+deletePos);
    top--;}
}
```

4

Abstracted Bag Container

```
template<class T>
class Bag
{
public:
    Bag(int bagCapacity = 10);    // Constructor
    ~Bag();                      // Destructor

    int Size() const;             // Return the number of elements
    bool IsEmpty() const;        // Check if bag is empty
    T& Element() const;          // Return an element in the bag

    void Push(const T&);          // Insert an element into the bag
    void Pop()                   // Delete an element from the bag

private:
    T *array;                    // Data array
    int capacity;                // Capacity of array
    int top;                     // Position of top element
};
```

5

Template Bag Implementation

```
template<class T>
Bag<T>::Bag( int bagCapacity):capacity( bagCapacity ) {
    if(capacity < 1) throw "Capacity must be > 0";
    array = new T [ capacity ];
    top = -1;
}

template<class T>
void Bag<T>::Push(const T& x) {
    if(capacity == top+1) ChangeSize1D(array, capacity, 2* capacity);
    capacity *= 2;
    array[++top]=x;
}

template<class T>
void Bag<T>::Pop() {
    if(IsEmpty()) throw "Bag is empty, cannot delete";
    int deletePos = top / 2; // Always delete the middle element
    copy (array+deletePos+1, array+top+1, array+deletePos);
    array[top--].~T();
}
```

6

The Stack

Stack

- A stack is an ordered list
 - in which
 - insertions (or called additions or **pushes**)
 - deletions (or called removals or **pops**)
 - Both made at one end called the top
 - Operate in

Stack: ADT

```
template < class T >
class Stack // A finite ordered list
{
public:
    // Constructor
    Stack (int stackCapacity = 10);

    // Check if the stack is empty
    bool IsEmpty ( ) const;

    // Return the top element
    T& Top ( ) const;

    // Insert a new element at top
    void Push (const T& item);

    // Delete one element from top
    void Pop ( );
private:
    T* stack;
    int top;    // init. value = -1
    int capacity;
};
```

9

Stack Operations: Push & Pop

```
template < class T >
void Stack < T >::Push (const T& x)
{
    // Add x to stack
    if(top == capacity - 1)
    {
        ChangeSize1D(stack, capacity, 2*capacity);
        capacity *= 2;
    }
    stack [ ++top ] = x;
}
```

```
template < class T >
void Stack < T >::Pop ( )
{
    // Delete top element from stack
    if(IsEmpty()) throw "Stack is empty. Cannot delete.";
    stack [ top-- ].~T(); // Delete the element
}
```

The Queue


Queue

- A queue is an ordered list
 - in which
 - insertions (or called additions or pushes)
 - deletions (or called removals or pops)
 - Made at **different ends**
 - New elements are inserted at **rear** end
 - Old elements are deleted at **front** end
 - Operate in

Queue Insertion

■ Insert a new element into queue


- f: front position
- r: rear position



Queue Deletion


■ Delete an old element from queue

- f: front position
- r: rear position




Problems


- What happen if $\text{rear} == \text{capacity}-1$?




- Approach 1: Add more space



- Approach 2: Shift left



Circular Queue



Initial


Insertion

Deletion


$\text{rear} = (\text{rear} + 1) \% \text{capacity};$

Circular Queue: Empty

■ $\text{rear} == \text{front}$?




Queue is empty




Queue is full


Circular Queue



Initial



Insertion



Deletion

$\text{rear} = (\text{rear} + 1) \% \text{capacity};$

Queue: ADT

```
template < class T >
class Queue // A finite ordered list
{
public:
    // Constructor
    Queue (int queueCapacity = 10);

    // Check if the stack is empty
    bool IsEmpty ( ) const;

    // Return the front element
    T& Front ( ) const;

    // Return the rear element
    T& Rear ( ) const;

    // Insert a new element at rear
    void Push (const T& item);

    // Delete one element from front
    void Pop ( );

private:
    T* queue;
    int front, rear; // init. value = -1
    int capacity;
};
```

Yi-Shin Chen -- Data Structures

19

Queue Operations: Front & Rear

```
template < class T >
void Queue < T >::IsEmpty() const { return front==rear; }

template < class T >
T& Queue < T >::Front() const {
    if(IsEmpty()) throw "Queue is empty!";
    return queue[(front+1)%capacity];
}

template < class T >
T& Queue < T >::Rear() const {
    if(IsEmpty()) throw "Queue is empty!";
    return queue[rear];
}
```

Yi-Shin Chen -- Data Structures


20

Queue Operations: Push & Pop

```
template < class T >
void Queue< T >::Push (const T& x)
{
    // Add x at rear of queue
    if((rear+1)%capacity == front)
    {
        // queue is going to full, double the capacity!
    }
    rear = (rear+1)%capacity;
    queue [rear] = x;
}
```



```
template < class T >
void Queue < T >::Pop ( )
{
    // Delete front element from queue
    if(IsEmpty()) throw "Queue is empty. Cannot delete.";
    front = (front+1)%capacity;
    queue[front].~T(); // Delete the element
}
```

Doubling Queue Capacity



Full circular queue

capacity=8




Doubling the array


Anything wrong?

Doubling Queue Capacity: Scenario 1

capacity=16




Doubling the array




Scenario 1: After shifting right segment

Doubling Queue Capacity: Scenario 2

capacity=16



Doubling the array



Scenario 2: Alternative configuration

Subtyping and Inheritance

In C++

Subtype

- Inheritance is used to express subtype relationships
 - A Data object of Type B IS-A data object of Type A
 - Type B is more specialized than Type A
 - E.g., Chair IS-A Furniture
- Bag is a data structure, where
 - Elements can be inserted and deleted
- Stack is a data structure, where
 - Elements can be inserted and deleted
- Stack is more specialized
 - Stack IS-A Bag

Generic Bag ADT

```
Class Bag
{
public:
    Bag(int bagCapacity=10);
    virtual ~Bag();
    virtual int Size() const;
    virtual bool IsEmpty() const;
    virtual int Element() const;
    virtual void Push(const int);
    virtual void Pop();
protected:
    int *array;
    int capacity;
    int top;
};
```

Implement operations not
exist in the Bag class

```
class Stack : public Bag
{
public:
    Stack(int stackCapacity=10);
    virtual ~Stack();
    int Top()const;
    virtual void Pop();
};
```

Evaluation of Expressions

Expression

$$X = A/B - C + D * E - A * C$$

- Operators

- +, -, *, /, ..., etc

- Operands

- A, B, C, D, E, F

- Execution order might affect the final result

Expression Evaluation

- For $X = A/B - C + D * E - A * C$

- If $A = 4, B=C=2, D=E=3$

- $X = ((4/2)-2)+(3*3)+(4*2)=1$

- For $X = (A/(B - C + D)) * (E - A) * C$

- If $A = 4, B=C=2, D=E=3$

- $X = (4/(2-2+3))*(3-4)*2 = -2.66666666$

Evaluation Rules

- Operators have priority
- Operator with higher priority is evaluated first
- Operators of equal priority are evaluated from left to right
- Unary operators are evaluated from right to left

Priority of Operators in CPP

Priority	Operators
1	Minus, !
2	*, /, %
3	+, -
4	<, <=, >=, >
5	=, !=
6	&&
7	

Infix and Postfix Notation

■ Infix notation

- Operator comes in-between the operands
- E.g., $A+B*C$
- Hard to evaluate using codes...

■ Postfix notation

- Each operator appears after its operands
- E.g., ABC^*+


Advantages of Postfix Notation

- You don't need parentheses
- Priority of operators is no longer relevant!
- Expression can be efficiently evaluated by
 - Making a left to right scan
 - **Stacking** operands
 - Evaluating operators
 - Push the result into stack

Example 1

■ Infix : $A+B - C \Rightarrow$ Postfix : $A B + C -$

■ Suppose $A = 4, B = 3, C = 2$




35

Example 1

■ Infix : $A+B - C \Rightarrow$ Postfix : $A B + C -$

■ Suppose $A = 4, B = 3, C = 2$




36

Example 1

■ Infix : $A+B - C \Rightarrow$ Postfix : $A B + C -$

■ Suppose $A = 4, B = 3, C = 2$




37

Example 1

■ Infix : $A+B - C \Rightarrow$ Postfix : $A B + C -$


■ Suppose $A = 4, B = 3, C = 2$



38

Example 1


- Infix : $A + B - C \Rightarrow$ Postfix : $A B + C -$
- Suppose $A = 4, B = 3, C = 2$



39

Example 2

- Infix : $X = A/B - C + D * E - A * C$
- Postfix : $X = AB/C - DE * + AC * -$



40

Evaluation Pseudo Codes

```
void Eval(Expression e)
{
    // Assume the last token of e is '#'
    // A function NextToken is used to get next token in e
    Stack<Token> stack; // initialize stack
    for (Token x = NextToken(e); x != '#'; x = NextToken(e)){
        if(x is an operand) stack.Push(x);
        else{
            // Remove the correct number of operands from stack
            // Perform the evaluation
            // Push the result back to stack
            // ***Try to fill up the codes by your own***
        }
    }
};
```

Infix to Postfix

- Fully parenthesize algorithm:
 - Fully parenthesize the expression
 - Move all operators so the they replace the corresponding right parentheses
 - Delete all parentheses

$((((A / B) - C) + (D * E)) - (A * C))$

Infix to Postfix

- Smarter algorithm
 - Scan the expression only once
 - Utilize **stack**
- The order of operands dose not change
- Output every visiting operand directly
- Use stack to store visited operators
 - Pop them out at the right moment
 - The **priority** of operator on top of stack is *higher or equal to* that of the incoming operator
 - left-to-right associativity

Example 1

■ Infix : $A + B * C$

Next token	Stack	Output
None	Empty	None
A	Empty	A
+	+	A
B	+	AB
*	+*	AB
C	+*	ABC
	+	ABC*
	Empty	ABC*+

Example 2

■ Infix : $A * (B + C) * D$

Next token	Stack	Output

45

Notes

■ Expression with ()

- '(' has the highest priority, always push to stack.
- Once pushed, '(' get lowest priority.
- Pop the operators until you see the matched ')'

Self-Study Topics

■ Prefix representation

infix	prefix
$A * B / C$	$/*ABC$
$A / B - C + D * E - A * C$	$-+ - / ABC * DE * AC$
$A * (B + C) / D - G$	$- / * A + BCDG$