

C++ Review

Yi-Shin Chen


Institute of Information Systems and Applications

Department of Computer Science

National Tsing Hua University

yishin@gmail.com

Evolution Of Programming Paradigms



Concept of Object-Oriented

Algorithmic Decomposition vs. Object-Oriented Decomposition

■ Algorithmic Decomposition

- Software decomposed into **steps**
- Steps are implemented as **functions**
 - E.g. C or Pascal
- Data structures are a secondary concern
 - Data is visible and accessible to all steps
 - No way to prevent irrelevant codes to access the data

■ Object-Oriented Decomposition

- Software decomposed into **objects**
 - E.g., C++
 - Interact with each other to solve the problem
- High reusability and flexibility

Object-Oriented Programming (OOP)

■ Object

- Basic unit that does the computation
- Contain data and procedural functions

■ Object-Oriented Programming

- Objects are fundamental building blocks
- Each object is an instance of some class
- Classes have inheritance relationships

C++ v.s. Java

■ Object-Oriented Language (C++)

- It supports objects
- It requires objects to belong to a class
- It supports inheritance

■ Object-Based Language (Java)

- It supports objects
- It requires objects to belong to a class

History of C++

- Creator of C++ : Bjarne Stroustrup
- C++ is an enhanced version of C
- Standardization:

Year	C++ Standard	Informal name
1998	ISO/IEC 14882:1998	C++98
2003	ISO/IEC 14882:2003	C++03
2007	ISO/IEC TR 19768:2007	C++TR1
2011	ISO/IEC 14882:2011	C++11

Wikipedia C++11 <http://www.stroustrup.com/C++11FAQ.html>

Programming Language Rank

Feb 2018	Feb 2017	Programming Language	Ratings	Change
1	1	Java	14.988%	-1.69%
2	2	C	11.857%	+3.41%
3	3	C++	5.726%	+0.30%
4	5	Python	5.168%	+1.12%
5	4	C#	4.453%	-0.45%
6	8	Visual Basic .NET	4.072%	+1.25%
7	6	PHP	3.420%	+0.35%

<https://www.tiobe.com/tiobe-index/>

Data Types

Abstraction and Encapsulation

■ Data Abstraction

- The separation between
 - Specification of a data object
 - Implementation

■ Data Encapsulation (Information Hiding)

- Conceals the implementation details from the outside world

■ Benefit to large software system design

Data Type

- A collection of **objects** and a set of **operations**
- Fundamental data type in C++:
 - Basic: char, int, float, double, and many more
 - Modifiers: short, long, signed, unsigned
- Example: int data type
 - Objects: 0, +1, -1, +2, -2, MAXINT, MININT
 - Operations: +, -, *, /, ==, <=


Grouping Data

- Examples:
 - Arrays
 - Collection of elements of the same basic data type
 - structs (C) and classes (C++)
 - Collection of elements

Example

Data Type1	Data Type2	Data Type3
Objects: int data;	Objects: float data;	Objects: Type1 data; int data2;
Operations: int Value(void) { return data; }	Operations: float Value(void) { return data; }	Operations: int Value(void) { return data.Value()+data2; }
void Calculate(void) {data = 100; }	void Calculate(void) {data= exp(-10); }	void Calculate(void) {data. Calculate(); data2 = 128; }

A Software that uses ADTs



Advantages of ADTs

- Simplification
- Testing and debugging
 - Each object can be tested and debugged separately
- Reusability
- Flexibility
 - Could freely modify the internal implementation without affecting the rest of codes



Basic C++

Program Organization

■ Header file (*.h)

- Store declarations

■ Hello_World.h

```
#ifndef _HELLO_WORLD_H_
#define _HELLO_WORLD_H_

void Hello_World(void);

// insert other declarations here
// ...

#endif
```

■ Source file (*.cpp)

- Store source codes

■ Hello_World.cpp

```
#include <iostream>
#include <Hello_World.h>

void Hello_World(void)
{
    std::cout << "Hello" << std::endl;
}
```

Scope in C++

■ Local scope

- A name declared in a block

■ Class scope

- Declaration associated with a class definition

■ Namespace scope

- Declaration associated with a namespace

■ File scope

Example

```
1 // using
2 #include <iostream>
3 using namespace std;
4
5 namespace first
6 {
7     int x = 5;
8     int y = 10;
9 }
10
11 namespace second
12 {
13     double x = 3.1416;
14     double y = 2.7183;
15 }
16
17 int main () {
18     using first::x;
19     using second::y;
20     cout << x << endl;
21     cout << y << endl;
22     cout << first::y << endl;
23     cout << second::x << endl;
24     return 0;
25 }
```

Data Declaration in C++

■ Constant values

- E.g., 5, 'a', 4.3

■ Variables

- E.g., double income;

■ Constant variables

- The content must be fixed at declaration
- E.g., **const** int MAX=500;

■ Enumeration types

- Declare a series of constants
- E.g., **enum** semester {SUMMER, FALL, SPRING};

Data Declaration in C++ (Contd.)

■ Pointers

- Hold memory address of objects
- E.g.,
`int i = 25;`
`int* np; np = &i;`

■ Reference types (C++ only)

- Provide an alternate name for an object
- E.g.,
`int i=5;`
`int& j=i;`
`i = 7;`
`cout << j << endl;`

Reference v.s. Pointer

■ The semantic differences between reference and pointer:

- Pointer **CAN** be NULL but reference **CANNOT** be NULL
 - reference must bind a variable at initialization

```
int * ptr = NULL;  
int & ref = NULL;
```

- Pointer **CAN** be changed to point different target in the program but reference variable **CANNOT** be changed.

```
int x= 10, y=20;  
ptr = &x ;  
ptr = &y ;  
int & ref = x;  
&ref = y;
```

Comment

■ One line comment:

// To increase the readability

■ Multiple Line comment:

/*

Usually comment out some functions/procedures

*/

23

Functions in C++

■ A function consists of

- A function name
- A list of arguments (input)
- A return type (output) or void
- The body

■ Example

```
int Max (int a, int b)
{
    if (a>b) return a;
    else return b;
}
```

Parameter Passing in C++

■ Call by **value**

```
int special_add(int a , int b)
{
    a = a+5;
    return a+b;
}
```

- Value is copied into local storage
- Will **not** modify the original copies

25

Parameter Passing in C++

■ Call by **pointer**

```
void swap(int *a , int *b){
    int temp=*a;
    *a=*b;
    *b=temp;
}
```

- **Will** modify the original objects

26

Quiz

- What if we want to pass a large object but do not want it to be modified in the function?

Function Overloading in C++

- In C++, we can have following functions:

```
int Max(int, int);  
int Max(int, int, int);  
int Max(int*, int);  
int Max(float, int);  
int Max(int, float);
```

- It is impossible to defined two functions with the same name in C

Dynamic Memory Allocation in C++

■ Dynamic Memory Allocation in C

- malloc, delete, realloc, memset, memcpy
- Memory leak and memory fragmentation problems

■ New dynamic memory allocation mechanism

- Using keywords “new” and “delete”
- Make sure you use ‘delete’ for pointer generated by ‘new’

29

Dynamic Memory Allocation in C++

■ C

```
#include <stdio>

int main () {

    int * x = (int*) malloc ( sizeof(int) );

    free(x);
    return 0;
}
```

■ C++

```
#include <iostream>

int main () {

    int * y = new int ;
    delete y ;

    // allocate an int array.
    int * data = new int [10];

    /* make sure you use 'delete' for
    pointer generated by 'new'. */
    delete [] data ;
    return 0;
}
```

Exceptions Handle

- Handle runtime errors or special conditions
- Provide more clear programming logic

```
#include <iostream>
using namespace std;

int main () {
    try {
        throw 20;
    }
    catch (int e) {
        cout << "An int-type exception
occurred.
        Exception Nr. " << e << endl;
    }
    return 0;
}
```

```
#include <iostream>
using namespace std;

int main () {
    try {
        throw "error occurs";
    }
    catch (char* e) {
        cout << "An char-type exception
occurred.
        Exception Nr. " << e << endl;
    }
    return 0;
}
```

31

Exceptions Handle

■ try-catch block

- Each try block is followed by **zero or more catch** blocks.
- Each **catch** block is visited sequentially until the matched block
- Each **catch** block has a parameter whose type determine the type of exception that may be caught

■ catch (char* e){}

- Catch exceptions of type char*

■ catch (bad_alloc e){}

- Catch exceptions of type **bad_alloc** (system-defined type)

■ catch (...){}

- Catch all exceptions regardless of their type

Exceptions Handle – throw

```
int main(void)
{
    int a = 0;

    func1();

    int b = a + 2;
    int c = 3;

    return 0;
}
```

```
void func1(){

    func2();

    int a = 2;
    //....
    return ;
}
```

```
void func2(){

    throw "error!";
    std::cout<<"hi";

    return ;
}
```

33

C++ Class

C++ Class

- Class can support **data abstraction** and **encapsulation**

```
// In the header file Rectangle.h
#ifndef RECTANGLE_H
#define RECTANGLE_H
class Rectangle {
public:    // the following members are public
        // the next four members are member functions
        Rectangle ( );    // constructor
        ~Rectangle( );    // destructor
        int GetHeight ( );    // return the height of the rectangle
        int GetWidth ( );    // return the width of the rectangle
private: // the following members are private
        // the following members are data member
        int xLow, yLow, height, width;
        // (xLow, yLow) are the coordinates of the bottom left corner of rec.
};
#endif
```

Data Abstraction

- Specification is placed in header file (e.g., *Rectangle.h*)
- Implementation is placed in source file (e.g., *Rectangle.cpp*)

```
// In the source file Rectangle.cpp
#include "Rectangle.h"

/* The prefix "Rectangle::" identifies GetHeight() and GetWidth() are member function of
class Rectangle. It is required because the member functions are implemented outside
the class definition*/

int Rectangle::GetHeight() {return height;}
int Rectangle::GetWidth() {return width;}

```

Class Usage

```
// In a source file main.cpp
#include <iostream>
#include "Rectangle.h"

main() {
    Rectangle r, s;    // r and s are objects of class "Rectangle"
    Rectangle *t = &s; // t is a pointer to class object s
    .
    .
    // use "." operator to access members of class objects.
    // use "->" operator to access members of class objects through pointers.
    If ( r.GetHigh ( ) * r.GetWidth ( ) > t->GetHeight ( ) * t->GetWidth ( ) )
        cout << "r";
    else cout << "s";
    cout << "has the greater area " << endl;
}
```

Data Encapsulation

■ C++

```
class Foo{
    private:
        int x;
    public:
        int y;
};

int main(void){
    Foo obj1 ;
    obj1.x = 11; // compile ERROR
    obj1.y = 22; // access y
}
```

■ C

```
struct Foo{
    int x;
    int y;
};

int main(void){
    struct Foo obj1 ;
    obj1.x = 11; // access x
    obj1.y = 22; // access y
}
```

Constructors and Destructors

```
// In the source file Rectangle.cpp
#include "Rectangle.h"

// constructor
Rectangle::Rectangle (void)
{
    xLow = 0; yLow = 0;
    height = 1; width = 1;
}

// destructor
Rectangle::~Rectangle (void)
{
    xLow = yLow = height = width = 0;
}

int Rectangle::GetHeight() {return height;}
int Rectangle::GetWidth() {return width;}
```

39

Constructors

- A member function to initialize the data members
- Constructor is invoked when an object is created
- Must have the same name as class
- No return type or return value
- A class can have more than one constructors

40

Type of Constructors

■ Default constructor

- A constructor with no arguments

```
Rectangle ( ); // default constructor
```

■ Augmented constructor

- A constructor with arguments

```
Rectangle (int, int, int, int); // augmented constructor
```

■ Copy constructor

- Must be specified if the STL containers are used to store your class object.

```
Rectangle (const Rectangle&); // copy constructor
```

41

Destructor

- A member function to delete data members when the object disappears
- Destructor is **automatically** invoked when a class object is out of scope or is deleted
- Must have the same name as class with prefix “~”.
- No return type or return value
- Take no arguments
- Only one destructor in a class

42

Default Methods

- The compiler will generate 4 default methods, if not specified

- Default constructor

```
Rectangle ( ); // default constructor
```

- Copy constructor

```
Rectangle (const Rectangle&); // copy constructor
```

- Destructor

```
~Rectangle (); // destructor
```

- Assignment operator

```
Rectangle& operator=(const Rectangle&); // operator "="
```

struct vs. class

■ C

```
struct MyData{  
  
    int id;  
};  
  
// instance struct  
struct MyData data1;
```

■ C++

```
class MyData{  
public:  
    int id;  
};  
  
// instance object  
MyData data1;
```

“struct” in C++

■ C++ - “struct”

```
struct Student{  
    int age;  
    public :  
    int id;  
    char name[100];  
};
```

■ C++ - “class”


```
class Student{  
    int age;  
    public:  
    int id;  
    char name[100];  
};
```

45

Inheritance

- Relate one class object to another
- Define a “IS-A” relationships between objects
 - **Type B IS-A** data type of **Type A** if B is a **specialized** version of A and A is more **general** than B
- Members (data and functions) in Type A are implicitly copied to Type B.
- Reusability of codes

Class Diagram of inheritance




47

Specialization

- Put non-common members in private block of base class
 - Derived class can not access these members
- Re-declare the members (data and functions) in the derived class (**overriding**)

48

Overriding



49

Polymorphism

- Manipulate different objects through the common interface

```
class Foo
{
    public:
    virtual char* getName()
    { return "foo"; }
};
```

```
class Bar : public Foo
{
    public:
    virtual char* getName()
    { return "Bar"; }
};
```

```
class Car : public Foo
{
    public:
    virtual char* getName()
    { return "Car"; }
};
```

```
int main(){
    Foo* myFoo = new Foo;
    Foo* myBar = new Bar;
    Foo* myCar = new Car;

    processObj(myFoo);
    processObj(myBar);
    processObj(myCar);
}

processObj(Foo* _obj)
{ ... _obj->getName() ... }
```

50

Polymorphism

■ Function Overloading

- Data type is determined in **compiler time**

```
int main(){
    Foo myFoo;
    Bar myBar;
    Car myCar;

    processObj (myFoo);
    processObj (myBar);
    processObj (myCar);
}
```

■ Dynamic Binding

- Data type is determined in **run time**

```
int main(){
    Foo* myFoo = new Foo;
    Foo* myBar = new Bar;
    Foo* myCar = new Car;


    processObj(myFoo);
    processObj(myBar);
    processObj(myCar);
}
```

51


How dose Dynamic Binding Work ?

■ Virtual Method Table

Base * ptr = new Base;



Base * ptr = new Derived;



Virtual method table of Derived pointer will be “sliced” when it be assigned to a base pointer

http://en.wikipedia.org/wiki/Virtual_method_table#cite_note-4
<http://www.cppblog.com/dawnbreak/archive/2009/03/10/76084.html>

52

Dynamic Binding: Pros and Con

■Pros:

- Ideal data abstraction.
- Powerful mechanism of OOP (Design Pattern)
- Widely used in large-scale software design

■Con:

- Decreasing performance
 - Additional memory to store virtual function table
 - Additional runtime cost to access virtual function table

53

References

■C++ Primer 5th

- [http://books.google.com.tw/books?hl=zh-TW&id=J1HMLyxqJfgC&q=operator+overaling#v=onepage&q=chapter%2014&f=false](http://books.google.com.tw/books?hl=zh-TW&id=J1HMLyxqJfgC&q=operator+overloading#v=onepage&q=chapter%2014&f=false)

■MIT's Introduction to C++


- <http://ocw.mit.edu/courses/electrical-engineering-and-computer-science/6-096-introduction-to-c-january-iap-2011/lecture-notes/>

■MSDN C++ Reference:

- [http://msdn.microsoft.com/en-us/library/3bstk3k5\(v=vs.100\).aspx](http://msdn.microsoft.com/en-us/library/3bstk3k5(v=vs.100).aspx)

■NTU OCW:

- <http://ocw.aca.ntu.edu.tw/ntu-ocw/index.php/ocw/cou/101S112>



54