Examples of Chunking

For HT-POL-001:

1. Show 3 representative chunks.
2. Show the source document and section for each chunk.
3. Show all metadata associated with each chunk.

Here are 3 representative chunks from **HT-POL-001 (HealthTech Payer Services — Medical Policy)**, including source documentation, section context, and metadata:

Chunk 1

Content:
```
# HealthTech Payer Services – Medical Policy\\n\\n**Document ID:** HT-POL-001 | **Effective Date:** January 1, 2026 | **Version:** 2.0 (CURRENT)\\n\\n**STATUS: CURRENT / APPROVED** | **CONFIDENTIALITY: INTERNAL**
```

Source Document: `HT-POL-001`
Section: `Document Header`

Metadata:


```
{
  "source": "blob",
  "blobType": "application/json",
  "loc": {
    "lines": {
      "from": 1,
      "to": 28
    }
  }
}
```

Chunk 2

Content:
```
## 1. Comprehensive Inpatient & Outpatient Coverage Policy\\n\\nThis policy defines the coverage criteria, pre-authorization guidelines, and medical necessity thresholds for inpatient and outpatient clinical procedures under HealthTech Benefit Plans.
```

Source Document: `HT-POL-001`
Section: `1. Comprehensive Inpatient & Outpatient Coverage Policy`

Metadata:


```
{
  "source": "blob",
  "blobType": "application/json",
  "loc": {
    "lines": {
      "from": 1,
      "to": 28
    }
  }
}
```

Chunk 3

Content:
`### 1.1 Clinical Necessity Principles\\n\\nServices are considered medically necessary only if provided in accordance with generally accepted standards of medical practice and supported by objective clinical evidence.`

Source Document: `HT-POL-001`
Section: `1.1 Clinical Necessity Principles`

Metadata:


```
{
  "source": "blob",
  "blobType": "application/json",
  "loc": {
    "lines": {
      "from": 1,
      "to": 28
    }
  }
}
```

Key Notes:

1. **All chunks** originate from the **current policy document** (`HT-POL-001`), which is explicitly marked as `VERSION 2.0 (CURRENT)` and effective from **January 1, 2026**.
2. **Metadata** is consistent across all chunks (as this is a single document in the vector store). The `loc` field indicates the original line range in the document (lines `1–28`).
3. **Section context** reflects the hierarchical structure of the policy document (e.g., `1.1` is a subsection of `1. Comprehensive...`).
4. *No legacy or superseded content* is included here (the legacy `HT-POL-001-OLD` document is explicitly inactive and excluded from this response).