

## Chapter 13

# Fibonacci numbers

The **Fibonacci numbers** form a sequence of integers defined recursively in the following way. The first two numbers in the Fibonacci sequence are **0 and 1**, and each subsequent number is the sum of the previous two.

$$F_n = \begin{cases} 0 & \text{for } n = 0, \\ 1 & \text{for } n = 1, \\ F_{n-1} + F_{n-2} & \text{for } n > 1. \end{cases}$$

The first twelve **Fibonacci numbers** are:

0	1	1	2	3	5	8	13	21	34	55	89
0	1	2	3	4	5	6	7	8	9	10	11

Notice that **recursive** enumeration as described by the definition is **very slow**. The definition of  $F_n$  repeatedly refers to the previous numbers from the Fibonacci sequence.

### 13.1: Finding Fibonacci numbers recursively.

```
1 def fibonacci(n):
2     if (n <= 1):
3         return n
4     return fibonacci(n - 1) + fibonacci(n - 2)
```

The above algorithm performs  $F_n$  additions of 1, and, as the sequence grows **exponentially**, we get an inefficient solution.

Enumeration of the Fibonacci numbers **can be done faster simply** by using a basis of **dynamic programming**. We can calculate the values  $F_0, F_1, \dots, F_n$  based on the previously calculated numbers (it is sufficient to remember only the last two values).

### 13.2: Finding Fibonacci numbers dynamically.

```
1 def fibonacciDynamic(n):
2     fib = [0] * (n + 2)
3     fib[1] = 1
4     for i in xrange(2, n + 1):
5         fib[i] = fib[i - 1] + fib[i - 2]
6     return fib[n]
```

The time complexity of the above algorithm is  **$O(n)$** .

### 13.1. Faster algorithms for Fibonacci numbers

Fibonacci numbers can be found in  $O(\log n)$  time. However, for this purpose we have to use matrix multiplication and the following formula:

$$\begin{bmatrix} 1 & 1 \\ 1 & 0 \end{bmatrix}^n = \begin{bmatrix} F_{n+1} & F_n \\ F_n & F_{n-1} \end{bmatrix}, \text{ for } n \geq 1.$$

Even faster solution is possible by using the following formula:

$$Fib_n = \frac{\left(\frac{1+\sqrt{5}}{2}\right)^n - \left(\frac{1-\sqrt{5}}{2}\right)^n}{\sqrt{5}} \quad (13.1)$$

These algorithms are not trivial and it will be presented in the future lessons.

### 13.2. Exercise

**Problem:** For all the given numbers  $x_0, x_1, \dots, x_{n-1}$ , such that  $1 \leq x_i \leq m \leq 1\,000\,000$ , check whether they may be presented as the sum of two Fibonacci numbers.

**Solution:** Notice that only a few tens of Fibonacci numbers are smaller than the maximal  $m$  (exactly 31). We consider all the pairs. If some of them sum to  $k \leq m$ , then we mark index  $k$  in the array to denote that the value  $k$  can be presented as the sum of two Fibonacci numbers.

In summary, for each number  $x_i$  we can answer whether it is the sum of two Fibonacci numbers in constant time. The total time complexity is  $O(n + m)$ .