

# visualkeras: A Python Package for Visualizing Keras and TensorFlow Models

Paul Gavrikov<sup>1,2</sup> and Santosh Patapati<sup>3</sup>

1 IMLA, Offenburg University 2 University of Mannheim 3 Cyrion

DOI: [10.xxxxxx/draft](https://doi.org/10.xxxxxx/draft)

## Software

- [Review](#)
- [Repository](#)
- [Archive](#)

Editor: [Open Journals](#)

## Reviewers:

- [@openjournals](#)

Submitted: 01 January 1970

Published: unpublished

## License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License ([CC BY 4.0](#))

## Summary

visualkeras is a Python package designed to facilitate the visualization of Keras and TensorFlow models. It provides an intuitive developer interface for generating visual representations of model architectures, making it easier for researchers and developers to understand and communicate their designs. The package supports layered volumetric views in 2D / 3D space and directed node-edge graph-based layouts. When provided with a functional or sequential Keras model, visualkeras can generate a highly customizable visualization through various parameters such as color, spacing, dynamic sizing modes, legends, dimensionality, textual annotations, orientation, and more.

## Statement of Need

The visualization of Artificial Intelligence (AI) and Machine Learning (ML) models plays a crucial role for understanding and communicating their architecture. The effectiveness of such visualizations plays a key role in the scientific process. Although detailed descriptions of model architectures and mathematics are often provided in research papers, architectural diagrams are essential for conveying complex structures and relationships in a more accessible manner.

The Keras package (Chollet & others, 2015) provides a high-level API for building and training deep learning models. Keras and its underlying framework, TensorFlow (Abadi et al., 2015), have been widely adopted in the AI and ML community. However, the built-in visualization tools in Keras are primitive and do not provide the flexibility needed for proper architectural representation. Images generated using Keras's built-in visualization tools require significant effort for readers to understand and are simply not suitable for scientific publication or communication purposes. visualkeras addresses this gap by providing a comprehensive set of tools for visualizing Keras models in a way that is both informative and visually appealing.

## Key Features

visualkeras offers a range of visualization features and customization options. The framework is split into two main components.

### Layered View

This component is designed to render both sequential and functional models using a pseudo-3D stacked box layout in a single continuous view. Each box visually represents a layer, with its width, height, and depth corresponding to the layer's spatial and channel dimensions under one of five sizing modes (accurate, balanced, capped, logarithmic, relative).

36 Rendering options can be toggled between three-dimensional (volumetric) and two-dimensional  
37 (flat) modes via the `draw_volume` parameter. Funnel-style connectors can be displayed be-  
38 tween boxes using `draw_funnel`, and `shade_step` controls the deviation in lightness to im-  
39 prove depth perception. Logical spacing can be introduced through special “dummy” layers  
40 (`SpacingDummyLayer`) which are incorporated into the model object itself. Users may add cus-  
41 tom annotations to each box via a `text_callable` function, which can be further customized  
42 with vertical offset adjustments provided by `text_vspacing`. A flexible `color_map` parameter  
43 allows users to color boxes based on layer type or user-defined attributes.

44 Layout control is further refined by adjusting spacing (inter-layer gaps), padding (margins at  
45 the beginning and end), and orientation settings. One-dimensional layers can be oriented using  
46 `one_dim_orientation`, and individual layers can be constrained to 2D rendering via `index_2D`.  
47 An entire model can be rendered flat by disabling volumetric rendering. Support for better  
48 visualizing decoder-like architectures is available through the `draw_reversed` option.

49 A configurable legend can be added, with options for adjusting text spacing (`legend_text_spacing_offset`)  
50 font properties (`font`, `font_color`), and whether to show dimensions at each layer  
51 (`show_dimension`). Finally, users can control scaling across the x-y plane and z-axis using  
52 `scale_xy` and `scale_z`. These dimensions can be explicitly capped or floored using `max_xy`,  
53 `max_z`, `min_xy`, and `min_z` parameters.

54 The final visualization is produced as a Pillow Image object (Clark, 2015), which can be  
55 displayed in Jupyter notebooks or saved to disk.

## 56 Graph View

57 This component generates a left-to-right node-edge visualization of any Keras or `tf.keras`  
58 model by treating each layer (or individual neuron) as a node and drawing directed connectors  
59 to represent data flow. Given a `Model` instance, the function computes a hierarchy of layers  
60 based on their graph depth, places nodes evenly spaced in horizontal layers, and centers them  
61 vertically within the image canvas. Each node is drawn as a fixed-size circle or box (specified  
62 by `node_size`), and may represent the entire layer or each neuron it contains, depending on  
63 the `show_neurons` parameter.

64 Connectors between nodes are rendered as lines whose color and thickness can be controlled  
65 through the `connector_fill` and `connector_width` arguments. Layout parameters such as  
66 `layer_spacing`, `node_spacing`, `padding`, and `background_fill` allow users to adjust the  
67 overall compactness, margins, and canvas appearance. For models with a large number of  
68 neurons in a layer, the `ellipsize_after` parameter can be used to replace excess nodes with  
69 an ellipsis symbol to prevent overcrowding. The `inout_as_tensor` option determines whether  
70 each tensor input or output is shown as a single tensor (rectangular shape) or expanded into  
71 multiple units.

72 Node coloring is fully customizable via the `color_map` parameter which maps layer classes to  
73 fill and outline colors. This allows for visually distinguishing different layer types.

74 Like the Layered View, the Graph View produces a Pillow Image object (Clark, 2015) that can  
75 be displayed in Jupyter notebooks or saved to disk.

## 76 Usage Examples

77 In this section, we provide examples of how to use `visualkeras` to visualize Keras models in  
78 different ways. The examples shown in Figure 1, Figure 2, Figure 3, and Figure 4 demonstrate  
79 the flexibility and customization options available in the package. The generated graphical  
80 visualizations can be displayed in Jupyter notebooks or saved as image files for use in publications  
81 or presentations.

## 82 Layered View

### 83 Basic Usage

```
import visualkeras
from tensorflow.keras.models import Sequential
from tensorflow.keras.layers import Dense, Conv2D, MaxPooling2D, Flatten, Dropout

# Define a simple sequential model
simple_sequential_model = Sequential([
    Conv2D(32, (3, 3), activation='relu', input_shape=(28, 28, 1)),
    MaxPooling2D((2, 2)),
    Conv2D(64, (3, 3), activation='relu'),
    MaxPooling2D((2, 2)),
    Conv2D(64, (3, 3), activation='relu'),
    Flatten(),
    Dense(64, activation='relu'),
    Dropout(0.5),
    Dense(10, activation='softmax')
])

# Basic usage of visualkeras
basic_layered_img = visualkeras.layered_view(simple_sequential_model, draw_funnel=False)

# Display the image
basic_layered_img.show()
```



Figure 1: An example of layered style visualization on a simple sequential model with little styling

### 84 Advanced Usage

```
import visualkeras
from tensorflow.keras.models import Model
from tensorflow.keras.layers import Dense, Conv2D, MaxPooling2D, Flatten, Dropout
from PIL import ImageFont
from collections import defaultdict

# Define custom font for the model visualization
custom_font = ImageFont.truetype("arial.ttf", 24)

# Define custom color map
color_map = defaultdict(dict)
color_map[Conv2D]['fill'] = 'orange'
color_map[MaxPooling2D]['fill'] = 'red'
color_map[Dense]['fill'] = 'teal'

# Define a larger sequential model with more complexity
complex_sequential_model = Sequential([
    Conv2D(32, (3, 3), activation='relu', input_shape=(224, 224, 3)),
    Conv2D(32, (3, 3), activation='relu'),
    MaxPooling2D((2, 2)),
```

```
Dropout(0.25),

Conv2D(64, (3, 3), activation='relu'),
Conv2D(64, (3, 3), activation='relu'),
MaxPooling2D((2, 2)),
Dropout(0.25),

Conv2D(128, (3, 3), activation='relu'),
MaxPooling2D((2, 2)),
Dropout(0.25),

Flatten(),
Dense(256, activation='relu'),
Dropout(0.5),
Dense(128, activation='relu'),
Dropout(0.5),
Dense(10, activation='softmax')
])

# Advanced usage of visualkeras with custom styling
advanced_layered_img = visualkeras.layered_view(
    complex_sequential_model,
    legend=True, # Show legend
    font=custom_font, # Custom font for legend
    color_map=color_map, # Custom colors
    draw_volume=True, # 3D volumetric rendering
    draw_funnel=True, # Show funnel connectors
    spacing=50, # Increase spacing between layers
    padding=30, # Add padding around the visualization
    scale_xy=2, # Scale x-y dimensions
    scale_z=1, # Scale z dimension
    max_z=400, # Cap maximum z dimension
    font_color='black', # Legend font color
    one_dim_orientation='y', # Orientation for 1D layers
    sizing_mode='accurate', # Use balanced sizing for layers
    type_ignore=[Flatten, Dropout], # Ignore Flatten and Dropout layers
)

# Display the image
advanced_layered_img.show()
```




Figure 2: An example of a more complex model's Layered View with custom styling

## 85 Graph View

### 86 Basic Usage

```
import visulkeras
from tensorflow.keras.models import Sequential
from tensorflow.keras.layers import Dense, Conv2D, MaxPooling2D, Flatten, Dropout

# Define a simple sequential model
simple_sequential_model = Sequential([
    Conv2D(32, (3, 3), activation='relu', input_shape=(28, 28, 1)),
    MaxPooling2D((2, 2)),
    Conv2D(64, (3, 3), activation='relu'),
    MaxPooling2D((2, 2)),
    Conv2D(64, (3, 3), activation='relu'),
    Flatten(),
    Dense(64, activation='relu'),
    Dropout(0.5),
    Dense(10, activation='softmax')
])

# Basic usage of visulkeras to create a graph view
basic_graph_img = visulkeras.graph_view(simple_sequential_model)

# Display the image
basic_graph_img.show()
```




Figure 3: An example of Graph View visualization on a simple sequential model with little styling

## 87 Advanced Usage

```
import visualkeras
from tensorflow.keras.models import Model
from tensorflow.keras.layers import Dense, Conv2D, MaxPooling2D, Flatten, Dropout
from collections import defaultdict

# Define a larger sequential model with more complexity
complex_sequential_model = Sequential([
    Conv2D(32, (3, 3), activation='relu', input_shape=(224, 224, 3)),
    Conv2D(32, (3, 3), activation='relu'),
    MaxPooling2D((2, 2)),
    Dropout(0.25),

    Conv2D(64, (3, 3), activation='relu'),
    Conv2D(64, (3, 3), activation='relu'),
    MaxPooling2D((2, 2)),
    Dropout(0.25),

    Conv2D(128, (3, 3), activation='relu'),
    MaxPooling2D((2, 2)),
    Dropout(0.25),

    Flatten(),
    Dense(256, activation='relu'),
    Dropout(0.5),
    Dense(128, activation='relu'),
    Dropout(0.5),
    Dense(10, activation='softmax')
])

# Define custom color map for the graph view
graph_color_map = defaultdict(dict)
graph_color_map[Conv2D]['fill'] = 'lightblue'
graph_color_map[Conv2D]['outline'] = 'darkblue'
graph_color_map[MaxPooling2D]['fill'] = 'lightcoral'
graph_color_map[MaxPooling2D]['outline'] = 'darkred'
graph_color_map[Flatten]['fill'] = 'lightgreen'
graph_color_map[Flatten]['outline'] = 'darkgreen'
graph_color_map[Dense]['fill'] = 'lightyellow'
graph_color_map[Dense]['outline'] = 'darkorange'
graph_color_map[Dropout]['fill'] = 'lightpink'
graph_color_map[Dropout]['outline'] = 'purple'

# Create advanced graph view with customizations
```

```
advanced_graph_img = visualkeras.graph_view(
    complex_sequential_model,
    color_map=graph_color_map,           # Custom color scheme
    node_size=60,                         # Larger nodes
    connector_fill='gray',                # Gray connectors
    connector_width=2,                    # Thicker connectors
    layer_spacing=180,                    # More spacing between layers
    node_spacing=40,                      # Spacing between nodes in same layer
    padding=40,                           # Padding around the diagram
    background_fill='white',              # White background
    ellipsize_after=8                     # Ellipsize layers with >8 neurons
)

# Display the image
advanced_graph_img.show()
```




Figure 4: An example of a more complex model's Graph View with custom styling

## Acknowledgements

We thanks and acknowledge the contributions of the open-source community which has supported the development of visualkeras over the years through their feature requests, ideas, bug reports, issue discussions, and pull requests. These contributions have allowed us to continuously improve the package and adapt it to the needs of the community. We are grateful for the collaborative spirit that has made visualkeras a valuable tool for visualizing Keras and TensorFlow models.

Namely, we thank Alejandro Lorenzo, Erik Schultheis, Alessio G. Monti, Willy Fitra Hendria (Hendria & Gavrikov, 2024), Krzysztof Mizgała, Cosmin M. Marina, Martin Kubovčík, and others who have contributed to the project through their feedback and contributions.

## References

- Abadi, M., Agarwal, A., Barham, P., Brevdo, E., Chen, Z., Citro, C., Corrado, G. S., Davis, A., Dean, J., Devin, M., Ghemawat, S., Goodfellow, I., Harp, A., Irving, G., Isard, M., Jia, Y., Jozefowicz, R., Kaiser, L., Kudlur, M., ... Zheng, X. (2015). *TensorFlow: Large-scale machine learning on heterogeneous systems*. <https://www.tensorflow.org/>
- Chollet, F., & others. (2015). *Keras*. <https://keras.io>.
- Clark, A. (2015). *Pillow (PIL fork) documentation*. [readthedocs. /url%7Bhttps://buildmedia.readthedocs.org/media/pdf/pillow/latest/pillow.pdf%7D](https://buildmedia.readthedocs.org/media/pdf/pillow/latest/pillow.pdf)
- Hendria, W. F., & Gavrikov, P. (2024). VisualTorch: Streamlining visualization for PyTorch neural network architectures. *Journal of Open Source Software*, 9(102), 6678. <https://doi.org/10.21105/joss.06678>