

# Data Structures for Range-Sum Queries

## The Evolution of the Data Cube

Paul Butler

CUMC 2010  
Waterloo, Ontario

July 2010

# The Range-Sum Problem: Example

| Name            | Born         | City     | Height | Siblings | Pets |
|-----------------|--------------|----------|--------|----------|------|
| Joseph Matthews | Jan 9, 1987  | Waterloo | 172    | 2        | 1    |
| Sarah MacDonald | Nov 17, 1988 | Halifax  | 167    | 0        | 2    |
| ⋮               | ⋮            | ⋮        | ⋮      | ⋮        | ⋮    |

- How many people in Vancouver were born before 1990?

# The Range-Sum Problem: Example

| Name            | Born         | City     | Height | Siblings | Pets |
|-----------------|--------------|----------|--------|----------|------|
| Joseph Matthews | Jan 9, 1987  | Waterloo | 172    | 2        | 1    |
| Sarah MacDonald | Nov 17, 1988 | Halifax  | 167    | 0        | 2    |
| ⋮               | ⋮            | ⋮        | ⋮      | ⋮        | ⋮    |

- ▶ How many people in Vancouver were born before 1990?
- ▶ What is the average number of siblings for people above 170 cm?

# The Range-Sum Problem: Example

| Name            | Born         | City     | Height | Siblings | Pets |
|-----------------|--------------|----------|--------|----------|------|
| Joseph Matthews | Jan 9, 1987  | Waterloo | 172    | 2        | 1    |
| Sarah MacDonald | Nov 17, 1988 | Halifax  | 167    | 0        | 2    |
| ⋮               | ⋮            | ⋮        | ⋮      | ⋮        | ⋮    |

- ▶ How many people in Vancouver were born before 1990?
- ▶ What is the average number of siblings for people above 170 cm?
- ▶ What is the total number of pets owned by people 18 to 24 in Calgary?

# The Range-Sum Problem: Definitions

## Definition (Measure)

A column whose values we want to aggregate in our queries.

# The Range-Sum Problem: Definitions

## Definition (Measure)

A column whose values we want to aggregate in our queries.

## Example

The **Pets** and **Siblings** columns from the last example are **measures**

# The Range-Sum Problem: Definitions

## Definition (Measure)

A column whose values we want to aggregate in our queries.

## Example

The **Pets** and **Siblings** columns from the last example are **measures**

## Definition (Dimension)

A column we want to use to select columns which belong to our aggregation.

# The Range-Sum Problem: Definitions

## Definition (Measure)

A column whose values we want to aggregate in our queries.

## Example

The **Pets** and **Siblings** columns from the last example are **measures**

## Definition (Dimension)

A column we want to use to select columns which belong to our aggregation.

## Example

The **Born**, **City**, and **Height** columns are **dimensions**.



# Dimensions vs. Measures

- ▶ For each column, **dimension** vs. **measure** depends on which questions you want to answer.

# Dimensions vs. Measures

- ▶ For each column, **dimension** vs. **measure** depends on which questions you want to answer.
- ▶ *What is the average age of people with two pets*

# Dimensions vs. Measures

- ▶ For each column, **dimension** vs. **measure** depends on which questions you want to answer.
- ▶ *What is the average age of people with two pets*

# Dimensions vs. Measures

- ▶ For each column, **dimension** vs. **measure** depends on which questions you want to answer.
- ▶ *What is the average age of people with two pets*
  - ▶ **Born** would be a **measure**
  - ▶ **Pets** would be a **dimension**

# The Naïve Approach

- ▶ Store the data as a table
- ▶ For every row:
  - ▶ If the dimension columns match our query, add the value in the measure column to a running total
- ▶ Return the running total

# The Naïve Approach

- ▶ Store the data as a table
- ▶ For every row:
  - ▶ If the dimension columns match our query, add the value in the measure column to a running total
- ▶ Return the running total

**Too slow** for large amounts of data!

# Data Cubes

We can aggregate the data into a multi-dimensional array. [3]

| Pets   |     | Born |      |      |      |      |      |     |
|--------|-----|------|------|------|------|------|------|-----|
|        |     | ...  | 1985 | 1986 | 1987 | 1988 | 1989 | ... |
| Height | ⋮   | ⋮    | ⋮    | ⋮    | ⋮    | ⋮    | ⋮    | ⋮   |
|        | 165 | ...  | 192  | 342  | 558  | 56   | 591  | ... |
|        | 166 | ...  | 325  | 275  | 707  | 855  | 484  | ... |
|        | 167 | ...  | 487  | 326  | 363  | 193  | 350  | ... |
|        | 168 | ...  | 326  | 363  | 193  | 350  | 422  | ... |
|        | 169 | ...  | 438  | 456  | 550  | 385  | 412  | ... |
|        | ⋮   | ⋮    | ⋮    | ⋮    | ⋮    | ⋮    | ⋮    | ⋮   |

# Data Cubes

We can aggregate the data into a multi-dimensional array. [3]

| Pets   |     | Born |      |      |      |      |      |     |
|--------|-----|------|------|------|------|------|------|-----|
|        |     | ...  | 1985 | 1986 | 1987 | 1988 | 1989 | ... |
| Height | ⋮   | ⋮    | ⋮    | ⋮    | ⋮    | ⋮    | ⋮    | ⋮   |
|        | 165 | ...  | 192  | 342  | 558  | 56   | 591  | ... |
|        | 166 | ...  | 325  | 275  | 707  | 855  | 484  | ... |
|        | 167 | ...  | 487  | 326  | 363  | 193  | 350  | ... |
|        | 168 | ...  | 326  | 363  | 193  | 350  | 422  | ... |
|        | 169 | ...  | 438  | 456  | 550  | 385  | 412  | ... |
|        | ⋮   | ⋮    | ⋮    | ⋮    | ⋮    | ⋮    | ⋮    | ⋮   |

Now cells not selected by the query are ignored.  
Less lookups, faster queries (but still too slow).



# Data Cubes

## Example

What is the total number of pets owned by people born between 1986 and 1988 and height between 166 and 168 cm?

| Pets   |     | Born |      |      |      |      |      |     |
|--------|-----|------|------|------|------|------|------|-----|
|        |     | ...  | 1985 | 1986 | 1987 | 1988 | 1989 | ... |
| Height | ⋮   | ⋮    | ⋮    | ⋮    | ⋮    | ⋮    | ⋮    | ⋮   |
|        | 165 | ...  | 192  | 342  | 558  | 56   | 591  | ... |
|        | 166 | ...  | 325  | 275  | 707  | 855  | 484  | ... |
|        | 167 | ...  | 487  | 326  | 363  | 193  | 350  | ... |
|        | 168 | ...  | 326  | 363  | 193  | 350  | 422  | ... |
|        | 169 | ...  | 438  | 456  | 550  | 385  | 412  | ... |
|        | ⋮   | ⋮    | ⋮    | ⋮    | ⋮    | ⋮    | ⋮    | ⋮   |

# Data Cubes

## Example

What is the total number of pets owned by people born between 1986 and 1988 and height between 166 and 168 cm?

| Pets   |     | Born |      |      |      |      |      |     |
|--------|-----|------|------|------|------|------|------|-----|
|        |     | ...  | 1985 | 1986 | 1987 | 1988 | 1989 | ... |
| Height | ⋮   | ⋮    | ⋮    | ⋮    | ⋮    | ⋮    | ⋮    | ⋮   |
|        | 165 | ...  | 192  | 342  | 558  | 56   | 591  | ... |
|        | 166 | ...  | 325  | 275  | 707  | 855  | 484  | ... |
|        | 167 | ...  | 487  | 326  | 363  | 193  | 350  | ... |
|        | 168 | ...  | 326  | 363  | 193  | 350  | 422  | ... |
|        | 169 | ...  | 438  | 456  | 550  | 385  | 412  | ... |
|        | ⋮   | ⋮    | ⋮    | ⋮    | ⋮    | ⋮    | ⋮    | ⋮   |

$$275 + 707 + 855 + 326 + 363 + 193 + 363 + 193 + 350 = \mathbf{3625}$$

# Data Cubes

We can calculate partial sums for each row, column, etc. [3]

| Pets   |     | Born |      |      |      |      |      |     |        |
|--------|-----|------|------|------|------|------|------|-----|--------|
|        |     | ...  | 1985 | 1986 | 1987 | 1988 | 1989 | ... | Sum    |
| Height | ⋮   | ⋮    | ⋮    | ⋮    | ⋮    | ⋮    | ⋮    | ⋮   | ⋮      |
|        | 165 | ...  | 192  | 342  | 558  | 56   | 591  | ... | 10937  |
|        | 166 | ...  | 325  | 275  | 707  | 855  | 484  | ... | 10998  |
|        | 167 | ...  | 487  | 326  | 363  | 193  | 350  | ... | 11064  |
|        | 168 | ...  | 326  | 363  | 193  | 350  | 422  | ... | 10913  |
|        | 169 | ...  | 438  | 456  | 550  | 385  | 412  | ... | 11347  |
|        | ⋮   | ⋮    | ⋮    | ⋮    | ⋮    | ⋮    | ⋮    | ⋮   | ⋮      |
|        | Sum | ...  | 8121 | 8255 | 8206 | 8820 | 8026 | ... | 202169 |

# Data Cubes

We can calculate partial sums for each row, column, etc. [3]

| Pets   |     | Born |      |      |      |      |      |     |        |
|--------|-----|------|------|------|------|------|------|-----|--------|
|        |     | ...  | 1985 | 1986 | 1987 | 1988 | 1989 | ... | Sum    |
| Height | ⋮   | ⋮    | ⋮    | ⋮    | ⋮    | ⋮    | ⋮    | ⋮   | ⋮      |
|        | 165 | ...  | 192  | 342  | 558  | 56   | 591  | ... | 10937  |
|        | 166 | ...  | 325  | 275  | 707  | 855  | 484  | ... | 10998  |
|        | 167 | ...  | 487  | 326  | 363  | 193  | 350  | ... | 11064  |
|        | 168 | ...  | 326  | 363  | 193  | 350  | 422  | ... | 10913  |
|        | 169 | ...  | 438  | 456  | 550  | 385  | 412  | ... | 11347  |
|        | ⋮   | ⋮    | ⋮    | ⋮    | ⋮    | ⋮    | ⋮    | ⋮   | ⋮      |
|        | Sum | ...  | 8121 | 8255 | 8206 | 8820 | 8026 | ... | 202169 |

Queries which only mention a subset of the dimensions now run faster.

# Data Cubes

## Example

How many pets are owned by people born between 1986 and 1988 (inclusive)?

| Pets   |     | Born |      |      |      |      |      |     |        |
|--------|-----|------|------|------|------|------|------|-----|--------|
|        |     | ...  | 1985 | 1986 | 1987 | 1988 | 1989 | ... | Sum    |
| Height | ⋮   | ⋮    | ⋮    | ⋮    | ⋮    | ⋮    | ⋮    | ⋮   | ⋮      |
|        | 165 | ...  | 192  | 342  | 558  | 56   | 591  | ... | 10937  |
|        | 166 | ...  | 325  | 275  | 707  | 855  | 484  | ... | 10998  |
|        | 167 | ...  | 487  | 326  | 363  | 193  | 350  | ... | 11064  |
|        | 168 | ...  | 326  | 363  | 193  | 350  | 422  | ... | 10913  |
|        | 169 | ...  | 438  | 456  | 550  | 385  | 412  | ... | 11347  |
|        | ⋮   | ⋮    | ⋮    | ⋮    | ⋮    | ⋮    | ⋮    | ⋮   | ⋮      |
|        | Sum | ...  | 8121 | 8255 | 8206 | 8820 | 8026 | ... | 202169 |

# Data Cubes

## Example

How many pets are owned by people born between 1986 and 1988 (inclusive)?

| Pets   |     | Born |      |      |      |      |      |     |        |
|--------|-----|------|------|------|------|------|------|-----|--------|
|        |     | ...  | 1985 | 1986 | 1987 | 1988 | 1989 | ... | Sum    |
| Height | ⋮   | ⋮    | ⋮    | ⋮    | ⋮    | ⋮    | ⋮    | ⋮   | ⋮      |
|        | 165 | ...  | 192  | 342  | 558  | 56   | 591  | ... | 10937  |
|        | 166 | ...  | 325  | 275  | 707  | 855  | 484  | ... | 10998  |
|        | 167 | ...  | 487  | 326  | 363  | 193  | 350  | ... | 11064  |
|        | 168 | ...  | 326  | 363  | 193  | 350  | 422  | ... | 10913  |
|        | 169 | ...  | 438  | 456  | 550  | 385  | 412  | ... | 11347  |
|        | ⋮   | ⋮    | ⋮    | ⋮    | ⋮    | ⋮    | ⋮    | ⋮   | ⋮      |
|        | Sum | ...  | 8121 | 8255 | 8206 | 8820 | 8026 | ... | 202169 |

$$8255 + 8206 + 8820 = \mathbf{25281}$$

With **Data Cubes**, the question becomes  
*How do we find the sum of values which fall inside a given (hyper)rectangle in a multidimensional array?*


# Prefix-Sum Table

Observation: range sums can be computed as a sum of four range queries starting from 0. [4]




# Prefix-Sum Table

Observation: range sums can be computed as a sum of four range queries starting from 0. [4]




# Prefix-Sum Table

Observation: range sums can be computed as a sum of four range queries starting from 0. [4]




# Prefix-Sum Table

Observation: range sums can be computed as a sum of four range queries starting from 0. [4]




# Prefix-Sum Table

Observation: range sums can be computed as a sum of four range queries starting from 0. [4]




# Prefix-Sum Table

Observation: range sums can be computed as a sum of four range queries starting from 0. [4]



# Prefix-Sum Table

Observation: range sums can be computed as a sum of four range queries starting from 0. [4]



In general:  $\leq 2^d$  operations, where  $d$  is number of dimensions.

With **Prefix-Sum Tables**, the question becomes  
*How do we find the sum of values which fall inside a given  
(hyper)rectangle in a multidimensional array **with one corner fixed  
at the origin?***

# Prefix-Sum Table

Array A

| Index | 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 |
|-------|---|---|---|---|---|---|---|---|---|
| 0     | 3 | 5 | 1 | 2 | 2 | 4 | 6 | 3 | 3 |
| 1     | 7 | 3 | 2 | 6 | 8 | 7 | 1 | 2 | 4 |
| 2     | 2 | 4 | 2 | 3 | 3 | 3 | 4 | 5 | 7 |
| 3     | 3 | 2 | 1 | 5 | 3 | 5 | 2 | 8 | 2 |
| 4     | 4 | 2 | 1 | 3 | 3 | 4 | 7 | 1 | 3 |
| 5     | 2 | 3 | 3 | 6 | 1 | 8 | 5 | 1 | 1 |
| 6     | 4 | 5 | 2 | 7 | 1 | 9 | 3 | 3 | 4 |
| 7     | 2 | 4 | 2 | 2 | 3 | 1 | 9 | 1 | 3 |
| 8     | 5 | 4 | 3 | 1 | 3 | 2 | 1 | 9 | 6 |

Array P

| Index | 0  | 1  | 2  | 3   | 4   | 5   | 6   | 7   | 8   |
|-------|----|----|----|-----|-----|-----|-----|-----|-----|
| 0     | 3  | 8  | 9  | 11  | 13  | 17  | 23  | 26  | 29  |
| 1     | 10 | 18 | 21 | 29  | 39  | 50  | 57  | 62  | 69  |
| 2     | 12 | 24 | 29 | 40  | 53  | 67  | 78  | 88  | 102 |
| 3     | 15 | 29 | 35 | 51  | 67  | 86  | 99  | 117 | 133 |
| 4     | 19 | 35 | 42 | 61  | 80  | 103 | 123 | 142 | 161 |
| 5     | 21 | 40 | 50 | 75  | 95  | 126 | 151 | 171 | 191 |
| 6     | 25 | 49 | 61 | 93  | 114 | 154 | 182 | 205 | 229 |
| 7     | 27 | 55 | 69 | 103 | 127 | 168 | 205 | 229 | 256 |
| 8     | 32 | 64 | 81 | 116 | 143 | 186 | 224 | 257 | 290 |

[1]



# Updating the Prefix-Sum Table

Array A

| Index | 0 | 1   | 2 | 3 | 4 | 5 | 6 | 7 | 8 |
|-------|---|-----|---|---|---|---|---|---|---|
| 0     | 3 | 5   | 1 | 2 | 2 | 4 | 6 | 3 | 3 |
| 1     | 7 | * 4 | 2 | 6 | 8 | 7 | 1 | 2 | 4 |
| 2     | 2 | 4   | 2 | 3 | 3 | 3 | 4 | 5 | 7 |
| 3     | 3 | 2   | 1 | 5 | 3 | 5 | 2 | 8 | 2 |
| 4     | 4 | 2   | 1 | 3 | 3 | 4 | 7 | 1 | 3 |
| 5     | 2 | 3   | 3 | 6 | 1 | 8 | 5 | 1 | 1 |
| 6     | 4 | 5   | 2 | 7 | 1 | 9 | 3 | 3 | 4 |
| 7     | 2 | 4   | 2 | 2 | 3 | 1 | 9 | 1 | 3 |
| 8     | 5 | 4   | 3 | 1 | 3 | 2 | 1 | 9 | 6 |

Array P

| Index | 0  | 1    | 2  | 3   | 4   | 5   | 6   | 7   | 8   |
|-------|----|------|----|-----|-----|-----|-----|-----|-----|
| 0     | 3  | 8    | 9  | 11  | 13  | 17  | 23  | 26  | 29  |
| 1     | 10 | * 19 | 22 | 30  | 40  | 51  | 58  | 63  | 70  |
| 2     | 12 | 25   | 30 | 41  | 54  | 68  | 79  | 89  | 103 |
| 3     | 15 | 30   | 36 | 52  | 68  | 87  | 100 | 118 | 134 |
| 4     | 19 | 36   | 43 | 62  | 81  | 104 | 124 | 143 | 162 |
| 5     | 21 | 41   | 51 | 76  | 96  | 127 | 152 | 172 | 192 |
| 6     | 25 | 50   | 62 | 94  | 115 | 155 | 183 | 206 | 230 |
| 7     | 27 | 56   | 70 | 104 | 128 | 169 | 206 | 230 | 257 |
| 8     | 32 | 65   | 82 | 117 | 144 | 187 | 225 | 258 | 291 |

[1]

# Relative Prefix Method

Geffner, Agrawal, El Abbadi, Smith [1] introduced two new tables

- ▶ relative-prefix table
- ▶ overlay table

# Overlay Table - Anchor Value

| Index | 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 |
|-------|---|---|---|---|---|---|---|---|---|
| 0     |   |   |   |   |   |   |   |   |   |
| 1     |   |   |   |   |   |   |   |   |   |
| 2     |   |   |   |   |   |   |   |   |   |
| 3     |   |   |   |   |   |   |   |   |   |
| 4     |   |   |   |   |   |   |   |   |   |
| 5     |   |   |   |   |   |   |   |   |   |
| 6     |   |   |   | V |   |   |   |   |   |
| 7     |   |   |   |   |   |   |   |   |   |
| 8     |   |   |   |   |   |   |   |   |   |

[1]

# Overlay Table - Outer Values

| Index | 0 | 1 | 2 | 3     | 4     | 5 | 6 | 7 | 8 |
|-------|---|---|---|-------|-------|---|---|---|---|
| 0     |   |   |   |       |       |   |   |   |   |
| 1     |   |   |   |       |       |   |   |   |   |
| 2     |   |   |   |       |       |   |   |   |   |
| 3     |   |   |   |       |       |   |   |   |   |
| 4     |   |   |   |       |       |   |   |   |   |
| 5     |   |   |   |       |       |   |   |   |   |
| 6     |   |   |   |       | $X_1$ |   |   |   |   |
| 7     |   |   |   | $Y_1$ |       |   |   |   |   |
| 8     |   |   |   |       |       |   |   |   |   |

| Index | 0 | 1 | 2 | 3     | 4 | 5     | 6 | 7 | 8 |
|-------|---|---|---|-------|---|-------|---|---|---|
| 0     |   |   |   |       |   |       |   |   |   |
| 1     |   |   |   |       |   |       |   |   |   |
| 2     |   |   |   |       |   |       |   |   |   |
| 3     |   |   |   |       |   |       |   |   |   |
| 4     |   |   |   |       |   |       |   |   |   |
| 5     |   |   |   |       |   |       |   |   |   |
| 6     |   |   |   |       |   | $X_2$ |   |   |   |
| 7     |   |   |   |       |   |       |   |   |   |
| 8     |   |   |   | $Y_2$ |   |       |   |   |   |

[1]

# Relative Prefix Table

Relative Prefix (RP) array

| Index | 0  | 1  | 2  | 3  | 4  | 5  | 6  | 7  | 8  |
|-------|----|----|----|----|----|----|----|----|----|
| 0     | 3  | 8  | 9  | 2  | 4  | 8  | 6  | 9  | 12 |
| 1     | 10 | 18 | 21 | 8  | 18 | 29 | 7  | 12 | 19 |
| 2     | 12 | 24 | 29 | 11 | 24 | 38 | 11 | 21 | 35 |
| 3     | 3  | 5  | 6  | 5  | 8  | 13 | 2  | 10 | 12 |
| 4     | 7  | 11 | 13 | 8  | 14 | 23 | 9  | 18 | 23 |
| 5     | 9  | 16 | 21 | 14 | 21 | 38 | 14 | 24 | 30 |
| 6     | 4  | 9  | 11 | 7  | 8  | 17 | 3  | 6  | 10 |
| 7     | 6  | 15 | 19 | 9  | 13 | 23 | 12 | 16 | 23 |
| 8     | 11 | 24 | 31 | 10 | 17 | 29 | 13 | 26 | 39 |

[1]

# Relative Prefix Method

Array A

| Index | 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 |
|-------|---|---|---|---|---|---|---|---|---|
| 0     | 3 | 5 | 1 | 2 | 2 | 4 | 6 | 3 | 3 |
| 1     | 7 | 3 | 2 | 6 | 8 | 7 | 1 | 2 | 4 |
| 2     | 2 | 4 | 2 | 3 | 3 | 3 | 4 | 5 | 7 |
| 3     | 3 | 2 | 1 | 5 | 3 | 5 | 2 | 8 | 2 |
| 4     | 4 | 2 | 1 | 3 | 3 | 4 | 7 | 1 | 3 |
| 5     | 2 | 3 | 3 | 6 | 1 | 8 | 5 | 1 | 1 |
| 6     | 4 | 5 | 2 | 7 | 1 | 9 | 3 | 3 | 4 |
| 7     | 2 | 4 | 2 | 2 | 3 | 1 | 9 | 1 | 3 |
| 8     | 5 | 4 | 3 | 1 | 3 | 2 | 1 | 9 | 6 |

Overlay boxes of size 3x3

| Index | 0  | 1  | 2  | 3  | 4  | 5  | 6   | 7  | 8  |
|-------|----|----|----|----|----|----|-----|----|----|
| 0     | 0  | 0  | 0  | 9  | 0  | 0  | 17  | 0  | 0  |
| 1     | 0  |    |    | 12 |    |    | 33  |    |    |
| 2     | 0  |    |    | 20 |    |    | 50  |    |    |
| 3     | 12 | 12 | 17 | 46 | 13 | 27 | 97  | 10 | 24 |
| 4     | 0  |    |    | 7  |    |    | 17  |    |    |
| 5     | 0  |    |    | 15 |    |    | 40  |    |    |
| 6     | 21 | 19 | 29 | 86 | 20 | 51 | 179 | 20 | 40 |
| 7     | 0  |    |    | 8  | *  |    | 14  |    |    |
| 8     | 0  |    |    | 20 |    |    | 32  |    |    |

Relative Prefix (RP) array

| Index | 0  | 1  | 2  | 3  | 4  | 5    | 6  | 7  | 8  |
|-------|----|----|----|----|----|------|----|----|----|
| 0     | 3  | 8  | 9  | 2  | 4  | 8    | 6  | 9  | 12 |
| 1     | 10 | 18 | 21 | 8  | 18 | 29   | 7  | 12 | 19 |
| 2     | 12 | 24 | 29 | 11 | 24 | 38   | 11 | 21 | 35 |
| 3     | 3  | 5  | 6  | 5  | 8  | 13   | 2  | 10 | 12 |
| 4     | 7  | 11 | 13 | 8  | 14 | 23   | 9  | 18 | 23 |
| 5     | 9  | 16 | 21 | 14 | 21 | 38   | 14 | 24 | 30 |
| 6     | 4  | 9  | 11 | 7  | 8  | 17   | 3  | 6  | 10 |
| 7     | 6  | 15 | 19 | 9  | 13 | * 23 | 12 | 16 | 23 |
| 8     | 11 | 24 | 31 | 10 | 17 | 29   | 13 | 26 | 39 |

[1]

# Updating Overlay and Relative Prefix Table

| Index | 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 |
|-------|---|---|---|---|---|---|---|---|---|
| 0     |   |   |   |   |   |   |   |   |   |
| 1     |   | * |   |   |   |   |   |   |   |
| 2     |   |   |   |   |   |   |   |   |   |
| 3     |   |   |   |   |   |   |   |   |   |
| 4     |   |   |   |   |   |   |   |   |   |
| 5     |   |   |   |   |   |   |   |   |   |
| 6     |   |   |   |   |   |   |   |   |   |
| 7     |   |   |   |   |   |   |   |   |   |
| 8     |   |   |   |   |   |   |   |   |   |

Figure 14. Overlay regions during an update.

Relative Prefix (RP) array

| Index | 0  | 1    | 2  | 3  | 4  | 5  | 6  | 7  | 8  |
|-------|----|------|----|----|----|----|----|----|----|
| 0     | 3  | 8    | 9  | 2  | 4  | 8  | 6  | 9  | 12 |
| 1     | 10 | * 19 | 22 | 8  | 18 | 29 | 7  | 12 | 19 |
| 2     | 12 | 25   | 30 | 11 | 24 | 38 | 11 | 21 | 35 |
| 3     | 3  | 5    | 6  | 5  | 8  | 13 | 2  | 10 | 12 |
| 4     | 7  | 11   | 13 | 8  | 14 | 23 | 9  | 18 | 23 |
| 5     | 9  | 16   | 21 | 14 | 21 | 38 | 14 | 24 | 30 |
| 6     | 4  | 9    | 11 | 7  | 8  | 17 | 3  | 6  | 10 |
| 7     | 6  | 15   | 19 | 9  | 13 | 23 | 12 | 16 | 23 |
| 8     | 11 | 24   | 31 | 10 | 17 | 29 | 13 | 26 | 39 |

Overlay boxes

| Index | 0  | 1  | 2  | 3  | 4  | 5  | 6   | 7  | 8  |
|-------|----|----|----|----|----|----|-----|----|----|
| 0     | 0  | 0  | 0  | 9  | 0  | 0  | 17  | 0  | 0  |
| 1     | 0  | *  |    | 13 |    |    | 34  |    |    |
| 2     | 0  |    |    | 21 |    |    | 51  |    |    |
| 3     | 12 | 13 | 18 | 47 | 13 | 27 | 98  | 10 | 24 |
| 4     | 0  |    |    | 7  |    |    | 17  |    |    |
| 5     | 0  |    |    | 15 |    |    | 40  |    |    |
| 6     | 21 | 20 | 30 | 87 | 20 | 51 | 180 | 20 | 40 |
| 7     | 0  |    |    | 8  |    |    | 14  |    |    |
| 8     | 0  |    |    | 20 |    |    | 32  |    |    |

# Dynamic Data Cube

Root:

|    |           |          |           |
|----|-----------|----------|-----------|
| Q  | 11        | R        | 15        |
|    | 29        |          | 33        |
|    | 40        |          | 48        |
| 15 | 29        | 35       | <b>51</b> |
|    |           | 16       | 35        |
|    |           |          | <b>48</b> |
|    |           |          | 66        |
| S  | 10        | <b>T</b> | 15        |
|    | <b>24</b> |          | 31        |
|    | 42        |          | 47        |
| 12 | 26        | 34       | 52        |
|    |           | 8        | 30        |
|    |           |          | 54        |
|    |           |          | 61        |

**T**:

|   |           |            |    |
|---|-----------|------------|----|
| U | 7         | <b>V</b>   | 8  |
| 4 | <b>16</b> | <b>12*</b> | 15 |
| W | 10        | Z          | 6  |
| 4 | 14        | 12         | 16 |

**V**:

|           |   |
|-----------|---|
| 7         | 1 |
| <b>5*</b> | 2 |

[2]



# Dynamic Data Cube

Root:

|                    |                 |          |             |
|--------------------|-----------------|----------|-------------|
| Q                  | 11              | R        | 15          |
|                    | 29              |          | 33          |
|                    | 40              |          | 48          |
| 15 29 35 <b>51</b> | 16 35 <b>48</b> | 66       |             |
| S                  | 10              | <b>T</b> | 15          |
|                    | <b>24</b>       |          | <b>*</b> 31 |
|                    | 42              |          | 47          |
| 12 26 34 52        | 8 30 54         | 61       |             |

**T**:

|             |               |
|-------------|---------------|
| U 7         | <b>V</b> 8    |
| 4 <b>16</b> | <b>12*</b> 15 |
| W 10        | Z 6           |
| 4 14        | 12 16         |

**V**:

|           |   |
|-----------|---|
| 7         | 1 |
| <b>5*</b> | 2 |

# Dynamic Data Cube

Root:

|    |    |    |    |           |          |    |    |           |    |
|----|----|----|----|-----------|----------|----|----|-----------|----|
| Q  |    |    |    | 11        | R        |    |    |           | 15 |
|    |    |    |    | 29        |          |    |    |           | 33 |
|    |    |    |    | 40        |          |    |    |           | 48 |
|    | 15 | 29 | 35 | <b>51</b> |          | 16 | 35 | <b>48</b> | 66 |
|    |    |    |    |           |          |    |    |           |    |
| S  |    |    |    | 10        | <b>T</b> |    |    |           | 15 |
|    |    |    |    | <b>24</b> |          |    |    |           | 31 |
|    |    |    |    |           |          |    |    |           | *  |
|    |    |    | 42 |           |          |    |    |           | 47 |
|    |    |    |    |           |          |    |    |           |    |
| 12 | 26 | 34 | 52 |           | 8        | 30 | 54 | 61        |    |

**T**:

|   |           |            |    |
|---|-----------|------------|----|
| U | 7         | <b>V</b>   | 8  |
| 4 | <b>16</b> | <b>12*</b> | 15 |
| W | 10        | Z          | 6  |
| 4 | 14        | 12         | 16 |

**V**:

|           |   |
|-----------|---|
| 7         | 1 |
| <b>5*</b> | 2 |



Steve Geffner, Divyakanth Agrawal, Amr El Abbadi, and Terry Smith.

Relative prefix sums: An efficient approach for querying dynamic olap data cubes.

Technical report, Santa Barbara, CA, USA, 1999.



Steven Geffner, Divyakant Agrawal, and Amr El Abbadi.

The dynamic data cube.

In Carlo Zaniolo, Peter C. Lockemann, Marc H. Scholl, and Torsten Grust, editors, *EDBT*, volume 1777 of *Lecture Notes in Computer Science*, pages 237–253. Springer, 2000.



Jim Gray, Adam Bosworth, Andrew Layman, Don Reichart, and Hamid Pirahesh.

Data cube: A relational aggregation operator generalizing group-by, cross-tab, and sub-totals.

pages 152–159, 1996.



Ching-Tien Ho, Rakesh Agrawal, Nimrod Megiddo, and Ramakrishnan Srikant.

Range queries in olap data cubes.

*SIGMOD Rec.*, 26(2):73–88, 1997.

## Slides

[github.com/paulgb/cumc2010/raw/master/slides.pdf](https://github.com/paulgb/cumc2010/raw/master/slides.pdf)

## Try Sage!

[sagemath.org](https://sagemath.org)