

echoclient

Generated by Doxygen 1.8.1.2

Sat Aug 31 2013 19:09:45



# Contents

|          |                                |          |
|----------|--------------------------------|----------|
| <b>1</b> | <b>File Index</b>              | <b>1</b> |
| 1.1      | File List                      | 1        |
| <b>2</b> | <b>File Documentation</b>      | <b>3</b> |
| 2.1      | helper.c File Reference        | 3        |
| 2.1.1    | Detailed Description           | 4        |
| 2.1.2    | Macro Definition Documentation | 4        |
| 2.1.2.1  | MAX_BUFFER_SIZE                | 4        |
| 2.1.3    | Function Documentation         | 4        |
| 2.1.3.1  | get_errmsg                     | 4        |
| 2.1.3.2  | mk_errmsg                      | 4        |
| 2.1.3.3  | mk_errno_errmsg                | 5        |
| 2.1.3.4  | set_errmsg                     | 5        |
| 2.1.3.5  | set_errno_errmsg               | 5        |
| 2.1.3.6  | trim                           | 5        |
| 2.1.3.7  | trim_left                      | 5        |
| 2.1.3.8  | trim_line_ending               | 6        |
| 2.1.3.9  | trim_right                     | 6        |
| 2.1.4    | Variable Documentation         | 6        |
| 2.1.4.1  | helper_error_msg               | 6        |
| 2.2      | helper.h File Reference        | 6        |
| 2.2.1    | Detailed Description           | 8        |
| 2.2.2    | Macro Definition Documentation | 8        |
| 2.2.2.1  | DFPRINTF                       | 8        |
| 2.2.2.2  | DPRINTF                        | 8        |
| 2.2.2.3  | ERROR_RETURN                   | 8        |
| 2.2.2.4  | FALSE                          | 8        |
| 2.2.2.5  | TRUE                           | 8        |
| 2.2.3    | Function Documentation         | 8        |
| 2.2.3.1  | get_errmsg                     | 8        |
| 2.2.3.2  | mk_errmsg                      | 9        |

|         |   |    |
|---------|---|----|
| 2.2.3.3 | <a href="#">mk_errno_errmsg</a>                 | 9  |
| 2.2.3.4 | <a href="#">set_errmsg</a>                      | 9  |
| 2.2.3.5 | <a href="#">set_errno_errmsg</a>                | 9  |
| 2.2.3.6 | <a href="#">trim</a>                            | 9  |
| 2.2.3.7 | <a href="#">trim_left</a>                       | 10 |
| 2.2.3.8 | <a href="#">trim_line_ending</a>                | 10 |
| 2.2.3.9 | <a href="#">trim_right</a>                      | 10 |
| 2.3     | <a href="#">main.c File Reference</a>           | 11 |
| 2.3.1   | <a href="#">Detailed Description</a>            | 11 |
| 2.3.2   | <a href="#">Macro Definition Documentation</a>  | 12 |
| 2.3.2.1 | <a href="#">MAX_BUFFER_LEN</a>                  | 12 |
| 2.3.3   | <a href="#">Function Documentation</a>          | 12 |
| 2.3.3.1 | <a href="#">connect_with_command_line_args</a>  | 12 |
| 2.3.3.2 | <a href="#">main</a>                            | 12 |
| 2.3.3.3 | <a href="#">run_echo_client</a>                 | 12 |
| 2.4     | <a href="#">socket_helpers.c File Reference</a> | 12 |
| 2.4.1   | <a href="#">Detailed Description</a>            | 13 |
| 2.4.2   | <a href="#">Macro Definition Documentation</a>  | 14 |
| 2.4.2.1 | <a href="#">MAX_BUFFER_SIZE</a>                 | 14 |
| 2.4.3   | <a href="#">Function Documentation</a>          | 14 |
| 2.4.3.1 | <a href="#">conn_socket_from_string</a>         | 14 |
| 2.4.3.2 | <a href="#">ignore_sigpipe</a>                  | 14 |
| 2.4.3.3 | <a href="#">port_from_string</a>                | 14 |
| 2.4.3.4 | <a href="#">socket_readline</a>                 | 14 |
| 2.4.3.5 | <a href="#">socket_readline_timeout</a>         | 15 |
| 2.4.3.6 | <a href="#">socket_writeline</a>                | 15 |
| 2.5     | <a href="#">socket_helpers.h File Reference</a> | 15 |
| 2.5.1   | <a href="#">Detailed Description</a>            | 16 |
| 2.5.2   | <a href="#">Function Documentation</a>          | 17 |
| 2.5.2.1 | <a href="#">conn_socket_from_string</a>         | 17 |
| 2.5.2.2 | <a href="#">ignore_sigpipe</a>                  | 17 |
| 2.5.2.3 | <a href="#">port_from_string</a>                | 17 |
| 2.5.2.4 | <a href="#">socket_readline</a>                 | 17 |
| 2.5.2.5 | <a href="#">socket_readline_timeout</a>         | 18 |
| 2.5.2.6 | <a href="#">socket_writeline</a>                | 18 |

# Chapter 1

## File Index

### 1.1 File List

Here is a list of all files with brief descriptions:

|                                  |   |    |
|----------------------------------|---|----|
| <a href="#">helper.c</a>         | Implementation of helper functions . . . . .        | 3  |
| <a href="#">helper.h</a>         | Interface to helper functions . . . . .             | 6  |
| <a href="#">main.c</a>           | Main function for echoclient . . . . .              | 11 |
| <a href="#">socket_helpers.c</a> | Implementation of socket helper functions . . . . . | 12 |
| <a href="#">socket_helpers.h</a> | Interface to socket helper functions . . . . .      | 15 |



## Chapter 2


# File Documentation

### 2.1 helper.c File Reference

Implementation of helper functions.

```
#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include <ctype.h>
#include <errno.h>
#include "helper.h"
```

Include dependency graph for helper.c:



#### Macros

- `#define MAX_BUFFER_SIZE 1024`  
*Maximum character buffer size.*

#### Functions

- `char * get_errmsg (void)`  
*Gets the global error message.*
- `void set_errmsg (const char *buffer)`  
*Sets the global error message.*
- `void set_errno_errmsg (const char *buffer)`  
*Sets the global error message based on errno.*
- `void mk_errmsg (const char *buffer, char **error_msg)`  
*Makes an error message.*

- void `mk_errno_errmsg` (const char \*buffer, char \*\*error\_msg)  
*Makes an error message based on errno.*
- char \* `trim_line_ending` (char \*buffer)  
*Trims CR and LF characters from the end of a string.*
- char \* `trim_right` (char \*buffer)  
*Trims trailing whitespace from a string.*
- char \* `trim_left` (char \*buffer)  
*Trims leading whitespace from a string.*
- char \* `trim` (char \*buffer)  
*Trims leading and trailing whitespace from a string.*

## Variables

- static char `helper_error_msg` [MAX\_BUFFER\_SIZE] = {0}  
*Global error message string.*

### 2.1.1 Detailed Description

Implementation of helper functions.

#### Author

Paul Griffiths

#### Copyright

Copyright 2013 Paul Griffiths. Distributed under the terms of the GNU General Public License. <http://www.gnu.org/licenses/>

### 2.1.2 Macro Definition Documentation

#### 2.1.2.1 #define MAX\_BUFFER\_SIZE 1024

Maximum character buffer size.

### 2.1.3 Function Documentation

#### 2.1.3.1 char\* get\_errmsg ( void )

Gets the global error message.

#### Returns

A pointer to the global error message.

#### 2.1.3.2 void mk\_errmsg ( const char \* buffer, char \*\* error\_msg )

Makes an error message.

This function provides a thread-safe way for a function to set an error message.

#### Parameters



|                  |  |
|------------------|--|
| <i>buffer</i>    | A buffer containing the error message.   |
| <i>error_msg</i> | A pointer to a char pointer which will refer to the error message. This should be free()d by the called. |

#### 2.1.3.3 void mk\_errno\_errmsg ( const char \* *buffer*, char \*\* *error\_msg* )

Makes an error message based on errno.

This function provides a thread-safe way for a function to set an error message, with the usual caveat that errno itself is not threadsafe.

##### Parameters

|                  |  |
|------------------|--|
| <i>buffer</i>    | A buffer containing the error message.   |
| <i>error_msg</i> | A pointer to a char pointer which will refer to the error message. This should be free()d by the called. |

#### 2.1.3.4 void set\_errmsg ( const char \* *buffer* )

Sets the global error message.

Uses a statically allocated buffer, so this is not thread-safe.

##### Parameters

|               |  |
|---------------|--|
| <i>buffer</i> | A buffer containing the error message. |
|---------------|--|

#### 2.1.3.5 void set\_errno\_errmsg ( const char \* *buffer* )

Sets the global error message based on errno.

Uses a statically allocated buffer, so this is not thread-safe.

##### Parameters

|               |  |
|---------------|--|
| <i>buffer</i> | A buffer containing the error message. |
|---------------|--|

#### 2.1.3.6 char\* trim ( char \* *buffer* )

Trims leading and trailing whitespace from a string.

##### Parameters

|               |                     |
|---------------|---------------------|
| <i>buffer</i> | The string to trim. |
|---------------|---------------------|

##### Returns

A pointer to the passed buffer.

#### 2.1.3.7 char\* trim\_left ( char \* *buffer* )

Trims leading whitespace from a string.

**Parameters**

|               |                     |
|---------------|---------------------|
| <i>buffer</i> | The string to trim. |
|---------------|---------------------|

**Returns**

A pointer to the passed buffer.

**2.1.3.8 char\* trim\_line\_ending ( char \* *buffer* )**

Trims CR and LF characters from the end of a string.

**Parameters**

|               |                     |
|---------------|---------------------|
| <i>buffer</i> | The string to trim. |
|---------------|---------------------|

**Returns**

A pointer to the passed buffer.

**2.1.3.9 char\* trim\_right ( char \* *buffer* )**

Trims trailing whitespace from a string.

**Parameters**

|               |                     |
|---------------|---------------------|
| <i>buffer</i> | The string to trim. |
|---------------|---------------------|

**Returns**

A pointer to the passed buffer.


**2.1.4 Variable Documentation****2.1.4.1 char helper\_error\_msg[MAX\_BUFFER\_SIZE] = {0} [static]**

Global error message string.

**2.2 helper.h File Reference**

Interface to helper functions.

This graph shows which files directly or indirectly include this file:



## Macros

- `#define TRUE 1`  
*TRUE identifier.*
- `#define FALSE 0`  
*FALSE identifier.*
- `#define ERROR_RETURN (-1)`  
*Generic function return failure code.*
- `#define DPRINTF(arg) printf arg`  
*Calls printf() only when DEBUG is defined.*
- `#define DFPRINTF(arg) fprintf arg`  
*Calls fprintf() only when DEBUG is defined.*

## Functions

- `char * get_errmsg (void)`  
*Gets the global error message.*
- `void set_errmsg (const char *buffer)`  
*Sets the global error message.*
- `void set_errno_errmsg (const char *buffer)`  
*Sets the global error message based on errno.*
- `void mk_errmsg (const char *buffer, char **error_msg)`  
*Makes an error message.*
- `void mk_errno_errmsg (const char *buffer, char **error_msg)`  
*Makes an error message based on errno.*
- `char * trim_line_ending (char *buffer)`  
*Trims CR and LF characters from the end of a string.*
- `char * trim_right (char *buffer)`  
*Trims trailing whitespace from a string.*
- `char * trim_left (char *buffer)`  
*Trims leading whitespace from a string.*
- `char * trim (char *buffer)`  
*Trims leading and trailing whitespace from a string.*

## 2.2.1 Detailed Description

Interface to helper functions. Interface to helper functions.

### Author

Paul Griffiths

### Copyright

Copyright 2013 Paul Griffiths. Distributed under the terms of the GNU General Public License. <http://www.gnu.org/licenses/>

## 2.2.2 Macro Definition Documentation

### 2.2.2.1 `#define DFPRINTF( arg ) fprintf arg`

Calls fprintf() only when DEBUG is defined.

#### Parameters

|            |                                    |
|------------|------------------------------------|
| <i>arg</i> | The normal parameters to fprintf() |
|------------|------------------------------------|

### 2.2.2.2 `#define DPRINTF( arg ) printf arg`

Calls printf() only when DEBUG is defined.

#### Parameters

|            |                                   |
|------------|-----------------------------------|
| <i>arg</i> | The normal parameters to printf() |
|------------|-----------------------------------|

### 2.2.2.3 `#define ERROR_RETURN (-1)`

Generic function return failure code.

Provided for visibility when returning with error.

### 2.2.2.4 `#define FALSE 0`

FALSE identifier.

### 2.2.2.5 `#define TRUE 1`

TRUE identifier.

## 2.2.3 Function Documentation

### 2.2.3.1 `char* get_errmsg ( void )`

Gets the global error message.

### Returns

A pointer to the global error message.

#### 2.2.3.2 void mk\_errmsg ( const char \* *buffer*, char \*\* *error\_msg* )

Makes an error message.

This function provides a thread-safe way for a function to set an error message.

##### Parameters

|                  |  |
|------------------|--|
| <i>buffer</i>    | A buffer containing the error message.   |
| <i>error_msg</i> | A pointer to a char pointer which will refer to the error message. This should be free()d by the called. |

#### 2.2.3.3 void mk\_errno\_errmsg ( const char \* *buffer*, char \*\* *error\_msg* )

Makes an error message based on errno.

This function provides a thread-safe way for a function to set an error message, with the usual caveat that errno itself is not threadsafe.

##### Parameters

|                  |  |
|------------------|--|
| <i>buffer</i>    | A buffer containing the error message.   |
| <i>error_msg</i> | A pointer to a char pointer which will refer to the error message. This should be free()d by the called. |

#### 2.2.3.4 void set\_errmsg ( const char \* *buffer* )

Sets the global error message.

Uses a statically allocated buffer, so this is not thread-safe.

##### Parameters

|               |  |
|---------------|--|
| <i>buffer</i> | A buffer containing the error message. |
|---------------|--|

#### 2.2.3.5 void set\_errno\_errmsg ( const char \* *buffer* )

Sets the global error message based on errno.

Uses a statically allocated buffer, so this is not thread-safe.

##### Parameters

|               |  |
|---------------|--|
| <i>buffer</i> | A buffer containing the error message. |
|---------------|--|

#### 2.2.3.6 char\* trim ( char \* *buffer* )

Trims leading and trailing whitespace from a string.

## Parameters

|               |                     |
|---------------|---------------------|
| <i>buffer</i> | The string to trim. |
|---------------|---------------------|

## Returns

A pointer to the passed buffer.

**2.2.3.7** `char* trim_left ( char * buffer )`

Trims leading whitespace from a string.

## Parameters

|               |                     |
|---------------|---------------------|
| <i>buffer</i> | The string to trim. |
|---------------|---------------------|

## Returns

A pointer to the passed buffer.

**2.2.3.8** `char* trim_line_ending ( char * buffer )`

Trims CR and LF characters from the end of a string.

## Parameters

|               |                     |
|---------------|---------------------|
| <i>buffer</i> | The string to trim. |
|---------------|---------------------|

## Returns

A pointer to the passed buffer.

**2.2.3.9** `char* trim_right ( char * buffer )`

Trims trailing whitespace from a string.

## Parameters

|               |                     |
|---------------|---------------------|
| <i>buffer</i> | The string to trim. |
|---------------|---------------------|

## Returns


A pointer to the passed buffer.

## 2.3 main.c File Reference

Main function for echoclient.

```
#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include <netinet/in.h>
#include <arpa/inet.h>
#include <sys/types.h>
#include <sys/socket.h>
#include <netdb.h>
#include <inttypes.h>
#include <unistd.h>
#include "socket_helpers.h"
#include "helper.h"
```

Include dependency graph for main.c:



## Macros

- `#define MAX_BUFFER_LEN 1024`  
*Maximum character buffer size.*

## Functions

- `void run_echo_client (const int c_sock)`  
*Runs the echo client.*
- `int connect_with_command_line_args (int argc, char **argv)`  
*Attempts to connect to a service specified in cmdline args.*
- `int main (int argc, char **argv)`  
*Main function.*

### 2.3.1 Detailed Description

Main function for echoclient. Main function for echoclient.

#### Author

Paul Griffiths

#### Copyright

Copyright 2013 Paul Griffiths. Distributed under the terms of the GNU General Public License. <http://www.gnu.org/licenses/>

## 2.3.2 Macro Definition Documentation

### 2.3.2.1 `#define MAX_BUFFER_LEN 1024`

Maximum character buffer size.

## 2.3.3 Function Documentation

### 2.3.3.1 `int connect_with_command_line_args ( int argc, char ** argv )`

Attempts to connect to a service specified in cmdline args.

Expects `argc` to be 3, with `argv[1]` specifying a hostname or IP address, and `argv[2]` specifying a valid port.

#### Parameters

|                   |  |
|-------------------|--|
| <code>argc</code> | Number of command line arguments, passed from <a href="#">main()</a> |
| <code>argv</code> | Command line arguments, passed from <a href="#">main()</a>           |

#### Returns

The file descriptor of the connected socket on success, or -1 on failure.

### 2.3.3.2 `int main ( int argc, char ** argv )`

Main function.

Connects to an echo server and runs the echo client.

#### Returns

Exit status.

### 2.3.3.3 `void run_echo_client ( const int c_sock )`

Runs the echo client.

#### Parameters

|                     |   |
|---------------------|---|
| <code>c_sock</code> | File descriptor of the connected socket to use. |
|---------------------|---|

## 2.4 `socket_helpers.c` File Reference

Implementation of socket helper functions.




```

#include <stdlib.h>
#include <string.h>
#include <stdio.h>
#include <unistd.h>
#include <netinet/in.h>
#include <arpa/inet.h>
#include <sys/types.h>
#include <sys/socket.h>
#include <netdb.h>
#include <sys/time.h>
#include <sys/select.h>
#include <errno.h>
#include <inttypes.h>
#include <signal.h>
#include "socket_helpers.h"
#include "helper.h"

```

Include dependency graph for socket\_helpers.c:



## Macros

- `#define MAX_BUFFER_SIZE 1024`  
*Maximum character buffer size.*

## Functions

- `ssize_t socket_readline` (const int socket, char \*buffer, const size\_t max\_len)  
*Reads a \n terminated line from a socket.*
- `ssize_t socket_readline_timeout` (const int socket, char \*buffer, const size\_t max\_len, struct timeval \*time\_out)  
*Reads a \n terminated line from a socket with timeout.*
- `ssize_t socket_writeline` (const int socket, const char \*buffer, const size\_t max\_len)  
*Writes a line to a socket.*
- `uint16_t port_from_string` (const char \*port\_str)  
*Extracts a valid TCP/UDP port from a string.*
- `int conn_socket_from_string` (const char \*host, const char \*port)  
*Creates a connected sock from a hostname and port.*
- `void ignore_sigpipe` (void)  
*Ignores the SIGPIPE signal.*

### 2.4.1 Detailed Description

Implementation of socket helper functions.

#### Author

Paul Griffiths

## Copyright

Copyright 2013 Paul Griffiths. Distributed under the terms of the GNU General Public License. <http://www.gnu.org/licenses/>

## 2.4.2 Macro Definition Documentation

### 2.4.2.1 #define MAX\_BUFFER\_SIZE 1024

Maximum character buffer size.

## 2.4.3 Function Documentation

### 2.4.3.1 int conn\_socket\_from\_string ( const char \* *host*, const char \* *port* )

Creates a connected sock from a hostname and port.

#### Parameters

|             |   |
|-------------|---|
| <i>host</i> | A string containing the hostname to which to connect. |
| <i>port</i> | A string containing the port to which to connect.     |

#### Returns

The file descriptor of the connected socket on success, or -1 on failure.

### 2.4.3.2 void ignore\_sigpipe ( void )

Ignores the SIGPIPE signal.

The write() system call will, when writing to a closed socket, elicit an RST (reset) flag. A second write() system call will trigger a SIGPIPE signal to be raised. The default action of SIGPIPE is to terminate the program, with no error message, which is not desirable. If we want to do anything special when SIGPIPE is triggered, we could set up a handler, but if we don't, then ignoring SIGPIPE is fine, provided our socket functions respond appropriately to the condition (write() will return EPIPE after an ignored SIGPIPE signal).

### 2.4.3.3 uint16\_t port\_from\_string ( const char \* *port\_str* )

Extracts a valid TCP/UDP port from a string.

#### Parameters

|                 |                                  |
|-----------------|----------------------------------|
| <i>port_str</i> | The string from which to extract |
|-----------------|----------------------------------|

#### Returns

The port number on success, or zero if *port\_str* does not contain a valid TCP/UDP port (port 0 is reserved and cannot be used).

### 2.4.3.4 ssize\_t socket\_readline ( const int *socket*, char \* *buffer*, const size\_t *max\_len* )

Reads a \n terminated line from a socket.

The function will not overwrite the buffer, so *max\_len* should be the size of the whole buffer, and function will at most write *max\_len* - 1 characters plus the terminating \0. Any terminating CR or LF characters will be stripped.

## Parameters

|                |   |
|----------------|---|
| <i>socket</i>  | File description of the socket  |
| <i>buffer</i>  | The buffer into which to read   |
| <i>max_len</i> | The maximum number of characters to read, including the terminating \0. |

## Returns

The number of characters read, or -1 on encountering an error.

#### 2.4.3.5 ssize\_t socket\_readline\_timeout ( const int *socket*, char \* *buffer*, const size\_t *max\_len*, struct timeval \* *time\_out* )

Reads a \n terminated line from a socket with timeout.

Behaves the same as [socket\\_readline\(\)](#), except it will time out if no input is available on the socket after the specified time. Any terminating CR or LF characters will be stripped.

## Parameters

|                 |  |
|-----------------|--|
| <i>socket</i>   | File description of the socket   |
| <i>buffer</i>   | The buffer into which to read  |
| <i>max_len</i>  | The maximum number of characters to read, including the terminating \0.  |
| <i>time_out</i> | A pointer to a <code>timeval</code> struct containing the timeout period. Note that some implementations of <code>select()</code> may alter this variable, so the calling function should consider it unusable after return. In addition, on such an implementation, the value will specify the cumulative timeout period over the entire read line operation, rather than resetting after reading each character. |

## Returns

The number of characters read, or -1 on encountering an error.

#### 2.4.3.6 ssize\_t socket\_writeline ( const int *socket*, const char \* *buffer*, const size\_t *max\_len* )

Writes a line to a socket.

The function adds a network-standard terminating CRLF, so the provided string should not normally end in any newline characters.

## Parameters

|                |  |
|----------------|--|
| <i>socket</i>  | File description of the socket   |
| <i>buffer</i>  | The buffer from which to write.  |
| <i>max_len</i> | The maximum number of characters to write to the buffer. Due to the addition of CRLF, <code>max_len + 2</code> characters may actually be written. |

## Returns


The number of characters written, or -1 on encountering an error.

## 2.5 socket\_helpers.h File Reference


Interface to socket helper functions.

```
#include <sys/time.h>
#include <inttypes.h>
```

Include dependency graph for `socket_helpers.h`:



This graph shows which files directly or indirectly include this file:



## Functions

- `ssize_t` [socket\\_readline](#) (`const int l_socket, char *buffer, const size_t max_len`)  
*Reads a \n terminated line from a socket.*
- `ssize_t` [socket\\_readline\\_timeout](#) (`const int l_socket, char *buffer, const size_t max_len, struct timeval *time_out`)  
*Reads a \n terminated line from a socket with timeout.*
- `ssize_t` [socket\\_writeline](#) (`const int l_socket, const char *buffer, const size_t max_len`)  
*Writes a line to a socket.*
- `uint16_t` [port\\_from\\_string](#) (`const char *port_str`)  
*Extracts a valid TCP/UDP port from a string.*
- `int` [conn\\_socket\\_from\\_string](#) (`const char *host, const char *port`)  
*Creates a connected sock from a hostname and port.*
- `void` [ignore\\_sigpipe](#) (`void`)  
*Ignores the SIGPIPE signal.*

### 2.5.1 Detailed Description

Interface to socket helper functions.

**Author**

Paul Griffiths

**Copyright**

Copyright 2013 Paul Griffiths. Distributed under the terms of the GNU General Public License. <http://www.gnu.org/licenses/>

**2.5.2 Function Documentation****2.5.2.1 int conn\_socket\_from\_string ( const char \* *host*, const char \* *port* )**

Creates a connected sock from a hostname and port.

**Parameters**

|             |   |
|-------------|---|
| <i>host</i> | A string containing the hostname to which to connect. |
| <i>port</i> | A string containing the port to which to connect.     |

**Returns**

The file descriptor of the connected socket on success, or -1 on failure.

**2.5.2.2 void ignore\_sigpipe ( void )**

Ignores the SIGPIPE signal.

The write() system call will, when writing to a closed socket, elicit an RST (reset) flag. A second write() system call will trigger a SIGPIPE signal to be raised. The default action of SIGPIPE is to terminate the program, with no error message, which is not desirable. If we want to do anything special when SIGPIPE is triggered, we could set up a handler, but if we don't, then ignoring SIGPIPE is fine, provided our socket functions respond appropriately to the condition (write() will return EPIPE after an ignored SIGPIPE signal).

**2.5.2.3 uint16\_t port\_from\_string ( const char \* *port\_str* )**

Extracts a valid TCP/UDP port from a string.

**Parameters**

|                 |                                  |
|-----------------|----------------------------------|
| <i>port_str</i> | The string from which to extract |
|-----------------|----------------------------------|

**Returns**

The port number on success, or zero if *port\_str* does not contain a valid TCP/UDP port (port 0 is reserved and cannot be used).

**2.5.2.4 ssize\_t socket\_readline ( const int *socket*, char \* *buffer*, const size\_t *max\_len* )**

Reads a \n terminated line from a socket.

The function will not overwrite the buffer, so *max\_len* should be the size of the whole buffer, and function will at most write *max\_len* - 1 characters plus the terminating \0. Any terminating CR or LF characters will be stripped.

## Parameters

|                |   |
|----------------|---|
| <i>socket</i>  | File description of the socket  |
| <i>buffer</i>  | The buffer into which to read   |
| <i>max_len</i> | The maximum number of characters to read, including the terminating \0. |

## Returns

The number of characters read, or -1 on encountering an error.

#### 2.5.2.5 `ssize_t socket_readline_timeout ( const int socket, char * buffer, const size_t max_len, struct timeval * time_out )`

Reads a \n terminated line from a socket with timeout.

Behaves the same as [socket\\_readline\(\)](#), except it will time out if no input is available on the socket after the specified time. Any terminating CR or LF characters will be stripped.

## Parameters

|                 |  |
|-----------------|--|
| <i>socket</i>   | File description of the socket   |
| <i>buffer</i>   | The buffer into which to read  |
| <i>max_len</i>  | The maximum number of characters to read, including the terminating \0.  |
| <i>time_out</i> | A pointer to a <code>timeval</code> struct containing the timeout period. Note that some implementations of <code>select()</code> may alter this variable, so the calling function should consider it unusable after return. In addition, on such an implementation, the value will specify the cumulative timeout period over the entire read line operation, rather than resetting after reading each character. |

## Returns

The number of characters read, or -1 on encountering an error.

#### 2.5.2.6 `ssize_t socket_writeline ( const int socket, const char * buffer, const size_t max_len )`

Writes a line to a socket.

The function adds a network-standard terminating CRLF, so the provided string should not normally end in any newline characters.

## Parameters

|                |  |
|----------------|--|
| <i>socket</i>  | File description of the socket   |
| <i>buffer</i>  | The buffer from which to write.  |
| <i>max_len</i> | The maximum number of characters to write to the buffer. Due to the addition of CRLF, <code>max_len + 2</code> characters may actually be written. |

## Returns

The number of characters written, or -1 on encountering an error.

# Index

conn\_socket\_from\_string  
    socket\_helpers.c, [14](#)  
    socket\_helpers.h, [17](#)  
connect\_with\_command\_line\_args  
    main.c, [12](#)

DFPRINTF  
    helper.h, [8](#)  
DPRINTF  
    helper.h, [8](#)

ERROR\_RETURN  
    helper.h, [8](#)

FALSE  
    helper.h, [8](#)

get\_errmsg  
    helper.c, [4](#)  
    helper.h, [8](#)

helper.c, [3](#)  
    get\_errmsg, [4](#)  
    helper\_error\_msg, [6](#)  
    MAX\_BUFFER\_SIZE, [4](#)  
    mk\_errmsg, [4](#)  
    mk\_errno\_errmsg, [5](#)  
    set\_errmsg, [5](#)  
    set\_errno\_errmsg, [5](#)  
    trim, [5](#)  
    trim\_left, [5](#)  
    trim\_line\_ending, [6](#)  
    trim\_right, [6](#)

helper.h, [6](#)  
    DFPRINTF, [8](#)  
    DPRINTF, [8](#)  
    ERROR\_RETURN, [8](#)  
    FALSE, [8](#)  
    get\_errmsg, [8](#)  
    mk\_errmsg, [9](#)  
    mk\_errno\_errmsg, [9](#)  
    set\_errmsg, [9](#)  
    set\_errno\_errmsg, [9](#)  
    TRUE, [8](#)  
    trim, [9](#)  
    trim\_left, [10](#)  
    trim\_line\_ending, [10](#)  
    trim\_right, [10](#)  
helper\_error\_msg  
    helper.c, [6](#)

ignore\_sigpipe  
    socket\_helpers.c, [14](#)  
    socket\_helpers.h, [17](#)

MAX\_BUFFER\_LEN  
    main.c, [12](#)

MAX\_BUFFER\_SIZE  
    helper.c, [4](#)  
    socket\_helpers.c, [14](#)

main  
    main.c, [12](#)

main.c, [11](#)  
    connect\_with\_command\_line\_args, [12](#)  
    MAX\_BUFFER\_LEN, [12](#)  
    main, [12](#)  
    run\_echo\_client, [12](#)

mk\_errmsg  
    helper.c, [4](#)  
    helper.h, [9](#)

mk\_errno\_errmsg  
    helper.c, [5](#)  
    helper.h, [9](#)

port\_from\_string  
    socket\_helpers.c, [14](#)  
    socket\_helpers.h, [17](#)

run\_echo\_client  
    main.c, [12](#)

set\_errmsg  
    helper.c, [5](#)  
    helper.h, [9](#)

set\_errno\_errmsg  
    helper.c, [5](#)  
    helper.h, [9](#)

socket\_helpers.c, [12](#)  
    conn\_socket\_from\_string, [14](#)  
    ignore\_sigpipe, [14](#)  
    MAX\_BUFFER\_SIZE, [14](#)  
    port\_from\_string, [14](#)  
    socket\_readline, [14](#)  
    socket\_readline\_timeout, [15](#)  
    socket\_writeline, [15](#)

socket\_helpers.h, [15](#)  
    conn\_socket\_from\_string, [17](#)  
    ignore\_sigpipe, [17](#)  
    port\_from\_string, [17](#)  
    socket\_readline, [17](#)  
    socket\_readline\_timeout, [18](#)

- socket\_writeline, [18](#)
- socket\_readline
  - socket\_helpers.c, [14](#)
  - socket\_helpers.h, [17](#)
- socket\_readline\_timeout
  - socket\_helpers.c, [15](#)
  - socket\_helpers.h, [18](#)
- socket\_writeline
  - socket\_helpers.c, [15](#)
  - socket\_helpers.h, [18](#)
- TRUE
  - helper.h, [8](#)
- trim
  - helper.c, [5](#)
  - helper.h, [9](#)
- trim\_left
  - helper.c, [5](#)
  - helper.h, [10](#)
- trim\_line\_ending
  - helper.c, [6](#)
  - helper.h, [10](#)
- trim\_right
  - helper.c, [6](#)
  - helper.h, [10](#)