ECONOMILL

LOW-COST LIGHT-DUTY MILL

MILLING

GENERAL DESCRIPTION

LOW-COST MILLING TOOL FOR LIGHT-DUTY JOBS, DRESSED WITH TUNGSTEN CARBIDE. IT IS EFFECTIVE FOR MILLING PACKERS, RETAINERS, BRIDGE PLUGS AND CEMENT. IT HAS STANDARD API CONNECTIONS, SO IT IS MADE UP AND BROKEN OUT WITH A STANDARD BIT BREAKER AND NEEDS NO ADDITIONAL SUB. FLUID IS DIRECTED ALONG EACH CUTTING BLADE AND THROUGH THE CENTRE OF THE HEAD FOR CUTTINGS REMOVAL AND COOLING.

TECHNICAL CHARACTERISTICS

Tool series	Dressed diameter (in.)	Top pin conn. (API Reg.)	Recommended make-up torque (ft-lb)	Overall length (in.)	Wt (lb)
3000	3-1/4 - 4-3/8	2-3/8	3,000 - 3,500	7-5/8	17
4000	4-1/2 - 5-3/8	2-7/8	6,000 - 7,000	8-5/8	26
5000	5-1/2 - 7-3/8	3-1/2	7,000 - 9,000	9	40
7000	7-1/2 - 8-3/4	4-1/2	12,000 - 16,000	11-1/2	76
10000	10-1/4 - 12-1/4	6-5/8	28,000 - 32,000	16-1/2	125

Dimensions in inches, weights in lb (approximate). Column order follows the source layout.

DESIGN FEATURES

- **Tungsten carbide dressing:** for packers, retainers, bridge plugs and cement.
- **Standard API pin connection:** made up with a standard bit breaker; no extra sub needed.
- **Circulation:** flow along each blade and through the head centre for cooling and cuttings removal.
- **Stabilizing ribs:** above the blades, to protect the casing.
- **Cast construction:** not to be used as a junk mill; cast material has lower strength.

PERFORMANCE PARAMETERS

Weight on mill	2,000 - 8,000 lb
Practice	Light weight, low speed
Surface speed	250 - 340 ft/min
Rotary speed	Surf. speed / (O.D. x 3.14)
If bouncing	Cut speed, then raise slowly
Stabilizer	Above mill, O.D. not larger

HOW TO ORDER

Please specify: 1. mill dressed diameter 2. size and weight of the casing to run through, if known 3. protective subs, available on request.