Enedril
Fishing and Drilling Solutions

BOOST

MUD PULSE MWD

Rock solid performance. A reliable and robust MWD system for today's aggressive drilling conditions: surveys, directional telemetry and gamma ray, to surface in real time.

185°C
standard rating · 200°C version available

20,000 psi
pressure rating

47.6 mm
outside diameter, 1.875"

400+ h
battery life with 2 modules

TELEMETRY

Inclination
0 - 180° · ±0.10°

Azimuth
0 - 360° · ±0.50°

Toolface
0 - 360° · ±0.20°

Gamma ray
orbital, 360° available

Shock & vibration
500 g · 24 MB memory

Stick-slip & RPM
downhole dynamics

Temperature
-35 to 200°C · ±0.5°C

Tool health
battery, annular pressure

WHY BOOST

Field-proven design
Rugged and dependable, rated 185°C.

Top or bottom mounted
Positive pulse, adjustable module placement.

Anti-plugging pulser
Motor driven, performs in LCM and high solids.

Wireline retrievable
Re-insertable, collars 3.5" to 8".

Down-linking
Adjustable logging, 4 programmable sequences.

Ratcheting military connector
Barrel-to-barrel, easy to assemble.

+33 (0)5 59 04 50 45

www.enedril.com · info@enedril.fr
3, avenue des Lacs · 64140 Lons · France