

IMPRESSION BLOCK

CLEAN OUT

GENERAL DESCRIPTION

IMPRESSION BLOCKS ARE MADE FROM A LOW ALLOY STEEL OUTER CASING, WITH EITHER A LEAD OR A TAR INNER FILLING, DEPENDING ON THE CONDITIONS IN WHICH THE IMPRESSION IS TAKEN. LEAD IS IDEAL FOR DEEPER, HIGHER TEMPERATURE CONDITIONS, WHILE TAR IS VERY GOOD FOR LARGE OD, SHALLOW APPLICATIONS. ANY SIZE OF IMPRESSION BLOCK CAN BE BUILT TO ORDER.

SPECIFICATIONS

Top connection	2-3/8 API REG	2-7/8 API REG	3-1/2 API REG
Tool OD (in)	4	5	6
Material used	Lead	Lead	Lead

Top connection	4-1/2 API REG	6-5/8 API REG	7-5/8 API REG
Tool OD (in)	8-1/2	12-1/4	17-1/2 - 26
Material used	Lead	Lead	Tar

Dimensions in inches. Other sizes on request.

DESIGN FEATURES

- **Steel body:** low alloy steel outer casing.
- **Lead filling:** deeper, higher temperature conditions.
- **Tar filling:** large OD, shallow applications.
- **Made to order:** any size can be built.

HOW TO ORDER

Please specify: 1. tool OD 2. top connection 3. filling (lead or tar) 4. casing or hole size.