



SUPER JUNK MILL

MILLING

GENERAL DESCRIPTION

THE JUNK MILL IS A HIGH-PERFORMANCE MILLING TOOL DESIGNED TO GRIND AND REMOVE METAL DEBRIS AND OBSTRUCTIONS IN THE WELLBORE, SUCH AS STUCK TOOLS, CASING FRAGMENTS OR DRILL BITS. IT IS USED IN TOUGH ENVIRONMENTS WHERE STANDARD MILLS MIGHT NOT SUFFICE, OFFERING SUPERIOR CUTTING POWER AND DURABILITY.

TECHNICAL CHARACTERISTICS

Dressed OD (in)	Top pin connection
3-1/2 - 4-1/4	2-3/8 API REG
4-1/2 - 5-1/2	2-7/8 API REG
5-1/2 - 7-1/2	3-1/2 API REG
7-1/2 - 9	4-1/2 API REG
9-1/2 - 12-1/4	6-5/8 API REG
13 - 15	6-5/8, 7-5/8
17 - 17-1/2	6-5/8, 7-5/8
18-1/2 - 26	6-5/8, 7-5/8

DRESSING OPTIONS



Conventional



Conebuster



Super

USAGE RECOMMENDATIONS

- **Circulation:** use with a robust circulation system to clear milling debris efficiently.
- **Debris collection:** often combined with a fishing magnet or a junk basket to collect any metallic debris left behind.
- **Stabilizers:** useful for tool stability, more consistent cutting action and longer mill life.

TYPES OF DEBRIS MILLED

- Broken drill bits
- Casing fragments
- Stuck tools
- Fishing equipment debris
- Miscellaneous metallic obstructions

HOW TO ORDER

Please specify: 1. dressed OD 2. top pin connection 3. dressing (conventional, Conebuster or Super).