Enedril
Fishing and Drilling Solutions

BOOST

MUD PULSE MWD

Rock solid performance. A reliable and robust MWD system for today's aggressive drilling conditions: surveys, directional telemetry and gamma ray, to surface in real time.

185°C	20,000 psi	47.6 mm	400+ h
standard rating · 200°C version available	pressure rating	outside diameter, 1.875"	battery life with 2 modules

TELEMETRY

Inclination 0 - 180° · ±0.10°	**Azimuth** 0 - 360° · ±0.50°	**Toolface** 0 - 360° · ±0.20°	**Gamma ray** orbital, 360° available
Shock & vibration 500 g · 24 MB memory	**Stick-slip & RPM** downhole dynamics	**Temperature** -35 to 200°C · ±0.5°C	**Tool health** battery, annular pressure

WHY BOOST

Field-proven design
Rugged and dependable, standard rated to 185°C.

Top or bottom mounted
Positive pulse systems, adjustable module placement.

Anti-plugging pulser
Motor driven, performs in LCM and high-solids mud.

Wireline retrievable
Retrievable and re-insertable, collars 3.5" to 8".

Down-linking
Adjustable logging sequences, 4 programmable.

Ratcheting military connector
Barrel-to-barrel, easy to assemble and service.

+33 (0)5 59 04 50 45
www.enedril.com · info@enedril.fr · 3, avenue des Lacs · 64140 Lons · France