JUNK BASKET

JUNK BASKET WITH DOUBLE CATCHERS

FISHING

GENERAL DESCRIPTION


SIMPLE, DEPENDABLE FISHING TOOL FOR RETRIEVING LOOSE JUNK FROM THE BOTTOM OF THE HOLE: BIT CONES, BEARINGS, BROKEN SLIPS, WIRELINE, HAND TOOLS, DEBRIS FROM TWISTED-OFF STRINGS AND MILLING CUTTINGS. TWO FREE-REVOLVING CATCHERS SIT INSIDE A MILL SHOE, SO THE BASKET CUTS A SHORT CORE THAT LOCKS THE JUNK IN THE BARREL. IT CAN ALSO TAKE A CORE SAMPLE, DRILL A FULL-GAUGE HOLE OR REAM. MAGNET INSERTS AND ACCESSORY SHOES ADAPT IT TO THE JOB.

TECHNICAL CHARACTERISTICS

Hole size	Barrel OD	Shoe OD	Max. fish Ø	Teeth	Wt (lb)
3-3/4 - 4-1/8	3-5/8	3-5/8	2-11/16	8	55
4-1/4 - 4-1/2	3-3/4	4-1/16	2-15/16	8	60
4-5/8 - 5	3-7/8	4-1/2	3-9/32	8	65
4-5/8 - 5	3-7/8	4-1/2	3-3/8	8	65
5-1/8 - 5-1/2	4-1/4	4-7/8	3-23/32	8	80
5-3/8 - 6	5-1/8	5-1/8	3-25/32	8	80
5-5/8 - 6	4-3/4	5-3/8	4-1/16	8	100
6-1/8 - 6-1/2	5-3/4	5-3/4	4-13/32	8	200
6-1/8 - 6-1/2	5-1/8	5-7/8	4-5/16	8	110

Hole size	Barrel OD	Shoe OD	Max. fish Ø	Teeth	Wt (lb)
6-1/8 - 6-1/2	5-1/4	5-7/8	4-1/2	8	110
6-5/8 - 7	5-3/4	6-1/4	4-13/16	8	125
7-1/4 - 8	6-1/2	7-1/8	5-7/16	8	160
8-1/4 - 9	7-1/2	8-1/8	6-3/16	8	205
9-1/4 - 10-1/8	8-1/2	9-1/8	7-3/16	10	255
10-1/4 - 11-5/8	9-3/8	10-1/8	8-1/16	12	290
11-3/4 - 12-1/2	10-3/8	11-1/4	9-1/16	12	360
12-5/8 - 15	11-3/8	12-1/4	10-1/16	12	450
15 - 20	13-3/4	14-1/2	12-1/16	16	655

Dimensions in inches, weights in lb (approximate). Shoes should be at least 1/8 in. over the barrel size.



DESIGN FEATURES

- **Double catchers:** the upper fingers reach half way to the centre and break the core on pull; the lower catcher has alternating long and short fingers forming a close-fitting basket.
- **Free-revolving catchers:** spin inside the shoe, which prevents finger breakage.
- **Rivet-free catchers:** manganese bronze or steel fingers, redressed easily on location.
- **Magnet insert:** replaces the two catchers and turns the basket into a fishing magnet, useful in hard formations or to clean the hole before diamond drilling.

SHOE SELECTION

- **Type A mill shoe:** side wings, hard metal facing; standard, for soft formations and loose fish.
- **Type B mill shoe:** hard-faced with sintered tungsten carbide, for hard formations.
- **Type C mill shoe:** flat bottom, hard-faced on bottom, inner and outer faces; cuts cores and burns metal.
- **Finger shoe:** for large, loose junk or junk too big for the catchers.

OPERATING PARAMETERS

Approach	Start circulation at reduced pressure just before bottom, rotate and lower slowly onto the fish
Mill shoes	1 ton on bottom, 50 - 150 rpm
Finger shoes	Rotate and lower slowly to about 2 tons on bottom
Breaking the core	Stop rotation and circulation, release torque, take an upward pull; a hydraulic jar above helps

After use, disassemble, clean and lubricate all internal parts, inspect catcher fingers and springs, and paint or grease the outside.

HOW TO ORDER

Please specify: 1. tool name and size 2. OD and type of shoe 3. top connection, if other than standard 4. recommended spares: 2 upper catchers, 2 lower catchers, 3 mill shoes, 2 finger shoes, 4 finger shoe replacements.