Enedril
Fishing and Drilling Solutions

BOOST

MUD PULSE MWD

Rock solid performance. A reliable and robust MWD system for today's aggressive drilling conditions: surveys, directional telemetry and gamma ray, to surface in real time.

185°C	20,000	47.6 mm	400+ h
standard rating 200°C version available	psi pressure rating	outside diameter 1.875"	battery life with 2 modules

TELEMETRY

Inclination
0 - 180° · ±0.10°

Azimuth
0 - 360° · ±0.50°

Toolface
0 - 360° · ±0.20°

Gamma ray
orbital, 360° available

Shock & vibration
500 g · 24 MB memory

Stick-slip & RPM
downhole dynamics

Temperature
-35 to 200°C · ±0.5°C

Tool health
battery, annular pressure

WHY BOOST

- **Field-proven design**
  Rugged and dependable, standard rated to 185°C.
- **Top or bottom mounted**
  Positive pulse systems, adjustable module placement.
- **Anti-plugging pulser**
  Motor driven, performs in LCM and high-solids mud.
- **Wireline retrievable**
  Retrievable and re-insertable, collars from 3.5" to 8".
- **Down-linking**
  Adjustable logging sequences, 4 programmable.
- **Ratcheting military connector**
  Barrel-to-barrel, easy to assemble and service.

+33 (0)5 59 04 50 45
www.enedril.com · info@enedril.fr
3, avenue des Lacs · 64140 Lons · France

CERTIFIED ISO 9001:2015 COMPANY