



- Version
- Authentication/Access Token (OAuth - Username/Password)
- Authentication/API Key (Machine 2 Machine)
- Authentication/JWT (JSON Web Token)
- Event Subscriptions
- Resellers
- Domains
- Phone Numbers
- Phone Numbers/Use Cases
- Users
- Devices
- Phones/Macs
- Phones/Macs/Supported Models and Servers
- Sites
- Call Center/Callqueues
- Call Center/Agents
- Call Center/Agent Actions
- Call Center/QueuedCalls
- Answer Rules
- Call Blocking
- Auto Attendant
- Media/Voicemail
- Media/Greetings
- Media/Music on Hold/Domain
- Media/Music on Hold/Server

Create a Connection

POST <https://{server}/ns-api/v2/connections>

or LOG IN TO SEE FULL REQUEST HISTORY

TIME	STATUS	USER AGENT
1h ago	202	Try It!
1 Request This Month		

BODY PARAMS

connection-orig-match-pattern string required	sip*@apido
This is the connection's origination match pattern	
domain string required length ≤ 64	apido
This is the main organization name. This is used to link resource to its group/tenant/organization/enterprise. ~ and * can be used alone in special cases to mean My Domain (~) and All Domains (*).	
description string	Example PRI Conn
This is the connection's description	
connection-term-match-pattern string	sip*@apido
Defaulted to connection-orig-match-pattern	
connection-audio-relay-enabled string	yes
Available options are "yes", "optional", "no". "Yes" will set the connection audio relay to "automatic". "Optional" will set it to "none". "No" will set it to "never". Default will be "yes".	
connection-address string	sip:2485551212@aj
This is the connection's address	
dial-plan string	US and Canada
This is the connection's dial plan	
dial-policy string	Permit All
This is the connection's dial policy	
limits-max-active-calls-orig integer	0
This is the connection's limit of maximum originating calls	
limits-max-active-calls-term integer	0
This is the connection's limit of maximum terminating calls	
limits-max-active-calls-total integer	0
This is the connection's limit of maximum total calls	
connection-linked-billing-user string	domain
This is the connection's linked billing user	
connection-sip-registration-username string	2485551212
This is the connection's authorized username	
connection-sip-registration-password string	authkey
This is the connection's password	
connection-sip-registration-realm string	apido
This is the connection's authentication realm	
connection-orig-enabled string enum Defaults to yes	yes
When enabled this setting will turn on voicemail for the user. Allowed: yes no	
connection-term-enabled string enum Defaults to yes	yes
When enabled this setting will turn on voicemail for the user. Allowed: yes no	
connection-translation-request-host string	apido
This is the connection's translation request host.	
connection-translation-destination-host string Defaults to "	apido
This is the connection's translation destination host. This typically comes from the connection-orig-match-pattern. Defaults to "	
connection-translation-request-user string Defaults to "	[*]
This is the connection's translation request user. This is typically set to [*]. Defaults to "	
connection-translation-destination-user string Defaults to "	[*]
This is the connection's translation destination user. This is typically set to [*]. Defaults to "	
connection-translation-source-user string Defaults to "	[*]
This is the connection's translation source user. This is typically set to [*]. Defaults to "	
connection-source-ip-checking-enabled string enum	yes
Defaults to no This setting when enable will request caller id blocking on outbound calls requesting privacy settings. This may lower the ability to connect certain calls if not setup properly to support privacy settings. Allowed: yes no	
connection-include-server-header-enabled string enum	yes

LANGUAGE



CREDENTIALS

BEARER

Bearer **nss_axJTse8m02cfiihvKJfFp4ohRg18uIG34CKMY4u6GXci1i**

URL

Base URL **https://portal.grid4voice.ucaas.tech/ns-api/v2/conne**

API REQUEST

REQUEST EXAMPLE

```
$ npx api install "@netsapiens-api/v44.4#17qk1qneafktnx"

33 'connection-block-video-in-sdp-enabled': 'no',
34 'connection-translation-destination-host': 'apido.pri',
35 'limits-max-active-calls-term': '0',
36 'connection-translation-request-host': 'apido.pri',
37 'connection-source-ip-checking-enabled': 'yes',
38 'connection-orig-enabled': 'yes',
39 'connection-translation-destination-user': '[*]',
40 'connection-require-sip-authentication-enabled': 'yes',
41 'connection-translation-source-host': 'apido.pri',
42 'minimum-call-duration-second': '1',
43 'connection-sip-registration-expires-datetime': '2025-05-
44 'connection-sip-authenticate-as-client-enabled': 'no'
45 })
46 .then(({ data }) => console.log(data))
47 .catch(err => console.error(err));
```

Try It!

RESPONSE

1 {}

Headers

Defaults to no	
This setting when enable will request caller id blocking on outbound calls requesting privacy settings. This may lower the ability to connect certain calls if not setup properly to support privacy settings.	
Allowed: <input checked="" type="checkbox"/> yes <input type="checkbox"/> no	
connection-relay-comfort-noise-enabled string	yes
Defaults to system-default	
This will set whether there is an RTP Relay comfort noise. Can be set to yes or no. If not set, will be set to system-default	
connection-pcmu-only-enabled string enum Defaults to no	no ▾
This setting when enable will request caller id blocking on outbound calls requesting privacy settings. This may lower the ability to connect certain calls if not setup properly to support privacy settings.	
Allowed: <input checked="" type="checkbox"/> yes <input type="checkbox"/> no	
connection-enforce-minimum-duration-enabled string enum Defaults to no	no ▾
This setting when enable will request caller id blocking on outbound calls requesting privacy settings. This may lower the ability to connect certain calls if not setup properly to support privacy settings.	
Allowed: <input checked="" type="checkbox"/> yes <input type="checkbox"/> no	
connection-bind-to-alternate-interface-enabled string enum Defaults to no	no ▾
This setting when enable will request caller id blocking on outbound calls requesting privacy settings. This may lower the ability to connect certain calls if not setup properly to support privacy settings.	
Allowed: <input checked="" type="checkbox"/> yes <input type="checkbox"/> no	
connection-block-video-in-sdp-enabled string enum Defaults to no	no ▾
This setting when enable will request caller id blocking on outbound calls requesting privacy settings. This may lower the ability to connect certain calls if not setup properly to support privacy settings.	
Allowed: <input checked="" type="checkbox"/> yes <input type="checkbox"/> no	
connection-sip-get-new-dialog-destination-from string Defaults to default-ip	default-ip
This will set the new dialog destination. Values available are contact-header or via-header. Default would be default-ip	
connection-sip-get-response-destination-from string Defaults to default-ip	default-ip
This will set the response desination. Values available will be contact-header or via-header. Default will be default-ip	
connection-require-encrypted-audio-enabled string Defaults to no	optional
This will set whether audio encryption is required. Options availabe are "optional" and "yes". Defaults to no	
connection-sip-transport-protocol string Defaults to UDP	UDP
This will set the SIP transport protocol. Options are "TCP" and "TLS". Default will be UDP	
connection-check-orig-matching-sip-header string Defaults to from	to
This will set whether to check whether the origination matches the SIP header. Options are "to", "request", or "contact". Default will default to "from"	
connection-sip-session-timer-enabled string Defaults to system-default	yes
This will set the SIP session timer. Options are setting to "no" or not setting at all, which will default to the system-default	
connection-prevent-rtp-port-change-enabled string enum Defaults to no	no ▾
This setting when enable will request caller id blocking on outbound calls requesting privacy settings. This may lower the ability to connect certain calls if not setup properly to support privacy settings.	
Allowed: <input checked="" type="checkbox"/> yes <input type="checkbox"/> no	
connection-hide-post-dial-delay-with-ringback-enabled string enum Defaults to no	no ▾
This setting when enable will request caller id blocking on outbound calls requesting privacy settings. This may lower the ability to connect certain calls if not setup properly to support privacy settings.	
Allowed: <input checked="" type="checkbox"/> yes <input type="checkbox"/> no	
connection-remote-ringback-handling string Defaults to allowed	allowed
This will set the remote ringback handling. Options are "no-ringback" and "local-only". Default will be set to "allowed".	
connection-block-media-in-sip-180-ringing string enum Defaults to no	yes ▾
This setting when enable will request caller id blocking on outbound calls requesting privacy settings. This may lower the ability to connect certain calls if not setup properly to support privacy settings.	
Allowed: <input checked="" type="checkbox"/> yes <input type="checkbox"/> no	
connection-allow-mid-call-uri-updates-enabled string enum Defaults to no	yes ▾
This setting when enable will request caller id blocking on outbound calls requesting privacy settings. This may lower the ability to connect certain calls if not setup properly to support privacy settings.	
Allowed: <input checked="" type="checkbox"/> yes <input type="checkbox"/> no	
connection-record-all-calls-enabled string enum Defaults to no	yes ▾
This setting when enable will request caller id blocking on outbound calls requesting privacy settings. This may lower the ability to connect certain calls if not setup properly to support privacy settings.	
Allowed: <input checked="" type="checkbox"/> yes <input type="checkbox"/> no	
connection-system-a-assisted-id-format string Defaults to system-a-assisted-id-format	system-a-assisted-id-format

connection-custom-p-asserted-id-formatstring

This will set the PAId of the connection. Example input "sample" will translate to "PAId=sample" in call rules

hello

connection-require-sip-authentication-enabledstring enum

Defaults to no

This setting when enable will request caller id blocking on outbound calls requesting privacy settings. This may lower the ability to connect certain calls if not setup properly to support privacy settings.

Allowed:

yes

no

yes

connection-translation-source-hoststring

apidog.pri

utc-offsetstring

This is the utc offset of the connection. Example "-7" for US/Pacific

-7

time-zonestring

This is the timezone of the connection

US/Pacific

minimum-call-duration-secondsinteger

Defaults to 0

connection-sip-registration-expires-datetimestring

2025-05-19 02:41:1

connection-sip-authenticate-as-client-enabledstring enum

Defaults to no

This setting when enable will request caller id blocking on outbound calls requesting privacy settings. This may lower the ability to connect certain calls if not setup properly to support privacy settings.

Allowed:

yes

no

no

connection-is-carrier-trunkstring enum

Defaults to no

This setting when enable will request caller id blocking on outbound calls requesting privacy settings. This may lower the ability to connect certain calls if not setup properly to support privacy settings.

Allowed:

yes

no

yes

call-routing

STRING | INTEGER | NUMBER | NULL

ARRAY | NULL

BOOLEAN | NULL

OBJECT | NULL

RESPONSES

202

RESPONSE BODY

object

HEADERS

object

400

401

404

Updated 7 days ago

Get All ConnectionsCount All Conections

Did this page help you? Yes No