OSHA Safety Glasses Checklist (29 CFR 1910.133)

For on-site checks of eye and face protection wherever eye or face hazards are present.

OSHA 29 CFR 1910.133

DATE	SHIFT
INSPECTOR	AREA / EQUIPMENT ID

Before you start

1. Mark every item OK, Defect or N/A; use N/A only where the hazard or task is not present in the area checked.
2. When an item fails, stop the task until the correct protection is in place, and record the defect and the corrective action.
3. The manufacturer's instructions and site rules may add checks beyond this list.

Legal basis: 29 CFR 1910.133: Eye and face protection (Part 1910 Subpart I, Personal Protective Equipment) Source: eCFR, Title 29, text as of 2026-11-09
Online version and sources: https://safetyindex.blog/us/standards/1910-133-eye-face-protection

SECTION A | Protection in use

No.	Check item	What to look for	OK	Defect	N/A	Notes
1	Flying particles Ref. 1910.133(a)(1)	Every employee exposed to flying particles is wearing suitable eyewear or face protection during the task.	☐	☐	☐	
2	Molten metal Ref. 1910.133(a)(1)	Workers exposed to molten metal have appropriate protection on and in position.	☐	☐	☐	
3	Liquid chemicals, acids and caustics Ref. 1910.133(a)(1)	Workers exposed to liquid chemicals, acid or caustic liquids wear protection appropriate to that hazard.	☐	☐	☐	
4	Chemical gases and vapors Ref. 1910.133(a)(1)	Workers exposed to chemical vapors or gases wear protection suited to the hazard.	☐	☐	☐	
5	Light radiation Ref. 1910.133(a)(1)	Workers exposed to light radiation that could injure the eyes wear appropriate protection.	☐	☐	☐	
6	Side protection Ref. 1910.133(a)(2)	Where flying objects are a hazard, the eyewear in use has side protection, built in or detachable.	☐	☐	☐	
7	Detachable side shields Ref. 1910.133(a)(2)	Clip-on or slide-on side shields are fitted to the frame and are of a type that meets 1910.133.	☐	☐	☐	
8	Prescription wearers Ref. 1910.133(a)(3)	Each employee wearing prescription lenses in operations with eye hazards wears protection with the prescription built in, or protection worn over the glasses.	☐	☐	☐	
9	Over-glasses fit Ref. 1910.133(a)(3)	Protection worn over prescription glasses leaves both the prescription lenses and the protective lenses in their proper position.	☐	☐	☐	

SECTION B | Filter shades for arc welding and cutting

No.	Check item	What to look for	OK	Defect	N/A	Notes
10	Filter lenses fitted Ref. 1910.133(a)(5)	Workers exposed to injurious light radiation use equipment with filter lenses that have a shade number suited to the work.	☐	☐	☐	
11	Shielded metal arc welding Ref. 1910.133(a)(5)	Shade no lighter than 7, 8, 10 or 11 for arc current below 60, 60-160, 160-250 or 250-550 respectively.	☐	☐	☐	
12	Gas metal arc and flux cored arc welding Ref. 1910.133(a)(5)	Shade no lighter than 7 below 60, and no lighter than 10 in the 60-160, 160-250 and 250-500 bands.	☐	☐	☐	
13	Gas tungsten arc welding Ref. 1910.133(a)(5)	Shade no lighter than 8 up to 150 arc current, and no lighter than 10 at 150-500.	☐	☐	☐	
14	Air carbon arc cutting Ref. 1910.133(a)(5)	Shade no lighter than 10 for light work (below 500) and 11 for heavy work (500-1000).	☐	☐	☐	
15	Plasma arc welding Ref. 1910.133(a)(5)	Shade no lighter than 6, 8, 10 or 11 for arc current below 20, 20-100, 100-400 or 400-800 respectively.	☐	☐	☐	
16	Plasma arc cutting Ref. 1910.133(a)(5)	With the arc in clear view, shade no lighter than 8 (below 300), 9 (300-400) or 10 (400-800).	☐	☐	☐	
17	Carbon arc welding Ref. 1910.133(a)(5)	Filter shade is 14 or darker.	☐	☐	☐	

SECTION C | Filter shades for gas welding, oxygen cutting, brazing and soldering

No.	Check item	What to look for	OK	Defect	N/A	Notes
18	Gas welding Ref. 1910.133(a)(5)	Shade no lighter than 4 for plate under 1/8 in., 5 for 1/8 to 1/2 in., and 6 for plate over 1/2 in.	☐	☐	☐	
19	Oxygen cutting Ref. 1910.133(a)(5)	Shade no lighter than 3 for plate under 1 in., 4 for 1 to 6 in., and 5 for plate over 6 in.	☐	☐	☐	
20	Torch brazing Ref. 1910.133(a)(5)	Filter shade is 3 or darker.	☐	☐	☐	
21	Torch soldering Ref. 1910.133(a)(5)	Filter shade is 2 or darker.	☐	☐	☐	
22	Shade selection Ref. 1910.133(a)(5)	The shade chosen gives a sufficient view of the weld zone and is not lighter than the table minimum for the operation.	☐	☐	☐	

SECTION D | Marking and design standard

No.	Check item	What to look for	OK	Defect	N/A	Notes
23	Manufacturer marking Ref. 1910.133(a)(4)	Each eye and face device carries a distinct marking that identifies its manufacturer.	☐	☐	☐	
24	Consensus standard Ref. 1910.133(b)(1)	Device markings or manufacturer documentation show compliance with ANSI/ISEA Z87.1-2010, ANSI Z87.1-2003 or ANSI Z87.1-1989 (R-1998).	☐	☐	☐	

General guidance only, not legal advice. Check the current regulation and your employer's procedures.

SECTION D | Marking and design standard

No.	Check item	What to look for	OK	Defect	N/A	Notes
25	Equivalent devices Ref. 1910.133(b)(2)	Any device not made to one of those editions comes with the employer's demonstration that it protects at least as well as a conforming device.	☐	☐	☐	

DEFECTS FOUND AND ACTION TAKEN

Item no.	Defect description	Reported to	Action taken / date closed

SIGN-OFF

SAFE TO OPERATE? ☐ Yes ☐ No: tagged out of service	
INSPECTOR SIGNATURE	DATE / TIME
SUPERVISOR REVIEW	DATE / TIME