OSHA Crane Inspection Checklist (29 CFR 1926.1412)

For the shift, monthly and annual/comprehensive inspections of cranes and derricks under 29 CFR 1926.1412.

OSHA 29 CFR 1926.1412

DATE	SHIFT
INSPECTOR	AREA / EQUIPMENT ID

Before you start

1. Mark every item OK, Defect or N/A; sections A and B apply at the shift, monthly and annual inspections, sections C to E at the annual/comprehensive inspection. For monthly and annual/comprehensive inspections, record the items checked, the results, the inspector's name and signature and the date (1926.1412(e)(3)(i), 1926.1412(f)(7)).
2. If a shift or monthly item fails, the competent person decides immediately whether it is a safety hazard; if so, the equipment is taken out of service until corrected (1926.1412(d)(2)), and a safety device or operational aid defect needs the action in 1926.1415 and 1926.1416 before use (1926.1412(d)(3)). Deficiencies found at the annual/comprehensive inspection are handled by the qualified person under 1926.1412(f)(4) to (f)(6).
3. The manufacturer's inspection procedures (1926.1412(j)) and site rules may add checks or require them more often.

Legal basis: 29 CFR 1926.1412: Inspections (Part 1926 Subpart CC, Cranes and Derricks in Construction) Source: eCFR, Title 29, text as of 2026-11-09
Online version and sources: https://safetyindex.blog/us/standards/1926-1412-inspections

SECTION A | Controls, lines, hooks and rope (each shift, monthly and annual)

No.	Check item	What to look for	OK	Defect	N/A	Notes
1	Control mechanisms Ref. 1926.1412(d)(1)(i)	No maladjustment interfering with proper operation	☐	☐	☐	
2	Control and drive mechanisms Ref. 1926.1412(d)(1)(ii)	No apparent excessive wear of components; no contamination by lubricants, water or other foreign matter	☐	☐	☐	
3	Air, hydraulic and other pressurized lines Ref. 1926.1412(d)(1)(iii)	No deterioration or leakage, including on lines that flex in normal operation	☐	☐	☐	
4	Hydraulic fluid level Ref. 1926.1412(d)(1)(iv)	Hydraulic system fluid at the proper level	☐	☐	☐	
5	Hooks and latches Ref. 1926.1412(d)(1)(v)	No deformation, cracks, excessive wear, or damage from chemicals or heat	☐	☐	☐	
6	Wire rope reeving Ref. 1926.1412(d)(1)(vi)	Reeving complies with the manufacturer's specifications	☐	☐	☐	
7	Wire rope Ref. 1926.1412(d)(1)(vii)	Rope inspected in accordance with 1926.1413(a)	☐	☐	☐	
8	Electrical apparatus Ref. 1926.1412(d)(1)(viii)	No malfunction, no apparent excessive deterioration, no dirt or moisture accumulation	☐	☐	☐	

SECTION B | Setup, cab and safety devices (each shift, monthly and annual)

No.	Check item	What to look for	OK	Defect	N/A	Notes
9	Tires (when in use) Ref. 1926.1412(d)(1)(ix)	Properly inflated and in proper condition	☐	☐	☐	

General guidance only, not legal advice. Check the current regulation and your employer's procedures.

SECTION B | Setup, cab and safety devices (each shift, monthly and annual)

No.	Check item	What to look for	OK	Defect	N/A	Notes
10	Ground conditions Ref. 1926.1412(d)(1)(x)	Ground gives proper support; no settling under or around outriggers/stabilizers or foundations; no ground water accumulation (excludes general railroad system track regulated under 49 CFR part 213)	☐	☐	☐	
11	Level Ref. 1926.1412(d)(1)(xi)	Equipment level within the manufacturer's tolerances before the shift and after each move and setup	☐	☐	☐	
12	Operator cab windows Ref. 1926.1412(d)(1)(xii)	No significant cracks, breaks or other deficiencies that would hamper the operator's view	☐	☐	☐	
13	Rails, rail stops, rail clamps and supporting surfaces (rail-travelling equipment) Ref. 1926.1412(d)(1)(xiii)	Checked with no deficiency found (not required for Federal Railroad Administration-regulated track that is part of the general railroad system)	☐	☐	☐	
14	Safety devices and operational aids Ref. 1926.1412(d)(1)(xiv)	All operate properly	☐	☐	☐	

SECTION C | Annual/comprehensive: structure, mechanical parts and power plant

No.	Check item	What to look for	OK	Defect	N/A	Notes
15	Structural members, boom and jib Ref. 1926.1412(f)(2)(i)(A)	Not deformed, cracked or significantly corroded	☐	☐	☐	
16	Bolts, rivets and other fasteners Ref. 1926.1412(f)(2)(i)(B)	None loose, failed or significantly corroded	☐	☐	☐	
17	Welds Ref. 1926.1412(f)(2)(i)(C)	No cracks	☐	☐	☐	
18	Sheaves and drums Ref. 1926.1412(f)(2)(ii)	No cracks or significant wear	☐	☐	☐	
19	Pins, bearings, shafts, gears, rollers and locking devices Ref. 1926.1412(f)(2)(iii)	No distortion, cracks or significant wear	☐	☐	☐	
20	Brake and clutch parts, linings, pawls and ratchets Ref. 1926.1412(f)(2)(iv)	No excessive wear	☐	☐	☐	
21	Safety device and operational aid accuracy Ref. 1926.1412(f)(2)(v)	Operate properly with no significant inaccuracies	☐	☐	☐	
22	Power plant Ref. 1926.1412(f)(2)(vi)	No safety-related problems such as leaking exhaust; emergency shut-down feature works; operates properly	☐	☐	☐	
23	Chains and chain drive sprockets Ref. 1926.1412(f)(2)(vii)	No excessive sprocket wear or excessive chain stretch	☐	☐	☐	
24	Travel steering, brakes and locking devices Ref. 1926.1412(f)(2)(viii)	All operate properly	☐	☐	☐	

General guidance only, not legal advice. Check the current regulation and your employer's procedures.

SECTION D | Annual/comprehensive: tires, hydraulics, pads, electrics, labels and seat						
No.	**Check item**	**What to look for**	**OK**	**Defect**	**N/A**	**Notes**
25	Tires Ref. 1926.1412(f)(2)(ix)	No damage or excessive wear	☐	☐	☐	
26	Hydraulic, pneumatic and other pressurized hoses, fittings and tubing Ref. 1926.1412(f)(2)(x)	No leak indications on flexible hose or at its junction with fittings; no leaks at threaded or clamped joints; hose outer covering free of blistering, abnormal deformation or other signs of failure; no excessive abrasion or scrubbing on hoses, rigid tubes or fittings	☐	☐	☐	
27	Hydraulic and pneumatic pumps and motors Ref. 1926.1412(f)(2)(xi)	No unusual noise or vibration, low operating speed, excessive fluid heating or low pressure; no loose bolts or fasteners; no leaks at shaft seals or joints between pump sections	☐	☐	☐	
28	Hydraulic and pneumatic valves Ref. 1926.1412(f)(2)(xii)	Spools free of sticking and leaks and return properly to neutral; no leaks; no valve housing cracks; relief valves reach correct pressure, using the manufacturer's pressure-check procedure where one exists	☐	☐	☐	
29	Hydraulic and pneumatic cylinders Ref. 1926.1412(f)(2)(xiii)	No drifting from fluid leaking across the piston; no leaks at rod seals or welded joints; rods free of scores, nicks or dents; no significant dents in the case (barrel); rod eyes and connecting joints not loose or deformed	☐	☐	☐	
30	Outrigger or stabilizer pads/floats Ref. 1926.1412(f)(2)(xiv)	No excessive wear or cracks	☐	☐	☐	
31	Slider pads Ref. 1926.1412(f)(2)(xv)	No excessive wear or cracks	☐	☐	☐	
32	Electrical components and wiring Ref. 1926.1412(f)(2)(xvi)	No cracked or split insulation; no loose or corroded terminations	☐	☐	☐	
33	Warning labels and decals Ref. 1926.1412(f)(2)(xvii)	All labels and decals originally supplied with the equipment by the manufacturer, or otherwise required under the standard, present and readable	☐	☐	☐	
34	Originally equipped operator seat Ref. 1926.1412(f)(2)(xviii)	Originally equipped operator seat (or equivalent) present	☐	☐	☐	

SECTION E | Seat, access, functional test and records						
No.	**Check item**	**What to look for**	**OK**	**Defect**	**N/A**	**Notes**
35	Operator seat condition Ref. 1926.1412(f)(2)(xix)	Seat serviceable	☐	☐	☐	
36	Originally equipped steps, ladders, handrails and guards Ref. 1926.1412(f)(2)(xx)	None missing	☐	☐	☐	
37	Steps, ladders, handrails and guards condition Ref. 1926.1412(f)(2)(xxi)	In usable, safe condition	☐	☐	☐	

SECTION E | Seat, access, functional test and records

No.	Check item	What to look for	OK	Defect	N/A	Notes
38	Annual functional test Ref. 1926.1412(f)(3)	Equipment, as configured in the inspection, tested and functioning properly	☐	☐	☐	
39	Monitored deficiencies Ref. 1926.1412(f)(6)	Each deficiency the qualified person determined needs monitoring is checked in the monthly inspections	☐	☐	☐	
40	Annual record retention Ref. 1926.1412(f)(7)	Record on file, kept at least 12 months by the employer that conducted the inspection	☐	☐	☐	
41	Monthly record retention Ref. 1926.1412(e)(3)(ii)	Record kept at least three months	☐	☐	☐	
42	Access to records Ref. 1926.1412(k)	Inspection documents within their retention period available to everyone who conducts inspections under 1926.1412	☐	☐	☐	

DEFECTS FOUND AND ACTION TAKEN

Item no.	Defect description	Reported to	Action taken / date closed

SIGN-OFF

SAFE TO OPERATE? ☐ Yes ☐ No: tagged out of service	
INSPECTOR SIGNATURE	DATE / TIME
SUPERVISOR REVIEW	DATE / TIME

General guidance only, not legal advice. Check the current regulation and your employer's procedures.