OSHA Bucket Truck Inspection Checklist (29 CFR 1910.67)

For supervisors checking a bucket truck or other vehicle-mounted aerial lift on site before use and before travel.

OSHA 29 CFR 1910.67

DATE	SHIFT
INSPECTOR	AREA / EQUIPMENT ID

Before you start

1. Mark every item OK, Defect or N/A.
2. If an item fails, report it and keep the lift out of use until the defect is corrected; record what was done.
3. The manufacturer's instructions and site rules may add checks to this list.

Legal basis: 29 CFR 1910.67: Vehicle-mounted elevating and rotating work platforms Work near overhead electric lines: 29 CFR 1910.333(c)(3), referenced in 1910.67(b)(4) Source: eCFR, Title 29 (text as of 2026-11-09)

Online version and sources: https://safetyindex.blog/us/standards/1910-67-vehicle-mounted-elevating-rotating-work

SECTION A | Equipment, modifications and electrical tests

No.	Check item	What to look for	OK	Defect	N/A	Notes
1	Design standard Ref. 1910.67(b)(1)	Records show a lift acquired on or after July 1, 1975 was designed and built to ANSI A92.2-1969, or an older lift meets it or was modified to conform	☐	☐	☐	
2	Field modifications Ref. 1910.67(b)(2)	Any field modification has written certification from the manufacturer or an equivalent entity, such as a nationally recognized testing laboratory	☐	☐	☐	
3	Electrical test record Ref. 1910.67(c)(3)	Test record shows testing to ANSI A92.2-1969 Section 5, or a DC voltage test approved by the manufacturer or an equivalent entity	☐	☐	☐	
4	Insulated portion Ref. 1910.67(c)(2)(xi)	No alteration to the insulated portion that might reduce its insulating value	☐	☐	☐	
5	Vehicle stability Ref. 1910.67(b)(3)	The vehicle provides a stable support for the aerial device	☐	☐	☐	

SECTION B | Operator, controls and setup

No.	Check item	What to look for	OK	Defect	N/A	Notes
6	Operator training Ref. 1910.67(c)(2)(ii)	The person operating the lift is trained	☐	☐	☐	
7	Daily controls test Ref. 1910.67(c)(2)(i)	Lift controls were tested today before use and found in safe working condition	☐	☐	☐	
8	Upper and lower controls Ref. 1910.67(c)(2)(ix)	A boom platform designed mainly as a personnel carrier has both platform (upper) and lower controls	☐	☐	☐	
9	Upper control position Ref. 1910.67(c)(2)(ix)	Upper controls are in or beside the platform, within easy reach of the operator	☐	☐	☐	
10	Lower control override Ref. 1910.67(c)(2)(ix)	Lower controls override the upper controls	☐	☐	☐	
11	Control markings Ref. 1910.67(c)(2)(ix)	Each control is plainly marked as to its function	☐	☐	☐	

General guidance only, not legal advice. Check the current regulation and your employer's procedures.

SECTION B | Operator, controls and setup

No.	Check item	What to look for	OK	Defect	N/A	Notes
12	Brakes Ref. 1910.67(c)(2)(vii)	Brakes are set	☐	☐	☐	
13	Outriggers Ref. 1910.67(c)(2)(vii)	Outriggers in use sit on pads or a solid surface	☐	☐	☐	
14	Wheel chocks Ref. 1910.67(c)(2)(vii)	On an incline, wheel chocks are installed before the lift is used	☐	☐	☐	

SECTION C | Working from the basket

No.	Check item	What to look for	OK	Defect	N/A	Notes
15	Fall protection worn Ref. 1910.67(c)(2)(v)	Each worker in the basket wears a fall arrest or restraint system that meets subpart I of part 1910	☐	☐	☐	
16	Attachment point Ref. 1910.67(c)(2)(v)	The system is connected at the boom or the basket	☐	☐	☐	
17	No belting off Ref. 1910.67(c)(2)(iii)	No worker is belted off to an adjacent pole, structure or equipment	☐	☐	☐	
18	Footing Ref. 1910.67(c)(2)(iv)	Workers stay on the basket floor; nobody sits or climbs on the basket edge	☐	☐	☐	
19	No raised work positions Ref. 1910.67(c)(2)(iv)	No planks, ladders or other devices are used as a work position	☐	☐	☐	
20	Climbers Ref. 1910.67(c)(2)(x)	No climbers are worn by anyone working from the lift	☐	☐	☐	
21	Load limits Ref. 1910.67(c)(2)(vi)	Boom and basket loads are within the manufacturer's specified limits	☐	☐	☐	
22	Lower control use Ref. 1910.67(c)(2)(ix)	Lower controls are operated only with permission from the worker in the lift, unless there is an emergency	☐	☐	☐	

SECTION D | Moving the truck

No.	Check item	What to look for	OK	Defect	N/A	Notes
23	No travel with boom raised Ref. 1910.67(c)(2)(viii)	Truck is not moved with the boom elevated and workers in the basket, unless the equipment is specifically designed for it	☐	☐	☐	
24	Boom cradled Ref. 1910.67(c)(2)(xii)	Before travel, the boom or booms are inspected and properly cradled	☐	☐	☐	
25	Outriggers stowed Ref. 1910.67(c)(2)(xii)	Before travel, outriggers are in the stowed position	☐	☐	☐	
26	Aerial ladder secured (ladder and tower trucks) Ref. 1910.67(c)(1)	Before highway travel, the aerial ladder is locked in the lower traveling position by the device above the cab and the manual device at the ladder base, or an equally effective means	☐	☐	☐	

General guidance only, not legal advice. Check the current regulation and your employer's procedures.

DEFECTS FOUND AND ACTION TAKEN

Item no.	Defect description	Reported to	Action taken / date closed

SIGN-OFF

SAFE TO OPERATE?	☐ Yes ☐ No: tagged out of service	
INSPECTOR SIGNATURE		DATE / TIME
SUPERVISOR REVIEW		DATE / TIME

General guidance only, not legal advice. Check the current regulation and your employer's procedures.