

# NLP Assignment 2

## Author

MTU / (John) Paul Nagle  
John.P.Nagle@mymtu.ie

## Abstract

This paper presents a cascaded speech-to-text translation system for the low-resource Irish-to-English language pair, developed as part of the Natural Language Processing module for the M.Sc. in AI at MTU. It addresses the challenges of translating Irish (Gaeilge) speech while implementing a two-stage pipeline combining Automatic Speech Recognition (ASR) and Machine Translation (MT) components. The baseline system integrates OpenAI’s Whisper model (Radford et al., 2023) for ASR with Meta’s NLLB-200 (NLLB Team et al., 2022) for neural machine translation. To address the low-resource nature of Irish, we develop an improved system utilising Irish-specific fine-tuned Whisper models that better handle the language’s unique phonological characteristics. We evaluate both systems on the IWSLT 2026 Irish-English test set using standard metrics including BLEU (Papineni et al., 2002) and chrF++ (Popović, 2015), with comprehensive error analysis identifying common failure modes such as language misidentification and morphological errors. Our results demonstrate the effectiveness of language-specific model adaptation in low-resource settings, while highlighting persistent challenges in cascaded architectures including error propagation from ASR to MT stages.

## 1 Problem Statement

This work addresses the challenge of low-resource speech-to-text translation for the Irish-to-English language pair. Speech translation (ST) — converting spoken audio in one language into text in another — presents significant difficulties for low-resource languages like Irish (Gaeilge), which has limited transcribed audio data and fewer high-quality pretrained models compared to well-resourced languages.

We implement a cascaded pipeline architecture combining Automatic Speech Recognition

(ASR) and Machine Translation (MT) components. This approach offers practical advantages in low-resource settings: ASR and MT components can be independently pretrained on large datasets, errors can be diagnosed at each stage, and strong off-the-shelf models are readily available. Our baseline system integrates OpenAI’s Whisper model for ASR with Meta’s NLLB-200 for neural machine translation.

The primary research question is: *How can we improve translation quality for low-resource Irish speech by optimizing component selection in a cascaded pipeline?* We evaluate two key dimensions: (1) the impact of Irish-specific fine-tuned ASR models versus general multilingual models, and (2) the comparative performance of multilingual (NLLB-200) versus bilingual (OPUS-MT) translation models. Our evaluation uses the IWSLT 2026 Irish-English dataset (Uppaal et al., 2026), measuring performance through BLEU, chrF++, and COMET metrics while conducting systematic error analysis to identify failure modes specific to Irish morphology and phonology.

## 2 Dataset

We utilize the IWSLT 2026 Irish-English speech translation dataset (Uppaal et al., 2026), which provides parallel Irish speech and English text for low-resource speech translation research. For this work, we exclusively use the development split located in `iwslt2026_ga-eng/iwslt2025_ga-eng/dev/`, as it is the only subset providing both Irish audio files (`wav/`) and corresponding English reference translations (`txt/`).

### 2.1 Dataset Composition

The development set contains 1120 audio samples with corresponding English translations. This limited dataset size reflects the low-resource nature of Irish speech translation and necessitates reliance on

pretrained models rather than training from scratch. While the dataset includes additional splits (training and test sets), these were not utilised in our pipelines due to the absence of paired English translations required for evaluation.

## 2.2 Audio Characteristics

All audio files are provided in WAV format with 16kHz sampling rate, mono channel configuration. Audio segments vary in duration, with filenames set so that an alphabetical listing matches the order of the translations in the dev.eng. The dataset includes both individual utterances and slightly longer continuous speech segments, reflecting realistic single sentence speech translation scenarios, but not longer conversations.

## 2.3 Annotation Format

Ground truth annotations are provided in TSV format (stamped.tsv) containing three fields: audio filename, start timestamp, and length in seconds. In some of the other unused data folders, english reference texts are also available as plain text files (train.eng, dev.eng, test.eng), but in the dev set we only have the dev.eng file for translations.

## 2.4 Preprocessing

Audio preprocessing is minimal to preserve authentic speech characteristics. We load audio files using the librosa library with 16kHz sampling rate to match Whisper model requirements. No additional noise reduction, normalization, or voice activity detection is applied, as pretrained models are designed to handle raw speech input. For translation evaluation, we tokenize reference texts using standard whitespace splitting to compute BLEU and chrF++ metrics.

## 2.5 Dataset Challenges

The dataset presents several challenges characteristic of low-resource speech translation: (1) extremely limited training data (1120 samples) necessitating reliance on pretrained models, (2) Irish phonological complexity including lenition, eclipsis, and dialectal variation, and (3) morphological richness with extensive inflection and mutation systems.

# 3 Pipeline Architectures

We implement four cascaded speech translation systems combining different ASR and MT components. All systems follow a two-stage architecture:

audio → Irish transcription (ASR) → English translation (MT).

## 3.1 Baseline System: Whisper-Large + NLLB

Our baseline combines OpenAI’s Whisper-large-v3 (Radford et al., 2023; OpenAI, 2023) for ASR with Meta’s NLLB-200-distilled-600M (NLLB Team et al., 2022; Meta AI, 2022) for MT. Whisper-large-v3 (1.5B parameters) is a multilingual ASR model trained on 680,000 hours of audio across 99 languages including Irish. We use the model without language-specific fine-tuning, relying on its general multilingual capabilities.

For translation, NLLB-200 (600M parameters) supports 200 languages including Irish (gle\_Latn) and English (eng\_Latn). We configure the model with forced BOS token for target language specification and beam search (num\_beams=5) for improved output quality.

**Pipeline flow:** Audio (16kHz WAV) → Whisper processor (mel-spectrogram extraction, 80 mel bins) → Whisper encoder-decoder → Irish transcript → NLLB tokenizer → NLLB encoder-decoder → English translation.

**Justification:** This baseline represents a strong starting point using state-of-the-art multilingual models with proven performance across diverse languages. Both models are readily available via HuggingFace and require no additional training.

## 3.2 Improved System 1: Specialized Whisper + NLLB

The first improvement replaces the general Whisper model with InoWouw/whisper-small-irish (InoWouw, 2023), a Whisper-small variant (244M parameters) fine-tuned specifically on Irish speech data. This model addresses the baseline’s tendency to misidentify Irish as Welsh or English due to phonological similarities.

### Key modifications:

- Irish-specific acoustic modeling trained on native speaker data
- Reduced model size (244M vs 1.5B parameters) with specialized performance
- Same mel-spectrogram preprocessing (80 bins, 16kHz) for compatibility
- Identical NLLB-200 MT component as baseline

**Justification:** Language-specific fine-tuning should improve ASR accuracy for Irish phonological features (lenition, eclipsis, broad/slender consonants), reducing error propagation to the MT stage. The smaller model size also improves inference speed.

### 3.3 Improved System 2: Whisper-Large + OPUS-MT

This variant maintains the baseline Whisper-large-v3 ASR but replaces NLLB with Helsinki-NLP’s opus-mt-ga-en (Helsinki-NLP, 2020), a bilingual Irish-English translation model from the OPUS-MT family. Unlike NLLB’s multilingual approach, OPUS-MT is trained exclusively on Irish-English parallel data.

#### Key modifications:

- Bilingual translation model (smaller, 300M parameters)
- Direct Irish→English optimization without multilingual interference
- Simpler tokenization without language-specific BOS tokens
- Same beam search configuration (num\_beams=5)

**Justification:** Bilingual models often outperform multilingual models on specific language pairs due to focused training. OPUS-MT may better handle Irish-specific translation challenges like VSO word order and prepositional pronouns.

### 3.4 Improved System 3: Specialized Whisper + OPUS-MT

Our best-performing system combines both improvements: Irish-specific ASR (InoWouw/whisper-small-irish) with bilingual MT (opus-mt-ga-en). This architecture optimizes both pipeline stages for the Irish-English language pair.

**Justification:** Combining specialized ASR and focused MT should provide synergistic improvements. Better Irish transcriptions from the specialized ASR reduce MT errors, while the bilingual MT model better handles the improved Irish input. This represents the most language-pair-specific configuration tested.

### 3.5 Implementation Details

All systems share common preprocessing: audio resampling to 16kHz mono using librosa, Whisper feature extraction with 80 mel-frequency bins, and beam search decoding. We process the complete IWSLT 2026 development set (1120 samples) for each system. Models run on GPU (CUDA) with float32 precision to ensure numerical stability. No audio augmentation or text post-processing is applied to maintain fair comparison across systems.

## 4 Experiment

### 4.1 Evaluation Setup

We evaluate all four pipeline systems on the complete IWSLT 2026 development set (1120 audio samples). Each system processes the same input audio files through its respective ASR and MT components, producing English translations that are compared against reference translations using automated metrics.

The evaluation pipeline follows a consistent procedure across all systems: (1) audio files are loaded and resampled to 16kHz mono format using librosa, (2) ASR models transcribe audio to Irish text, (3) MT models translate Irish transcriptions to English, and (4) outputs are evaluated against reference translations. All models run on GPU (NVIDIA L4) with float32 precision to ensure numerical stability and reproducibility.

We set random seed to 42 across all random number generators (Python random, NumPy, PyTorch) to ensure reproducible results. No audio augmentation, voice activity detection, or text post-processing is applied to maintain fair comparison across systems.

### 4.2 Metrics

We employ three complementary automatic evaluation metrics to assess translation quality:

**BLEU** (Papineni et al., 2002): Measures n-gram precision between hypothesis and reference translations (1-4 grams). We use SacreBLEU implementation for reproducibility. BLEU is the standard MT metric but can be overly sensitive to word choice variations.

**chrF++** (Popović, 2015): Character-level F-score metric with word n-gram bonuses (word\_order=2). More robust than BLEU for morphologically rich languages like Irish, as it captures partial matches at character level and is less sensitive to word order variations.

**COMET** (Rei et al., 2020): Neural metric (wmt22-comet-da model) that uses cross-lingual embeddings to assess semantic similarity. Correlates better with human judgments than surface-form metrics but requires more computational resources.

Additionally, we report diagnostic metrics: **Coverage** (proportion of non-empty outputs), **Repetition Rate** (frequency of degenerate repeated n-grams), **Length Ratio** (hypothesis/reference length), and **Processing Time** (average seconds per file).

### 4.3 Experimental Conditions

All experiments run on Google Colab with NVIDIA L4 GPU. Models are loaded in float32 precision to avoid numerical instability. ASR models use beam search decoding with default parameters. MT models employ beam search with num\_beams=5 and early\_stopping=True for improved output quality.

The complete development set (1120 samples) is processed for each system configuration. Processing times vary by model size: baseline systems (Whisper-large-v3 + NLLB/OPUS-MT) average 1.56-1.70 seconds per file, while specialized systems (Whisper-small-irish + NLLB/OPUS-MT) average 0.64-0.82 seconds per file due to the smaller ASR model (244M vs 1.5B parameters).

All systems achieve 100% coverage (no empty outputs), indicating robust pipeline operation. Evaluation uses the evaluate library for BLEU/chrF++ and unbabel-comet for COMET scoring, with batch\_size=8 and gpus=1 for COMET inference.

## 5 BLEU/chrF++/COMET Scores

Table 1 presents comprehensive evaluation results for all four pipeline configurations on the IWSLT 2026 development set (1120 samples). The Specialised ASR + NLLB system achieves the highest BLEU score (4.36) and chrF++ score (22.25), representing substantial improvements of +2.85 BLEU and +6.35 chrF++ over the baseline (Table 2). The Specialised ASR + OPUS-MT configuration follows closely with BLEU 3.40 and chrF++ 21.56, showing gains of +1.89 BLEU and +5.66 chrF++ relative to baseline.

The baseline systems demonstrate significantly lower performance, with Baseline ASR + NLLB achieving BLEU 1.51 and chrF++ 15.90, while Baseline ASR + OPUS-MT scores marginally

lower at BLEU 1.42 and chrF++ 15.19. Notably, switching from NLLB to OPUS-MT in the baseline configuration yields minimal improvement (-0.09 BLEU, -0.71 chrF++), suggesting that MT model selection has limited impact when ASR quality is poor.

COMET scores reveal a different pattern: Specialised ASR + NLLB achieves the highest semantic similarity (0.4752), followed by Specialised ASR + OPUS-MT (0.4384), Baseline ASR + NLLB (0.4375), and Baseline ASR + OPUS-MT (0.4168). The relatively modest COMET differences compared to surface-form metrics suggest that while specialized ASR improves lexical accuracy substantially, semantic content preservation remains challenging across all systems.

All systems achieve 100% coverage with no empty outputs, indicating robust pipeline operation. However, repetition rates vary considerably: Baseline ASR + NLLB exhibits the highest repetition rate (4.11%), while Specialised ASR + OPUS-MT shows the lowest (0.62%). This suggests that improved ASR quality reduces degenerate MT outputs, particularly when combined with the bilingual OPUS-MT model.

Length ratios remain close to 1.0 across all systems (1.02-1.07), indicating that hypothesis lengths approximate reference lengths reasonably well. Average hypothesis lengths range from 10.07 to 10.55 words compared to the reference average of 9.88 words, with specialized systems producing slightly longer outputs.

Processing efficiency differs substantially between baseline and specialized systems. Baseline configurations average 1.56-1.70 seconds per file due to the large Whisper-large-v3 model (1.5B parameters), while specialized systems process files in 0.64-0.82 seconds using the smaller Whisper-small-irish model (244M parameters). This represents a 52-62% reduction in processing time while simultaneously improving translation quality.

The results demonstrate that Irish-specific ASR fine-tuning is the primary driver of translation improvements in cascaded pipelines. The specialized ASR model’s superior handling of Irish phonology (lenition, eclipsis, dialectal variation) reduces error propagation to the MT stage. MT model selection (NLLB vs OPUS-MT) shows secondary importance: NLLB performs better with specialized ASR (+0.96 BLEU over OPUS-MT), while both MT models perform similarly poorly with baseline ASR. This suggests that high-quality Irish transcrip-

tions enable NLLB’s multilingual capabilities to function effectively, whereas poor transcriptions limit both MT approaches equally.

## 6 Qualitative Analysis

## 7 Result Interpretations

## 8 Summary

### References

- Helsinki-NLP. 2020. OPUS-MT irish-english translation model. <https://huggingface.co/Helsinki-NLP/opus-mt-ga-en>. License: Apache-2.0.
- InoWouw. 2023. Whisper small irish. <https://huggingface.co/InoWouw/whisper-small-irish>. License: Apache-2.0.
- Meta AI. 2022. NLLB-200 distilled 600m. <https://huggingface.co/facebook/nllb-200-distilled-600M>. License: CC-BY-NC-4.0.
- NLLB Team, Marta R. Costa-jussà, James Cross, Onur Çelebi, Maha Elbayad, Kenneth Heafield, Kevin Hefernan, Elahe Kalbassi, Janice Lam, Daniel Licht, Jean Maillard, Anna Sun, Skyler Wang, Guillaume Wenzek, Al Youngblood, Bapi Akula, Loic Barrault, Gabriel Mejia-Gonzalez, Prangthip Hansanti, and 20 others. 2022. No language left behind: Scaling human-centered machine translation. *arXiv preprint arXiv:2207.04672*.
- OpenAI. 2023. Whisper large v3. <https://huggingface.co/openai/whisper-large-v3>. License: Apache-2.0.
- Kishore Papineni, Salim Roukos, Todd Ward, and Wei-Jing Zhu. 2002. BLEU: a method for automatic evaluation of machine translation. In *Proceedings of the 40th Annual Meeting of the Association for Computational Linguistics*, pages 311–318.
- Maja Popović. 2015. chrF: character n-gram F-score for automatic MT evaluation. In *Proceedings of the Tenth Workshop on Statistical Machine Translation*, pages 392–395.
- Alec Radford, Jong Wook Kim, Tao Xu, Greg Brockman, Christine McLeavey, and Ilya Sutskever. 2023. Robust speech recognition via large-scale weak supervision. *arXiv preprint arXiv:2212.04356*.
- Ricardo Rei, Craig Stewart, Ana C Farinha, and Alon Lavie. 2020. COMET: A neural framework for MT evaluation. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 2685–2702.
- Shashwat Uppaal and 1 others. 2026. IWSLT 2026 irish-english speech translation dataset. [https://github.com/shashwatup9k/iwslt2026\\_ga-eng](https://github.com/shashwatup9k/iwslt2026_ga-eng). Accessed: 2026-05-12.

## A AI Use Declaration

I used AI to blah blah blah.



Table 1: Overall Comparison Table

| System                  | Samples | Valid | BLEU | chrF++ | COMET  | Coverage | Rep % | Avg Hyp Len | Avg Ref Len | Length Ratio | Avg Time/File (s) |
|-------------------------|---------|-------|------|--------|--------|----------|-------|-------------|-------------|--------------|-------------------|
| Specialised ASR+NLLB    | 1120    | 1120  | 4.36 | 22.25  | 0.4752 | 100.0    | 2.59  | 10.40       | 9.88        | 1.05         | 0.82              |
| Specialised ASR+OPUS-MT | 1120    | 1120  | 3.40 | 21.56  | 0.4384 | 100.0    | 0.62  | 10.55       | 9.88        | 1.07         | 0.64              |
| Baseline ASR+NLLB       | 1120    | 1120  | 1.51 | 15.90  | 0.4375 | 100.0    | 4.11  | 10.31       | 9.88        | 1.04         | 1.70              |
| Baseline ASR+OPUS-MT    | 1120    | 1120  | 1.42 | 15.19  | 0.4168 | 100.0    | 2.32  | 10.07       | 9.88        | 1.02         | 1.56              |

Table 2: Relative Comparison vs Baseline ASR + NLLB

| System                    | BLEU | BLEU $\Delta$ vs Baseline | chrF++ | chrF++ $\Delta$ vs Baseline | Coverage | Coverage $\Delta$ vs Baseline | Avg Time/File (s) | Time/File $\Delta$ vs Baseline |
|---------------------------|------|---------------------------|--------|-----------------------------|----------|-------------------------------|-------------------|--------------------------------|
| Specialised ASR + NLLB    | 4.36 | 2.85                      | 22.25  | 6.35                        | 100.0    | 0.0                           | 0.82              | -0.88                          |
| Specialised ASR + OPUS-MT | 3.40 | 1.89                      | 21.56  | 5.66                        | 100.0    | 0.0                           | 0.64              | -1.06                          |
| Baseline ASR + NLLB       | 1.51 | 0.00                      | 15.90  | 0.00                        | 100.0    | 0.0                           | 1.70              | 0.00                           |
| Baseline ASR + OPUS-MT    | 1.42 | -0.09                     | 15.19  | -0.71                       | 100.0    | 0.0                           | 1.56              | -0.14                          |