

# Software and systems engineering

Paulo Borba  
Informatics Center  
Federal University of Pernambuco

[phmb@cin.ufpe.br](mailto:phmb@cin.ufpe.br) ♦ [twitter.com/pauloborba](https://twitter.com/pauloborba)

# To do before class

- Watch video
- Read related part of chapter 10 in the textbook
- Send questions and opinions through slack

# Software and systems engineering

Paulo Borba  
Informatics Center  
Federal University of Pernambuco

[phmb@cin.ufpe.br](mailto:phmb@cin.ufpe.br) ♦ [twitter.com/pauloborba](https://twitter.com/pauloborba)

# Configuration management I, basic concepts and operations

Software and system  
development is often  
done in teams!

Team members  
contribute to the same  
artifacts

Productivity and quality  
problems sharing requirements,  
source code, etc. via...

- email
- dropbox
- google docs

Source code (artifact)  
control systems



# Version Control

## purposes (De Rosso & Jackson)

- **Data management:** make a set of changes persistent
- **Change management:** group logically related changes, record coherent points
- **Collaboration:** synchronise changes
- **Parallel development:** isolated lines of development
- **Disconnected operation**




# Overview of main concepts

# Creating a local repository

From scratch

# git init




From an existing  
repository

git clone

server

remote repository




project  
history






server


## remote repository



## local repository




## staging area



## stash




## working area



files and  
folders pointed  
by HEAD

developer machine


# Commit graph




Persisting and recording  
changes

Locally changing files

## local repository




## staging area




## stash




## working area



developer machine



## local repository




## staging area



## stash



## working area




developer machine

git add

indicating that files are  
of interest

## local repository




staging area




stash



working area




developer machine






# local repository




## staging area



## stash



## working area




developer machine


git commit

recording changes

## local repository




## staging area




## stash




## working area



developer machine



## local repository




staging area




stash




working area



developer machine



named  
pointers are  
updated




Could select subset of  
changes that are in the  
stage area

`git commit -a`

combining commands

## local repository




staging area




stash



working area




developer machine





## local repository




staging area



stash



working area




developer machine

Collaborating


At creation time, local  
and remote commit  
histories are identical

server


## remote repository



## local repository




## staging area



## stash



## working area




developer machine


But history might have  
evolved in the local  
repository

server

## remote repository



## local repository




## staging area



## stash



## working area




developer machine

git push


sending changes to a  
remote repository

server

## remote repository



## local repository




## staging area




## stash



## working area




developer machine






server

## remote repository



## local repository




## staging area



## stash



## working area




developer machine


But history might have  
evolved in the remote  
repository

server


## remote repository



## local repository




## staging area



## stash



## working area




developer machine

git pull


getting changes from a  
remote repository

server


## remote repository



## local repository




## staging area




## stash



## working area




developer machine




server

## remote repository



## local repository




## staging area



## stash



## working area





developer machine

When you don't have  
write access to the  
remote repository...


Create your own  
remote repository, a  
fork




## remote repository



## remote repository



## fork




Push to fork


Create and send Pull  
Request  
(from fork to remote)

# Pull request collaboration model


server



remote repository




fork




1 push

3 pull

local repository



local repository



developer machine A

developer machine B

Take notes,  
now!

# Hands on exercises

# Configuration management I, basic concepts and operations

# Configuration management 2, advanced concepts and operations




What if the changes  
you are making are  
tentative or risky?

And you don't want to  
compromise other  
tasks and developers


Supporting independent  
(parallel) development

Naturally supported  
with local repositories


server



remote repository




fork




1 push

3 pull

local repository



local repository



developer machine A


developer machine B


But can we also  
support independence  
locally?

git branch

branches as pointers

multiple development  
lines










git checkout


changing branches






evolving a branch by  
creating new commits





git checkout effect on  
working area

# local repository




staging area



stash




working area



developer machine



# local repository




## staging area



## stash





## working area




developer machine

evolving another  
branch by creating new  
commits









# Integrating code contributions

git merge

merging locally










multiple branches and  
lines

multiple merges








# commit hashes


```
ed7058d9fd9ef55eed72abf29752bc50aa43ac5b
```

```
331cd13938e1487b8fbb2dd2fe7714d4934cf274
```


```
5fe7dfebaabc5c60f521568f96288f72dfb82c4c
```


# git checkout for branches and hashes














merge conflicts

no problem when  
different files are  
changed






no problem if the same  
files are changed in  
different areas







but conflict if the same  
files are changed in the  
same areas

```
class C {  
    m() {  
        ...  
    }  
    ...  
}
```

```
class C {  
    n() {  
        ...  
    }  
    m() {  
        ...  
    }  
    ...  
}
```

```
class C {  
    o() {  
        ...  
    }  
    m() {  
        ...  
    }  
    ...  
}
```


```
class C {  
    <<<<<<  
    n() {  
        ...  
    }  
    =====  
    o() {  
        ...  
    }  
    >>>>>>  
    m() {  
        ...  
    }  
    ...  
}
```

conflict markers

no merge  
commit is created

separators define areas


```
class C {  
    m() {  
        ...  
    }  
    ...  
}
```




```
class C {  
    m() {  
        ...  
    }  
    o() {  
        ...  
        ...  
    }  
    ...  
}
```



```
class C {  
    n() {  
        ...  
    }  
    m() {  
        ...  
    }  
    o() {  
        ...  
        ...  
    }  
    ...  
}
```





```
class C {  
    n() {  
        ...  
    }  
    m() {  
        ...  
    }  
    ...  
}
```



separator

git merge does not  
detect semantic  
conflicts

```
m(x){  
  if (x==null) return;  
  y = x;  
  if (x!=null) y = x.n();  
}
```





```
m(x){  
  if (x==null) return;  
  y = x;  
  y = x.n();  
}
```

```
m(x){  
  y = x;  
  if (x!=null) y = x.n();  
}
```

git merge

```
m(x){  
  y = x;  
  y = x.n();  
}
```



Take notes,  
now!



# Hands on exercises

# Configuration management 2, advanced concepts and operations

# Configuration management 3, continuous integration and deployment

# Branches

# Branches are used for supporting...

- independent development
  - feature or component development
  - bug fixing
- bug fixing in previous releases
- customer specific variants (not a good idea, better options available)

# Branches isolate changes until they are...

- mature (do not break other functionality)
- chosen for a release (in master)
- ready to be updated with other changes (from master, without breaking development flow)
- reconciled with alternative functionality

But we should use with  
care

# Risks of branching

- isolation provided by branches reduce pressure to integrate changes (increase time to market)
- delayed integration
  - increase the risk of conflicts, which are harder to solve the latter they are detected
  - developers might avoid refactoring because of the risk of conflicts



promiscuous— branch to branch  
— integration, or from master to  
branch, could reduce the risks



Code integration is not  
restricted to branches  
in a single repository

git pull  
(fetch + merge)


merging with remote

server

remote repository




local repository



developer machine A


server

remote repository



push


local repository




developer machine A

server

remote repository



local repository




developer machine A


git stash

temporarily saving  
partial changes

## local repository




## staging area



## stash




## working area




developer machine




# local repository




## staging area



## stash




## working area




developer machine

stash area is a stack


# local repository




## staging area



## stash



## working area




developer machine


git stash drop (pop)

git stash apply


# local repository




## staging area



## stash




## working area




developer machine


# local repository




## staging area



## stash



## working area



developer machine

stash code is integrated  
to the working area


conflicts might arise


# Other code integration commands





git rebase


# merge might complicate history













interactive rebase

squash

git cherry-pick








Advanced

git config

git tag



# git reset

**reset --soft X**: makes HEAD and the current branch point to X (X could be HEAD~ or hash)

**reset --mixed X** (default): same as before plus updates stage (index) with X contents

**reset --hard X**: same as before plus updates working directory with X contents

# Commit

- 1 hash: 40 hex characters (SHA)
- Parent commits, message, author/commiter, email, time
- Not diffs
- Root (Merkle) tree, contains names of files and folders inside (and file modes)
- Blobs (binary large objects; file contents, not names)
- `git cat-file -p commit_hash` (to see commit contents, all with identifiers based on SHA)



# Summary of git concepts

# Workflows

- Creating repositories (locals, remotes, bare, fork, clone)
- Recording changes (working area, stage, tracked, ignored, assume unchanged, commit)
- Branching (pointer, master, HEAD, stash)

# Workflows

- Tagging (pointer not updated by commit)
- Integrating changes (merge, rebase, cherry-pick, conflicts, squash)
- Synchronizing repositories (push, pull, PR, remote branch, upstream branch)

# Storage areas

- Non-bare Repository
- Bare Repository
- Commit
- Staging Area
- Stash

# References




- Head
- Tag
- Branch
- Upstream Branch (sync default)
- Remote Branch

# File classifications

- Tracked
- Untracked
- Ignored
- Assume Unchanged
- In Conflict

at least daily

Continuous  
building and testing  
integration  
deployment





# Advantages and disadvantages

- No need for hotfixes
- Better support for a global engineering team
- Scales (number of developers, commits, etc.)
- Conflicts are detected early
- High quality, confident developers
- Might break development flow (due to code that might not even be released)
- Need for Gatekeeper system
  - feature flags might pollute the code
  - part of the functionality might become dead code

# Before integrating...

- Review scenarios and features, or write scenarios in pairs
- Make sure they follow style and quality criteria
- Organize review procedures and meetings

# Checklist

# Checklist

- Clear commit messages, exactly corresponding to what has changed
  - no language errors
- Commit early and often
  - avoid tangled commits
  - aim for conceptual, modular changes
- Often integrate your code (small integrations, by merging to or from master)

# Checklist

- Antes de enviar um pull request, deve-se, obrigatoriamente, fazer um merge ou rebase para que suas modificações sejam aplicadas à versão mais atual do repositório central do seu projeto, não à última versão que você tinha na sua máquina e com informações desnecessárias.
- A mensagem do pull request deve descrever com precisão e clareza o seu conteúdo.
- Cada pull request deve incluir somente os arquivos que foram alterados para a atividade.

# Checklist

- Pull requests não devem conter arquivos gerados ou de configuração particular de cada máquina ou IDE, como `.classpath`, `.project`, `.class`. O mesmo vale para arquivos de log e similares. Não deve-se dar commits nesses arquivos. Use o `.gitignore` para evitar esse problema.
- Evite pular linhas, adicionar espaços, etc. em partes do código que você não precisa modificar; cada mudança desses precisa ser analisada por quem vai integrar a sua contribuição ao repositório principal, e podem gerar conflitos.
- Tenha certeza de que todos os testes estejam passando na versão incluída no pull request.

# Change requests and change managements

# Issues or change requests

- Bug report
- Need for new feature or scenario
- Need for changing a particular feature
- Need for code improvement
- Need for performance improvement
- Chore description (provide no direct value to the customer)



Take notes,  
now!

# Hands on exercises

# Configuration management 3

# CM research at CIn

- Advanced merging tools: Paulo
- Collaboration conflicts characteristics: Paulo

# To do after class

- Answer questionnaire (check classroom assignment), study correct answers
- Finish exercise (check classroom assignment), study correct answers
- Read, again, part of chapter 10 in the textbook
- Evaluate classes
- Study questions from previous exams

# To do after class

- Use Pro Git, and Git Cheat Sheet as references
- Read either Git concepts simplified or A Visual Git Reference
- Opcionalmente, ler artigo que descreve um workflow colaborativo, e outro artigo que adiciona mais alguns detalhes
- Opcionalmente, instale e use uma ferramenta que ajuda na resolução de conflitos

# Questions from previous exams

- Explique brevemente (a) o que é um branch em um sistema de controle de versão, e (b) porque você criaria um em seu projeto. Explique também (c) o propósito e o funcionamento da operação de merge.
- Podemos tanto fazer merge de mudanças do branch principal em um branch de feature (atualizando o branch de feature) quanto fazer merge de mudanças de um branch de feature no branch principal (atualizando o branch principal)? Explique brevemente sua resposta.