

PQC Adoption in Practice: Overcoming the Server-Side Implementation Gap

Day 17 | Category: PQC Adoption & Industry Status

Date: 2026-07-26 | **DAILY MONITORING**

PQC Adoption in Practice: Overcoming the Server-Side Implementation Gap

While major web browsers have enthusiastically adopted post-quantum cryptography, a significant gap remains on the server side. As of mid-2026, browser support for hybrid key exchange (like X25519Kyber768) is nearly universal. However, website and API server adoption lags dangerously behind. This gap isn't just a statistic; it represents a window of opportunity for attackers performing "Harvest Now, Decrypt Later" (HNDL) attacks.

The Disparity in Numbers

The adoption metrics clearly show a two-tiered internet. A handful of hyper-scalers and tech giants have deployed PQC, while the vast majority of the web remains unprotected against future quantum threats.

Web Segment	Hybrid PQC Adoption Rate (July 2026)
Top 100 Websites (e.g., Google, Cloudflare, Meta)	~45%
Top 1,000 Websites	~28%
Top 1 Million Websites	~9%
Internal Enterprise Services	< 2% (estimated)

The Call to Action: The responsibility now shifts from browser developers to us—the system administrators, DevOps engineers, and security professionals. Closing this gap is critical to rendering HNDL attacks ineffective on a global scale.

Closing the Gap: Enabling PQC on Your Servers

The good news is that for many modern servers, enabling hybrid PQC support is a straightforward configuration change. If you are using a recent version of OpenSSL (3.2+), enabling it on your web server is simple.

NGINX Configuration

In your `nginx.conf` file, within the `server` block for your HTTPS site, add or modify the `ssl_ecdh_curve` directive:

```
# Enables hybrid PQC key exchange alongside robust classical curves
ssl_ecdh_curve X25519Kyber768:X25519:P-256;
```

Apache Configuration

For Apache with `mod_ssl` and OpenSSL 3.2+, you can add the following to your SSL configuration:

```
# In httpd-ssl.conf or your vhost config
SSL0penSSLConfCmd Curves X25519Kyber768:X25519:P-256
```

After applying these changes, a server restart is required. You can then test your server's configuration using tools like SSL Labs or by inspecting the connection details in a modern browser.

Daily Quiz

- 1. What is the most significant risk associated with the server-side PQC adoption gap?
- 2. Which OpenSSL version is generally required for straightforward PQC configuration in NGINX and Apache?
- 3. What does the term "X25519Kyber768" represent in a TLS configuration?