PQC DAILY STUDY SERIES

Validating PQC Implementations in Network Protocols

Day 43 | Category: PQC Adoption & Industry Status Date: 2026-10-28 | DAILY MONITORING

Validating Post-Quantum Cryptography Implementations

The Critical Need for Rigorous Testing

As the internet ecosystem transitions to Post-Quantum Cryptography (PQC), simply deploying new algorithms like ML-KEM and ML-DSA is not enough. We must ensure these implementations are correct, secure, and performant. Validation is a multi-faceted process that goes beyond simple compliance, aiming to build trust in these new cryptographic systems. A flawed implementation can be as dangerous as a broken algorithm, creating a false sense of security.

> **Key Insight:** The security of a cryptographic system relies on both the strength of the algorithm and the correctness of its implementation. Implementation bugs can lead to catastrophic security failures, even with a theoretically secure algorithm.

Core Areas of PQC Validation

Validating a PQC implementation, especially within complex network protocols like TLS 1.3 or IKEv2, involves several key testing areas:

- **Conformance Testing:** Does the implementation correctly follow the algorithm's specification as defined in NIST FIPS 203, 204, and 205? This is verified using Known Answer Tests (KATs), where test vectors (pre-computed inputs and expected outputs) are used to check every function of the cryptographic primitive.
- **Interoperability Testing:** Can our implementation successfully communicate with other independent implementations? This is crucial for an open internet. Failures here can lead to connection errors and partitioned networks, hindering adoption. Events like the ETSI PQC Plugtests are vital for this purpose.
- **Performance and Resilience Testing:** How does the implementation perform under various network conditions (e.g., high latency, packet loss)? We must measure handshake times, CPU usage, and memory footprint to ensure the PQC solution does not unacceptably degrade user experience or open doors for Denial-of-Service (DoS) attacks.
- **Security and Side-Channel Analysis:** Are there any "leaks" in the implementation? Side-channel attacks (e.g., timing attacks, power analysis) exploit physical effects of the computation rather than

the algorithm itself. Validating resistance to these attacks requires specialized expertise and tools to ensure secret keys are not inadvertently exposed.

PQC Validation Methods at a Glance

Validation Type	Primary Goal	Common Tools/Methods	Applicability in Protocols
Conformance (KAT)	Verify correctness against spec	NIST CAVP Test Vectors	Ensures algorithms like ML-KEM are computed correctly during a TLS handshake.
Interoperability	Ensure seamless communication	Automated testbeds, multi-vendor Plugtests	Verifies a browser using one library can connect to a web server using another.
Performance	Measure overhead and efficiency	Benchmarking suites, network simulators	Assesses the impact of larger PQC key sizes on TLS handshake latency.
Side-Channel Resistance	Prevent leakage of secret data	Static/dynamic analysis tools, physical measurement	Protects the ML-DSA private key on a server from being extracted via timing variations.

Daily Self-Assessment Quiz

1. What is the primary purpose of Known Answer Tests (KATs) in PQC validation?
2. Why is interoperability testing essential for the successful deployment of PQC across the internet?
3. Besides algorithmic correctness, what kind of attack vector does side-channel analysis aim to identify and mitigate?