

Performance Implications of PQC in Network Protocols

Day 21 | Category: PQC Adoption & Industry Status

Date: 2026-09-14 |

DAILY MONITORING

The Performance Overhead of PQC in Real-World Protocols

As the transition to Post-Quantum Cryptography (PQC) accelerates, a critical factor for successful adoption is its performance impact on existing internet protocols like TLS 1.3, SSH, and IPsec. While PQC ensures security against quantum threats, its algorithms often come with larger key sizes and more computationally intensive operations compared to their classical counterparts. This study explores the real-world performance overhead and the mitigation strategies being employed.

Key Performance Metrics

When evaluating PQC's impact, we focus on three primary metrics:

- Latency:** The additional time required to establish a secure connection (e.g., the TLS handshake). This is critical for user-facing applications where responsiveness is key.
- Computational Cost:** The extra CPU cycles required for cryptographic operations. This affects server capacity and the battery life of client devices.
- Bandwidth Consumption:** The increase in data exchanged due to larger public keys and signatures. This is a concern for constrained networks and high-traffic services.

Real-World Impact: For a typical TLS 1.3 handshake, a hybrid key exchange combining a classical algorithm (like X25519) with a PQC algorithm (like ML-KEM-768) can increase the handshake latency by 20-50 milliseconds and add over a kilobyte to the connection overhead. While this may seem small, it can be significant at scale or in latency-sensitive applications.

Performance Comparison: Classical vs. PQC in TLS 1.3

Metric	Classical (ECDHE - P-256)	PQC Hybrid (ML-KEM-768 + X25519)	Impact
Public Key Size	~32 bytes	~1184 bytes	~37x Larger

Metric	Classical (ECDHE - P-256)	PQC Hybrid (ML-KEM-768 + X25519)	Impact
Handshake Latency	~30-50 ms	~50-100 ms	1.5x - 2x Slower
Computational Cost	Low	Moderate to High	Increased CPU load on servers

Mitigation Strategies and Future Outlook

To address these performance challenges, the industry is focused on several strategies:

- **Algorithm Optimization:** Implementing highly optimized, platform-specific versions of PQC algorithms to reduce CPU load.
- **Hybrid KEM Efficiency:** Research into more efficient ways to combine classical and quantum-resistant keys to minimize data overhead.
- **Protocol-Level Adjustments:** Exploring modifications to protocols like TLS to reduce the number of round trips required during a PQC-enabled handshake.

The goal is to achieve a "quantum-ready" internet without a noticeable degradation in user experience. As hardware and software evolve, the performance gap between classical and post-quantum cryptography is expected to narrow significantly.

Daily Quiz

1. What are the three primary metrics used to evaluate the performance impact of PQC on network protocols?
2. Approximately how much larger is an ML-KEM-768 public key compared to a classical P-256 public key?
3. What is a "hybrid key exchange" and why is it the preferred method for transitioning to PQC in protocols like TLS?