

Activity: Build a Membership Form

Topic	HTML Forms and Input Types
Activity Details	Individual · no CSS, no JavaScript
Submit	<code>membership.html</code> + screenshots (see Step 11)

The Goal

The **Student IT Society** needs a sign-up form. You will build it one box at a time. After **every step**, press **F5** in Chrome to see your work.

Your finished form must have all of these:

- ☐ `<form>`
- ☐ Every box: a `<label for>` matching its `id`
- ☐ 9 input types: `text`, `email`, `tel`, `password`, `date`, `number`, `radio`, `checkbox`, `file`
- ☐ Radios and checkboxes inside `<fieldset>` + `<legend>`
- ☐ One `<button type="submit">`
- ☐ Checks: `required`, `minlength`, `min/max`, `pattern`

Step 1 — File + boilerplate

Make a folder `it-society`, create `membership.html` inside it, and type this:

```
html

<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>Join the Student IT Society</title>
</head>
<body>
  <h1>Student IT Society – Membership Form</h1>

</body>
</html>
```

Step 2 — The <form> wrapper

Under the `<h1>`, add the form tags. **Every box from now on goes between them.**

```
html

<form>

  ... entire code goes here ...

</form>
```

Something to Remember:

- We are not connecting to a server yet, so our `<form>` tag has no attributes. When you build real forms later, these are the ones you will use:

Attribute	What it does	Example
<code>action</code>	The address the answers are sent to. If left out, they go back to the same page.	<code>action="/join"</code>
<code>method</code>	How the answers are sent. <code>get</code> shows them in the address bar; <code>post</code> hides them. Use <code>post</code> for passwords and personal data.	<code>method="post"</code>
<code>enctype</code>	Needed only when the form uploads a file. Without it, only the file's name is sent.	<code>enctype="multipart/form-data"</code>

Step 3 — Two text boxes

```
html

<label for="fullname">Full name * (2-60 characters)</label>
<input type="text" id="fullname" name="fullname"
      minlength="2" maxlength="60" required>

<label for="sid">Student ID * (e.g. 2026-00123)</label>
<input type="text" id="sid" name="student_id"
      pattern="[0-9]{4}-[0-9]{5}" title="Format: YYYY-NNNNN" required>
```

- `for` and `id` must match — click the label, the cursor should jump into the box.
- `name` is the word the answer is sent under. **No name = not sent.**
- `pattern`: `[0-9]{4}` = four digits, `-` = a dash, `[0-9]{5}` = five digits. `title` shows in the error.

TIP Put the rule in the label — “(2–60 characters)” — and mark required boxes with `*`.

Step 4 — Email, mobile, password

html

```
<label for="email">School email *</label>
<input type="email" id="email" name="email" required>

<label for="mobile">Mobile (09XXXXXXXX)</label>
<input type="tel" id="mobile" name="mobile"
        pattern="09[0-9]{9}" title="11 digits, starting with 09">

<label for="pw">Password * (8+ characters)</label>
<input type="password" id="pw" name="pw" minlength="8" required>
```

- **email** → free “not an email” check and the @ keyboard on phones. **password** → dots instead of letters.

COMMON MISTAKE A mobile number is **tel**, not **number**. Rule: use **number** only if it makes sense to **add 1** to the value.

Step 5 — Date and number

html

```
<label for="dob">Date of birth</label>
<input type="date" id="dob" name="dob" max="2010-12-31">

<label for="exp">Years of programming experience (0-10)</label>
<input type="number" id="exp" name="experience" min="0" max="10" value="0">
```

- **min/max** = **numbers and dates** (how big). **minlength/maxlength** = **text** (how many letters).
- Dates in code are always **year-month-day**.

Step 6 — Radio buttons: pick ONE

html

```
<fieldset>
  <legend>Year level *</legend>

  <input type="radio" id="yr1" name="year_level" value="1" checked>
  <label for="yr1">1st year</label>

  <input type="radio" id="yr2" name="year_level" value="2">
  <label for="yr2">2nd year</label>

  <input type="radio" id="yr3" name="year_level" value="3">
  <label for="yr3">3rd year</label>

  <input type="radio" id="yr4" name="year_level" value="4">
  <label for="yr4">4th year</label>
</fieldset>
```

- Same `name` on every radio = one group. Different `value` on each = what gets sent.

COMMON MISTAKE Different names → the visitor can pick all four. Test it: clicking 2nd year must unpick 1st year.

Step 7 — Checkboxes: pick MANY

html

```
<fieldset>
  <legend>Interests</legend>

  <input type="checkbox" id="i-web" name="interest" value="web">
  <label for="i-web">Web development</label>

  <input type="checkbox" id="i-mobile" name="interest" value="mobile">
  <label for="i-mobile">Mobile apps</label>

  <input type="checkbox" id="i-db" name="interest" value="db">
  <label for="i-db">Databases</label>
</fieldset>
```

- Radio = one answer. Checkbox = many (or none). An unticked checkbox is not sent at all.

Step 8 — Photo upload

html

```
<label for="photo">1×1 photo (JPG or PNG)</label>
<input type="file" id="photo" name="photo" accept=".jpg,.jpeg,.png">
```

Step 9 — Agree box + Submit button

Put these last, just before `</form>`. Then press F5 and read and review the whole form.

html

```
<input type="checkbox" id="agree" name="agree" required>
<label for="agree">I agree to the Society's rules *</label>

<button type="submit">Join the Society</button>
```

Step 10 — Test the browser's checks

Try each one and **screenshot the error**. Screenshot each error output and compile them in a single MS Word document.

#	Try this	What did Chrome say?
1	Click Join with everything empty	
2	Email: juan@example	
3	Student ID: 2026-123	
4	Mobile: 0917123	
5	Password: 5 characters	
6	Experience: -1	
7	Click 2nd year — does 1st year un-pick?	
8	Leave I agree unticked, click Join	