

4.17.1 / 2019-05-25

- Revert "Improve error message for `null/undefined` to `res.status`"

4.17.0 / 2019-05-16

- Add `express.raw` to parse bodies into `Buffer`
- Add `express.text` to parse bodies into string
- Improve error message for non-strings to `res.sendFile`
- Improve error message for `null/undefined` to `res.status`
- Support multiple hosts in `X-Forwarded-Host`
- deps: accepts@~1.3.7
- deps: body-parser@1.19.0
 - Add encoding `MIK`
 - Add petabyte (`pb`) support
 - Fix parsing array brackets after index
 - deps: bytes@3.1.0
 - deps: http-errors@1.7.2
 - deps: iconv-lite@0.4.24
 - deps: qs@6.7.0
 - deps: raw-body@2.4.0
 - deps: type-is@~1.6.17
- deps: content-disposition@0.5.3
- deps: cookie@0.4.0
 - Add `SameSite=None` support
- deps: finalhandler@~1.1.2
 - Set stricter `Content-Security-Policy` header
 - deps: parseurl@~1.3.3
 - deps: statuses@~1.5.0
- deps: parseurl@~1.3.3
- deps: proxy-addr@~2.0.5
 - deps: ipaddr.js@1.9.0
- deps: qs@6.7.0
 - Fix parsing array brackets after index
- deps: range-parser@~1.2.1
- deps: send@0.17.1
 - Set stricter CSP header in redirect & error responses
 - deps: http-errors@~1.7.2
 - deps: mime@1.6.0
 - deps: ms@2.1.1
 - deps: range-parser@~1.2.1
 - deps: statuses@~1.5.0
 - perf: remove redundant `path.normalize` call
- deps: serve-static@1.14.1
 - Set stricter CSP header in redirect response
 - deps: parseurl@~1.3.3

- deps: send@0.17.1
- deps: setprototypeof@1.1.1
- deps: statuses@~1.5.0
 - Add **103 Early Hints**
- deps: type-is@~1.6.18
 - deps: mime-types@~2.1.24
 - perf: prevent internal **throw** on invalid type

4.16.4 / 2018-10-10

- Fix issue where **"Request aborted"** may be logged in **res.sendFile**
- Fix JSDoc for **Router** constructor
- deps: body-parser@1.18.3
 - Fix deprecation warnings on Node.js 10+
 - Fix stack trace for strict json parse error
 - deps: depd@~1.1.2
 - deps: http-errors@~1.6.3
 - deps: iconv-lite@0.4.23
 - deps: qs@6.5.2
 - deps: raw-body@2.3.3
 - deps: type-is@~1.6.16
- deps: proxy-addr@~2.0.4
 - deps: ipaddr.js@1.8.0
- deps: qs@6.5.2
- deps: safe-buffer@5.1.2

4.16.3 / 2018-03-12

- deps: accepts@~1.3.5
 - deps: mime-types@~2.1.18
- deps: depd@~1.1.2
 - perf: remove argument reassignment
- deps: encodeurl@~1.0.2
 - Fix encoding **%** as last character
- deps: finalhandler@1.1.1
 - Fix 404 output for bad / missing pathnames
 - deps: encodeurl@~1.0.2
 - deps: statuses@~1.4.0
- deps: proxy-addr@~2.0.3
 - deps: ipaddr.js@1.6.0
- deps: send@0.16.2
 - Fix incorrect end tag in default error & redirects
 - deps: depd@~1.1.2
 - deps: encodeurl@~1.0.2
 - deps: statuses@~1.4.0
- deps: serve-static@1.13.2
 - Fix incorrect end tag in redirects

- deps: encodeurl@~1.0.2
- deps: send@0.16.2
- deps: statuses@~1.4.0
- deps: type-is@~1.6.16
 - deps: mime-types@~2.1.18

4.16.2 / 2017-10-09

- Fix `TypeError` in `res.send` when given `Buffer` and `ETag` header set
- perf: skip parsing of entire `X-Forwarded-Proto` header

4.16.1 / 2017-09-29

- deps: send@0.16.1
- deps: serve-static@1.13.1
 - Fix regression when `root` is incorrectly set to a file
 - deps: send@0.16.1

4.16.0 / 2017-09-28

- Add `"json escape"` setting for `res.json` and `res.jsonp`
- Add `express.json` and `express.urlencoded` to parse bodies
- Add `options` argument to `res.download`
- Improve error message when autoloading invalid view engine
- Improve error messages when non-function provided as middleware
- Skip `Buffer` encoding when not generating ETag for small response
- Use `safe-buffer` for improved Buffer API
- deps: accepts@~1.3.4
 - deps: mime-types@~2.1.16
- deps: content-type@~1.0.4
 - perf: remove argument reassignment
 - perf: skip parameter parsing when no parameters
- deps: etag@~1.8.1
 - perf: replace regular expression with substring
- deps: finalhandler@1.1.0
 - Use `res.headersSent` when available
- deps: parseurl@~1.3.2
 - perf: reduce overhead for full URLs
 - perf: unroll the "fast-path" `RegExp`
- deps: proxy-addr@~2.0.2
 - Fix trimming leading / trailing OWS in `X-Forwarded-For`
 - deps: forwarded@~0.1.2
 - deps: ipaddr.js@1.5.2
 - perf: reduce overhead when no `X-Forwarded-For` header
- deps: qs@6.5.1
 - Fix parsing & compacting very deep objects
- deps: send@0.16.0

- /
- Add 70 new types for file extensions
- Add `immutable` option
- Fix missing `</html>` in default error & redirects
- Set charset as "UTF-8" for .js and .json
- Use instance methods on stream to check for listeners
- deps: mime@1.4.1
- perf: improve path validation speed
- deps: serve-static@1.13.0
 - Add 70 new types for file extensions
 - Add `immutable` option
 - Set charset as "UTF-8" for .js and .json
 - deps: send@0.16.0
- deps: setprototypeof@1.1.0
- deps: utils-merge@1.0.1
- deps: vary@~1.1.2
 - perf: improve header token parsing speed
- perf: re-use options object when generating ETags
- perf: remove dead `.charset` set in `res.jsonp`

4.15.5 / 2017-09-24

- deps: debug@2.6.9
- deps: finalhandler@~1.0.6
 - deps: debug@2.6.9
 - deps: parseurl@~1.3.2
- deps: fresh@0.5.2
 - Fix handling of modified headers with invalid dates
 - perf: improve ETag match loop
 - perf: improve `If-None-Match` token parsing
- deps: send@0.15.6
 - Fix handling of modified headers with invalid dates
 - deps: debug@2.6.9
 - deps: etag@~1.8.1
 - deps: fresh@0.5.2
 - perf: improve `If-Match` token parsing
- deps: serve-static@1.12.6
 - deps: parseurl@~1.3.2
 - deps: send@0.15.6
 - perf: improve slash collapsing

4.15.4 / 2017-08-06

- deps: debug@2.6.8
- deps: depd@~1.1.1
 - Remove unnecessary `Buffer` loading
- deps: finalhandler@~1.0.4
 - deps: debug@2.6.8

- deps: proxy-addr@~1.1.5
 - Fix array argument being altered
 - deps: ipaddr.js@1.4.0
- deps: qs@6.5.0
- deps: send@0.15.4
 - deps: debug@2.6.8
 - deps: depd@~1.1.1
 - deps: http-errors@~1.6.2
- deps: serve-static@1.12.4
 - deps: send@0.15.4

4.15.3 / 2017-05-16

- Fix error when `res.set` cannot add charset to `Content-Type`
- deps: debug@2.6.7
 - Fix `DEBUG_MAX_ARRAY_LENGTH`
 - deps: ms@2.0.0
- deps: finalhandler@~1.0.3
 - Fix missing `</html>` in HTML document
 - deps: debug@2.6.7
- deps: proxy-addr@~1.1.4
 - deps: ipaddr.js@1.3.0
- deps: send@0.15.3
 - deps: debug@2.6.7
 - deps: ms@2.0.0
- deps: serve-static@1.12.3
 - deps: send@0.15.3
- deps: type-is@~1.6.15
 - deps: mime-types@~2.1.15
- deps: vary@~1.1.1
 - perf: hoist regular expression

4.15.2 / 2017-03-06

- deps: qs@6.4.0
 - Fix regression parsing keys starting with `[`

4.15.1 / 2017-03-05

- deps: send@0.15.1
 - Fix issue when `Date.parse` does not return `NaN` on invalid date
 - Fix strict violation in broken environments
- deps: serve-static@1.12.1
 - Fix issue when `Date.parse` does not return `NaN` on invalid date
 - deps: send@0.15.1

4.15.0 / 2017-03-01

- Add debug message when loading view engine
- Add `next("router")` to exit from router
- Fix case where `router.use` skipped requests routes did not
- Remove usage of `res._headers` private field
 - Improves compatibility with Node.js 8 nightly
- Skip routing when `req.url` is not set
- Use `%o` in path debug to tell types apart
- Use `Object.create` to setup request & response prototypes
- Use `setprototypeof` module to replace `__proto__` setting
- Use `statuses` instead of `http` module for status messages
- deps: debug@2.6.1
 - Allow colors in workers
 - Deprecated `DEBUG_FD` environment variable set to `3` or higher
 - Fix error when running under React Native
 - Use same color for same namespace
 - deps: ms@0.7.2
- deps: etag@~1.8.0
 - Use SHA1 instead of MD5 for ETag hashing
 - Works with FIPS 140-2 OpenSSL configuration
- deps: finalhandler@~1.0.0
 - Fix exception when `err` cannot be converted to a string
 - Fully URL-encode the pathname in the 404
 - Only include the pathname in the 404 message
 - Send complete HTML document
 - Set `Content-Security-Policy: default-src 'self'` header
 - deps: debug@2.6.1
- deps: fresh@0.5.0
 - Fix false detection of `no-cache` request directive
 - Fix incorrect result when `If-None-Match` has both `*` and ETags
 - Fix weak `ETag` matching to match spec
 - perf: delay reading header values until needed
 - perf: enable strict mode
 - perf: hoist regular expressions
 - perf: remove duplicate conditional
 - perf: remove unnecessary boolean coercions
 - perf: skip checking modified time if ETag check failed
 - perf: skip parsing `If-None-Match` when no `ETag` header
 - perf: use `Date.parse` instead of `new Date`
- deps: qs@6.3.1
 - Fix array parsing from skipping empty values
 - Fix compacting nested arrays
- deps: send@0.15.0
 - Fix false detection of `no-cache` request directive
 - Fix incorrect result when `If-None-Match` has both `*` and ETags
 - Fix weak `ETag` matching to match spec
 - Remove usage of `res._headers` private field

- Support `If-Match` and `If-Unmodified-Since` headers
- Use `res.getHeaderNames()` when available
- Use `res.headersSent` when available
- deps: debug@2.6.1
- deps: etag@~1.8.0
- deps: fresh@0.5.0
- deps: http-errors@~1.6.1
- deps: serve-static@1.12.0
 - Fix false detection of `no-cache` request directive
 - Fix incorrect result when `If-None-Match` has both `*` and ETags
 - Fix weak `ETag` matching to match spec
 - Remove usage of `res._headers` private field
 - Send complete HTML document in redirect response
 - Set default CSP header in redirect response
 - Support `If-Match` and `If-Unmodified-Since` headers
 - Use `res.getHeaderNames()` when available
 - Use `res.headersSent` when available
 - deps: send@0.15.0
- perf: add fast match path for `*` route
- perf: improve `req.ips` performance

4.14.1 / 2017-01-28

- deps: content-disposition@0.5.2
- deps: finalhandler@0.5.1
 - Fix exception when `err.headers` is not an object
 - deps: statuses@~1.3.1
 - perf: hoist regular expressions
 - perf: remove duplicate validation path
- deps: proxy-addr@~1.1.3
 - deps: ipaddr.js@1.2.0
- deps: send@0.14.2
 - deps: http-errors@~1.5.1
 - deps: ms@0.7.2
 - deps: statuses@~1.3.1
- deps: serve-static@~1.11.2
 - deps: send@0.14.2
- deps: type-is@~1.6.14
 - deps: mime-types@~2.1.13

4.14.0 / 2016-06-16

- Add `acceptRanges` option to `res.sendFile/res.sendfile`
- Add `cacheControl` option to `res.sendFile/res.sendfile`
- Add `options` argument to `req.range`
 - Includes the `combine` option
- Encode URL in `res.location/res.redirect` if not already encoded

/

- Fix some redirect handling in `res.sendFile/res.sendfile`
- Fix Windows absolute path check using forward slashes
- Improve error with invalid arguments to `req.get()`
- Improve performance for `res.json/res.jsonp` in most cases
- Improve `Range` header handling in `res.sendFile/res.sendfile`
- deps: accepts@~1.3.3
 - Fix including type extensions in parameters in `Accept` parsing
 - Fix parsing `Accept` parameters with quoted equals
 - Fix parsing `Accept` parameters with quoted semicolons
 - Many performance improvements
 - deps: mime-types@~2.1.11
 - deps: negotiator@0.6.1
- deps: content-type@~1.0.2
 - perf: enable strict mode
- deps: cookie@0.3.1
 - Add `sameSite` option
 - Fix cookie `Max-Age` to never be a floating point number
 - Improve error message when `encode` is not a function
 - Improve error message when `expires` is not a `Date`
 - Throw better error for invalid argument to parse
 - Throw on invalid values provided to `serialize`
 - perf: enable strict mode
 - perf: hoist regular expression
 - perf: use for loop in parse
 - perf: use string concatenation for serialization
- deps: finalhandler@0.5.0
 - Change invalid or non-numeric status code to 500
 - Overwrite status message to match set status code
 - Prefer `err.statusCode` if `err.status` is invalid
 - Set response headers from `err.headers` object
 - Use `statuses` instead of `http` module for status messages
- deps: proxy-addr@~1.1.2
 - Fix accepting various invalid netmasks
 - Fix IPv6-mapped IPv4 validation edge cases
 - IPv4 netmasks must be contiguous
 - IPv6 addresses cannot be used as a netmask
 - deps: ipaddr.js@1.1.1
- deps: qs@6.2.0
 - Add `decoder` option in `parse` function
- deps: range-parser@~1.2.0
 - Add `combine` option to combine overlapping ranges
 - Fix incorrectly returning -1 when there is at least one valid range
 - perf: remove internal function
- deps: send@0.14.1
 - Add `acceptRanges` option
 - Add `cacheControl` option
 - Attempt to combine multiple ranges into single range

- Correctly inherit from `Stream` class
- Fix `Content-Range` header in 416 responses when using `start/end` options
- Fix `Content-Range` header missing from default 416 responses
- Fix redirect error when `path` contains raw non-URL characters
- Fix redirect when `path` starts with multiple forward slashes
- Ignore non-byte `Range` headers
- deps: http-errors@~1.5.0
- deps: range-parser@~1.2.0
- deps: statuses@~1.3.0
- perf: remove argument reassignment
- deps: serve-static@~1.11.1
 - Add `acceptRanges` option
 - Add `cacheControl` option
 - Attempt to combine multiple ranges into single range
 - Fix redirect error when `req.url` contains raw non-URL characters
 - Ignore non-byte `Range` headers
 - Use status code 301 for redirects
 - deps: send@0.14.1
- deps: type-is@~1.6.13
 - Fix type error when given invalid type to match against
 - deps: mime-types@~2.1.11
- deps: vary@~1.1.0
 - Only accept valid field names in the `field` argument
- perf: use strict equality when possible

4.13.4 / 2016-01-21

- deps: content-disposition@0.5.1
 - perf: enable strict mode
- deps: cookie@0.1.5
 - Throw on invalid values provided to `serialize`
- deps: depd@~1.1.0
 - Support web browser loading
 - perf: enable strict mode
- deps: escape-html@~1.0.3
 - perf: enable strict mode
 - perf: optimize string replacement
 - perf: use faster string coercion
- deps: finalhandler@0.4.1
 - deps: escape-html@~1.0.3
- deps: merge-descriptors@1.0.1
 - perf: enable strict mode
- deps: methods@~1.1.2
 - perf: enable strict mode
- deps: parseurl@~1.3.1
 - perf: enable strict mode
- deps: proxy-addr@~1.0.10

- deps: ipaddr.js@1.0.5
- perf: enable strict mode
- deps: range-parser@~1.0.3
 - perf: enable strict mode
- deps: send@0.13.1
 - deps: depd@~1.1.0
 - deps: destroy@~1.0.4
 - deps: escape-html@~1.0.3
 - deps: range-parser@~1.0.3
- deps: serve-static@~1.10.2
 - deps: escape-html@~1.0.3
 - deps: parseurl@~1.3.0
 - deps: send@0.13.1

4.13.3 / 2015-08-02

- Fix infinite loop condition using `mergeParams: true`
- Fix inner numeric indices incorrectly altering parent `req.params`

4.13.2 / 2015-07-31

- deps: accepts@~1.2.12
 - deps: mime-types@~2.1.4
- deps: array-flatten@1.1.1
 - perf: enable strict mode
- deps: path-to-regexp@0.1.7
 - Fix regression with escaped round brackets and matching groups
- deps: type-is@~1.6.6
 - deps: mime-types@~2.1.4

4.13.1 / 2015-07-05

- deps: accepts@~1.2.10
 - deps: mime-types@~2.1.2
- deps: qs@4.0.0
 - Fix dropping parameters like `hasOwnProperty`
 - Fix various parsing edge cases
- deps: type-is@~1.6.4
 - deps: mime-types@~2.1.2
 - perf: enable strict mode
 - perf: remove argument reassignment

4.13.0 / 2015-06-20

- Add settings to debug output
- Fix `res.format` error when only `default` provided

/

- Fix issue where `next('route')` in `app.param` would incorrectly skip values
- Fix hiding platform issues with `decodeURIComponent`
 - Only `URIErrors` are a 400
- Fix using `*` before params in routes
- Fix using capture groups before params in routes
- Simplify `res.cookie` to call `res.append`
- Use `array-flatten` module for flattening arrays
- deps: accepts@~1.2.9
 - deps: mime-types@~2.1.1
 - perf: avoid argument reassignment & argument slice
 - perf: avoid negotiator recursive construction
 - perf: enable strict mode
 - perf: remove unnecessary bitwise operator
- deps: cookie@0.1.3
 - perf: deduce the scope of try-catch deopt
 - perf: remove argument reassignments
- deps: escape-html@1.0.2
- deps: etag@~1.7.0
 - Always include entity length in ETags for hash length extensions
 - Generate non-Stats ETags using MD5 only (no longer CRC32)
 - Improve stat performance by removing hashing
 - Improve support for JXcore
 - Remove base64 padding in ETags to shorten
 - Support "fake" stats objects in environments without fs
 - Use MD5 instead of MD4 in weak ETags over 1KB
- deps: finalhandler@0.4.0
 - Fix a false-positive when unpinning in Node.js 0.8
 - Support `statusCode` property on `Error` objects
 - Use `unpipe` module for unpinning requests
 - deps: escape-html@1.0.2
 - deps: on-finished@~2.3.0
 - perf: enable strict mode
 - perf: remove argument reassignment
- deps: fresh@0.3.0
 - Add weak `ETag` matching support
- deps: on-finished@~2.3.0
 - Add defined behavior for HTTP `CONNECT` requests
 - Add defined behavior for HTTP `Upgrade` requests
 - deps: ee-first@1.1.1
- deps: path-to-regexp@0.1.6
- deps: send@0.13.0
 - Allow Node.js HTTP server to set `Date` response header
 - Fix incorrectly removing `Content-Location` on 304 response
 - Improve the default redirect response headers
 - Send appropriate headers on default error response
 - Use `http-errors` for standard emitted errors
 - Use `statuses` instead of `http` module for status messages

- deps: escape-html@1.0.2
- deps: etag@~1.7.0
- deps: fresh@0.3.0
- deps: on-finished@~2.3.0
- perf: enable strict mode
- perf: remove unnecessary array allocations
- deps: serve-static@~1.10.0
 - Add **fallthrough** option
 - Fix reading options from options prototype
 - Improve the default redirect response headers
 - Malformed URLs now **next()** instead of 400
 - deps: escape-html@1.0.2
 - deps: send@0.13.0
 - perf: enable strict mode
 - perf: remove argument reassignment
- deps: type-is@~1.6.3
 - deps: mime-types@~2.1.1
 - perf: reduce try block size
 - perf: remove bitwise operations
- perf: enable strict mode
- perf: isolate **app.render** try block
- perf: remove argument reassignments in application
- perf: remove argument reassignments in request prototype
- perf: remove argument reassignments in response prototype
- perf: remove argument reassignments in routing
- perf: remove argument reassignments in **View**
- perf: skip attempting to decode zero length string
- perf: use saved reference to **http.STATUS_CODES**

4.12.4 / 2015-05-17

- deps: accepts@~1.2.7
 - deps: mime-types@~2.0.11
 - deps: negotiator@0.5.3
- deps: debug@~2.2.0
 - deps: ms@0.7.1
- deps: depd@~1.0.1
- deps: etag@~1.6.0
 - Improve support for JXcore
 - Support "fake" stats objects in environments without **fs**
- deps: finalhandler@0.3.6
 - deps: debug@~2.2.0
 - deps: on-finished@~2.2.1
- deps: on-finished@~2.2.1
 - Fix **isFinished(req)** when data buffered
- deps: proxy-addr@~1.0.8
 - deps: ipaddr.js@1.0.1

- deps: qs@2.4.2
- Fix allowing parameters like `constructor`
- deps: send@0.12.3
 - deps: debug@~2.2.0
 - deps: depd@~1.0.1
 - deps: etag@~1.6.0
 - deps: ms@0.7.1
 - deps: on-finished@~2.2.1
- deps: serve-static@~1.9.3
 - deps: send@0.12.3
- deps: type-is@~1.6.2
 - deps: mime-types@~2.0.11

4.12.3 / 2015-03-17

- deps: accepts@~1.2.5
 - deps: mime-types@~2.0.10
- deps: debug@~2.1.3
 - Fix high intensity foreground color for bold
 - deps: ms@0.7.0
- deps: finalhandler@0.3.4
 - deps: debug@~2.1.3
- deps: proxy-addr@~1.0.7
 - deps: ipaddr.js@0.1.9
- deps: qs@2.4.1
 - Fix error when parameter `hasOwnProperty` is present
- deps: send@0.12.2
 - Throw errors early for invalid `extensions` or `index` options
 - deps: debug@~2.1.3
- deps: serve-static@~1.9.2
 - deps: send@0.12.2
- deps: type-is@~1.6.1
 - deps: mime-types@~2.0.10

4.12.2 / 2015-03-02

- Fix regression where `"Request aborted"` is logged using `res.sendFile`

4.12.1 / 2015-03-01

- Fix constructing application with non-configurable prototype properties
- Fix `ECONNRESET` errors from `res.sendFile` usage
- Fix `req.host` when using "trust proxy" hops count
- Fix `req.protocol/req.secure` when using "trust proxy" hops count
- Fix wrong `code` on aborted connections from `res.sendFile`
- deps: merge-descriptors@1.0.0

4.12.0 / 2015-02-23

- Fix `"trust proxy"` setting to inherit when app is mounted
- Generate `ETags` for all request responses
 - No longer restricted to only responses for `GET` and `HEAD` requests
- Use `content-type` to parse `Content-Type` headers
- `deps: accepts@~1.2.4`
 - Fix preference sorting to be stable for long acceptable lists
 - `deps: mime-types@~2.0.9`
 - `deps: negotiator@0.5.1`
- `deps: cookie-signature@1.0.6`
- `deps: send@0.12.1`
 - Always read the stat size from the file
 - Fix mutating passed-in `options`
 - `deps: mime@1.3.4`
- `deps: serve-static@~1.9.1`
 - `deps: send@0.12.1`
- `deps: type-is@~1.6.0`
 - fix argument reassignment
 - fix false-positives in `hasBody Transfer-Encoding` check
 - support wildcard for both type and subtype (`/*/*`)
 - `deps: mime-types@~2.0.9`

4.11.2 / 2015-02-01

- Fix `res.redirect` double-calling `res.end` for `HEAD` requests
- `deps: accepts@~1.2.3`
 - `deps: mime-types@~2.0.8`
- `deps: proxy-addr@~1.0.6`
 - `deps: ipaddr.js@0.1.8`
- `deps: type-is@~1.5.6`
 - `deps: mime-types@~2.0.8`

4.11.1 / 2015-01-20

- `deps: send@0.11.1`
 - Fix root path disclosure
- `deps: serve-static@~1.8.1`
 - Fix redirect loop in Node.js 0.11.14
 - Fix root path disclosure
 - `deps: send@0.11.1`

4.11.0 / 2015-01-13

- Add `res.append(field, val)` to append headers
- Deprecate leading `:` in `name` for `app.param(name, fn)`

/

- Deprecate `req.param()` -- use `req.params`, `req.body`, or `req.query` instead
- Deprecate `app.param(fn)`
- Fix `OPTIONS` responses to include the `HEAD` method properly
- Fix `res.sendFile` not always detecting aborted connection
- Match routes iteratively to prevent stack overflows
- deps: accepts@~1.2.2
 - deps: mime-types@~2.0.7
 - deps: negotiator@0.5.0
- deps: send@0.11.0
 - deps: debug@~2.1.1
 - deps: etag@~1.5.1
 - deps: ms@0.7.0
 - deps: on-finished@~2.2.0
- deps: serve-static@~1.8.0
 - deps: send@0.11.0

4.10.8 / 2015-01-13

- Fix crash from error within `OPTIONS` response handler
- deps: proxy-addr@~1.0.5
 - deps: ipaddr.js@0.1.6

4.10.7 / 2015-01-04

- Fix `Allow` header for `OPTIONS` to not contain duplicate methods
- Fix incorrect "Request aborted" for `res.sendFile` when `HEAD` or 304
- deps: debug@~2.1.1
- deps: finalhandler@0.3.3
 - deps: debug@~2.1.1
 - deps: on-finished@~2.2.0
- deps: methods@~1.1.1
- deps: on-finished@~2.2.0
- deps: serve-static@~1.7.2
 - Fix potential open redirect when mounted at root
- deps: type-is@~1.5.5
 - deps: mime-types@~2.0.7

4.10.6 / 2014-12-12

- Fix exception in `req.fresh/req.stale` without response headers

4.10.5 / 2014-12-10

- Fix `res.send` double-calling `res.end` for `HEAD` requests
- deps: accepts@~1.1.4
 - deps: mime-types@~2.0.4

- deps: type-is@~1.5.4
 - deps: mime-types@~2.0.4

4.10.4 / 2014-11-24

- Fix `res.sendFile` logging standard write errors

4.10.3 / 2014-11-23

- Fix `res.sendFile` logging standard write errors
- deps: etag@~1.5.1
- deps: proxy-addr@~1.0.4
 - deps: ipaddr.js@0.1.5
- deps: qs@2.3.3
 - Fix `arrayLimit` behavior

4.10.2 / 2014-11-09

- Correctly invoke async router callback asynchronously
- deps: accepts@~1.1.3
 - deps: mime-types@~2.0.3
- deps: type-is@~1.5.3
 - deps: mime-types@~2.0.3

4.10.1 / 2014-10-28

- Fix handling of URLs containing `://` in the path
- deps: qs@2.3.2
 - Fix parsing of mixed objects and values

4.10.0 / 2014-10-23

- Add support for `app.set('views', array)`
 - Views are looked up in sequence in array of directories
- Fix `res.send(status)` to mention `res.sendStatus(status)`
- Fix handling of invalid empty URLs
- Use `content-disposition` module for `res.attachment/res.download`
 - Sends standards-compliant `Content-Disposition` header
 - Full Unicode support
- Use `path.resolve` in view lookup
- deps: debug@~2.1.0
 - Implement `DEBUG_FD` env variable support
- deps: depd@~1.0.0
- deps: etag@~1.5.0
 - Improve string performance
 - Slightly improve speed for weak ETags over 1KB

- deps: finalhandler@0.3.2
 - Terminate in progress response only on error
 - Use **on-finished** to determine request status
 - deps: debug@~2.1.0
 - deps: on-finished@~2.1.1
- deps: on-finished@~2.1.1
 - Fix handling of pipelined requests
- deps: qs@2.3.0
 - Fix parsing of mixed implicit and explicit arrays
- deps: send@0.10.1
 - deps: debug@~2.1.0
 - deps: depd@~1.0.0
 - deps: etag@~1.5.0
 - deps: on-finished@~2.1.1
- deps: serve-static@~1.7.1
 - deps: send@0.10.1

4.9.8 / 2014-10-17

- Fix **res.redirect** body when redirect status specified
- deps: accepts@~1.1.2
 - Fix error when media type has invalid parameter
 - deps: negotiator@0.4.9

4.9.7 / 2014-10-10

- Fix using same param name in array of paths

4.9.6 / 2014-10-08

- deps: accepts@~1.1.1
 - deps: mime-types@~2.0.2
 - deps: negotiator@0.4.8
- deps: serve-static@~1.6.4
 - Fix redirect loop when index file serving disabled
- deps: type-is@~1.5.2
 - deps: mime-types@~2.0.2

4.9.5 / 2014-09-24

- deps: etag@~1.4.0
- deps: proxy-addr@~1.0.3
 - Use **forwarded** npm module
- deps: send@0.9.3
 - deps: etag@~1.4.0
- deps: serve-static@~1.6.3

- deps: send@0.9.3

4.9.4 / 2014-09-19

- deps: qs@2.2.4
 - Fix issue with object keys starting with numbers truncated

4.9.3 / 2014-09-18

- deps: proxy-addr@~1.0.2
 - Fix a global leak when multiple subnets are trusted
 - deps: ipaddr.js@0.1.3

4.9.2 / 2014-09-17

- Fix regression for empty string `path` in `app.use`
- Fix `router.use` to accept array of middleware without path
- Improve error message for bad `app.use` arguments

4.9.1 / 2014-09-16

- Fix `app.use` to accept array of middleware without path
- deps: depd@0.4.5
- deps: etag@~1.3.1
- deps: send@0.9.2
 - deps: depd@0.4.5
 - deps: etag@~1.3.1
 - deps: range-parser@~1.0.2
- deps: serve-static@~1.6.2
 - deps: send@0.9.2

4.9.0 / 2014-09-08

- Add `res.sendStatus`
- Invoke callback for `sendfile` when client aborts
 - Applies to `res.sendFile`, `res.sendfile`, and `res.download`
 - `err` will be populated with request aborted error
- Support IP address host in `req.subdomains`
- Use `etag` to generate `ETag` headers
- deps: accepts@~1.1.0
 - update `mime-types`
- deps: cookie-signature@1.0.5
- deps: debug@~2.0.0
- deps: finalhandler@0.2.0
 - Set `X-Content-Type-Options: nosniff` header
 - deps: debug@~2.0.0

- deps: fresh@0.2.4
- deps: media-typer@0.3.0
 - Throw error when parameter format invalid on parse
- deps: qs@2.2.3
 - Fix issue where first empty value in array is discarded
- deps: range-parser@~1.0.2
- deps: send@0.9.1
 - Add **lastModified** option
 - Use **etag** to generate **ETag** header
 - deps: debug@~2.0.0
 - deps: fresh@0.2.4
- deps: serve-static@~1.6.1
 - Add **lastModified** option
 - deps: send@0.9.1
- deps: type-is@~1.5.1
 - fix **hasbody** to be true for **content-length: 0**
 - deps: media-typer@0.3.0
 - deps: mime-types@~2.0.1
- deps: vary@~1.0.0
 - Accept valid **Vary** header string as **field**

4.8.8 / 2014-09-04

- deps: send@0.8.5
 - Fix a path traversal issue when using **root**
 - Fix malicious path detection for empty string path
- deps: serve-static@~1.5.4
 - deps: send@0.8.5

4.8.7 / 2014-08-29

- deps: qs@2.2.2
 - Remove unnecessary cloning

4.8.6 / 2014-08-27

- deps: qs@2.2.0
 - Array parsing fix
 - Performance improvements

4.8.5 / 2014-08-18

- deps: send@0.8.3
 - deps: destroy@1.0.3
 - deps: on-finished@2.1.0
- deps: serve-static@~1.5.3

- /
- deps: send@0.8.3

4.8.4 / 2014-08-14

- deps: qs@1.2.2
- deps: send@0.8.2
 - Work around `fd` leak in Node.js 0.10 for `fs.ReadStream`
- deps: serve-static@~1.5.2
 - deps: send@0.8.2

4.8.3 / 2014-08-10

- deps: parseurl@~1.3.0
- deps: qs@1.2.1
- deps: serve-static@~1.5.1
 - Fix parsing of weird `req.originalUrl` values
 - deps: parseurl@~1.3.0
 - deps: utils-merge@1.0.0

4.8.2 / 2014-08-07

- deps: qs@1.2.0
 - Fix parsing array of objects

4.8.1 / 2014-08-06

- fix incorrect deprecation warnings on `res.download`
- deps: qs@1.1.0
 - Accept urlencoded square brackets
 - Accept empty values in implicit array notation

4.8.0 / 2014-08-05

- add `res.sendFile`
 - accepts a file system path instead of a URL
 - requires an absolute path or `root` option specified
- deprecate `res.sendfile` -- use `res.sendFile` instead
- support mounted app as any argument to `app.use()`
- deps: qs@1.0.2
 - Complete rewrite
 - Limits array length to 20
 - Limits object depth to 5
 - Limits parameters to 1,000
- deps: send@0.8.1
 - Add `extensions` option
- deps: serve-static@~1.5.0

- /
- Add `extensions` option
 - deps: send@0.8.1

4.7.4 / 2014-08-04

- fix `res.sendFile` regression for serving directory index files
- deps: send@0.7.4
 - Fix incorrect 403 on Windows and Node.js 0.11
 - Fix serving index files without root dir
- deps: serve-static@~1.4.4
 - deps: send@0.7.4

4.7.3 / 2014-08-04

- deps: send@0.7.3
 - Fix incorrect 403 on Windows and Node.js 0.11
- deps: serve-static@~1.4.3
 - Fix incorrect 403 on Windows and Node.js 0.11
 - deps: send@0.7.3

4.7.2 / 2014-07-27

- deps: depd@0.4.4
 - Work-around v8 generating empty stack traces
- deps: send@0.7.2
 - deps: depd@0.4.4
- deps: serve-static@~1.4.2

4.7.1 / 2014-07-26

- deps: depd@0.4.3
 - Fix exception when global `Error.stackTraceLimit` is too low
- deps: send@0.7.1
 - deps: depd@0.4.3
- deps: serve-static@~1.4.1

4.7.0 / 2014-07-25

- fix `req.protocol` for proxy-direct connections
- configurable query parser with `app.set('query parser', parser)`
 - `app.set('query parser', 'extended')` parse with "qs" module
 - `app.set('query parser', 'simple')` parse with "querystring" core module
 - `app.set('query parser', false)` disable query string parsing
 - `app.set('query parser', true)` enable simple parsing

- deprecate `res.json(status, obj)` -- use `res.status(status).json(obj)` instead
- deprecate `res.jsonp(status, obj)` -- use `res.status(status).jsonp(obj)` instead
- deprecate `res.send(status, body)` -- use `res.status(status).send(body)` instead
- deps: debug@1.0.4
- deps: depd@0.4.2
 - Add `TRACE_DEPRECATION` environment variable
 - Remove non-standard grey color from color output
 - Support `--no-deprecation` argument
 - Support `--trace-deprecation` argument
- deps: finalhandler@0.1.0
 - Respond after request fully read
 - deps: debug@1.0.4
- deps: parseurl@~1.2.0
 - Cache URLs based on original value
 - Remove no-longer-needed URL mis-parse work-around
 - Simplify the "fast-path" `RegExp`
- deps: send@0.7.0
 - Add `dotfiles` option
 - Cap `maxAge` value to 1 year
 - deps: debug@1.0.4
 - deps: depd@0.4.2
- deps: serve-static@~1.4.0
 - deps: parseurl@~1.2.0
 - deps: send@0.7.0
- perf: prevent multiple `Buffer` creation in `res.send`

4.6.1 / 2014-07-12

- fix `subapp.mountpath` regression for `app.use(subapp)`

4.6.0 / 2014-07-11

- accept multiple callbacks to `app.use()`
- add explicit "Rosetta Flash JSONP abuse" protection
 - previous versions are not vulnerable; this is just explicit protection
- catch errors in multiple `req.param(name, fn)` handlers
- deprecate `res.redirect(url, status)` -- use `res.redirect(status, url)` instead
- fix `res.send(status, num)` to send `num` as json (not error)
- remove unnecessary escaping when `res.jsonp` returns JSON response
- support non-string `path` in `app.use(path, fn)`
 - supports array of paths
 - supports `RegExp`
- router: fix optimization on router exit

- router: refactor location of `try` blocks
- router: speed up standard `app.use(fn)`
- deps: debug@1.0.3
 - Add support for multiple wildcards in namespaces
- deps: finalhandler@0.0.3
 - deps: debug@1.0.3
- deps: methods@1.1.0
 - add `CONNECT`
- deps: parseurl@~1.1.3
 - faster parsing of href-only URLs
- deps: path-to-regexp@0.1.3
- deps: send@0.6.0
 - deps: debug@1.0.3
- deps: serve-static@~1.3.2
 - deps: parseurl@~1.1.3
 - deps: send@0.6.0
- perf: fix arguments reassign deopt in some `res` methods

4.5.1 / 2014-07-06

- fix routing regression when altering `req.method`

4.5.0 / 2014-07-04

- add deprecation message to non-plural `req.accepts*`
- add deprecation message to `res.send(body, status)`
- add deprecation message to `res.vary()`
- add `headers` option to `res.sendFile`
 - use to set headers on successful file transfer
- add `mergeParams` option to `Router`
 - merges `req.params` from parent routes
- add `req.hostname` -- correct name for what `req.host` returns
- deprecate things with `depd` module
- deprecate `req.host` -- use `req.hostname` instead
- fix behavior when handling request without routes
- fix handling when `route.all` is only route
- invoke `router.param()` only when route matches
- restore `req.params` after invoking router
- use `finalhandler` for final response handling
- use `media-type` to alter content-type charset
- deps: accepts@~1.0.7
- deps: send@0.5.0
 - Accept string for `maxage` (converted by `ms`)
 - Include link in default redirect response
- deps: serve-static@~1.3.0
 - Accept string for `maxAge` (converted by `ms`)
 - Add `setHeaders` option

- /
- Include HTML link in redirect response
- deps: send@0.5.0
- deps: type-is@~1.3.2

4.4.5 / 2014-06-26

- deps: cookie-signature@1.0.4
 - fix for timing attacks

4.4.4 / 2014-06-20

- fix `res.attachment` Unicode filenames in Safari
- fix "trim prefix" debug message in `express:router`
- deps: accepts@~1.0.5
- deps: buffer-crc32@0.2.3

4.4.3 / 2014-06-11

- fix persistence of modified `req.params[name]` from `app.param()`
- deps: accepts@1.0.3
 - deps: negotiator@0.4.6
- deps: debug@1.0.2
- deps: send@0.4.3
 - Do not throw uncatchable error on file open race condition
 - Use `escape-html` for HTML escaping
 - deps: debug@1.0.2
 - deps: finished@1.2.2
 - deps: fresh@0.2.2
- deps: serve-static@1.2.3
 - Do not throw uncatchable error on file open race condition
 - deps: send@0.4.3

4.4.2 / 2014-06-09

- fix catching errors from top-level handlers
- use `vary` module for `res.vary`
- deps: debug@1.0.1
- deps: proxy-addr@1.0.1
- deps: send@0.4.2
 - fix "event emitter leak" warnings
 - deps: debug@1.0.1
 - deps: finished@1.2.1
- deps: serve-static@1.2.2
 - fix "event emitter leak" warnings
 - deps: send@0.4.2
- deps: type-is@1.2.1

4.4.1 / 2014-06-02

- deps: methods@1.0.1
- deps: send@0.4.1
 - Send `max-age` in `Cache-Control` in correct format
- deps: serve-static@1.2.1
 - use `escape-html` for escaping
 - deps: send@0.4.1

4.4.0 / 2014-05-30

- custom etag control with `app.set('etag', val)`
 - `app.set('etag', function(body, encoding){ return '"etag"' })` custom etag generation
 - `app.set('etag', 'weak')` weak tag
 - `app.set('etag', 'strong')` strong etag
 - `app.set('etag', false)` turn off
 - `app.set('etag', true)` standard etag
- mark `res.send` ETag as weak and reduce collisions
- update accepts to 1.0.2
 - Fix interpretation when header not in request
- update send to 0.4.0
 - Calculate ETag with md5 for reduced collisions
 - Ignore stream errors after request ends
 - deps: debug@0.8.1
- update serve-static to 1.2.0
 - Calculate ETag with md5 for reduced collisions
 - Ignore stream errors after request ends
 - deps: send@0.4.0

4.3.2 / 2014-05-28

- fix handling of errors from `router.param()` callbacks

4.3.1 / 2014-05-23

- revert "fix behavior of multiple `app.VERB` for the same path"
 - this caused a regression in the order of route execution

4.3.0 / 2014-05-21

- add `req.baseUrl` to access the path stripped from `req.url` in routes
- fix behavior of multiple `app.VERB` for the same path
- fix issue routing requests among sub routers
- invoke `router.param()` only when necessary instead of every match
- proper proxy trust with `app.set('trust proxy', trust)`

- /
- `app.set('trust proxy', 1)` trust first hop
- `app.set('trust proxy', 'loopback')` trust loopback addresses
- `app.set('trust proxy', '10.0.0.1')` trust single IP
- `app.set('trust proxy', '10.0.0.1/16')` trust subnet
- `app.set('trust proxy', '10.0.0.1, 10.0.0.2')` trust list
- `app.set('trust proxy', false)` turn off
- `app.set('trust proxy', true)` trust everything
- set proper `charset` in `Content-Type` for `res.send`
- update type-is to 1.2.0
 - support suffix matching

4.2.0 / 2014-05-11

- deprecate `app.del()` -- use `app.delete()` instead
- deprecate `res.json(obj, status)` -- use `res.json(status, obj)` instead
 - the edge-case `res.json(status, num)` requires `res.status(status).json(num)`
- deprecate `res.jsonp(obj, status)` -- use `res.jsonp(status, obj)` instead
 - the edge-case `res.jsonp(status, num)` requires `res.status(status).jsonp(num)`
- fix `req.next` when inside router instance
- include `ETag` header in `HEAD` requests
- keep previous `Content-Type` for `res.jsonp`
- support PURGE method
 - add `app.purge`
 - add `router.purge`
 - include PURGE in `app.all`
- update debug to 0.8.0
 - add `enable()` method
 - change from `stderr` to `stdout`
- update methods to 1.0.0
 - add PURGE

4.1.2 / 2014-05-08

- fix `req.host` for IPv6 literals
- fix `res.jsonp` error if callback param is object

4.1.1 / 2014-04-27

- fix `package.json` to reflect supported node version

4.1.0 / 2014-04-24

- pass options from `res.sendfile` to `send`
- preserve casing of headers in `res.header` and `res.set`

/

- support unicode file names in `res.attachment` and `res.download`
- update accepts to 1.0.1
 - deps: negotiator@0.4.0
- update cookie to 0.1.2
 - Fix for `maxAge == 0`
 - made compat with expires field
- update send to 0.3.0
 - Accept API options in options object
 - Coerce option types
 - Control whether to generate etags
 - Default directory access to 403 when index disabled
 - Fix sending files with dots without root set
 - Include file path in etag
 - Make "Can't set headers after they are sent." catchable
 - Send full entity-body for multi range requests
 - Set etags to "weak"
 - Support "If-Range" header
 - Support multiple index paths
 - deps: mime@1.2.11
- update serve-static to 1.1.0
 - Accept options directly to `send` module
 - Resolve relative paths at middleware setup
 - Use `parseurl` to parse the URL from request
 - deps: send@0.3.0
- update type-is to 1.1.0
 - add non-array values support
 - add `multipart` as a shorthand

4.0.0 / 2014-04-09

- remove:
 - node 0.8 support
 - `connect` and `connect's` patches except for charset handling
 - `express(1)` - moved to [express-generator](#)
 - `express.createServer()` - it has been deprecated for a long time. Use `express()`
 - `app.configure` - use logic in your own app code
 - `app.router` - is removed
 - `req.auth` - use `basic-auth` instead
 - `req.accepted*` - use `req.accepts*()` instead
 - `res.location` - relative URL resolution is removed
 - `res.charset` - include the charset in the content type when using `res.set()`
 - all bundled middleware except `static`
- change:
 - `app.route` -> `app.mountpath` when mounting an express app in another express app

- /
- `json spaces` no longer enabled by default in development
- `req.accepts*` -> `req.accepts*s` - i.e. `req.acceptsEncoding` -> `req.acceptsEncodings`
- `req.params` is now an object instead of an array
- `res.locals` is no longer a function. It is a plain js object. Treat it as such.
- `res.headerSent` -> `res.headersSent` to match node.js `ServerResponse` object
- refactor:
 - `req.accepts*` with `accepts`
 - `req.is` with `type-is`
 - `path-to-regexp`
- add:
 - `app.router()` - returns the app Router instance
 - `app.route()` - Proxy to the app's `Router#route()` method to create a new route
 - Router & Route - public API

3.21.2 / 2015-07-31

- deps: connect@2.30.2
 - deps: body-parser@~1.13.3
 - deps: compression@~1.5.2
 - deps: errorhandler@~1.4.2
 - deps: method-override@~2.3.5
 - deps: serve-index@~1.7.2
 - deps: type-is@~1.6.6
 - deps: vhost@~3.0.1
- deps: vary@~1.0.1
 - Fix setting empty header from empty `field`
 - perf: enable strict mode
 - perf: remove argument reassignments

3.21.1 / 2015-07-05

- deps: basic-auth@~1.0.3
- deps: connect@2.30.1
 - deps: body-parser@~1.13.2
 - deps: compression@~1.5.1
 - deps: errorhandler@~1.4.1
 - deps: morgan@~1.6.1
 - deps: pause@0.1.0
 - deps: qs@4.0.0
 - deps: serve-index@~1.7.1
 - deps: type-is@~1.6.4

3.21.0 / 2015-06-18

- deps: basic-auth@1.0.2
 - perf: enable strict mode
 - perf: hoist regular expression
 - perf: parse with regular expressions
 - perf: remove argument reassignment
- deps: connect@2.30.0
 - deps: body-parser@~1.13.1
 - deps: bytes@2.1.0
 - deps: compression@~1.5.0
 - deps: cookie@0.1.3
 - deps: cookie-parser@~1.3.5
 - deps: csurf@~1.8.3
 - deps: errorhandler@~1.4.0
 - deps: express-session@~1.11.3
 - deps: finalhandler@0.4.0
 - deps: fresh@0.3.0
 - deps: morgan@~1.6.0
 - deps: serve-favicon@~2.3.0
 - deps: serve-index@~1.7.0
 - deps: serve-static@~1.10.0
 - deps: type-is@~1.6.3
- deps: cookie@0.1.3
 - perf: deduce the scope of try-catch deopt
 - perf: remove argument reassignments
- deps: escape-html@1.0.2
- deps: etag@~1.7.0
 - Always include entity length in ETags for hash length extensions
 - Generate non-Stats ETags using MD5 only (no longer CRC32)
 - Improve stat performance by removing hashing
 - Improve support for JXcore
 - Remove base64 padding in ETags to shorten
 - Support "fake" stats objects in environments without fs
 - Use MD5 instead of MD4 in weak ETags over 1KB
- deps: fresh@0.3.0
 - Add weak **ETag** matching support
- deps: mkdirp@0.5.1
 - Work in global strict mode
- deps: send@0.13.0
 - Allow Node.js HTTP server to set **Date** response header
 - Fix incorrectly removing **Content-Location** on 304 response
 - Improve the default redirect response headers
 - Send appropriate headers on default error response
 - Use **http-errors** for standard emitted errors
 - Use **statuses** instead of **http** module for status messages
 - deps: escape-html@1.0.2
 - deps: etag@~1.7.0
 - deps: fresh@0.3.0

- deps: on-finished@~2.3.0
- perf: enable strict mode
- perf: remove unnecessary array allocations

3.20.3 / 2015-05-17

- deps: connect@2.29.2
 - deps: body-parser@~1.12.4
 - deps: compression@~1.4.4
 - deps: connect-timeout@~1.6.2
 - deps: debug@~2.2.0
 - deps: depd@~1.0.1
 - deps: errorhandler@~1.3.6
 - deps: finalhandler@0.3.6
 - deps: method-override@~2.3.3
 - deps: morgan@~1.5.3
 - deps: qs@2.4.2
 - deps: response-time@~2.3.1
 - deps: serve-favicon@~2.2.1
 - deps: serve-index@~1.6.4
 - deps: serve-static@~1.9.3
 - deps: type-is@~1.6.2
- deps: debug@~2.2.0
 - deps: ms@0.7.1
- deps: depd@~1.0.1
- deps: proxy-addr@~1.0.8
 - deps: ipaddr.js@1.0.1
- deps: send@0.12.3
 - deps: debug@~2.2.0
 - deps: depd@~1.0.1
 - deps: etag@~1.6.0
 - deps: ms@0.7.1
 - deps: on-finished@~2.2.1

3.20.2 / 2015-03-16

- deps: connect@2.29.1
 - deps: body-parser@~1.12.2
 - deps: compression@~1.4.3
 - deps: connect-timeout@~1.6.1
 - deps: debug@~2.1.3
 - deps: errorhandler@~1.3.5
 - deps: express-session@~1.10.4
 - deps: finalhandler@0.3.4
 - deps: method-override@~2.3.2
 - deps: morgan@~1.5.2
 - deps: qs@2.4.1

- deps: serve-index@~1.6.3
- deps: serve-static@~1.9.2
- deps: type-is@~1.6.1
- deps: debug@~2.1.3
 - Fix high intensity foreground color for bold
 - deps: ms@0.7.0
- deps: merge-descriptors@1.0.0
- deps: proxy-addr@~1.0.7
 - deps: ipaddr.js@0.1.9
- deps: send@0.12.2
 - Throw errors early for invalid **extensions** or **index** options
 - deps: debug@~2.1.3

3.20.1 / 2015-02-28

- Fix **req.host** when using "trust proxy" hops count
- Fix **req.protocol/req.secure** when using "trust proxy" hops count

3.20.0 / 2015-02-18

- Fix **"trust proxy"** setting to inherit when app is mounted
- Generate **ETags** for all request responses
 - No longer restricted to only responses for **GET** and **HEAD** requests
- Use **content-type** to parse **Content-Type** headers
- deps: connect@2.29.0
 - Use **content-type** to parse **Content-Type** headers
 - deps: body-parser@~1.12.0
 - deps: compression@~1.4.1
 - deps: connect-timeout@~1.6.0
 - deps: cookie-parser@~1.3.4
 - deps: cookie-signature@1.0.6
 - deps: csurf@~1.7.0
 - deps: errorhandler@~1.3.4
 - deps: express-session@~1.10.3
 - deps: http-errors@~1.3.1
 - deps: response-time@~2.3.0
 - deps: serve-index@~1.6.2
 - deps: serve-static@~1.9.1
 - deps: type-is@~1.6.0
- deps: cookie-signature@1.0.6
- deps: send@0.12.1
 - Always read the stat size from the file
 - Fix mutating passed-in **options**
 - deps: mime@1.3.4

3.19.2 / 2015-02-01

- deps: connect@2.28.3
 - deps: compression@~1.3.1
 - deps: csurf@~1.6.6
 - deps: errorhandler@~1.3.3
 - deps: express-session@~1.10.2
 - deps: serve-index@~1.6.1
 - deps: type-is@~1.5.6
- deps: proxy-addr@~1.0.6
 - deps: ipaddr.js@0.1.8

3.19.1 / 2015-01-20

- deps: connect@2.28.2
 - deps: body-parser@~1.10.2
 - deps: serve-static@~1.8.1
- deps: send@0.11.1
 - Fix root path disclosure

3.19.0 / 2015-01-09

- Fix **OPTIONS** responses to include the **HEAD** method property
- Use **readline** for prompt in **express(1)**
- deps: commander@2.6.0
- deps: connect@2.28.1
 - deps: body-parser@~1.10.1
 - deps: compression@~1.3.0
 - deps: connect-timeout@~1.5.0
 - deps: csurf@~1.6.4
 - deps: debug@~2.1.1
 - deps: errorhandler@~1.3.2
 - deps: express-session@~1.10.1
 - deps: finalhandler@0.3.3
 - deps: method-override@~2.3.1
 - deps: morgan@~1.5.1
 - deps: serve-favicon@~2.2.0
 - deps: serve-index@~1.6.0
 - deps: serve-static@~1.8.0
 - deps: type-is@~1.5.5
- deps: debug@~2.1.1
- deps: methods@~1.1.1
- deps: proxy-addr@~1.0.5
 - deps: ipaddr.js@0.1.6
- deps: send@0.11.0
 - deps: debug@~2.1.1
 - deps: etag@~1.5.1
 - deps: ms@0.7.0
 - deps: on-finished@~2.2.0

3.18.6 / 2014-12-12

- Fix exception in `req.fresh/req.stale` without response headers

3.18.5 / 2014-12-11

- deps: connect@2.27.6
 - deps: compression@~1.2.2
 - deps: express-session@~1.9.3
 - deps: http-errors@~1.2.8
 - deps: serve-index@~1.5.3
 - deps: type-is@~1.5.4

3.18.4 / 2014-11-23

- deps: connect@2.27.4
 - deps: body-parser@~1.9.3
 - deps: compression@~1.2.1
 - deps: errorhandler@~1.2.3
 - deps: express-session@~1.9.2
 - deps: qs@2.3.3
 - deps: serve-favicon@~2.1.7
 - deps: serve-static@~1.5.1
 - deps: type-is@~1.5.3
- deps: etag@~1.5.1
- deps: proxy-addr@~1.0.4
 - deps: ipaddr.js@0.1.5

3.18.3 / 2014-11-09

- deps: connect@2.27.3
 - Correctly invoke async callback asynchronously
 - deps: csurf@~1.6.3

3.18.2 / 2014-10-28

- deps: connect@2.27.2
 - Fix handling of URLs containing `://` in the path
 - deps: body-parser@~1.9.2
 - deps: qs@2.3.2

3.18.1 / 2014-10-22

- Fix internal `utils.merge` deprecation warnings
- deps: connect@2.27.1

- deps: body-parser@~1.9.1
- deps: express-session@~1.9.1
- deps: finalhandler@0.3.2
- deps: morgan@~1.4.1
- deps: qs@2.3.0
- deps: serve-static@~1.7.1
- deps: send@0.10.1
 - deps: on-finished@~2.1.1

3.18.0 / 2014-10-17

- Use **content-disposition** module for `res.attachment/res.download`
 - Sends standards-compliant **Content-Disposition** header
 - Full Unicode support
- Use **etag** module to generate **ETag** headers
- deps: connect@2.27.0
 - Use **http-errors** module for creating errors
 - Use **utils-merge** module for merging objects
 - deps: body-parser@~1.9.0
 - deps: compression@~1.2.0
 - deps: connect-timeout@~1.4.0
 - deps: debug@~2.1.0
 - deps: depd@~1.0.0
 - deps: express-session@~1.9.0
 - deps: finalhandler@0.3.1
 - deps: method-override@~2.3.0
 - deps: morgan@~1.4.0
 - deps: response-time@~2.2.0
 - deps: serve-favicon@~2.1.6
 - deps: serve-index@~1.5.0
 - deps: serve-static@~1.7.0
- deps: debug@~2.1.0
 - Implement **DEBUG_FD** env variable support
- deps: depd@~1.0.0
- deps: send@0.10.0
 - deps: debug@~2.1.0
 - deps: depd@~1.0.0
 - deps: etag@~1.5.0

3.17.8 / 2014-10-15

- deps: connect@2.26.6
 - deps: compression@~1.1.2
 - deps: csurf@~1.6.2
 - deps: errorhandler@~1.2.2

3.17.7 / 2014-10-08

- deps: connect@2.26.5
 - Fix accepting non-object arguments to **logger**
 - deps: serve-static@~1.6.4

3.17.6 / 2014-10-02

- deps: connect@2.26.4
 - deps: morgan@~1.3.2
 - deps: type-is@~1.5.2

3.17.5 / 2014-09-24

- deps: connect@2.26.3
 - deps: body-parser@~1.8.4
 - deps: serve-favicon@~2.1.5
 - deps: serve-static@~1.6.3
- deps: proxy-addr@~1.0.3
 - Use **forwarded** npm module
- deps: send@0.9.3
 - deps: etag@~1.4.0

3.17.4 / 2014-09-19

- deps: connect@2.26.2
 - deps: body-parser@~1.8.3
 - deps: qs@2.2.4

3.17.3 / 2014-09-18

- deps: proxy-addr@~1.0.2
 - Fix a global leak when multiple subnets are trusted
 - deps: ipaddr.js@0.1.3

3.17.2 / 2014-09-15

- Use **crc** instead of **buffer-crc32** for speed
- deps: connect@2.26.1
 - deps: body-parser@~1.8.2
 - deps: depd@0.4.5
 - deps: express-session@~1.8.2
 - deps: morgan@~1.3.1
 - deps: serve-favicon@~2.1.3
 - deps: serve-static@~1.6.2
- deps: depd@0.4.5
- deps: send@0.9.2

- deps: depd@0.4.5
- deps: etag@~1.3.1
- deps: range-parser@~1.0.2

3.17.1 / 2014-09-08

- Fix error in `req.subdomains` on empty host

3.17.0 / 2014-09-08

- Support `X-Forwarded-Host` in `req.subdomains`
- Support IP address host in `req.subdomains`
- deps: connect@2.26.0
 - deps: body-parser@~1.8.1
 - deps: compression@~1.1.0
 - deps: connect-timeout@~1.3.0
 - deps: cookie-parser@~1.3.3
 - deps: cookie-signature@1.0.5
 - deps: csurf@~1.6.1
 - deps: debug@~2.0.0
 - deps: errorhandler@~1.2.0
 - deps: express-session@~1.8.1
 - deps: finalhandler@0.2.0
 - deps: fresh@0.2.4
 - deps: media-typer@0.3.0
 - deps: method-override@~2.2.0
 - deps: morgan@~1.3.0
 - deps: qs@2.2.3
 - deps: serve-favicon@~2.1.3
 - deps: serve-index@~1.2.1
 - deps: serve-static@~1.6.1
 - deps: type-is@~1.5.1
 - deps: vhost@~3.0.0
- deps: cookie-signature@1.0.5
- deps: debug@~2.0.0
- deps: fresh@0.2.4
- deps: media-typer@0.3.0
 - Throw error when parameter format invalid on parse
- deps: range-parser@~1.0.2
- deps: send@0.9.1
 - Add `lastModified` option
 - Use `etag` to generate `ETag` header
 - deps: debug@~2.0.0
 - deps: fresh@0.2.4
- deps: vary@~1.0.0
 - Accept valid `Vary` header string as `field`

3.16.10 / 2014-09-04

- deps: connect@2.25.10
 - deps: serve-static@~1.5.4
- deps: send@0.8.5
 - Fix a path traversal issue when using **root**
 - Fix malicious path detection for empty string path

3.16.9 / 2014-08-29

- deps: connect@2.25.9
 - deps: body-parser@~1.6.7
 - deps: qs@2.2.2

3.16.8 / 2014-08-27

- deps: connect@2.25.8
 - deps: body-parser@~1.6.6
 - deps: csurf@~1.4.1
 - deps: qs@2.2.0

3.16.7 / 2014-08-18

- deps: connect@2.25.7
 - deps: body-parser@~1.6.5
 - deps: express-session@~1.7.6
 - deps: morgan@~1.2.3
 - deps: serve-static@~1.5.3
- deps: send@0.8.3
 - deps: destroy@1.0.3
 - deps: on-finished@2.1.0

3.16.6 / 2014-08-14

- deps: connect@2.25.6
 - deps: body-parser@~1.6.4
 - deps: qs@1.2.2
 - deps: serve-static@~1.5.2
- deps: send@0.8.2
 - Work around **fd** leak in Node.js 0.10 for **fs.ReadStream**

3.16.5 / 2014-08-11

- deps: connect@2.25.5
 - Fix backwards compatibility in **logger**

3.16.4 / 2014-08-10

- Fix original URL parsing in `res.location`
- `deps: connect@2.25.4`
 - Fix `query` middleware breaking with argument
 - `deps: body-parser@~1.6.3`
 - `deps: compression@~1.0.11`
 - `deps: connect-timeout@~1.2.2`
 - `deps: express-session@~1.7.5`
 - `deps: method-override@~2.1.3`
 - `deps: on-headers@~1.0.0`
 - `deps: parseurl@~1.3.0`
 - `deps: qs@1.2.1`
 - `deps: response-time@~2.0.1`
 - `deps: serve-index@~1.1.6`
 - `deps: serve-static@~1.5.1`
- `deps: parseurl@~1.3.0`

3.16.3 / 2014-08-07

- `deps: connect@2.25.3`
 - `deps: multiparty@3.3.2`

3.16.2 / 2014-08-07

- `deps: connect@2.25.2`
 - `deps: body-parser@~1.6.2`
 - `deps: qs@1.2.0`

3.16.1 / 2014-08-06

- `deps: connect@2.25.1`
 - `deps: body-parser@~1.6.1`
 - `deps: qs@1.1.0`

3.16.0 / 2014-08-05

- `deps: connect@2.25.0`
 - `deps: body-parser@~1.6.0`
 - `deps: compression@~1.0.10`
 - `deps: csurf@~1.4.0`
 - `deps: express-session@~1.7.4`
 - `deps: qs@1.0.2`
 - `deps: serve-static@~1.5.0`
- `deps: send@0.8.1`
 - Add `extensions` option

3.15.3 / 2014-08-04

- fix `res.sendFile` regression for serving directory index files
- deps: connect@2.24.3
 - deps: serve-index@~1.1.5
 - deps: serve-static@~1.4.4
- deps: send@0.7.4
 - Fix incorrect 403 on Windows and Node.js 0.11
 - Fix serving index files without root dir

3.15.2 / 2014-07-27

- deps: connect@2.24.2
 - deps: body-parser@~1.5.2
 - deps: depd@0.4.4
 - deps: express-session@~1.7.2
 - deps: morgan@~1.2.2
 - deps: serve-static@~1.4.2
- deps: depd@0.4.4
 - Work-around v8 generating empty stack traces
- deps: send@0.7.2
 - deps: depd@0.4.4

3.15.1 / 2014-07-26

- deps: connect@2.24.1
 - deps: body-parser@~1.5.1
 - deps: depd@0.4.3
 - deps: express-session@~1.7.1
 - deps: morgan@~1.2.1
 - deps: serve-index@~1.1.4
 - deps: serve-static@~1.4.1
- deps: depd@0.4.3
 - Fix exception when global `Error.stackTraceLimit` is too low
- deps: send@0.7.1
 - deps: depd@0.4.3

3.15.0 / 2014-07-22

- Fix `req.protocol` for proxy-direct connections
- Pass options from `res.sendFile` to `send`
- deps: connect@2.24.0
 - deps: body-parser@~1.5.0
 - deps: compression@~1.0.9
 - deps: connect-timeout@~1.2.1
 - deps: debug@1.0.4

- deps: depd@0.4.2
- deps: express-session@~1.7.0
- deps: finalhandler@0.1.0
- deps: method-override@~2.1.2
- deps: morgan@~1.2.0
- deps: multipart@3.3.1
- deps: parseurl@~1.2.0
- deps: serve-static@~1.4.0
- deps: debug@1.0.4
- deps: depd@0.4.2
 - Add **TRACE_DEPRECATION** environment variable
 - Remove non-standard grey color from color output
 - Support **--no-deprecation** argument
 - Support **--trace-deprecation** argument
- deps: parseurl@~1.2.0
 - Cache URLs based on original value
 - Remove no-longer-needed URL mis-parse work-around
 - Simplify the "fast-path" **RegExp**
- deps: send@0.7.0
 - Add **dotfiles** option
 - Cap **maxAge** value to 1 year
 - deps: debug@1.0.4
 - deps: depd@0.4.2

3.14.0 / 2014-07-11

- add explicit "Rosetta Flash JSONP abuse" protection
 - previous versions are not vulnerable; this is just explicit protection
- deprecate **res.redirect(url, status)** -- use **res.redirect(status, url)** instead
- fix **res.send(status, num)** to send **num** as json (not error)
- remove unnecessary escaping when **res.jsonp** returns JSON response
- deps: basic-auth@1.0.0
 - support empty password
 - support empty username
- deps: connect@2.23.0
 - deps: debug@1.0.3
 - deps: express-session@~1.6.4
 - deps: method-override@~2.1.0
 - deps: parseurl@~1.1.3
 - deps: serve-static@~1.3.1
- deps: debug@1.0.3
 - Add support for multiple wildcards in namespaces
- deps: methods@1.1.0
 - add **CONNECT**
- deps: parseurl@~1.1.3
 - faster parsing of href-only URLs

3.13.0 / 2014-07-03

- add deprecation message to `app.configure`
- add deprecation message to `req.auth`
- use `basic-auth` to parse `Authorization` header
- deps: connect@2.22.0
 - deps: csurf@~1.3.0
 - deps: express-session@~1.6.1
 - deps: multipart@3.3.0
 - deps: serve-static@~1.3.0
- deps: send@0.5.0
 - Accept string for `maxage` (converted by `ms`)
 - Include link in default redirect response

3.12.1 / 2014-06-26

- deps: connect@2.21.1
 - deps: cookie-parser@1.3.2
 - deps: cookie-signature@1.0.4
 - deps: express-session@~1.5.2
 - deps: type-is@~1.3.2
- deps: cookie-signature@1.0.4
 - fix for timing attacks

3.12.0 / 2014-06-21

- use `media-typer` to alter content-type charset
- deps: connect@2.21.0
 - deprecate `connect(middleware)` -- use `app.use(middleware)` instead
 - deprecate `connect.createServer()` -- use `connect()` instead
 - fix `res.setHeader()` patch to work with `with get -> append -> set` pattern
 - deps: compression@~1.0.8
 - deps: errorhandler@~1.1.1
 - deps: express-session@~1.5.0
 - deps: serve-index@~1.1.3

3.11.0 / 2014-06-19

- deprecate things with `depd` module
- deps: buffer-crc32@0.2.3
- deps: connect@2.20.2
 - deprecate `verify` option to `json` -- use `body-parser` npm module instead
 - deprecate `verify` option to `urlencoded` -- use `body-parser` npm module instead
 - deprecate things with `depd` module
 - use `finalhandler` for final response handling

- use **media-typer** to parse **content-type** for charset
- deps: body-parser@1.4.3
- deps: connect-timeout@1.1.1
- deps: cookie-parser@1.3.1
- deps: csurf@1.2.2
- deps: errorhandler@1.1.0
- deps: express-session@1.4.0
- deps: multiparty@3.2.9
- deps: serve-index@1.1.2
- deps: type-is@1.3.1
- deps: vhost@2.0.0

3.10.5 / 2014-06-11

- deps: connect@2.19.6
 - deps: body-parser@1.3.1
 - deps: compression@1.0.7
 - deps: debug@1.0.2
 - deps: serve-index@1.1.1
 - deps: serve-static@1.2.3
- deps: debug@1.0.2
- deps: send@0.4.3
 - Do not throw uncatchable error on file open race condition
 - Use **escape-html** for HTML escaping
 - deps: debug@1.0.2
 - deps: finished@1.2.2
 - deps: fresh@0.2.2

3.10.4 / 2014-06-09

- deps: connect@2.19.5
 - fix "event emitter leak" warnings
 - deps: csurf@1.2.1
 - deps: debug@1.0.1
 - deps: serve-static@1.2.2
 - deps: type-is@1.2.1
- deps: debug@1.0.1
- deps: send@0.4.2
 - fix "event emitter leak" warnings
 - deps: finished@1.2.1
 - deps: debug@1.0.1

3.10.3 / 2014-06-05

- use **vary** module for **res.vary**
- deps: connect@2.19.4
 - deps: errorhandler@1.0.2

- deps: method-override@2.0.2
- deps: serve-favicon@2.0.1
- deps: debug@1.0.0

3.10.2 / 2014-06-03

- deps: connect@2.19.3
 - deps: compression@1.0.6

3.10.1 / 2014-06-03

- deps: connect@2.19.2
 - deps: compression@1.0.4
- deps: proxy-addr@1.0.1

3.10.0 / 2014-06-02

- deps: connect@2.19.1
 - deprecate `methodOverride()` -- use `method-override` npm module instead
 - deps: body-parser@1.3.0
 - deps: method-override@2.0.1
 - deps: multipart@3.2.8
 - deps: response-time@2.0.0
 - deps: serve-static@1.2.1
- deps: methods@1.0.1
- deps: send@0.4.1
 - Send `max-age` in `Cache-Control` in correct format

3.9.0 / 2014-05-30

- custom etag control with `app.set('etag', val)`
 - `app.set('etag', function(body, encoding){ return '"etag"' })` custom etag generation
 - `app.set('etag', 'weak')` weak tag
 - `app.set('etag', 'strong')` strong etag
 - `app.set('etag', false)` turn off
 - `app.set('etag', true)` standard etag
- Include ETag in HEAD requests
- mark `res.send` ETag as weak and reduce collisions
- update connect to 2.18.0
 - deps: compression@1.0.3
 - deps: serve-index@1.1.0
 - deps: serve-static@1.2.0
- update send to 0.4.0
 - Calculate ETag with md5 for reduced collisions
 - Ignore stream errors after request ends

- /
- deps: debug@0.8.1

3.8.1 / 2014-05-27

- update connect to 2.17.3
 - deps: body-parser@1.2.2
 - deps: express-session@1.2.1
 - deps: method-override@1.0.2

3.8.0 / 2014-05-21

- keep previous `Content-Type` for `res.jsonp`
- set proper `charset` in `Content-Type` for `res.send`
- update connect to 2.17.1
 - fix `res.charset` appending charset when `content-type` has one
 - deps: express-session@1.2.0
 - deps: morgan@1.1.1
 - deps: serve-index@1.0.3

3.7.0 / 2014-05-18

- proper proxy trust with `app.set('trust proxy', trust)`
 - `app.set('trust proxy', 1)` trust first hop
 - `app.set('trust proxy', 'loopback')` trust loopback addresses
 - `app.set('trust proxy', '10.0.0.1')` trust single IP
 - `app.set('trust proxy', '10.0.0.1/16')` trust subnet
 - `app.set('trust proxy', '10.0.0.1, 10.0.0.2')` trust list
 - `app.set('trust proxy', false)` turn off
 - `app.set('trust proxy', true)` trust everything
- update connect to 2.16.2
 - deprecate `res.headerSent` -- use `res.headersSent`
 - deprecate `res.on("header")` -- use on-headers module instead
 - fix edge-case in `res.appendHeader` that would append in wrong order
 - json: use body-parser
 - urlencoded: use body-parser
 - dep: bytes@1.0.0
 - dep: cookie-parser@1.1.0
 - dep: csurf@1.2.0
 - dep: express-session@1.1.0
 - dep: method-override@1.0.1

3.6.0 / 2014-05-09

- deprecate `app.del()` -- use `app.delete()` instead
- deprecate `res.json(obj, status)` -- use `res.json(status, obj)` instead

- /
- the edge-case `res.json(status, num)` requires `res.status(status).json(num)`
- deprecate `res.jsonp(obj, status)` -- use `res.jsonp(status, obj)` instead
 - the edge-case `res.jsonp(status, num)` requires `res.status(status).jsonp(num)`
- support PURGE method
 - add `app.purge`
 - add `router.purge`
 - include PURGE in `app.all`
- update connect to 2.15.0
 - Add `res.appendHeader`
 - Call error stack even when response has been sent
 - Patch `res.headerSent` to return Boolean
 - Patch `res.headersSent` for node.js 0.8
 - Prevent default 404 handler after response sent
 - dep: compression@1.0.2
 - dep: connect-timeout@1.1.0
 - dep: debug@^0.8.0
 - dep: errorhandler@1.0.1
 - dep: express-session@1.0.4
 - dep: morgan@1.0.1
 - dep: serve-favicon@2.0.0
 - dep: serve-index@1.0.2
- update debug to 0.8.0
 - add `enable()` method
 - change from stderr to stdout
- update methods to 1.0.0
 - add PURGE
- update mkdirp to 0.5.0

3.5.3 / 2014-05-08

- fix `req.host` for IPv6 literals
- fix `res.jsonp` error if callback param is object

3.5.2 / 2014-04-24

- update connect to 2.14.5
- update cookie to 0.1.2
- update mkdirp to 0.4.0
- update send to 0.3.0

3.5.1 / 2014-03-25

- pin less-middleware in generated app

3.5.0 / 2014-03-06

2020-12-17

- bump deps

3.4.8 / 2014-01-13

- prevent incorrect automatic OPTIONS responses #1868 @dpatti
- update binary and examples for jade 1.0 #1876 @yossi, #1877 @reqshark, #1892 @matheusazzi
- throw 400 in case of malformed paths @rlidwka

3.4.7 / 2013-12-10

- update connect

3.4.6 / 2013-12-01

- update connect (raw-body)

3.4.5 / 2013-11-27

- update connect
- res.location: remove leading ./ #1802 @kapouer
- res.redirect: fix `res.redirect('toString')` #1829 @michaelficarra
- res.send: always send ETag when content-length > 0
- router: add Router.all() method

3.4.4 / 2013-10-29

- update connect
- update supertest
- update methods
- express(1): replace bodyParser() with urlencoded() and json() #1795 @chirag04

3.4.3 / 2013-10-23

- update connect

3.4.2 / 2013-10-18

- update connect
- downgrade commander

3.4.1 / 2013-10-15

- update connect

/

- update commander
- jsonp: check if callback is a function
- router: wrap encodeURIComponent in a try/catch #1735 (@lxe)
- res.format: now includes charset @1747 (@sorribas)
- res.links: allow multiple calls @1746 (@sorribas)

3.4.0 / 2013-09-07

- add res.vary(). Closes #1682
- update connect

3.3.8 / 2013-09-02

- update connect

3.3.7 / 2013-08-28

- update connect

3.3.6 / 2013-08-27

- Revert "remove charset from json responses. Closes #1631" (causes issues in some clients)
- add: req.accepts take an argument list

3.3.4 / 2013-07-08

- update send and connect

3.3.3 / 2013-07-04

- update connect

3.3.2 / 2013-07-03

- update connect
- update send
- remove .version export

3.3.1 / 2013-06-27

- update connect

3.3.0 / 2013-06-26

- update connect
- add support for multiple X-Forwarded-Proto values. Closes #1646
- change: remove charset from json responses. Closes #1631
- change: return actual booleans from req.accept* functions
- fix jsonp callback array throw

3.2.6 / 2013-06-02

- update connect

3.2.5 / 2013-05-21

- update connect
- update node-cookie
- add: throw a meaningful error when there is no default engine
- change generation of ETags with res.send() to GET requests only. Closes #1619

3.2.4 / 2013-05-09

- fix `req.subdomains` when no Host is present
- fix `req.host` when no Host is present, return undefined

3.2.3 / 2013-05-07

- update connect / qs

3.2.2 / 2013-05-03

- update qs

3.2.1 / 2013-04-29

- add app.VERB() paths array deprecation warning
- update connect
- update qs and remove all ~ semver crap
- fix: accept number as value of Signed Cookie

3.2.0 / 2013-04-15

- add "view" constructor setting to override view behaviour
- add req.acceptsEncoding(name)
- add req.acceptedEncodings
- revert cookie signature change causing session race conditions
- fix sorting of Accept values of the same quality

3.1.2 / 2013-04-12

- add support for custom Accept parameters
- update cookie-signature

3.1.1 / 2013-04-01

- add X-Forwarded-Host support to `req.host`
- fix relative redirects
- update mkdirp
- update buffer-crc32
- remove legacy `app.configure()` method from app template.

3.1.0 / 2013-01-25

- add support for leading "." in "view engine" setting
- add array support to `res.set()`
- add node 0.8.x to travis.yml
- add "subdomain offset" setting for tweaking `req.subdomains`
- add `res.location(url)` implementing `res.redirect()`-like setting of Location
- use `app.get()` for x-powered-by setting for inheritance
- fix colons in passwords for `req.auth`

3.0.6 / 2013-01-04

- add http verb methods to Router
- update connect
- fix mangling of the `res.cookie()` options object
- fix jsonp whitespace escape. Closes #1132

3.0.5 / 2012-12-19

- add throwing when a non-function is passed to a route
- fix: explicitly remove Transfer-Encoding header from 204 and 304 responses
- revert "add 'etag' option"

3.0.4 / 2012-12-05

- add 'etag' option to disable `res.send()` Etags
- add escaping of urls in text/plain in `res.redirect()` for old browsers interpreting as html
- change crc32 module for a more liberal license
- update connect

3.0.3 / 2012-11-13

- update connect

- update cookie module
- fix cookie max-age

3.0.2 / 2012-11-08

- add OPTIONS to cors example. Closes #1398
- fix route chaining regression. Closes #1397

3.0.1 / 2012-11-01

- update connect

3.0.0 / 2012-10-23

- add `make clean`
- add "Basic" check to `req.auth`
- add `req.auth` test coverage
- add `cb` & `cb(payload)` to `res.jsonp()`. Closes #1374
- add backwards compat for `res.redirect()` status. Closes #1336
- add support for `res.json()` to retain previously defined Content-Types. Closes #1349
- update connect
- change `res.redirect()` to utilize a pathname-relative Location again. Closes #1382
- remove non-primitive string support for `res.send()`
- fix view-locals example. Closes #1370
- fix route-separation example

3.0.0rc5 / 2012-09-18

- update connect
- add redis search example
- add static-files example
- add "x-powered-by" setting (`app.disable('x-powered-by')`)
- add "application/octet-stream" redirect Accept test case. Closes #1317

3.0.0rc4 / 2012-08-30

- add `res.jsonp()`. Closes #1307
- add "verbose errors" option to error-pages example
- add another route example to `express(1)` so people are not so confused
- add redis online user activity tracking example
- update connect dep
- fix etag quoting. Closes #1310
- fix error-pages 404 status
- fix jsonp callback char restrictions

- remove old OPTIONS default response

3.0.0rc3 / 2012-08-13

- update connect dep
- fix signed cookies to work with `connect.cookieParser()` ("s:" prefix was missing) [tnydwrd]
- fix `res.render()` clobbering of "locals"

3.0.0rc2 / 2012-08-03

- add CORS example
- update connect dep
- deprecate `.createServer()` & remove old stale examples
- fix: escape `res.redirect()` link
- fix vhost example

3.0.0rc1 / 2012-07-24

- add more examples to view-locals
- add scheme-relative redirects (`res.redirect("//foo.com")`) support
- update cookie dep
- update connect dep
- update send dep
- fix `express(1)` -h flag, use -H for hogan. Closes #1245
- fix `res.sendFile()` socket error handling regression

3.0.0beta7 / 2012-07-16

- update connect dep for `send()` root normalization regression

3.0.0beta6 / 2012-07-13

- add `err.view` property for view errors. Closes #1226
- add "jsonp callback name" setting
- add support for `"/foo/:bar*" non-greedy matches`
- change `res.sendFile()` to use `send()` module
- change `res.send` to use "response-send" module
- remove `app.locals.use` and `res.locals.use`, use regular middleware

3.0.0beta5 / 2012-07-03

- add "make check" support
- add route-map example
- add `res.json(obj, status)` support back for BC
- add "methods" dep, remove internal methods module

- update connect dep
- update auth example to utilize cores pbkdf2
- updated tests to use "supertest"

3.0.0beta4 / 2012-06-25

- Added `req.auth`
- Added `req.range(size)`
- Added `res.links(obj)`
- Added `res.send(body, status)` support back for backwards compat
- Added `.default()` support to `res.format()`
- Added 2xx / 304 check to `req.fresh`
- Revert "Added + support to the router"
- Fixed `res.send()` freshness check, respect `res.statusCode`

3.0.0beta3 / 2012-06-15

- Added hogan `--hjs` to `express(1)` [nullfirm]
- Added another example to content-negotiation
- Added `fresh` dep
- Changed: `res.send()` always checks freshness
- Fixed: expose connects mime module. Closes #1165

3.0.0beta2 / 2012-06-06

- Added `+` support to the router
- Added `req.host`
- Changed `req.param()` to check route first
- Update connect dep

3.0.0beta1 / 2012-06-01

- Added `res.format()` callback to override default 406 behaviour
- Fixed `res.redirect()` 406. Closes #1154

3.0.0alpha5 / 2012-05-30

- Added `req.ip`
- Added `{ signed: true }` option to `res.cookie()`
- Removed `res.signedCookie()`
- Changed: dont reverse `req.ips`
- Fixed "trust proxy" setting check for `req.ips`

3.0.0alpha4 / 2012-05-09

- Added: allow `[]` in jsonp callback. Closes #1128

/

- Added `PORT` env var support in generated template. Closes #1118 [benatkin]
- Updated: connect 2.2.2

3.0.0alpha3 / 2012-05-04

- Added public `app.routes`. Closes #887
- Added `view-locals` example
- Added `mvc` example
- Added `res.locals.use()`. Closes #1120
- Added conditional-GET support to `res.send()`
- Added: coerce `res.set()` values to strings
- Changed: moved `static()` in generated apps below router
- Changed: `res.send()` only set ETag when not previously set
- Changed connect 2.2.1 dep
- Changed: `make test` now runs unit / acceptance tests
- Fixed req/res proto inheritance

3.0.0alpha2 / 2012-04-26

- Added `make benchmark` back
- Added `res.send()` support for `String` objects
- Added client-side data exposing example
- Added `res.header()` and `req.header()` aliases for BC
- Added `express.createServer()` for BC
- Perf: memoize parsed urls
- Perf: connect 2.2.0 dep
- Changed: make `expressInit()` middleware self-aware
- Fixed: use `app.get()` for all core settings
- Fixed redis session example
- Fixed session example. Closes #1105
- Fixed generated express dep. Closes #1078

3.0.0alpha1 / 2012-04-15

- Added `app.locals.use(callback)`
- Added `app.locals` object
- Added `app.locals(obj)`
- Added `res.locals` object
- Added `res.locals(obj)`
- Added `res.format()` for content-negotiation
- Added `app.engine()`
- Added `res.cookie()` JSON cookie support
- Added "trust proxy" setting
- Added `req.subdomains`
- Added `req.protocol`
- Added `req.secure`
- Added `req.path`

- Added `req.ips`
- Added `req.fresh`
- Added `req.stale`
- Added comma-delimited / array support for `req.accepts()`
- Added debug instrumentation
- Added `res.set(obj)`
- Added `res.set(field, value)`
- Added `res.get(field)`
- Added `app.get(setting)`. Closes #842
- Added `req.acceptsLanguage()`
- Added `req.acceptsCharset()`
- Added `req.accepted`
- Added `req.acceptedLanguages`
- Added `req.acceptedCharsets`
- Added "json replacer" setting
- Added "json spaces" setting
- Added X-Forwarded-Proto support to `res.redirect()`. Closes #92
- Added `--less` support to `express(1)`
- Added `express.response` prototype
- Added `express.request` prototype
- Added `express.application` prototype
- Added `app.path()`
- Added `app.render()`
- Added `res.type()` to replace `res.contentType()`
- Changed: `res.redirect()` to add relative support
- Changed: enable "jsonp callback" by default
- Changed: renamed "case sensitive routes" to "case sensitive routing"
- Rewrite of all tests with mocha
- Removed "root" setting
- Removed `res.redirect('home')` support
- Removed `req.notify()`
- Removed `app.register()`
- Removed `app.redirect()`
- Removed `app.is()`
- Removed `app.helpers()`
- Removed `app.dynamicHelpers()`
- Fixed `res.sendFile()` with non-GET. Closes #723
- Fixed `express(1)` public dir for windows. Closes #866

2.5.9/ 2012-04-02

- Added support for PURGE request method [pbuyale]
- Fixed `express(1)` generated app `app.address()` before `listening` [mmalecki]

2.5.8 / 2012-02-08

- Update mkdirp dep. Closes #991

2.5.7 / 2012-02-06

- Fixed `app.all` duplicate DELETE requests [mscdex]

2.5.6 / 2012-01-13

- Updated hamljs dev dep. Closes #953

2.5.5 / 2012-01-08

- Fixed: set `filename` on cached templates [matthewleon]

2.5.4 / 2012-01-02

- Fixed `express(1)` eol on 0.4.x. Closes #947

2.5.3 / 2011-12-30

- Fixed `req.is()` when a charset is present

2.5.2 / 2011-12-10

- Fixed: `express(1)` LF -> CRLF for windows

2.5.1 / 2011-11-17

- Changed: updated connect to 1.8.x
- Removed sass.js support from `express(1)`

2.5.0 / 2011-10-24

- Added `./routes` dir for generated app by default
- Added npm install reminder to `express(1)` app gen
- Added 0.5.x support
- Removed `make test-cov` since it wont work with node 0.5.x
- Fixed `express(1)` public dir for windows. Closes #866

2.4.7 / 2011-10-05

- Added `mkdirp` to `express(1)`. Closes #795
- Added simple `json-config` example
- Added shorthand for the parsed request's pathname via `req.path`
- Changed connect dep to 1.7.x to fix npm issue...
- Fixed `res.redirect()` **HEAD** support. [reported by xerox]
- Fixed `req.flash()`, only escape args

/

- Fixed absolute path checking on windows. Closes #829 [reported by andrewpmckenzie]

2.4.6 / 2011-08-22

- Fixed multiple param callback regression. Closes #824 [reported by TroyGoode]

2.4.5 / 2011-08-19

- Added support for routes to handle errors. Closes #809
- Added `app.routes.all()`. Closes #803
- Added "basepath" setting to work in conjunction with reverse proxies etc.
- Refactored `Route` to use a single array of callbacks
- Added support for multiple callbacks for `app.param()`. Closes #801 Closes #805
- Changed: removed `.call(self)` for route callbacks
- Dependency: `qs >= 0.3.1`
- Fixed `res.redirect()` on windows due to `join()` usage. Closes #808

2.4.4 / 2011-08-05

- Fixed `res.header()` intention of a set, even when `undefined`
- Fixed `*`, value no longer required
- Fixed `res.send(204)` support. Closes #771

2.4.3 / 2011-07-14

- Added docs for `status` option special-case. Closes #739
- Fixed `options.filename`, exposing the view path to template engines

2.4.2. / 2011-07-06

- Revert "removed jsonp stripping" for XSS

2.4.1 / 2011-07-06

- Added `res.json()` JSONP support. Closes #737
- Added `extending-templates` example. Closes #730
- Added "strict routing" setting for trailing slashes
- Added support for multiple envs in `app.configure()` calls. Closes #735
- Changed: `res.send()` using `res.json()`
- Changed: when cookie `path === null` don't default it
- Changed; default cookie path to "home" setting. Closes #731
- Removed `pids/logs` creation from `express(1)`

2.4.0 / 2011-06-28

- Added chainable `res.status(code)`
- Added `res.json()`, an explicit version of `res.send(obj)`
- Added simple web-service example

2.3.12 / 2011-06-22

- #express is now on freenode! come join!
- Added `req.get(field, param)`
- Added links to Japanese documentation, thanks @hideyukisaito!
- Added; the `express(1)` generated app outputs the env
- Added `content-negotiation` example
- Dependency: connect `>= 1.5.1 < 2.0.0`
- Fixed view layout bug. Closes #720
- Fixed; ignore body on 304. Closes #701

2.3.11 / 2011-06-04

- Added `npm test`
- Removed generation of dummy test file from `express(1)`
- Fixed; `express(1)` adds express as a dep
- Fixed; prune on `prepublish`

2.3.10 / 2011-05-27

- Added `req.route`, exposing the current route
- Added `package.json` generation support to `express(1)`
- Fixed call to `app.param()` function for optional params. Closes #682

2.3.9 / 2011-05-25

- Fixed bug-ish with `../' in res.partial()` calls

2.3.8 / 2011-05-24

- Fixed `app.options()`

2.3.7 / 2011-05-23

- Added route `Collection`, ex: `app.get('/user/:id').remove();`
- Added support for `app.param(fn)` to define param logic
- Removed `app.param()` support for callback with return value
- Removed module.parent check from `express(1)` generated app. Closes #670
- Refactored router. Closes #639

2.3.6 / 2011-05-20

/

- Changed; using devDependencies instead of git submodules
- Fixed redis session example
- Fixed markdown example
- Fixed view caching, should not be enabled in development

2.3.5 / 2011-05-20

- Added export `.view` as alias for `.View`

2.3.4 / 2011-05-08

- Added `./examples/say`
- Fixed `res.sendFile()` bug preventing the transfer of files with spaces

2.3.3 / 2011-05-03

- Added "case sensitive routes" option.
- Changed; split methods supported per rfc [slaskis]
- Fixed route-specific middleware when using the same callback function several times

2.3.2 / 2011-04-27

- Fixed view hints

2.3.1 / 2011-04-26

- Added `app.match()` as `app.match.all()`
- Added `app.lookup()` as `app.lookup.all()`
- Added `app.remove()` for `app.remove.all()`
- Added `app.remove.VERB()`
- Fixed template caching collision issue. Closes #644
- Moved router over from connect and started refactor

2.3.0 / 2011-04-25

- Added options support to `res.clearCookie()`
- Added `res.helpers()` as alias of `res.locals()`
- Added; json defaults to UTF-8 with `res.send()`. Closes #632. [Daniel * Dependency `connect >= 1.4.0`
- Changed; auto set Content-Type in `res.attachment` [Aaron Heckmann]
- Renamed "cache views" to "view cache". Closes #628
- Fixed caching of views when using several apps. Closes #637
- Fixed gotcha invoking `app.param()` callbacks once per route middleware. Closes #638
- Fixed partial lookup precedence. Closes #631 Shaw]

2.2.2 / 2011-04-12

- Added second callback support for `res.download()` connection errors
- Fixed `filename` option passing to template engine

2.2.1 / 2011-04-04

- Added `layout(path)` helper to change the layout within a view. Closes #610
- Fixed `partial()` collection object support. Previously only anything with `.length` would work. When `.length` is present one must still be aware of holes, however now `{ collection: {foo: 'bar'}}` is valid, exposes `keyInCollection` and `keysInCollection`.
- Performance improved with better view caching
- Removed `request` and `response` locals
- Changed; errorHandler page title is now `Express` instead of `Connect`

2.2.0 / 2011-03-30

- Added `app.lookup.VERB()`, ex `app.lookup.put('/user/:id')`. Closes #606
- Added `app.match.VERB()`, ex `app.match.put('/user/12')`. Closes #606
- Added `app.VERB(path)` as alias of `app.lookup.VERB()`.
- Dependency `connect >= 1.2.0`

2.1.1 / 2011-03-29

- Added; expose `err.view` object when failing to locate a view
- Fixed `res.partial()` call `next(err)` when no callback is given [reported by aheckmann]
- Fixed; `res.send(undefined)` responds with 204 [aheckmann]

2.1.0 / 2011-03-24

- Added `<root>/_?<name>` partial lookup support. Closes #447
- Added `request`, `response`, and `app` local variables
- Added `settings` local variable, containing the app's settings
- Added `req.flash()` exception if `req.session` is not available
- Added `res.send(bool)` support (json response)
- Fixed stylus example for latest version
- Fixed; wrap try/catch around `res.render()`

2.0.0 / 2011-03-17

- Fixed up index view path alternative.

/

- Changed; `res.locals()` without object returns the locals

2.0.0rc3 / 2011-03-17

- Added `res.locals(obj)` to compliment `res.local(key, val)`
- Added `res.partial()` callback support
- Fixed recursive error reporting issue in `res.render()`

2.0.0rc2 / 2011-03-17

- Changed; `partial()` "locals" are now optional
- Fixed `SlowBuffer` support. Closes #584 [reported by tyrda01]
- Fixed `.filename` view engine option [reported by drudge]
- Fixed blog example
- Fixed `{req,res}.app` reference when mounting [Ben Weaver]

2.0.0rc / 2011-03-14

- Fixed; expose `HTTPSServer` constructor
- Fixed `express(1)` default test charset. Closes #579 [reported by secoif]
- Fixed; default charset to utf-8 instead of utf8 for lame IE [reported by NickP]

2.0.0beta3 / 2011-03-09

- Added support for `res.contentType()` literal The original `res.contentType('.json')`, `res.contentType('application/json')`, and `res.contentType('json')` will work now.
- Added `res.render()` status option support back
- Added charset option for `res.render()`
- Added `.charset` support (via connect 1.0.4)
- Added view resolution hints when in development and a lookup fails
- Added layout lookup support relative to the page view. For example while rendering `./views/user/index.jade` if you create `./views/user/layout.jade` it will be used in favour of the root layout.
- Fixed `res.redirect()`. RFC states absolute url [reported by unlink]
- Fixed; default `res.send()` string charset to utf8
- Removed `Partial` constructor (not currently used)

2.0.0beta2 / 2011-03-07

- Added `res.render()` `.locals` support back to aid in migration process
- Fixed flash example

2.0.0beta / 2011-03-03

- Added HTTPS support

- Added `res.cookie()` maxAge support
- Added `req.header()` `Referer` / `Referer` special-case, either works
- Added mount support for `res.redirect()`, now respects the mount-point
- Added `union()` util, taking place of `merge(clone())` combo
- Added stylus support to express(1) generated app
- Added secret to session middleware used in examples and generated app
- Added `res.local(name, val)` for progressive view locals
- Added default param support to `req.param(name, default)`
- Added `app.disabled()` and `app.enabled()`
- Added `app.register()` support for omitting leading ".", either works
- Added `res.partial()`, using the same interface as `partial()` within a view. Closes #539
- Added `app.param()` to map route params to async/sync logic
- Added; aliased `app.helpers()` as `app.locals()`. Closes #481
- Added extname with no leading "." support to `res.contentType()`
- Added `cache views` setting, defaulting to enabled in "production" env
- Added index file partial resolution, eg: `partial('user')` may try `views/user/index.jade`.
- Added `req.accepts()` support for extensions
- Changed; `res.download()` and `res.sendfile()` now utilize Connect's static file server `connect.static.send()`.
- Changed; replaced `connect.utils.mime()` with npm `mime` module
- Changed; allow `req.query` to be pre-defined (via middleware or other parent)
- Changed view partial resolution, now relative to parent view
- Changed view engine signature. no longer `engine.render(str, options, callback)`, now `engine.compile(str, options) -> Function`, the returned function accepts `fn(locals)`.
- Fixed `req.param()` bug returning Array.prototype methods. Closes #552
- Fixed; using `Stream#pipe()` instead of `sys.pump()` in `res.sendfile()`
- Fixed; using `qs` module instead of `querystring`
- Fixed; strip unsafe chars from jsonp callbacks
- Removed "stream threshold" setting

1.0.8 / 2011-03-01

- Allow `req.query` to be pre-defined (via middleware or other parent app)
- "connect": ">= 0.5.0 < 1.0.0". Closes #547
- Removed the long deprecated **EXPRESS_ENV** support

1.0.7 / 2011-02-07

- Fixed `render()` setting inheritance. Mounted apps would not inherit "view engine"

1.0.6 / 2011-02-07

- Fixed `view engine` setting bug when period is in dirname

2020-12-17

1.0.5 / 2011-02-05

- Added secret to generated app `session()` call

1.0.4 / 2011-02-05

- Added `qs` dependency to `package.json`
- Fixed namespaced `require()`s for latest connect support

1.0.3 / 2011-01-13

- Remove unsafe characters from JSONP callback names [Ryan Grove]

1.0.2 / 2011-01-10

- Removed nested require, using `connect.router`

1.0.1 / 2010-12-29

- Fixed for middleware stacked via `createServer()` previously the `foo` middleware passed to `createServer(foo)` would not have access to Express methods such as `res.send()` or props like `req.query` etc.

1.0.0 / 2010-11-16

- Added; deduce partial object names from the last segment. For example by default `partial('forum/post', postObject)` will give you the `post` object, providing a meaningful default.
- Added http status code string representation to `res.redirect()` body
- Added; `res.redirect()` supporting `text/plain` and `text/html` via **Accept**.
- Added `req.is()` to aid in content negotiation
- Added partial local inheritance [suggested by masylum]. Closes #102 providing access to parent template locals.
- Added `-s, --session[s]` flag to `express(1)` to add session related middleware
- Added `--template` flag to `express(1)` to specify the template engine to use.
- Added `--css` flag to `express(1)` to specify the stylesheet engine to use (or just plain css by default).
- Added `app.all()` support [thanks aheckmann]
- Added partial direct object support. You may now `partial('user', user)` providing the "user" local, vs previously `partial('user', { object: user })`.
- Added `route-separation` example since many people question ways to do this with CommonJS modules. Also view the `blog` example for an alternative.
- Performance; caching view path derived partial object names
- Fixed partial local inheritance precedence. [reported by Nick Poulden] Closes #454

- /
- Fixed jsonp support; [text/javascript](#) as per mailinglist discussion

1.0.0rc4 / 2010-10-14

- Added `NODE_ENV` support, `EXPRESS_ENV` is deprecated and will be removed in 1.0.0
- Added route-middleware support (very helpful, see the [docs](#))
- Added `jsonp_callback` setting to enable/disable jsonp autowrapping [Dav Glass]
- Added callback query check on response.send to autowrap JSON objects for simple webservice implementations [Dav Glass]
- Added `partial()` support for array-like collections. Closes #434
- Added support for swappable querystring parsers
- Added session usage docs. Closes #443
- Added dynamic helper caching. Closes #439 [suggested by maritz]
- Added authentication example
- Added basic Range support to `res.sendFile()` (and `res.download()` etc)
- Changed; `express(1)` generated app using 2 spaces instead of 4
- Default env to "development" again [aheckmann]
- Removed `context` option is no more, use "scope"
- Fixed; exposing `./support` libs to examples so they can run without installs
- Fixed mvc example

1.0.0rc3 / 2010-09-20

- Added confirmation for `express(1)` app generation. Closes #391
- Added extending of flash formatters via `app.flashFormatters`
- Added flash formatter support. Closes #411
- Added streaming support to `res.sendFile()` using `sys.pump()` when `>=` "stream threshold"
- Added `stream threshold` setting for `res.sendFile()`
- Added `res.send()` **HEAD** support
- Added `res.clearCookie()`
- Added `res.cookie()`
- Added `res.render()` headers option
- Added `res.redirect()` response bodies
- Added `res.render()` status option support. Closes #425 [thanks aheckmann]
- Fixed `res.sendFile()` responding with 403 on malicious path
- Fixed `res.download()` bug; when an error occurs remove `Content-Disposition`
- Fixed; mounted apps settings now inherit from parent app [aheckmann]
- Fixed; stripping Content-Length / Content-Type when 204
- Fixed `res.send()` 204. Closes #419
- Fixed multiple `Set-Cookie` headers via `res.header()`. Closes #402
- Fixed bug messing with error handlers when `listenFD()` is called instead of `listen()`. [thanks guillermo]

1.0.0rc2 / 2010-08-17

- Added `app.register()` for template engine mapping. Closes #390
- Added `res.render()` callback support as second argument (no options)
- Added callback support to `res.download()`
- Added callback support for `res.sendFile()`
- Added support for middleware access via `express.middlewareName()` vs `connect.middlewareName()`
- Added "partials" setting to docs
- Added default expresso tests to `express(1)` generated app. Closes #384
- Fixed `res.sendFile()` error handling, defer via `next()`
- Fixed `res.render()` callback when a layout is used [thanks guillermo]
- Fixed; `make install` creating `~/.node_libraries` when not present
- Fixed issue preventing error handlers from being defined anywhere. Closes #387

1.0.0rc / 2010-07-28

- Added mounted hook. Closes #369
- Added connect dependency to `package.json`
- Removed "reload views" setting and support code development env never caches, production always caches.
- Removed `param` in route callbacks, signature is now simply (req, res, next), previously (req, res, params, next). Use `req.params` for path captures, `req.query` for GET params.
- Fixed "home" setting
- Fixed middleware/router precedence issue. Closes #366
- Fixed; `configure()` callbacks called immediately. Closes #368

1.0.0beta2 / 2010-07-23

- Added more examples
- Added; exporting `Server` constructor
- Added `Server#helpers()` for view locals
- Added `Server#dynamicHelpers()` for dynamic view locals. Closes #349
- Added support for absolute view paths
- Added; `home` setting defaults to `Server#route` for mounted apps. Closes #363
- Added Guillermo Rauch to the contributor list
- Added support for "as" for non-collection partials. Closes #341
- Fixed `install.sh`, ensuring `~/.node_libraries` exists. Closes #362 [thanks jf]
- Fixed `res.render()` exceptions, now passed to `next()` when no callback is given [thanks guillermo]
- Fixed instanceof `Array` checks, now `Array.isArray()`
- Fixed `express(1)` expansion of public dirs. Closes #348
- Fixed middleware precedence. Closes #345
- Fixed view watcher, now async [thanks aheckmann]

1.0.0beta / 2010-07-15

- Re-write
 - much faster
 - much lighter
 - Check ExpressJS.com for migration guide and updated docs

0.14.0 / 2010-06-15

- Utilize relative requires
- Added Static bufferSize option [aheckmann]
- Fixed caching of view and partial subdirectories [aheckmann]
- Fixed mime.type() comments now that ".ext" is not supported
- Updated haml submodule
- Updated class submodule
- Removed bin/express

0.13.0 / 2010-06-01

- Added node v0.1.97 compatibility
- Added support for deleting cookies via Request#cookie('key', null)
- Updated haml submodule
- Fixed not-found page, now using using charset utf-8
- Fixed show-exceptions page, now using using charset utf-8
- Fixed view support due to fs.readFile Buffers
- Changed; mime.type() no longer accepts ".type" due to node extname() changes

0.12.0 / 2010-05-22

- Added node v0.1.96 compatibility
- Added view **helpers** export which act as additional local variables
- Updated haml submodule
- Changed ETag; removed inode, modified time only
- Fixed LF to CRLF for setting multiple cookies
- Fixed cookie compilation; values are now urlencoded
- Fixed cookies parsing; accepts quoted values and url escaped cookies

0.11.0 / 2010-05-06

- Added support for layouts using different engines
 - this.render('page.html.haml', { layout: 'super-cool-layout.html.ejs' })
 - this.render('page.html.haml', { layout: 'foo' }) // assumes 'foo.html.haml'
 - this.render('page.html.haml', { layout: false }) // no layout
- Updated ext submodule
- Updated haml submodule
- Fixed EJS partial support by passing along the context. Issue #307

0.10.1 / 2010-05-03

- Fixed binary uploads.

0.10.0 / 2010-04-30

- Added charset support via Request#charset (automatically assigned to 'UTF-8' when respond()'s encoding is set to 'utf8' or 'utf-8').
- Added "encoding" option to Request#render(). Closes #299
- Added "dump exceptions" setting, which is enabled by default.
- Added simple ejs template engine support
- Added error response support for text/plain, application/json. Closes #297
- Added callback function param to Request#error()
- Added Request#sendHead()
- Added Request#stream()
- Added support for Request#respond(304, null) for empty response bodies
- Added ETag support to Request#sendfile()
- Added options to Request#sendfile(), passed to fs.createReadStream()
- Added filename arg to Request#download()
- Performance enhanced due to pre-reversing plugins so that plugins.reverse() is not called on each request
- Performance enhanced by preventing several calls to toLowerCase() in Router#match()
- Changed; Request#sendfile() now streams
- Changed; Renamed Request#halt() to Request#respond(). Closes #289
- Changed; Using sys.inspect() instead of JSON.encode() for error output
- Changed; run() returns the http.Server instance. Closes #298
- Changed; Defaulting Server#host to null (INADDR_ANY)
- Changed; Logger "common" format scale of 0.4f
- Removed Logger "request" format
- Fixed; Catching ENOENT in view caching, preventing error when "views/partials" is not found
- Fixed several issues with http client
- Fixed Logger Content-Length output
- Fixed bug preventing Opera from retaining the generated session id. Closes #292

0.9.0 / 2010-04-14

- Added DSL level error() route support
- Added DSL level notFound() route support
- Added Request#error()
- Added Request#notFound()
- Added Request#render() callback function. Closes #258
- Added "max upload size" setting
- Added "magic" variables to collection partials (__index__, __length__, __isFirst__, __isLast__). Closes #254

/

- Added [haml.js](#) submodule; removed haml-js
- Added callback function support to Request#halt() as 3rd/4th arg
- Added preprocessing of route param wildcards using param(). Closes #251
- Added view partial support (with collections etc)
- Fixed bug preventing falsey params (such as ?page=0). Closes #286
- Fixed setting of multiple cookies. Closes #199
- Changed; view naming convention is now NAME.TYPE.ENGINE (for example page.html.haml)
- Changed; session cookie is now httpOnly
- Changed; Request is no longer global
- Changed; Event is no longer global
- Changed; "sys" module is no longer global
- Changed; moved Request#download to Static plugin where it belongs
- Changed; Request instance created before body parsing. Closes #262
- Changed; Pre-caching views in memory when "cache view contents" is enabled. Closes #253
- Changed; Pre-caching view partials in memory when "cache view partials" is enabled
- Updated support to node --version 0.1.90
- Updated dependencies
- Removed set("session cookie") in favour of use(Session, { cookie: { ... } })
- Removed utils.mixin(); use Object#mergeDeep()

0.8.0 / 2010-03-19

- Added coffeescript example app. Closes #242
- Changed; cache api now async friendly. Closes #240
- Removed deprecated 'express/static' support. Use 'express/plugins/static'

0.7.6 / 2010-03-19

- Added Request#isXHR. Closes #229
- Added [make install](#) (for the executable)
- Added [express](#) executable for setting up simple app templates
- Added "GET /public/*" to Static plugin, defaulting to /public
- Added Static plugin
- Fixed; Request#render() only calls cache.get() once
- Fixed; Namespacing View caches with "view:"
- Fixed; Namespacing Static caches with "static:"
- Fixed; Both example apps now use the Static plugin
- Fixed set("views"). Closes #239
- Fixed missing space for combined log format
- Deprecated Request#sendfile() and 'express/static'
- Removed Server#running

0.7.5 / 2010-03-16

/

- Added Request#flash() support without args, now returns all flashes
- Updated ext submodule

0.7.4 / 2010-03-16

- Fixed session reaper
- Changed; class.js replacing js-oo Class implementation (quite a bit faster, no browser cruft)

0.7.3 / 2010-03-16

- Added package.json
- Fixed requiring of haml / sass due to kiwi removal

0.7.2 / 2010-03-16

- Fixed GIT submodules (HAH!)

0.7.1 / 2010-03-16

- Changed; Express now using submodules again until a PM is adopted
- Changed; chat example using millisecond conversions from ext

0.7.0 / 2010-03-15

- Added Request#pass() support (finds the next matching route, or the given path)
- Added Logger plugin (default "common" format replaces CommonLogger)
- Removed Profiler plugin
- Removed CommonLogger plugin

0.6.0 / 2010-03-11

- Added seed.yml for kiwi package management support
- Added HTTP client query string support when method is GET. Closes #205
- Added support for arbitrary view engines. For example "foo.engine.html" will now require('engine'), the exports from this module are cached after the first require().
- Added async plugin support
- Removed usage of RESTful route funcs as http client get() etc, use http.get() and friends
- Removed custom exceptions

0.5.0 / 2010-03-10

- Added ext dependency (library of js extensions)
- Removed extname() / basename() utils. Use path module
- Removed toArray() util. Use arguments.values
- Removed escapeRegexp() util. Use RegExp.escape()
- Removed process.mixin() dependency. Use utils.mixin()
- Removed Collection
- Removed ElementCollection
- Shameless self promotion of ebook "Advanced JavaScript" (<http://dev-mag.com>)



0.4.0 / 2010-02-11

- Added flash() example to sample upload app
- Added high level restful http client module (express/http)
- Changed; RESTful route functions double as HTTP clients. Closes #69
- Changed; throwing error when routes are added at runtime
- Changed; defaulting render() context to the current Request. Closes #197
- Updated haml submodule

0.3.0 / 2010-02-11

- Updated haml / sass submodules. Closes #200
- Added flash message support. Closes #64
- Added accepts() now allows multiple args. fixes #117
- Added support for plugins to halt. Closes #189
- Added alternate layout support. Closes #119
- Removed Route#run(). Closes #188
- Fixed broken specs due to use(Cookie) missing

0.2.1 / 2010-02-05

- Added "plot" format option for Profiler (for gnuplot processing)
- Added request number to Profiler plugin
- Fixed binary encoding for multipart file uploads, was previously defaulting to UTF8
- Fixed issue with routes not firing when not files are present. Closes #184
- Fixed process.Promise -> events.Promise

0.2.0 / 2010-02-03

- Added parseParam() support for name[] etc. (allows for file inputs with "multiple" attr) Closes #180
- Added Both Cache and Session option "reapInterval" may be "reapEvery". Closes #174
- Added expiration support to cache api with reaper. Closes #133
- Added cache Store.Memory#reap()

/

- Added Cache; cache api now uses first class Cache instances
- Added abstract session Store. Closes #172
- Changed; cache Memory.Store#get() utilizing Collection
- Renamed MemoryStore -> Store.Memory
- Fixed use() of the same plugin several time will always use latest options. Closes #176

0.1.0 / 2010-02-03

- Changed; Hooks (before / after) pass request as arg as well as evaluated in their context
- Updated node support to 0.1.27 Closes #169
- Updated dirname(__filename) -> __dirname
- Updated libxmljs support to v0.2.0
- Added session support with memory store / reaping
- Added quick uid() helper
- Added multi-part upload support
- Added Sass.js support / submodule
- Added production env caching view contents and static files
- Added static file caching. Closes #136
- Added cache plugin with memory stores
- Added support to StaticFile so that it works with non-textual files.
- Removed dirname() helper
- Removed several globals (now their modules must be required)

0.0.2 / 2010-01-10

- Added view benchmarks; currently haml vs ejs
- Added Request#attachment() specs. Closes #116
- Added use of node's parseQuery() util. Closes #123
- Added `make init` for submodules
- Updated Haml
- Updated sample chat app to show messages on load
- Updated libxmljs parseString -> parseHtmlString
- Fixed `make init` to work with older versions of git
- Fixed specs can now run independent specs for those who can't build deps. Closes #127
- Fixed issues introduced by the node url module changes. Closes 126.
- Fixed two assertions failing due to Collection#keys() returning strings
- Fixed faulty Collection#toArray() spec due to keys() returning strings
- Fixed `make test` now builds libxmljs.node before testing

0.0.1 / 2010-01-03

- Initial release