



```
std::vector<std::int32_t> vector{ 1, 2, 3, 4, 5 };
```

vector	1	2	3	4	5
	0	1	2	3	4

# Vectors

Data Structures – C++ Fundamentals

# Agenda

## What Are Vectors?

- Properties

- Benefits

- Drawbacks

## Dynamic-array Details

- Abstract Data Types

- How Do They Work?

- Operations

- Vector-specific Details

## Dynamic Allocation

- The Stack

- Return-value Optimization

- The Heap

- Vectors and the Heap

## Working with Vectors

- Syntax

- Undefined Behavior

- Iterator Invalidation

# What Are Vectors?

# Vector Properties

What is a vector?

Vectors are C++'s implementation of a data abstraction known as a *dynamic array*

# Vector Properties

What is a vector?

Vectors are C++'s implementation of a data abstraction known as a *dynamic array*

What is a dynamic array?

A *dynamic array* is a dynamically sizable array

# Vector Properties

What is a vector?

Vectors are C++'s implementation of a data abstraction known as a *dynamic array*

What is a dynamic array?

A *dynamic array* is a dynamically sizable array

- Dynamic arrays share the same properties as arrays

# Vector Properties

What is a vector?

Vectors are C++'s implementation of a data abstraction known as a *dynamic array*

What is a dynamic array?

A *dynamic array* is a dynamically sizable array

- Dynamic arrays share the same properties as arrays
- Dynamic arrays resize themselves as elements are added

# Dynamic-array Properties



# Dynamic-array Properties

- The sizes of dynamic arrays change as more elements are added

# Dynamic-array Properties

- The sizes of dynamic arrays change as more elements are added
- The initial size of a dynamic array is known at compile-time, but dynamic-array sizes will change at *runtime*

# Dynamic-array Properties

- The sizes of dynamic arrays change as more elements are added
- The initial size of a dynamic array is known at compile-time, but dynamic-array sizes will change at *runtime*
- Values are stored contiguously

# Dynamic-array Properties

- The sizes of dynamic arrays change as more elements are added
- The initial size of a dynamic array is known at compile-time, but dynamic-array sizes will change at *runtime*
- Values are stored contiguously
- Values can be accessed at random

# Dynamic-array Properties

- The sizes of dynamic arrays change as more elements are added
- The initial size of a dynamic array is known at compile-time, but dynamic-array sizes will change at *runtime*
- Values are stored contiguously
- Values can be accessed at random
- Values are ordered (indexed for dynamic arrays)

# Benefits of Dynamic Arrays

# Benefits of Dynamic Arrays

- Dynamic-size benefits

# Benefits of Dynamic Arrays

- Dynamic-size benefits
  - Can store an unspecified number of elements



# Benefits of Dynamic Arrays

- Dynamic-size benefits
  - Can store an unspecified number of elements
- Contiguous benefits

# Benefits of Dynamic Arrays

- Dynamic-size benefits
  - Can store an unspecified number of elements
- Contiguous benefits
  - Great cache locality

# Benefits of Dynamic Arrays

- Dynamic-size benefits
  - Can store an unspecified number of elements
- Contiguous benefits
  - Great cache locality
  - Fast element lookup

# Benefits of Dynamic Arrays

- Dynamic-size benefits
  - Can store an unspecified number of elements
- Contiguous benefits
  - Great cache locality
  - Fast element lookup
- Sequence benefits

# Benefits of Dynamic Arrays

- Dynamic-size benefits
  - Can store an unspecified number of elements
- Contiguous benefits
  - Great cache locality
  - Fast element lookup
- Sequence benefits
  - Elements can be traversed in particular orders

# Benefits of Dynamic Arrays

- Dynamic-size benefits
  - Can store an unspecified number of elements
- Contiguous benefits
  - Great cache locality
  - Fast element lookup
- Sequence benefits
  - Elements can be traversed in particular orders
  - Can be subsequenced

# Drawbacks of Dynamic Arrays

# Drawbacks of Dynamic Arrays

- Dynamic size isn't free



# Drawbacks of Dynamic Arrays

- Dynamic size isn't free
  - Dynamic arrays use more memory than the minimum amount of memory needed to store their elements

# Drawbacks of Dynamic Arrays

- Dynamic size isn't free
  - Dynamic arrays use more memory than the minimum amount of memory needed to store their elements
  - Dynamic-array data is stored on the heap

# Dynamic-array Details

# Abstract Data Types

An *abstract data type* (ADT) is a theoretical representation of a data type which outlines its properties and abilities

# Abstract Data Types

An *abstract data type* (ADT) is a theoretical representation of a data type which outlines its properties and abilities

- They don't mention concrete implementation details

# Abstract Data Types

An *abstract data type* (ADT) is a theoretical representation of a data type which outlines its properties and abilities

- They don't mention concrete implementation details
- They allow for classifying a data type based on its properties and operations rather than on its implementation

# Abstract Data Types

An *abstract data type* (ADT) is a theoretical representation of a data type which outlines its properties and abilities

- They don't mention concrete implementation details
- They allow for classifying a data type based on its properties and operations rather than on its implementation
- Programmers can abstract away any implementation details that don't matter by using ADTs

# Data Abstractions

A *data abstraction* is a specification of operations on a set of values



# Data Abstractions

A *data abstraction* is a specification of operations on a set of values

- Data abstractions are ADTs that are meant for representing data structures

# Data Abstractions

A *data abstraction* is a specification of operations on a set of values

- Data abstractions are ADTs that are meant for representing data structures
- *Data structures* are concrete implementations of data abstractions using a particular representation of the data

# Data Abstractions

A *data abstraction* is a specification of operations on a set of values

- Data abstractions are ADTs that are meant for representing data structures
- *Data structures* are concrete implementations of data abstractions using a particular representation of the data
- A dynamic array is a data abstraction since there are multiple data structures that could implement it

# How Might We Implement a Dynamic Array?


# How Might We Implement a Dynamic Array?

- Let's say we want to write a program which asks a user to enter an unlimited number of integers until they enter "stop"

# How Might We Implement a Dynamic Array?

- Let's say we want to write a program which asks a user to enter an unlimited number of integers until they enter "stop"
- How could we store the user's numbers using only **`std::array`**?

# How Might We Implement a Dynamic Array?



# How Might We Implement a Dynamic Array?

nums 

--	--	--	--	--

user enters their  
first number → 6



# How Might We Implement a Dynamic Array?



number is stored  
in first slot

# How Might We Implement a Dynamic Array?



user enters their  
second number → 3

# How Might We Implement a Dynamic Array?



number is stored  
in second slot

# How Might We Implement a Dynamic Array?



the user continues  
entering numbers → 8

# How Might We Implement a Dynamic Array?



the user continues  
entering numbers →

# How Might We Implement a Dynamic Array?



the user continues  
entering numbers



1

# How Might We Implement a Dynamic Array?



the user continues  
entering numbers →

# How Might We Implement a Dynamic Array?

nums 

6	3	8	1	
---	---	---	---	--

the user continues  
entering numbers



2



# How Might We Implement a Dynamic Array?

nums 

6	3	8	1	2
---	---	---	---	---

the user continues  
entering numbers →

# How Might We Implement a Dynamic Array?

nums 

6	3	8	1	2
---	---	---	---	---

the user continues  
entering numbers




7

# How Might We Implement a Dynamic Array?


nums 

6	3	8	1	2
---	---	---	---	---


now what? 

7

# How Might We Implement a Dynamic Array?




# How Might We Implement a Dynamic Array?




7

# How Might We Implement a Dynamic Array?




7

# How Might We Implement a Dynamic Array?



7


# How Might We Implement a Dynamic Array?



7




# How Might We Implement a Dynamic Array?



7

# How Might We Implement a Dynamic Array?




# How Might We Implement a Dynamic Array?



replace old array  
with new array

# How Might We Implement a Dynamic Array?



# Dynamic-array Operations

# Dynamic-array Operations

- What operations do dynamic arrays have?

# Dynamic-array Operations

- What operations do dynamic arrays have?
  - Size (constant time)

# Dynamic-array Operations

- What operations do dynamic arrays have?
  - Size (constant time)
  - Get (constant time)



# Dynamic-array Operations

- What operations do dynamic arrays have?
  - Size (constant time)
  - Get (constant time)
  - Set (constant time)

# Dynamic-array Operations

- What operations do dynamic arrays have?
  - Size (constant time)
  - Get (constant time)
  - Set (constant time)
  - Append (constant time)

# Dynamic-array Operations

- What operations do dynamic arrays have?
  - Size (constant time)
  - Get (constant time)
  - Set (constant time)
  - Append (constant time)
  - Insert (linear time)

# Dynamic-array Operations

- What operations do dynamic arrays have?
  - Size (constant time)
  - Get (constant time)
  - Set (constant time)
  - Append (constant time)
  - Insert (linear time)
  - Remove (linear time)

# Dynamic-array Operations

- What operations do dynamic arrays have?
  - Size (constant time)
  - Get (constant time)
  - Set (constant time)
  - Append (constant time)
  - Insert (linear time)
  - Remove (linear time)
  - Pop (linear time)

# Does `std::vector` Do Anything Differently?

## Does `std::vector` Do Anything Differently?

- Vectors require *dynamic allocation* since the sizes of the backing arrays need to change if required

## Does `std::vector` Do Anything Differently?

- Vectors require *dynamic allocation* since the sizes of the backing arrays need to change if required
- This means vectors allocate their data on the *heap*



## Does `std::vector` Do Anything Differently?

- Vectors require *dynamic allocation* since the sizes of the backing arrays need to change if required
- This means vectors allocate their data on the *heap*
- Dynamic allocation is a bit expensive if it's never needed

## Does `std::vector` Do Anything Differently?

- Vectors require *dynamic allocation* since the sizes of the backing arrays need to change if required
- This means vectors allocate their data on the *heap*
- Dynamic allocation is a bit expensive if it's never needed
- Vectors don't allocate memory if they're constructed empty

## Does `std::vector` Do Anything Differently?

- Vectors require *dynamic allocation* since the sizes of the backing arrays need to change if required
- This means vectors allocate their data on the *heap*
- Dynamic allocation is a bit expensive if it's never needed
- Vectors don't allocate memory if they're constructed empty
- First element added triggers allocation of an array with one slot. From there, array size increases by a factor of two

# Dynamic Allocation

# What Is the Stack?

# What Is the Stack?

- The stack is working memory allocated for our program

# What Is the Stack?

- The stack is working memory allocated for our program
- It's known as *automatic memory* since C++ handles it for us

# What Is the Stack?

- The stack is working memory allocated for our program
- It's known as *automatic memory* since C++ handles it for us
- When variables are declared, new slots are pushed onto the stack automatically



# What Is the Stack?

- The stack is working memory allocated for our program
- It's known as *automatic memory* since C++ handles it for us
- When variables are declared, new slots are pushed onto the stack automatically
- When variables go out of scope, the slots for those variables are popped off the stack automatically

# What Is the Stack?

- The stack is working memory allocated for our program
- It's known as *automatic memory* since C++ handles it for us
- When variables are declared, new slots are pushed onto the stack automatically
- When variables go out of scope, the slots for those variables are popped off the stack automatically
- When functions are called, stack memory is allocated to hold the arguments, local-variable data, and return-value data if function is non-void

# What Is the Stack?

- The stack is working memory allocated for our program
- It's known as *automatic memory* since C++ handles it for us
- When variables are declared, new slots are pushed onto the stack automatically
- When variables go out of scope, the slots for those variables are popped off the stack automatically
- When functions are called, stack memory is allocated to hold the arguments, local-variable data, and return-value data if function is non-void
- The memory allocated for a function called is known as a *stack frame*

# Advantages of the Stack

# Advantages of the Stack

- Quick allocations and deallocations

# Advantages of the Stack

- Quick allocations and deallocations
- Automatically managed by C++

# Advantages of the Stack

- Quick allocations and deallocations
- Automatically managed by C++
- It has a strict structure, so it's easy to keep it organized

# Any Disadvantages with the Stack?



# Any Disadvantages with the Stack?

- Newer data must be popped off the stack before older data

# Any Disadvantages with the Stack?

- Newer data must be popped off the stack before older data
- How do we keep data alive outside a function when it's created inside a function?

# Any Disadvantages with the Stack?

- Newer data must be popped off the stack before older data
- How do we keep data alive outside a function when it's created inside a function?
- The data is copied from the location referenced by the local variable to the location meant for the return value

# Any Disadvantages with the Stack?

- Newer data must be popped off the stack before older data
- How do we keep data alive outside a function when it's created inside a function?
- The data is copied from the location referenced by the local variable to the location meant for the return value
- What if the data is large? How expensive is this copy?

# Any Disadvantages with the Stack?

- Newer data must be popped off the stack before older data
- How do we keep data alive outside a function when it's created inside a function?
- The data is copied from the location referenced by the local variable to the location meant for the return value
- What if the data is large? How expensive is this copy?
- Are there ways to avoid these copies?

# Return-value Optimization (RVO)

# Return-value Optimization (RVO)

- When possible, C++ can avoid any copying when returning by using the location where the value would end up after the function ends instead of a temporary location within the stack frame

# Return-value Optimization (RVO)

- When possible, C++ can avoid any copying when returning by using the location where the value would end up after the function ends instead of a temporary location within the stack frame
- RVO only applies when return type is non-primitive



# Return-value Optimization (RVO)

- When possible, C++ can avoid any copying when returning by using the location where the value would end up after the function ends instead of a temporary location within the stack frame
- RVO only applies when return type is non-primitive
- Two kinds of RVO:

# Return-value Optimization (RVO)

- When possible, C++ can avoid any copying when returning by using the location where the value would end up after the function ends instead of a temporary location within the stack frame
- RVO only applies when return type is non-primitive
- Two kinds of RVO:
  - Unnamed return-value optimization (URVO)

# Return-value Optimization (RVO)

- When possible, C++ can avoid any copying when returning by using the location where the value would end up after the function ends instead of a temporary location within the stack frame
- RVO only applies when return type is non-primitive
- Two kinds of RVO:
  - Unnamed return-value optimization (URVO)
  - Named return-value optimization (NRVO)

# URVO Example

```
1  #include <array>
2  #include <cstdint>
3  #include <cstdlib>
4
5  std::array<std::int32_t, 5> get_nums() noexcept {
6      return std::array{ 1, 2, 3, 4, 5 };
7  }
8
9  int main() {
10     const auto nums{get_nums()};
11     return EXIT_SUCCESS;
12 }
```

# URVO Example

```
1  #include <array>
2  #include <cstdint>
3  #include <cstdlib>
4
5  std::array<std::int32_t, 5> get_nums() noexcept {
6      return std::array{ 1, 2, 3, 4, 5 };
7  }
8
9  int main() {
10     const auto nums{get_nums()};
11     return EXIT_SUCCESS;
12 }
```

← returned value is a  
temporary

# URVO Example

```
1  #include <array>
2  #include <cstdint>
3  #include <cstdlib>
4
5  std::array<std::int32_t, 5> get_nums() noexcept {
6      return std::array{ 1, 2, 3, 4, 5 };
7  }
8
9  int main() {
10     const auto nums{get_nums()};
11     return EXIT_SUCCESS;
12 }
```

returned value is a  
*temporary*

array will be created and  
stored directly in **nums**

# Things to Know about URVO

# Things to Know about URVO

- As of C++17, URVO is mandatory for all compilers to perform



# Things to Know about URVO


- As of C++17, URVO is mandatory for all compilers to perform
- URVO only applies if the return value is a temporary

# NRVO Example

```
1  #include <array>
2  #include <cstdint>
3  #include <cstdlib>
4
5  #include <UTL/random.hpp>
6
7  std::array<std::int32_t, 5> get_random_nums() {
8      namespace rand = utl::random;
9      std::array<std::int32_t, 5> nums{};
10     for (std::int32_t &num : nums) {
11         num = rand::uniform<std::int32_t>(-10, 10);
12     }
13     return nums;
14 }
15
16 int main() {
17     const auto nums{get_random_nums()};
18     return EXIT_SUCCESS;
19 }
```

# NRVO Example


return value is created  
before return statement




```
1  #include <array>
2  #include <cstdint>
3  #include <cstdlib>
4
5  #include <UTL/random.hpp>
6
7  std::array<std::int32_t, 5> get_random_nums() {
8      namespace rand = utl::random;
9      std::array<std::int32_t, 5> nums{};
10     for (std::int32_t &num : nums) {
11         num = rand::uniform<std::int32_t>(-10, 10);
12     }
13     return nums;
14 }
15
16 int main() {
17     const auto nums{get_random_nums()};
18     return EXIT_SUCCESS;
19 }
```

# NRVO Example

return value is created  
before return statement



return value can be created  
directly in result variable



```
1  #include <array>
2  #include <cstdint>
3  #include <cstdlib>
4
5  #include <UTL/random.hpp>
6
7  std::array<std::int32_t, 5> get_random_nums() {
8      namespace rand = utl::random;
9      std::array<std::int32_t, 5> nums{};
10     for (std::int32_t &num : nums) {
11         num = rand::uniform<std::int32_t>(-10, 10);
12     }
13     return nums;
14 }
15
16 int main() {
17     const auto nums{get_random_nums()};
18     return EXIT_SUCCESS;
19 }
```

# Things to Know about NRVO

# Things to Know about NRVO

- NRVO is a type of *copy elision*

# Things to Know about NRVO

- NRVO is a type of *copy elision*

## Copy elision

The creation of an object from an object of the same type can be omitted, even if the creation or destruction would have side effects

# Things to Know about NRVO

- NRVO is a type of *copy elision*

## Copy elision

The creation of an object from an object of the same type can be omitted, even if the creation or destruction would have side effects

- Copy elision is one of two allowed optimizations that can change observable side effects



# Things to Know about NRVO

- NRVO is a type of *copy elision*

## Copy elision

The creation of an object from an object of the same type can be omitted, even if the creation or destruction would have side effects

- Copy elision is one of two allowed optimizations that can change observable side effects
- Copy elision is *optional* for compilers to perform

# Things RVO Can't Fix

# Things RVO Can't Fix

- The stack isn't that big, so storing large amounts of data is difficult

# What Is the Heap?

# What Is the Heap?

- The heap is large region of memory available for on-demand (dynamic) allocations


# What Is the Heap?

- The heap is large region of memory available for on-demand (dynamic) allocations
- The structure of the stack makes it inconvenient for storing data which needs to persist for a while

# What Is the Heap?


- The heap is large region of memory available for on-demand (dynamic) allocations
- The structure of the stack makes it inconvenient for storing data which needs to persist for a while
- Newer memory must be freed before older memory can be freed

# What Is the Heap?






# What Is the Heap?




# What Is the Heap?

let's say **C** will  
last for most of  
the program



# What Is the Heap?



# What Is the Heap?

- The heap can be used to allocate large chunks of memory which need to last for a while

# What Is the Heap?

- The heap can be used to allocate large chunks of memory which need to last for a while
- Each of these chunks can be freed at any time, regardless of when it was allocated

# How Do Vectors Use Dynamic Allocation?

# How Do Vectors Use Dynamic Allocation?

- Information like the size and the capacity is stored on the stack

# How Do Vectors Use Dynamic Allocation?

- Information like the size and the capacity is stored on the stack
- Elements are stored on the heap



# How Do Vectors Use Dynamic Allocation?

- Information like the size and the capacity is stored on the stack
- Elements are stored on the heap
- New elements can be added or removed without worrying about the stack

# How Do Vectors Use Dynamic Allocation?

- Information like the size and the capacity is stored on the stack
- Elements are stored on the heap
- New elements can be added or removed without worrying about the stack
- Old backing arrays can have their memories freed as soon as they're no longer needed

# How Do Vectors Use Dynamic Allocation?

- Information like the size and the capacity is stored on the stack
- Elements are stored on the heap
- New elements can be added or removed without worrying about the stack
- Old backing arrays can have their memories freed as soon as they're no longer needed
- Only the existing elements will need to get copied when a new backing array is created

# Working with Vectors

# Vector Syntax: Creation

# Vector Syntax: Creation

```
std::vector<std::int32_t> vec1{ 1, 2, 3, 4, 5 };
```

# Vector Syntax: Creation

```
std::vector<std::int32_t> vec1{ 1, 2, 3, 4, 5 };
```

← creates a vector with  
the listed elements

# Vector Syntax: Creation

`std::vector<std::int32_t> vec1{ 1, 2, 3, 4, 5 }; ← creates a vector with the listed elements`

Annotations:

- `std::vector`: C++ vector type (from `<vector>`)
- `<std::int32_t>`: element type
- `vec1`: variable name
- `{ 1, 2, 3, 4, 5 }`: elements



# Vector Syntax: Creation

`std::vector`  
C++ vector type  
(from `<vector>`)

`<std::int32_t>`  
element type

`vec1`  
variable name

`{ 1, 2, 3, 4, 5 }`  
elements

← creates a vector with the listed elements

```
std::vector<double> vec2{};
```

# Vector Syntax: Creation

`std::vector`  
C++ vector type  
(from `<vector>`)

`<std::int32_t>`  
element type

`vec1`  
variable name

`{ 1, 2, 3, 4, 5 }`  
elements

← creates a vector with the listed elements

`std::vector<double> vec2{};` ← creates an empty vector

# Vector Syntax: Creation

`std::vector`  
C++ vector type  
(from `<vector>`)

`<std::int32_t>`  
element type

`vec1`  
variable name

`{ 1, 2, 3, 4, 5 }`  
elements

← creates a vector with the listed elements

`std::vector<double> vec2{};` ← creates an empty vector

`std::vector<std::uint16_t> vec3(10);`

# Vector Syntax: Creation

`std::vector`  
C++ vector type  
(from `<vector>`)

`<std::int32_t>`  
element type

`vec1`  
variable name

`{ 1, 2, 3, 4, 5 }`  
elements

← creates a vector with the listed elements

`std::vector<double> vec2{};` ← creates an empty vector

`std::vector<std::uint16_t> vec3(10);` ← creates a vector with 10 default-constructed values

# Vector Syntax: Creation

`std::vector`  
C++ vector type  
(from `<vector>`)

element type  
`<std::int32_t>`

variable name  
`vec1`

elements  
`{ 1, 2, 3, 4, 5 }`

← creates a vector with the listed elements

`std::vector<double> vec2{};` ← creates an empty vector

`std::vector<std::uint16_t> vec3(10);` ← creates a vector with 10 default-constructed values

↑ note the parentheses

# Vector Syntax: Creation

`std::vector`  
C++ vector type  
(from `<vector>`)

`<std::int32_t>`  
element type

`vec1`  
variable name

`{ 1, 2, 3, 4, 5 }`  
elements

← creates a vector with the listed elements

`std::vector<double> vec2{};` ← creates an empty vector

`std::vector<std::uint16_t> vec3(10);` ← creates a vector with 10 default-constructed values

↑ note the parentheses

`std::vector vec4(5, 'z');`

# Vector Syntax: Creation

`std::vector`  
C++ vector type  
(from `<vector>`)

element type  
`<std::int32_t>`

variable name  
`vec1`

elements  
`{ 1, 2, 3, 4, 5 }`

← creates a vector with the listed elements





`std::vector<double> vec2{};` ← creates an empty vector

`std::vector<std::uint16_t> vec3(10);` ← creates a vector with 10 default-constructed values

↑ note the parentheses

`std::vector vec4(5, 'z');` ← creates a vector with five copies of the value 'z'

# Vector Syntax: Creation

`std::vector`  C++ vector type (from `<vector>`)   
  element type `<std::int32_t>`   
 `vec1`  variable name   
  elements `{ 1, 2, 3, 4, 5 };`   
 ← creates a vector with the listed elements

`std::vector<double> vec2{};` ← creates an empty vector

`std::vector<std::uint16_t> vec3(10);` ← creates a vector with 10 default-constructed values

↑ note the parentheses

`std::vector vec4(5, 'z');` ← creates a vector with five copies of the value 'z'

↑ if omitted, compiler will deduce type from arguments



# Vector Syntax: Accessing

```
1  std::vector<std::int32_t> vec{ 1, 2, 3, 4, 5 };  
2  cout << vec.front() << '\n';
```

# Vector Syntax: Accessing

```
1 std::vector<std::int32_t> vec{ 1, 2, 3, 4, 5 };  
2 cout << vec.front() << '\n';
```

1

# Vector Syntax: Accessing

```
1  std::vector<std::int32_t> vec{ 1, 2, 3, 4, 5 };  
2  cout << vec.front() << '\n';
```

1

```
3  cout << vec.back() << '\n';
```

# Vector Syntax: Accessing

```
1  std::vector<std::int32_t> vec{ 1, 2, 3, 4, 5 };  
2  cout << vec.front() << '\n';
```

1

```
3  cout << vec.back() << '\n';
```

5

# Vector Syntax: Accessing

```
1  std::vector<std::int32_t> vec{ 1, 2, 3, 4, 5 };  
2  cout << vec.front() << '\n';
```

1

```
3  cout << vec.back() << '\n';
```

5

```
4  cout << vec.at(2) << '\n';
```

# Vector Syntax: Accessing

```
1 std::vector<std::int32_t> vec{ 1, 2, 3, 4, 5 };  
2 cout << vec.front() << '\n';
```

1

```
3 cout << vec.back() << '\n';
```

5

```
4 cout << vec.at(2) << '\n';
```

3

# Vector Syntax: Accessing

```
5 cout << "size: " << vec.size() << '\n';
```

# Vector Syntax: Accessing

```
5 cout << "size: " << vec.size() << '\n';
```

```
size: 5
```



# Vector Syntax: Accessing

```
5 cout << "size: " << vec.size() << '\n';
```

size: 5

```
6 cout << "capacity: " << vec.capacity() << '\n';
```

# Vector Syntax: Accessing

```
5 cout << "size: " << vec.size() << '\n';
```

size: 5

```
6 cout << "capacity: " << vec.capacity() << '\n';
```

capacity: 5

# Vector Syntax: Accessing

```
5 cout << "size: " << vec.size() << '\n';
```

size: 5

```
6 cout << "capacity: " << vec.capacity() << '\n';
```

capacity: 5

```
7 cout << vec.at(17) << '\n';
```

# Vector Syntax: Accessing

```
5 cout << "size: " << vec.size() << '\n';
```

size: 5

```
6 cout << "capacity: " << vec.capacity() << '\n';
```

capacity: 5

```
7 cout << vec.at(17) << '\n';
```

libc++abi: terminating due to uncaught exception of type std::out\_of\_range: vector

Process finished with exit code 134 (interrupted by signal 6:SIGABRT)

# Vector Syntax: Modifying

```
1  std::vector words{ "hello", "world", "C++" };  
2  words.front() = "goodbye";  
3  cout << words.front() << '\n';
```

# Vector Syntax: Modifying

```
1 std::vector words{ "hello", "world", "C++" };  
2 words.front() = "goodbye";  
3 cout << words.front() << '\n';
```

goodbye

# Vector Syntax: Modifying

```
1 std::vector words{ "hello", "world", "C++" };  
2 words.front() = "goodbye";  
3 cout << words.front() << '\n';
```

goodbye

```
4 words.at(2) = "Java";  
5 cout << words.at(2) << '\n';
```

# Vector Syntax: Modifying

```
1 std::vector words{ "hello", "world", "C++" };  
2 words.front() = "goodbye";  
3 cout << words.front() << '\n';
```

goodbye

```
4 words.at(2) = "Java";  
5 cout << words.at(2) << '\n';
```

Java



# Vector Syntax: Modifying

```
1 std::vector words{ "hello", "world", "C++" };  
2 words.front() = "goodbye";  
3 cout << words.front() << '\n';
```

goodbye

```
4 words.at(2) = "Java";  
5 cout << words.at(2) << '\n';
```

Java

```
6 words.at(-1) = "word";
```

# Vector Syntax: Modifying

```
1 std::vector words{ "hello", "world", "C++" };  
2 words.front() = "goodbye";  
3 cout << words.front() << '\n';
```

goodbye

```
4 words.at(2) = "Java";  
5 cout << words.at(2) << '\n';
```

Java

```
6 words.at(-1) = "word";
```

libc++abi: terminating due to uncaught exception of type std::out\_of\_range: vector

Process finished with exit code 134 (interrupted by signal 6:SIGABRT)

# Vector Syntax: Adding

```
1  std::vector<std::uint16_t> nums{};
2  for (std::uint16_t i{10}; i ≤ 50; ++i) {
3      nums.push_back(i);
4  }
5  // Assumes insertion operator has been overloaded for vectors.
6  cout << nums << '\n';
```

# Vector Syntax: Adding

```
1  std::vector<std::uint16_t> nums{};
2  for (std::uint16_t i{1U}; i ≤ 5U; ++i) {
3      nums.push_back(i);
4  }
5  // Assumes insertion operator has been overloaded for vectors.
6  cout << nums << '\n';
```

[1, 2, 3, 4, 5]

# Vector Syntax: Adding

```
1  std::vector<std::uint16_t> nums{};
2  for (std::uint16_t i{10}; i ≤ 50; ++i) {
3      nums.push_back(i);
4  }
5  // Assumes insertion operator has been overloaded for vectors.
6  cout << nums << '\n';
```

[1, 2, 3, 4, 5]

```
7  auto middle_iter{std::next(nums.begin(), nums.size() >> 1)};
8  cout << "middle element: " << *middle_iter << '\n';
9  middle_iter = nums.insert(middle_iter, 00);
10 cout << "new middle element: " << *middle_iter << '\n';
11 cout << nums << '\n';
```

# Vector Syntax: Adding

```
1  std::vector<std::uint16_t> nums{};
2  for (std::uint16_t i{10}; i ≤ 50; ++i) {
3      nums.push_back(i);
4  }
5  // Assumes insertion operator has been overloaded for vectors.
6  cout << nums << '\n';
```

[1, 2, 3, 4, 5]

```
7  auto middle_iter{std::next(nums.begin(), nums.size() >> 1)};
8  cout << "middle element: " << *middle_iter << '\n';
9  middle_iter = nums.insert(middle_iter, 0U);
10 cout << "new middle element: " << *middle_iter << '\n';
11 cout << nums << '\n';
```

middle element: 3  
new middle element: 0  
[1, 2, 0, 3, 4, 5]

# Vector Syntax: Adding

```
12  nums.insert(nums.begin(), { 7U, 8U, 9U });  
13  cout << nums << '\n';
```

# Vector Syntax: Adding

```
12  nums.insert(nums.begin(), { 70, 80, 90 });  
13  cout << nums << '\n';
```

[7, 8, 9, 1, 2, 0, 3, 4, 5]



# Vector Syntax: Adding

```
12  nums.insert(nums.begin(), { 7U, 8U, 9U });  
13  cout << nums << '\n';
```

[7, 8, 9, 1, 2, 0, 3, 4, 5]

```
14  nums.insert(nums.end(), 2U, 6U);  
15  cout << nums << endl;
```

# Vector Syntax: Adding

```
12  nums.insert(nums.begin(), { 7U, 8U, 9U });  
13  cout << nums << '\n';
```

[7, 8, 9, 1, 2, 0, 3, 4, 5]

```
14  nums.insert(nums.end(), 2U, 6U);  
15  cout << nums << endl;
```

[7, 8, 9, 1, 2, 0, 3, 4, 5, 6, 6]

Process finished with exit code 0

# Vector Syntax: Emplacing

# Vector Syntax: Emplacing

- What if we wanted to add an object to a vector?

# Vector Syntax: Emplacing

- What if we wanted to add an object to a vector?

```
1  std::vector<std::bitset<8>> bitsets{};  
2  bitsets.push_back(std::bitset<8>{0b11001100});  
3  cout << bitsets << '\n';
```

# Vector Syntax: Emplacing

- What if we wanted to add an object to a vector?

```
1 std::vector<std::bitset<8>> bitsets{};  
2 bitsets.push_back(std::bitset<8>{0b11001100});  
3 cout << bitsets << '\n';
```

[11001100]

# Vector Syntax: Emplacing

- What if we wanted to add an object to a vector?

```
1 std::vector<std::bitset<8>> bitsets{};  
2 bitsets.push_back(std::bitset<8>{0b11001100});  
3 cout << bitsets << '\n';
```

[11001100]

- This works, but it's annoying to write the type every time

# Vector Syntax: Emplacing

- What if we wanted to add an object to a vector?

```
1 std::vector<std::bitset<8>> bitsets{};  
2 bitsets.push_back(std::bitset<8>{0b11001100});  
3 cout << bitsets << '\n';
```

[11001100]

- This works, but it's annoying to write the type every time
- This solution is also not as efficient as it could be



# Vector Syntax: Emplacing

- This is where *emplacing* comes in!

# Vector Syntax: Emplacing

- This is where *emplacing* comes in!
- Emplacing lets us construct objects in place

# Vector Syntax: Emplacing

- This is where *emplacing* comes in!
- Emplacing lets us construct objects in place

```
4  const auto &r_last_element{bitsets.emplace_back(0b10101010)};  
5  cout << "last element: " << r_last_element << '\n';  
6  cout << bitsets << '\n';
```

# Vector Syntax: Emplacing

- This is where *emplacing* comes in!
- Emplacing lets us construct objects in place

```
4  const auto &r_last_element{bitsets.emplace_back(0b10101010)};  
5  cout << "last element: " << r_last_element << '\n';  
6  cout << bitsets << '\n';
```

```
last element: 10101010  
[11001100, 10101010]
```

# Vector Syntax: Emplacing

- This is where *emplacing* comes in!
- Emplacing lets us construct objects in place

```
4  const auto &r_last_element{bitsets.emplace_back(0b10101010)};  
5  cout << "last element: " << r_last_element << '\n';  
6  cout << bitsets << '\n';
```

```
last element: 10101010  
[11001100, 10101010]
```

```
7  const auto start_iter{bitsets.emplace(bitsets.begin(), 0b11110000)};  
8  cout << "first element: " << *start_iter << '\n';  
9  cout << bitsets << '\n';
```

# Vector Syntax: Emplacing

- This is where *emplacing* comes in!
- Emplacing lets us construct objects in place

```
4  const auto &r_last_element{bitsets.emplace_back(0b10101010)};  
5  cout << "last element: " << r_last_element << '\n';  
6  cout << bitsets << '\n';
```

last element: 10101010  
[11001100, 10101010]

```
7  const auto start_iter{bitsets.emplace(bitsets.begin(), 0b11110000)};  
8  cout << "first element: " << *start_iter << '\n';  
9  cout << bitsets << '\n';
```

first element: 11110000  
[11110000, 11001100, 10101010]

# Vector Syntax: Removing

```
1  std::vector letters{ 'a', 'b', 'a', 'b', 'c', 'd', 'e', 'f', 'g' };  
2  cout << letters << '\n';  
3  letters.pop_back();  
4  cout << letters << '\n';
```

# Vector Syntax: Removing

```
1  std::vector letters{ 'a', 'b', 'a', 'b', 'c', 'd', 'e', 'f', 'g' };
2  cout << letters << '\n';
3  letters.pop_back();
4  cout << letters << '\n';
```

[a, b, a, b, c, d, e, f, g]  
[a, b, a, b, c, d, e, f]



# Vector Syntax: Removing

```
1  std::vector letters{ 'a', 'b', 'a', 'b', 'c', 'd', 'e', 'f', 'g' };
2  cout << letters << '\n';
3  letters.pop_back();
4  cout << letters << '\n';
```

[a, b, a, b, c, d, e, f, g]  
[a, b, a, b, c, d, e, f]

```
5  auto middle_iter{std::next(letters.begin(), letters.size() >> 1)};
6  cout << *middle_iter << '\n';
7  middle_iter = letters.erase(middle_iter);
8  cout << *middle_iter << '\n';
9  cout << letters << '\n';
```

# Vector Syntax: Removing

```
1 std::vector letters{ 'a', 'b', 'a', 'b', 'c', 'd', 'e', 'f', 'g' };  
2 cout << letters << '\n';  
3 letters.pop_back();  
4 cout << letters << '\n';
```

[a, b, a, b, c, d, e, f, g]  
[a, b, a, b, c, d, e, f]

```
5 auto middle_iter{std::next(letters.begin(), letters.size() >> 1)};  
6 cout << *middle_iter << '\n';  
7 middle_iter = letters.erase(middle_iter);  
8 cout << *middle_iter << '\n';  
9 cout << letters << '\n';
```

c  
d  
[a, b, a, b, d, e, f]

# Vector Syntax: Removing

```
10  const auto start_iter{std::prev(letters.end(), 3)};
11  auto end_iter{std::prev(letters.end())};
12  cout << *start_iter << ' ' << *end_iter << '\n';
13  end_iter = letters.erase(start_iter, end_iter);
14  cout << *end_iter << '\n'; // `start_iter` is no longer valid
15  cout << letters << '\n';
```

# Vector Syntax: Removing

```
10 const auto start_iter{std::prev(letters.end(), 3)};  
11 auto end_iter{std::prev(letters.end())};  
12 cout << *start_iter << ' ' << *end_iter << '\n';  
13 end_iter = letters.erase(start_iter, end_iter);  
14 cout << *end_iter << '\n'; // `start_iter` is no longer valid  
15 cout << letters << '\n';
```

```
d f  
f  
[a, b, a, b, f]
```

# Vector Syntax: Removing

```
10 const auto start_iter{std::prev(letters.end(), 3)};  
11 auto end_iter{std::prev(letters.end())};  
12 cout << *start_iter << ' ' << *end_iter << '\n';  
13 end_iter = letters.erase(start_iter, end_iter);  
14 cout << *end_iter << '\n'; // `start_iter` is no longer valid  
15 cout << letters << '\n';
```

```
d f  
f  
[a, b, a, b, f]
```

```
16 std::size_t removed_count{std::erase(letters, 'a')};  
17 cout << "removed " << removed_count << '\n';  
18 cout << letters << '\n';
```

# Vector Syntax: Removing

```
10 const auto start_iter{std::prev(letters.end(), 3)};  
11 auto end_iter{std::prev(letters.end())};  
12 cout << *start_iter << ' ' << *end_iter << '\n';  
13 end_iter = letters.erase(start_iter, end_iter);  
14 cout << *end_iter << '\n'; // `start_iter` is no longer valid  
15 cout << letters << '\n';
```

d f  
f  
[a, b, a, b, f]

```
16 std::size_t removed_count{std::erase(letters, 'a')};  
17 cout << "removed " << removed_count << '\n';  
18 cout << letters << '\n';
```

removed 2  
[b, b, f]

# Vector Syntax: Removing

```
19  std::vector<std::int16_t> nums{ 1, 2, 3, 4, 5, 6, 7, 8 };
20  cout << nums << '\n';
21  removed_count = std::erase_if(nums, [](const std::int16_t num) noexcept {
22      return 3 ≤ num && num ≤ 6;
23  });
24  cout << "removed " << removed_count << '\n';
25  cout << nums << endl;
```

# Vector Syntax: Removing

```
19 std::vector<std::int16_t> nums{ 1, 2, 3, 4, 5, 6, 7, 8 };
20 cout << nums << '\n';
21 removed_count = std::erase_if(nums, [](const std::int16_t num) noexcept {
22     return 3 ≤ num && num ≤ 6;
23 });
24 cout << "removed " << removed_count << '\n';
25 cout << nums << endl;
```

[1, 2, 3, 4, 5, 6, 7, 8]

removed 4

[1, 2, 7, 8]

Process finished with exit code 0



# Vector Syntax: Misc.

```
1  std::vector nums{ 1.2, 3.4, 4.7 };
2  cout << nums << " : size: " << nums.size() << ", cap: ";
3  cout << nums.capacity() << ", empty: " << nums.empty() << '\n';
4  nums.clear();
5  cout << nums << " : size: " << nums.size() << ", cap: ";
6  cout << nums.capacity() << ", empty: " << nums.empty() << endl;
```

# Vector Syntax: Misc.

```
1  std::vector<double> nums{ 1.2, 3.4, 4.7 };
2  cout << nums << " : size: " << nums.size() << ", cap: ";
3  cout << nums.capacity() << ", empty: " << nums.empty() << '\n';
4  nums.clear();
5  cout << nums << " : size: " << nums.size() << ", cap: ";
6  cout << nums.capacity() << ", empty: " << nums.empty() << endl;
```

```
[1.2, 3.4, 4.7] : size: 3, cap: 3, empty: false
[] : size: 0, cap: 3, empty: true
```

Process finished with exit code 0

# Vector Syntax: Resizing

```
1  std::vector<std::int32_t> nums{};
2  cout << nums << " : cap: " << nums.capacity() << ", size: " << nums.size() << '\n';
3  nums.reserve(10U); // can only increase capacity
4  cout << nums << " : cap: " << nums.capacity() << ", size: " << nums.size() << '\n';
5  for (std::int32_t i{0}; i < 10; ++i) { nums.push_back(i); }
6  cout << nums << " : cap: " << nums.capacity() << ", size: " << nums.size() << '\n';
```

# Vector Syntax: Resizing

```
1 std::vector<std::int32_t> nums{};
2 cout << nums << " : cap: " << nums.capacity() << ", size: " << nums.size() << '\n';
3 nums.reserve(10U); // can only increase capacity
4 cout << nums << " : cap: " << nums.capacity() << ", size: " << nums.size() << '\n';
5 for (std::int32_t i{0}; i < 10; ++i) { nums.push_back(i); }
6 cout << nums << " : cap: " << nums.capacity() << ", size: " << nums.size() << '\n';
```

```
[] : cap: 0, size: 0
[] : cap: 10, size: 0
[0, 1, 2, 3, 4, 5, 6, 7, 8, 9] : cap: 10, size: 10
```

# Vector Syntax: Resizing

```
7  nums.push_back(10);  
8  cout << nums << " : cap: " << nums.capacity() << ", size: " << nums.size() << '\n';  
9  nums.shrink_to_fit(); // may or may not shrink capacity to size  
10 cout << nums << " : cap: " << nums.capacity() << ", size: " << nums.size() << endl;
```

# Vector Syntax: Resizing

```
7  nums.push_back(10);  
8  cout << nums << " : cap: " << nums.capacity() << ", size: " << nums.size() << '\n';  
9  nums.shrink_to_fit(); // may or may not shrink capacity to size  
10 cout << nums << " : cap: " << nums.capacity() << ", size: " << nums.size() << endl;
```

```
[0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10] : cap: 20, size: 11  
[0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10] : cap: 11, size: 11
```

Process finished with exit code 0

# Vector Syntax: Resizing

```
7  nums.push_back(10);  
8  cout << nums << " : cap: " << nums.capacity() << ", size: " << nums.size() << '\n';  
9  nums.shrink_to_fit(); // may or may not shrink capacity to size  
10 cout << nums << " : cap: " << nums.capacity() << ", size: " << nums.size() << endl;
```

```
[0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10] : cap: 20, size: 11  
[0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10] : cap: 11, size: 11
```

Process finished with exit code 0

- Don't overuse these methods!

# Vector Syntax: Resizing

```
1  std::vector<double> nums{ 1.1, 2.2, 3.3, 4.4, 5.5 };
2  cout << nums << '\n';
3  nums.resize(10U);
4  cout << nums << '\n';
5  nums.resize(3U);
6  cout << nums << '\n';
```



# Vector Syntax: Resizing

```
1  std::vector<double> nums{ 1.1, 2.2, 3.3, 4.4, 5.5 };
2  cout << nums << '\n';
3  nums.resize(10U);
4  cout << nums << '\n';
5  nums.resize(3U);
6  cout << nums << '\n';
```

[1.1, 2.2, 3.3, 4.4, 5.5]

[1.1, 2.2, 3.3, 4.4, 5.5, 0, 0, 0, 0, 0]

[1.1, 2.2, 3.3]

# Vector Syntax: Resizing

```
7  nums.resize(6U, 3.14);  
8  cout << nums << '\n';  
9  nums.resize(4U, -2.71);  
10 cout << nums << endl;
```

# Vector Syntax: Resizing

```
7  nums.resize(6U, 3.14);  
8  cout << nums << '\n';  
9  nums.resize(4U, -2.71);  
10 cout << nums << endl;
```

```
[1.1, 2.2, 3.3, 3.14, 3.14, 3.14]  
[1.1, 2.2, 3.3, 3.14]
```

Process finished with exit code 0

# Vector Syntax: Iteration

```
1  const std::vector<std::int16_t> nums{ 1, -2, 23, 4, 13 };
```

```
2  cout << "nums: ";  
3  for (std::size_t i{0U}; i < nums.size(); ++i) {  
4      cout << nums.at(i) << ' ';  
5  }  
6  cout << '\n';
```

Output:

nums: 1 -2 23 4 13

# Vector Syntax: Iteration

```
1  const std::vector<std::int16_t> nums{ 1, -2, 23, 4, 13 };
```

```
2  cout << "nums: ";  
3  for (std::size_t i{0U}; i < nums.size(); ++i) {  
4      cout << nums.at(i) << ' ';  
5  }  
6  cout << '\n';
```

Output:

nums: 1 -2 23 4 13

```
7  cout << "nums: ";  
8  for (std::size_t i{nums.size()}; i > 0U; --i) {  
9      cout << nums.at(i - 1U) << ' ';  
10 }  
11 cout << '\n';
```

Output:

nums: 13 4 23 -2 1

# Vector Syntax: Iteration

```
12  cout << "nums: ";  
13  for (auto iter{nums.cbegin()}; iter != nums.cend(); ++iter) {  
14      cout << *iter << ' ';  
15  }  
16  cout << '\n';
```

Output:

nums: 1 -2 23 4 13

# Vector Syntax: Iteration

```
12 cout << "nums: ";  
13 for (auto iter{nums.cbegin()}; iter != nums.cend(); ++iter) {  
14     cout << *iter << ' ';  
15 }  
16 cout << '\n';
```

Output:

nums: 1 -2 23 4 13

```
17 cout << "nums: ";  
18 for (auto iter{nums.crbegin()}; iter != nums.crend(); ++iter) {  
19     cout << *iter << ' ';  
20 }  
21 cout << '\n';
```

Output:

nums: 13 4 23 -2 1

# Vector Syntax: Iteration

```
22 cout << "nums: ";  
23 for (const std::int16_t num : nums) { cout << num << ' '; }  
24 cout << '\n';
```

Output:

nums: 1 -2 23 4 13



# Undefined Behavior

```
1  std::vector<std::int16_t> nums{ 1, -2, 23, 4, 13 };  
2  cout << nums[2] << '\n'; // UB if index out of range  
3  cout << nums.front() << '\n'; // UB if `nums` is empty  
4  cout << nums.back() << '\n'; // UB if `nums` is empty  
5  nums.pop_back(); // UB if `nums` is empty
```

# Undefined Behavior

```
1  std::vector<std::int16_t> nums{ 1, -2, 23, 4, 13 };  
2  cout << nums[2] << '\n'; // UB if index out of range  
3  cout << nums.front() << '\n'; // UB if `nums` is empty  
4  cout << nums.back() << '\n'; // UB if `nums` is empty  
5  nums.pop_back(); // UB if `nums` is empty
```

- Additionally, we're met with UB if certain requirements aren't met for type **T**

# Iterator Invalidation

# Iterator Invalidation

*Iterator invalidation* is when an existing iterator is rendered unusable by an operation performed on the underlying object

# Iterator Invalidation

*Iterator invalidation* is when an existing iterator is rendered unusable by an operation performed on the underlying object

- The data they point to is no longer in the underlying object

# Iterator Invalidation

*Iterator invalidation* is when an existing iterator is rendered unusable by an operation performed on the underlying object

- The data they point to is no longer in the underlying object
- The memory an iterator points to has been deallocated or repurposed

# Iterator Invalidation

- Any time a vector resizes, all iterators are invalidated

# Iterator Invalidation

- Any time a vector resizes, all iterators are invalidated
- Any time an element is removed, iterators pointing to that element or any element after it in the sequence are invalidated



# Iterator Invalidation

- Any time a vector resizes, all iterators are invalidated
- Any time an element is removed, iterators pointing to that element or any element after it in the sequence are invalidated
- These both include the end iterator

# Iterator Invalidation

```
1  std::vector<std::int32_t> nums{ 1, 2, 3 };
2  const auto end_iter{nums.end()};
3  const auto middle_iter{std::next(nums.begin(), nums.size() >> 1)};
4  nums.erase(middle_iter); // middle_iter and all after invalidated
5  cout << *middle_iter << '\n'; // 🤖
6  for (auto iter{nums.begin()}; iter != end_iter; ++iter) { // 🤖
7      cout << *iter << ' ';
8  }
9  cout << '\n';
```

# Iterator Invalidation

```
1  std::vector<std::int32_t> nums{ 1, 2, 3 };
2  const auto end_iter{nums.end()};
3  const auto middle_iter{std::next(nums.begin(), nums.size() >> 1)};
4  nums.erase(middle_iter); // middle_iter and all after invalidated
5  cout << *middle_iter << '\n'; // 🤖
6  for (auto iter{nums.begin()}; iter != end_iter; ++iter) { // 🤖
7      cout << *iter << ' ';
8  }
9  cout << '\n';
```

```
3
1 3 3
```

# Iterator Invalidation

```
10 std::vector words{ "hello"s, "world"s };  
11 const auto begin_iter{words.begin()};  
12 words.push_back("word"s); // all iterators invalidated due to resize  
13 cout << *begin_iter << endl; // 🤖
```

# Iterator Invalidation

```
10 std::vector words{ "hello"s, "world"s };
11 const auto begin_iter{words.begin()};
12 words.push_back("word"s); // all iterators invalidated due to resize
13 cout << *begin_iter << endl; // 🤖
```

??t?

Process finished with exit code 0