

Track - Australia



AERODYNAMICS
TRANSMISSION
CAMBER/TOE
SUSPENSION
ROLLBARS
RIDEHEIGHT
BRAKES
FRONT TYRES
REAR TYRES

FRONT - 45 REAR - 25
ON - 100 OFF - 35
ALL LEFT
FRONT - 41 REAR - 20
FRONT - 3 REAR - 9
FRONT - 24 REAR - 40
PRES - 100 BIAS - 55-54
LEFT - 29.5 RIGHT 29.5
LEFT - 26.5 RIGHT 26.5

NOTES

RACE

Focus on front left tyre wear + corner exit speed



AERODYNAMICS
TRANSMISSION
CAMBER/TOE
SUSPENSION
ROLLBARS
RIDEHEIGHT
BRAKES
FRONT TYRES
REAR TYRES

FRONT - 50 REAR - 40
ON - 100 OFF - 30
ALL LEFT
FRONT - 41 REAR - 20
FRONT - 3 REAR - 9
FRONT - 24 REAR - 40
PRES - 100 BIAS - 54-53
LEFT - 29.5 RIGHT 29.5
LEFT - 26.5 RIGHT 26.5

NOTES

INTERMEDIATES

Drive off-line on straights to reduce temperatures and tyre wear.



AERODYNAMICS
TRANSMISSION
CAMBER/TOE
SUSPENSION
ROLLBARS
RIDEHEIGHT
BRAKES
FRONT TYRES
REAR TYRES

FRONT - 45 REAR - 25
ON - 100 OFF - 30
ALL LEFT
FRONT - 41 REAR - 20
FRONT - 3 REAR - 9
FRONT - 24 REAR - 40
PRES - 100 BIAS - 54
LEFT - 29.5 RIGHT 29.5
LEFT - 26.5 RIGHT 26.5

NOTES

QUALIFYING

For more rear stability, increase off-throttle differential to 35%



AERODYNAMICS
TRANSMISSION
CAMBER/TOE
SUSPENSION
ROLLBARS
RIDEHEIGHT
BRAKES
FRONT TYRES
REAR TYRES

FRONT - 50 REAR - 40
ON - 100 OFF - 30
ALL LEFT
FRONT - 41 REAR - 20
FRONT - 3 REAR - 9
FRONT - 24 REAR - 40
PRES - 100 BIAS - 54-53
LEFT - 29.5 RIGHT 29.5
LEFT - 26.5 RIGHT 26.5

NOTES

WETS

Drive off-line on straights to help control tyre temperatures