

Track - China



AERODYNAMICS
TRANSMISSION
CAMBER/TOE
SUSPENSION
ROLLBARS
RIDEHEIGHT
BRAKES
FRONT TYRES
REAR TYRES

FRONT - 50 REAR - 40
ON - 100 OFF - 45
ALL LEFT
FRONT - 41 REAR - 41
FRONT - 1 REAR - 6
FRONT - 21 REAR - 40
PRES - 100 BIAS - 56-55
LEFT - 29.5 RIGHT 29.5
LEFT - 26.5 RIGHT 26.5

NOTES

RACE

Avoid overworking the front-left tyre, as this will increase understeer.



AERODYNAMICS
TRANSMISSION
CAMBER/TOE
SUSPENSION
ROLLBARS
RIDEHEIGHT
BRAKES
FRONT TYRES
REAR TYRES

FRONT - 50 REAR - 44
ON - 100 OFF - 45
ALL LEFT
FRONT - 41 REAR - 41
FRONT - 1 REAR - 6
FRONT - 21 REAR - 40
PRES - 100 BIAS - 55-54
LEFT - 29.5 RIGHT 29.5
LEFT - 26.5 RIGHT 26.5

NOTES

INTERMEDIATES

Prioritise corner exit speed over corner entry aggression



AERODYNAMICS
TRANSMISSION
CAMBER/TOE
SUSPENSION
ROLLBARS
RIDEHEIGHT
BRAKES
FRONT TYRES
REAR TYRES

FRONT - 50 REAR - 40
ON - 100 OFF - 45
ALL LEFT
FRONT - 41 REAR - 41
FRONT - 1 REAR - 6
FRONT - 21 REAR - 40
PRES - 100 BIAS - 55
LEFT - 29.5 RIGHT 29.5
LEFT - 26.5 RIGHT 26.5

NOTES

QUALIFYING

For less rear sliding at low speed, increase off-throttle differential to 50%



AERODYNAMICS
TRANSMISSION
CAMBER/TOE
SUSPENSION
ROLLBARS
RIDEHEIGHT
BRAKES
FRONT TYRES
REAR TYRES

FRONT - 50 REAR - 44
ON - 100 OFF - 45
ALL LEFT
FRONT - 41 REAR - 41
FRONT - 1 REAR - 6
FRONT - 21 REAR - 40
PRES - 100 BIAS - 55-54
LEFT - 29.5 RIGHT 29.5
LEFT - 26.5 RIGHT 26.5

NOTES

WETS

Avoid wheelspin and sliding to protect tyre temperatures.