



NOTES

1. FUSING 1.5A PER C.C.T.
2. SHELF JACK WIRING TO BE IN 20 SWG
3. CONNECT TO DT TO SUIT LOCAL CONDITIONS RATIOS: ab-a-e=1:20 ac-a-e=1:10 ad-a-e=1:5
4. (B) DENOTES SMOOTHED SUPPLY WHEN THERE IS NO UNSMOOTHED SUPPLY ON P.A.X. DELETE CONNECTIONS SHOWN THUS —•— & ADD STRAP SHOWN THUS —XX—
5. EITHER CONDENSER C1 OR C3, OR BOTH WIRED IN SERIES OR PARALLEL AS REQUIRED TO ADJUST TONE TO APPROX 400 CPS

OSCILLATOR C2 VALUE AMENDED	(77184)	5	27.1.65
RETRACED	(1250)	4	22.2.64
OSCILLATOR MODIFIED C2 WAS 0.1 CV491 WAS 455 (52915)		4	6.1.59
TERM. SR ADDED	40552	3	13.3.56
C3 ADDED IN VO NOTE 5 ADDED	38715	2	
AMENDMENT PARTICULARS			
ISSUE		DATE	APPD.
E.T. LTD. BEESTON, NOTTINGHAM, ENGLAND			
ENG. DEPT. APPROVED	DRAWN	CHECKED	WIRING CIRCUIT

50 LINE P.A.X.
RINGING & TONES CIRCUIT

24V E

94551/SW