



BriteTest

Runner Reference

Document Version: 1.0

Runner Version: 1.0.0

Test Version: 1.0.0

This document provides a reference to the Runner API. It includes types, structs, unions, enums, macros, and functions. Additionally, it provides a reference to Runner Framework concepts.

Copyright (c) 2026 Paul Sinclair

License SPDX-License-Identifier: MIT

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the “Software”), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED “AS IS”, WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Preface

This document is intended for BriteTest user and contributors who need a reference for the BriteTest Runner framework and API.

For a list of other BriteTest documents and the repository layout, see the Documentation Guide (`Documentation_Guide.md`).

For a glossary of terms, see the Glossary Reference (`Glossary_Reference.md`).

Document Version History

Document	Runner	Test	Date	Comment	Author/Editor
1.0	1.0.0	1.0.0	2026-06-11	Initial version.	Paul Sinclair

- The **Document** column records the document's version with the format `M.u` (Major, update).
- The **Runner** column records the Runner API version current at the time this document version was published and is defined by its `RA_RUNNER_VERSION` macro.
- The **Test** column records the Test API version current at the time this document version was published and is defined by its `RA_TEST_VERSION` macro.
- Both Runner and Test use the version format "`M.m.p`" (Major, minor, patch).
- `M` is the same for the Document, Runner, and Test versions.

The document's update version tracks released updates to this document and does not correspond to a minor or patch version. `u` increments when document changes are published in a release without a change to `M`, and it resets to 0 when `M` is incremented.

Table of Contents

Introduction	1
Types	2
ra_result_t	2
ra_state_t	2
Enums	3
ra_exit_code_t	3
ra_return_code_t	3
Macros for Limits	5
Macros for the Orchestrator Function	6
RA_DECLARE_ORCHESTRATOR	6
RA_INIT_ORCHESTRATOR	6
RA_PARSE_ARGS	6
RA_OPEN_REPORT	7
RA_WRITE_RESULT	7
RA_CLOSE_REPORT	7
RA_EXIT	7
6. Macros for a Test Group Function	8
6.1. RA_DECLARE_GROUP	8
6.2. RA_INIT_GROUP	8
6.3. RA_RETURN	8
7. Macros to Execute a Test Group or a Test	9
7.1. RA_GROUP	9
7.2. RA_TEST	9
8. Macros for Concurrent Blocks	10
8.1. RA_BEGIN_CONCURRENT	10
8.2. RA_END_CONCURRENT	10
9. Macros for Versioning	11
9.1. RA_RUNNER_VERSION	11
9.2. RA_VERSION_MAJOR	11
9.3. RA_VERSION_MINOR	11
9.4. RA_VERSION_PATCH	11

9.5. RA_VERSION_NUM	11
9.6. RA_VERSION_HEX	12
9.7. RA_VERSION_CMP	12
10. Macros for Customization	13
10.1. RA_PRINT_ERR_HELP	13
11. Functions for Customization	14
11.1. ra_funcname	14
11.2. ra_print_note	14
12. Test Command Line	15
13. Output and Golden Files	16
13.1. Output Files	17
13.2. Golden Files	18
13.3. Output/Golden Rationale	18

1. Introduction

TODO: add introduction, common rules.

2. Types

2.1. ra_result_t

Type for result counters.

Note: A test group function or test with a fault sets its result with the fault count set to `SIZE_MAX` to indicate a function-level fault.

See also: - `ra_currentresult(void)` in Customization Helper Functions. - `RA_GROUP(...)` notes on fault capture semantics and how function-level faults are represented.

```
typedef struct
{
    size_t pass;
    size_t fail;
    size_t fault;
    size_t injected_fail;
    size_t injected_fault;
} ra_result_t;
```

2.2 ra_state_t

Type for maintaining the state of the orchestrator (main) or a test function.

```
typedef struct
{
    size_t id;
    char *funcname;
    size_t current_level;
    size_t groupid;
    char *groupname;
    int isolation; // 0 none, 1 thread, 2 process.
    size_t category_id;
    size_t num_results_merged;
    size_t pass;
    size_t fail;
    size_t fault;
    size_t injected_fail;
    size_t injected_fault;
    size_t total_pass;
    size_t total_fail;
    size_t total_fault;
    size_t total_injected_fail;
    size_t total_injected_fault;
    ra_state_t parent;
    ra_state_t prev;
    ra_state_t next;
} ra_state_t;
```

3. Enums

3.1. ra_exit_code_t

Exit codes are grouped into classes: - Normal exit (*if* not a test run request): RA_EXIT[_*] (0-99). - Test outcome (*if* a test run request): RA_TEST[_]* (0-99). - Fatal usage (of framework): RA_FATAL_USAGE[_*] (100-199). - Fatal internal (in framework): RA_FATAL_INTERNAL[_*] (200-299). - Fatal system (call failed): RA_FATAL_SYSTEM[_*] (300-399).

Fatal codes indicate that the runner could not complete normal or test execution.

RA_FATAL_USAGE, RA_FATAL_INTERNAL, and RA_FATAL_SYSTEM are general codes for when a more specific code does not apply for the class.

typedef enum

```
{
    // Normal Exit (*if* not a test run request): 0-99.
    RA_EXIT_OK = 0,

    // Test Outcome (*if* a test run request): 0-99.
    RA_TEST_PASS = 0,
    RA_TEST_FAIL = 1,
    RA_TEST_FAULT = 2,
    RA_TEST_FAIL_FAULT = 3,

    // Fatal Usage (of framework): 100-199.
    RA_FATAL_USAGE = 100,
    RA_FATAL_USAGE_INVALID_ARG = 101,
    RA_FATAL_USAGE_INVALID_STATE = 102,

    // Fatal Internal (in framework): 200-299,
    RA_FATAL_INTERNAL = 200,
    RA_FATAL_INTERNAL_ASSERT = 201,
    RA_FATAL_INTERNAL_INVARIANT = 202,

    // Fatal System (call failed) 300-399.
    RA_FATAL_SYSTEM = 300,
    RA_FATAL_SYSTEM_OPEN = 301,
    RA_FATAL_SYSTEM_READ = 302,
    RA_FATAL_SYSTEM_WRITE = 303,
    RA_FATAL_SYSTEM_FORK = 304,
    RA_FATAL_SYSTEM_THREAD = 305
} ra_exit_code_t;
```

3.2. ra_return_code_t

Return codes are for functions that return an integer (e.g., `int`) and are grouped into classes: - Success - Compare - Boolean - RA_INVALID[_*] invalid usage codes (invalid arguments). - RA_SYSTEM[_*] failed system codes (OS/runtime/resource failures).

RA_INVALID and RA_SYSTEM) are general codes for when a more specific code does not apply for the class.

```
typedef enum
{
    // Success
    RA_OK = 0,

    // Compare
    RA_LESS = -1,
    RA_EQUAL = 0,
    RA_GREATER = 1,

    // Boolean
    RA_FALSE = 0,
    RA_TRUE = 1,

    // -100 to -199: Invalid Usage.
    RA_INVALID = -100,
    RA_INVALID_ARG = -101,
    RA_INVALID_ARG_VERSION = -102,
    RA_INVALID_ARG_TOO_LONG = -103,

    // -300 to -399: Failed system call.
    RA_SYSTEM = -300,
    RA_SYSTEM_OPEN = -301,
    RA_SYSTEM_READ = -302,
    RA_SYSTEM_WRITE = -303,
    RA_SYSTEM_FORK = -304,
    RA_SYSTEM_THREAD = -305
} ra_return_code_t;
```


4. Macros for Limits

Maximum values for path length, filename length, and guard levels.

```
#define RA_MAX_PATH_LEN ((size_t)4096) #define RA_MAX_FILENAME_LEN  
((size_t)255) #define RA_MAX_LEVEL ((size_t)32)
```

Note: The limit of 32 levels is unlikely to be exceeded if there are 2 or more `RA_GROUP` or `RA_TEST` macros at each level. It is expected that a level will generally have 2 or more per level.

5. Macros for the Orchestrator Function

Macros used to define or declare the Orchestrator (`main`) function

5.1. `RA_DECLARE_ORCHESTRATOR(funcname) [;]`

A semicolon is not allowed if the macro is followed by its definition `{...}` of the orchestrator function; otherwise, it is required and indicates this is a declaration and a forward-reference to the orchestrator function.

funcname: - Token specifying `main`.

Fatal exit: - `FATAL_USAGE_DECLARE_ORCHESTRATOR` - `FATAL_INTERNAL` - `FATAL_SYSTEM`

5.2. `RA_INIT_ORCHESTRATOR(funcname, id, project, size_t maxparallel);`

funcname: - Token specifying `main`.

id: - A pointer to a string specifying only alphanumeric characters which is used to identify the orchestrator function. - Default is `"o"` *if* `id` is `NULL` pointer or its string is empty. - A short `id` (not exceeding 3 characters) is recommended. - The `id` must be unique for the orchestrator and test group functions; a violation causes the test runner to terminate.

project: - A token identifying the project. - The token is used to generate a default report title if one is not set by the `RA_PARSE_ARGS(...)` macro.

maxparallel: Maximum number of `RA_GROUP` and `RA_TEST` macros that are allowed to execute in parallel.

Fatal exit: - `FATAL_USAGE_INIT_ORCHESTRATOR` - `FATAL_INTERNAL` - `FATAL_SYSTEM`

5.3. `RA_PARSE_ARGS(size_t maxargs, char *customflags, char *defaultreportfilename)`

maxargs: - The maximum number arguments in the command line. - The value must 2 or greater. - The first 2 arguments and BriteTest flags are parsed by the macro. - Additional arguments must be parsed by customization code.

customflags: - A string of custom flags (e.g., `"-l-file-Q"`). - The macro causes the test runner to terminate if a non-BriteTest flag is not in the string. - The actual parsing of these must be customization code.

defaultreportfilename: - A string defining a default report file name without an extension. The extension is `.md` since the report uses Markdown Document formatting. - The maximum length including a null terminator character is `MAX_FILENAME_LEN` (129),

Termination Exit Codes: - `RA_ARG_ERROR` - `RA_FLAG_ERROR`

See “Test Command Line” for details on command-line argument and flags.

5.4. RA_OPEN_REPORT(char *title);

title: - A string defining the report title. - If **title** is NULL or empty, a generated default report title “ Test Report” is used. - The maximum length including a null terminator character is **MAX_TITLE_LEN** (129),

Termination Exit Codes: - **RA_OPEN_ERROR**

5.5. RA_WRITE_RESULT(gtm, char *category);

gtm: - A **RA_GROUP(...)** or **RA_TEST(,,)** macro.

category: - A pointer to a string with the name or description of the test category. - The maximum length including a null terminator character is **MAX_CATEOGRY_LEN** (129).

Termination Exit Codes: **RA_WRITE_ERROR**.

5.6. RA_CLOSE_REPORT(char *notes);

notes: - A string of note lines to append to the test report. - Each note line must end with '**\n**' (newline). - If **notes** is NULL or empty, there are no notes to append. - The maximum length including a null terminator character is **MAX_NOTE_LEN** (10001).

Termination Exit Codes: - **RA_CLOSE_ERROR**

The macro writes the totals, pre-defined explanatory notes, **notes**, notes from the temporary notes file, and final summary line to the test report file, and then closes the test report.

5.7. RA_EXIT;

Exit codes: - **RA_PASS** (0) - **RA_FAIL** (1) - **RA_FAULT** (2) - **RA_FAIL_FAULT** (3)

Termination Exit Codes: - **RA_EXIT_ERROR**

6. Macros for a Test Group Function

Macros used to define or declare a test group function.

6.1. RA_DECLARE_GROUP(funcname)

funcname: - Token specifying a function name other than `main`.

A semicolon is not allowed if the macro is followed by its definition `{...}` of the test group function; otherwise, it is required and indicates this is a declaration and a forward-reference to the test group function.

Termination Exit Codes: - `RA_DECLARE_GROUP_ERROR`

6.2. RA_INIT_GROUP(funcname, id, maxparallel)

funcname: - The same token as the specified token for `funcname` in the preceding `RA_DECLARE_GROUP` macro defining the containing test group function.

id: - A pointer to a string specifying only alphanumeric characters which is used to identify the test group function. - Default is `"funcname"` if `id` is NULL pointer or its string is empty.
- A short id (not exceeding 3 characters) is recommended. - `id` must be unique for the orchestrator and test group functions; a violation causes the test runner to terminate.

maxparallel: - Maximum number of `RA_GROUP` and `RA_TEST` macros that are allowed to execute in parallel.

Termination Exit Codes: - `RA_INIT_GROUP_ERROR`

6.3. RA_RETURN

Termination Exit Codes: - `RA_RETURN_ERROR`

7. Macros to Execute a Test Group or a Test

- `RA_GROUP(funcname, id, [include], [isolation])[;]`
- `RA_TEST(expression, id, [include], [isolation])[;]`

A semicolon is not allowed if the macro is used as an argument to the `RA_WRITE_RESULT` macro; otherwise, it is required.

id: - A pointer to a string specifying only alphanumeric characters for the test group or test. - The value must be unique within the containing orchestrator or test group function - A short id (not exceeding 3 characters) is recommended or use the default. - If `id` is a NULL pointer or its string is empty, default is `n`, where `n` is 1 for the first `RA_GROUP` or `RA_TEST` macro where `id` is NULL or empty, and incremented by 1 for each subsequent `RA_GROUP` and `RA_TEST` macro where `id` is a NULL pointer or its string is empty. - See the `RA_ID` macro for obtaining the `id` for the next generated id.

include: - A single character token or omit (defaults to 1): - 0 — Never execute. This is useful to disable a test (e.g., failing or faulting test for which the fix has been deferred). - 1 — Always execute (e.g., smoke tests). - 2-9 — Execute only when the `-In` flag is specified in the test command line and `n >= include`. - I — Execute only when the `-I` flag is specified in the test command line. This is useful for injecting a fail/fault for verifying behavior and report output if fails/faults were to occur. See also `RA_FAIL` and `RA_FAULT(type)` for simulating a fail or fault, respectively.

See “Test Command Line” for details on command line flags.

isolation: - Single character token or omit (defaults to 0): - 0 — Same thread. - 1 — Separate thread. - 2 — Separate process.

See “Isolation” in the Runner Guide.

7.1. `RA_GROUP(funcname, id, [include], [isolation])[;]`

Termination Exit Codes: - `RA_GROUP_ERROR`

7.2. `RA_TEST(expression, id, [include], [isolation])[;]`

Termination Exit Codes: - `RA_TEST_ERROR`

8. Macros for Concurrent Blocks

8.1. `RA_BEGIN_CONCURRENT(blockname)`

blockname: - Token specifying the name of the block. - Token must be the same as for the subsequent matching `RA_END_CONCURRENT(blockname)`.

Termination Exit Codes: - `RA_BEGIN_GROUP_ERROR`

8.2. `RA_END_CONCURRENT(blockname);`

blockname: - Token specifying the name of the block. - Token must be the same as for the preceding matching `RA_BEGIN_CONCURRENT(blockname)`.

Termination Exit Codes: - `RA_END_GROUP_ERROR`

9. Macros for Versioning

9.1. RA_RUNNER_VERSION

Value: - BriteTest Runner's version as a literal string of type `char[n]`, where `n` is between 5 and 9 (including the terminating null character). - Format: `M.m.p`, where `M`, `m`, and `p` are one or two digits. - `M` is the major version, `m` is the minor version, and `p` is the patch version.

The major version is incremented for major additions, removal of deprecated features, or unavoidable incompatible API changes.

The minor version is incremented for backward-compatible additions or deprecating features.

The patch version is incremented for bug fixes or internal improvements.

Examples: - `RA_RUNNER_VERSION` $\rightarrow$ `"1.0.9"` - `RA_RUNNER_VERSION` $\rightarrow$ `"1.3.11"` - `RA_RUNNER_VERSION` $\rightarrow$ `"12.05.18"`

9.2. RA_VERSION_MAJOR(v)

`v`: pointer to a version string.

Value: - The major version in `v` cast to `int`. - Value is `RA_INVALID_VERSION ((int)-2)` if `v` is an invalid version string.

Examples: - `RA_VERSION_MAJOR("5.0.9")` $\rightarrow$ `(int)5` - `RA_VERSION_MAJOR("5.000.9")` $\rightarrow$ `RA_INVALID_VERSION`

9.3. RA_VERSION_MINOR(v)

`v`: pointer to a version string.

Value: - The minor version in `v` cast to `int`. - Value is `RA_INVALID_VERSION ((int)-2)` if `v` is an invalid version string.

Examples: - `RA_VERSION_MINOR("5.00.9")` $\rightarrow$ `(int)0` - `RA_VERSION_MINOR("5.1.001")` $\rightarrow$ `RA_INVALID_VERSION`

9.4. RA_VERSION_PATCH(v)

`v`: pointer to a version string.

Value: - The patch version in `v` cast to `int`. - Value is `RA_INVALID_VERSION ((int)-2)` if `v` is an invalid version string.

Examples: - `RA_VERSION_PATCH("5.0.12")` $\rightarrow$ `(int)12` - `RA_VERSION_PATCH("5.000.9")` $\rightarrow$ `RA_INVALID_VERSION`

9.5. RA_VERSION_NUM(v)

`v`: pointer to a version string.

Value: - Representation of the version `v` cast to `int`. - Value is `RA_INVALID_VERSION ((int)-2)` if `v` is an invalid version string.

Form: MMmmpp for comparisons, e.g., 10000 for version 1.0.0, 10200 for version 1.2.0, or 11212 for version 1.12.12.

Examples: - `RA_VERSION_NUM("1.0.9")` $\rightarrow$ `(int)0x010009` - `RA_VERSION_NUM("2.5.3")` $\rightarrow$ `(int)0x020503`

9.6. `RA_VERSION_HEX(v)`

v: - Pointer to a version string.

Value: - Hex representation of version `v` cast to `int`. - Value is `RA_INVALID_VERSION` `((int)-2)` *if* `v` is an invalid version string.

Hexadecimal form 0xMMmmpp for display/debugging, e.g., 0x010000 for version 1.0.0, 0x010200 for version 1.2.0, or 0x011212 for version 1.12.12.

Examples: - `RA_VERSION_HEX("1.0.9")` $\rightarrow$ `0x010009` - `RA_VERSION_HEX("2.5.3")` $\rightarrow$ `0x020503`

9.7. `RA_VERSION_CMP(v1, v2)`

v1: - Pointer to a version string.

v2: - Pointer to a version string.

Value: - Integer (`int`) result comparing version `v1` to `v2`: - `RA_EQUAL` `((int)0)` — equal - `RA_LESS` `((int)-1)` — `v1` is less than `v2` - `RA_GREATER` `((int)1)` — `v1` is greater than `v2` - `RA_INVALID_VERSION` `((int)-2)` — invalid `v1` or invalid `v2` - Leading zeros in `M`, `m`, and `p` are ignored during comparison.

Examples: - `RA_VERSION_CMP(RA_RUNNER_VERSION, "1.10.0")` $\rightarrow$ `RA_GREATER` (*if* `RA_RUNNER_VERSION` is `"1.10.6"`) - `RA_VERSION_CMP(RA_RUNNER_VERSION, "1.10.0")` $\rightarrow$ `RA_LESS` (*if* `RA_RUNNER_VERSION` is `"1.8.0"`) - `RA_VERSION_CMP(RA_RUNNER_VERSION, "1.10.0")` $\rightarrow$ `RA_EQUAL` (*if* `RA_RUNNER_VERSION` is `"1.10.0"`) - `RA_VERSION_CMP("1.10.0x", "1.10.0")` $\rightarrow$ `RA_INVALID_VERSION` - `RA_VERSION_CMP("1.10.0", "1.10y.0")` $\rightarrow$ `RA_INVALID_VERSION`

10. Macros for Customization

10.1. `RA_PRINT_ERR_HELP(char *err, char help)`

Print err and help text to stdout. - `err` is prefixed with `ra_err_prefix()`. - Help text is formed using `ra_usage()` and `ra_help()`.

err - Pointer to error string.

help - 0: don't print help text. - non-zero: print help text.

Fatal exit: - `FATAL_USAGE` - `FATAL_INTERNAL` - `FATAL_SYSTEM`

Note: Use `ra_set_err_prefix()` to set the prefix.

Note: Use `ra_set_usage()` and/or `ra_set_help()` to define the help text.

11. Functions for Customization

11.1. int ra_funcname(char *funcname, size_t outlen)

11.2. int ra_print_note(const char *notes)

Opens a temporary file if not already open and writes the notes to the temporary file.

notes: - A string of note lines to write to the temporary file. - Each note line must end with '\n' (newline). - If **notes** is NULL or empty, the temporary file is removed if it exists. - The maximum length including a null terminator character is MAX_NOTE_LEN (10001).

Return: - RA_SUCCESS - RA_NOTES_REMOVED - RA_NOTES_OPEN_ERROR - RA_PRINT_NOTE_ERROR

void ra_current_time(char *current_time, size_t size)

Get the current time as a formatted string.

current_time: - Buffer to store the formatted time string.

size Size of the buffer.

Note: On error, current_time is set to “unknown time”.

Customization: Get and set.

```
char *ra_executable_name(void) void ra_set_executable_name(char *en) char
*ra_defaibt_dirpath(void) void ra_set_defaibt_dirpath(char *dp) char *ra_err_prefix(void)
void ra_set_err_prefix(char *pe) char *ra_args_options(void) void ra_set_args_options(char
*ao) char *ra_usage(void) void ra_set_usage(char *u) char *ra_help(void) void
ra_set_help(char *h)
```

Customization Helper Functions

```
size_t ra_currentlevel(void) ra_resubt_t ra_currentresult(void) ra_total_t
ra_currenttotal(void) size_t ra_maxparallel(size_t level) size_t ra_currentparallel(void)
int ra_isisolated(void) int ra_isthreadisolated(void) int ra_isprocessisolated(void)
size_t ra_groupid(void) char *ra_groupname(void)
```

```
char *ra_project(void) size_t ra_maxargs(void) char *ra_title(void) size_t
ra_categoryid(void) char *ra_category(void) char *ra_funcname(void) char
*ra_notes(void) char *ra_assertexpression(void) char ra_inject(void) char
ra_isolation(void) char ra_orchestrator(void) char ra_testfunction(void) char
ra_assert(void)
```

```
char *ra_dirpath(void) char *ra_filepath(void) char *ra_filename(void)
```

Return: 1 true, 0 false int ra_isfilename(char *name)

Return: 1 true, 0 false, -101 invalid directory path. int ra_isreaddirpath(char *path)
int ra_iswritedirpath(char *path)

Return 1 true, 0 false, -103 invalid file path. int ra_isreadfilepath(char *path) int
ra_iswritefilepath(char *path)

12. Test Command Line

TODO.

13. Output and Golden Files

Output files in `tests/output/` and golden files in `tests/golden/` subdirectories of the repository root provide a directory layout for capturing and validating test output.

13.1. Output Files

A copy of a named output file is captured to `tests/output/` : - If the output file name has the form `.`, the `tests/output/` file is named `-.ext`. - If the output file name has the form `(with no extension)`, the `tests/output/` file is named `-`.

A copy of `stdout` is captured in `tests/output/` output file named `stdout-<uid>` and a copy of `stderr` is captured as an output file named `stderr-<uid>`.

`<uid>` is a unique id string for each captured output file within a test run. It is used to avoid filename collisions when the same output file name appears multiple times (e.g., tests of a command line varying options each generationg `stdout` and `stderrj`).

Temporary files are not captured in `tests/output/`.

A metadata file (in Markdown Document format) for each output file is also written to `tests/output/`: - If the output file name has the form `.`, the `tests/output/` metadata file is named `-.ext.md`. - If the output file name has the form `(with no extension)`, the `tests/output/` file is named `-.md`.

An output file and its metadata file in `tests/output/` may be copied (promoted) to the `tests/golden/` subdirectory of the repository root directory. See the following section.

13.2. Golden Files

A metadata golden file having a name with the form `.ext` applies to all golden files named `-ext` and can be added manually or by customization code added to the test runner.

A metadata golden file having a name with the form `.md` applies to all golden files named `-` with no extension and can be added manually or by customization code added to the test runner.

Golden files (located in the `tests/golden/`) are handled as follows:

- If the corresponding golden file with the same name does not exist,
 - If a metadata golden file `.ext` exists and contains the line `## MATCH`, comparison is skipped and a match is forced. If it contains the line `## MISMATCH`, comparison is skipped and a mismatch is forced. Additional markdown text can follow either marker to document why the outcome is forced for that file or set of files.
 - Otherwise, the output file is automatically copied (promoted) into the `tests/golden` directory and a match forced.
 - The test report notes that the file was promoted.
- If the corresponding golden file exists and contains the line `## MATCH`, comparison is skipped and a match is forced.
- If the corresponding golden file exists and contains the line `## MISMATCH`, comparison is skipped and a mismatch is forced.
- Otherwise, the output file is compared with its existing golden file of the same name in the `tests/golden` directory to determine whether they match.

If an output file does not match its golden file but inspection determines the output is correct, update the golden file with a copy of the output. Alternatively, remove the golden file so that the next run will automatically promote the output.

13.3. Output/Golden Rationale

BriteTest uses a parallel `tests/golden` directory with golden files that keep the exact same filename as their corresponding test output. This design avoids the common problems found in extension-based naming schemes:

- **No filename collisions** Different outputs such as `foo.c` and `foo.h` remain distinct (`foo-<uid>.c` vs. `foo-<uid>.h`) instead of collapsing into a single `foo.golden`.
- **No special-case rules** The golden filename is always identical to the output filename.
- **Preserves file type information** Because the original extension is retained, it is immediately clear whether a golden file contains text, Markdown Document, JSON, HTML, binary data, or something else.
- **Simpler mental model** Developers do not need to remember naming conventions or extension-replacement rules. Golden files simply live in a parallel directory and share the same name as the output they validate.