

GnuCOBOL Sample Programs

For Version 2.2 Final [7Sept2017]

Gary L. Cutler (cutlergl@gmail.com).
For updates Vincent B. Coen (vbcoen@gmail.com).

This manual documents GnuCOBOL 2.2 Final, 7Sept2017 build.

Document Copyright 2009-2014 Gary L. Cutler, FSF (Free Software Foundation).

Updates: Copyright 2014-2017 Vincent B. Coen, Gary L. Cutler & FSF.

Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License [FDL], Version 1.3 or any later version published by the Free Software Foundation; with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts. A copy of the license is included in the section entitled "GNU Free Documentation License".

Table of Contents

1. FileStat-Msgs.....	1
2. COBDUMP	3
3. Colors.....	9
4. DAY-FROM-DATE.....	31
5. GCic.....	35
6. STREAMIO	141
7. GNU Free Documentation License.....	159

1. FileStat-Msgs

The FileStat-Msgs.cpy copybook contains an EVALUATE statement to translate the two-digit file status codes that may be generated by file I/O statements.

The copybook assumes that the file status data item name is "STATUS" and the error message data item is named "MSG". By using the COPY statement's REPLACING clause, however, you may use the data names you wish, as follows:

```
COPY FileStat-Msgs
    REPLACING STATUS BY file-status-data-item-name
                MSG    BY error-message-data-item-name
```

Here's the FileStat-Msgs.cpy copybook:

```
EVALUATE STATUS
    WHEN 00 MOVE 'SUCCESS' TO MSG
    WHEN 02 MOVE 'SUCCESS DUPLICATE' TO MSG
    WHEN 04 MOVE 'SUCCESS INCOMPLETE' TO MSG
    WHEN 05 MOVE 'SUCCESS OPTIONAL' TO MSG
    WHEN 07 MOVE 'SUCCESS NO UNIT' TO MSG
    WHEN 10 MOVE 'END OF FILE' TO MSG
    WHEN 14 MOVE 'OUT OF KEY RANGE' TO MSG
    WHEN 21 MOVE 'KEY INVALID' TO MSG
    WHEN 22 MOVE 'KEY EXISTS' TO MSG
    WHEN 23 MOVE 'KEY NOT EXISTS' TO MSG
    WHEN 30 MOVE 'PERMANENT ERROR' TO MSG
    WHEN 31 MOVE 'INCONSISTENT FILENAME' TO MSG
    WHEN 34 MOVE 'BOUNDARY VIOLATION' TO MSG
    WHEN 35 MOVE 'FILE NOT FOUND' TO MSG
    WHEN 37 MOVE 'PERMISSION DENIED' TO MSG
    WHEN 38 MOVE 'CLOSED WITH LOCK' TO MSG
    WHEN 39 MOVE 'CONFLICT ATTRIBUTE' TO MSG
    WHEN 41 MOVE 'ALREADY OPEN' TO MSG
    WHEN 42 MOVE 'NOT OPEN' TO MSG
    WHEN 43 MOVE 'READ NOT DONE' TO MSG
    WHEN 44 MOVE 'RECORD OVERFLOW' TO MSG
    WHEN 46 MOVE 'READ ERROR' TO MSG
    WHEN 47 MOVE 'INPUT DENIED' TO MSG
    WHEN 48 MOVE 'OUTPUT DENIED' TO MSG
    WHEN 49 MOVE 'I/O DENIED' TO MSG
    WHEN 51 MOVE 'RECORD LOCKED' TO MSG
    WHEN 52 MOVE 'END-OF-PAGE' TO MSG
    WHEN 57 MOVE 'I/O LINAGE' TO MSG
    WHEN 61 MOVE 'FILE SHARING FAILURE' TO MSG
    WHEN 91 MOVE 'FILE NOT AVAILABLE' TO MSG
END-EVALUATE.
```


2. COBDUMP

COBDUMP is a useful little utility subroutine to produce a formatted hexadecimal and character dump of the data area passed to it.

If you follow the GnuCOBOL forums, you've undoubtedly heard about the CBL_OC_DUMP subroutine that was the winning entry in a GnuCOBOL programming contest. It's a great tool for producing data dumps, and it's now included in the official GnuCOBOL distributions.

For now though, I'll keep using my good ol' "COBDUMP" routine. It's been my travelling companion from COBOL job to COBOL job since 1971. Here it is, all tuned up for GnuCOBOL, with new tires and a fresh coat of paint.

In addition to general GnuCOBOL concepts, this program provides a useful demonstration of the following:

- Coding a GnuCOBOL subroutine
- Using "USAGE POINTER" data items
- Using the "ANY LENGTH" data item attribute
- Coding for an "OPTIONAL" subprogram argument
- Using the "NUMBER-OF-CALL-PARAMETERS" special register
- Using the "C\$PRINTABLE" built-in system subroutine

The program source and cross-reference listing, produced using the GnuCOBOL Interactive Compiler front-end (GCic.cbl, one of the sample programs included here), begins on the next page.

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/COBDUMP.cbl

Line Statement

Page: 1

```

=====
1      >>SOURCE FORMAT IS FIXED
2      IDENTIFICATION DIVISION.
3      PROGRAM-ID.    COBDUMP.
4      *>*****
5      *> This is an OpenCOBOL subroutine that will generate a      **
6      *> formatted Hex/Char dump of a storage area. To use this  **
7      *> subroutine, simply CALL it as follows:                    **
8      *>                                                           **
9      *> CALL "COBDUMP" USING <data-item>                          **
10     *> [ <length> ]                                             **
11     *>                                                           **
12     *> If specified, the <length> argument specifies how many   **
13     *> bytes of <data-item> are to be dumped. If absent, all of **
14     *> <data-item> will be dumped (i.e. LENGTH(<data-item>) will **
15     *> be assumed for <length>).                                **
16     *>                                                           **
17     *> >>> Note that the subroutine name MUST be specified in   <<< **
18     *> >>> UPPERCASE                                           <<< **
19     *>                                                           **
20     *> The dump is generated to STDERR, so you may pipe it to a  **
21     *> file when you execute your program using "2> file".      **
22     *>                                                           **
23     *> AUTHOR:          GARY L. CUTLER                          **
24     *>                                                           **
25     *> NOTE:           The author has a sentimental attachment to **
26     *>                 this subroutine - it's been around since 1971 **
27     *>                 and it's been converted to and run on 10 dif- **
28     *>                 ferent operating system/compiler environments **
29     *>                                                           **
30     *> DATE-WRITTEN: October 14, 1971                          **
31     *>                                                           **
32     *>*****
33     *> DATE  CHANGE DESCRIPTION                                **
34     *> ===== **
35     *> GC1071 Initial coding - Univac Dept. of Defense COBOL '68 **
36     *> GC0577 Converted to Univac ASCII COBOL (ACOB) - COBOL '74 **
37     *> GC1182 Converted to Univac UTS4000 COBOL - COBOL '74 w/    **
38     *> SCREEN SECTION enhancements                               **
39     *> GC0883 Converted to Honeywell/Bull COBOL - COBOL '74      **
40     *> GC0983 Converted to IBM VS COBOL - COBOL '74             **
41     *> GC0887 Converted to IBM VS COBOL II - COBOL '85          **
42     *> GC1294 Converted to Micro Focus COBOL V3.0 - COBOL '85 w/ **
43     *> extensions                                               **
44     *> GC0703 Converted to Unisys Universal Compiling System (UCS) **
45     *> COBOL (UCOB) - COBOL '85                                **
46     *> GC1204 Converted to Unisys Object COBOL (OCOB) - COBOL 2002 **
47     *> GC0609 Converted to OpenCOBOL 1.1 - COBOL '85 w/ some COBOL **
48     *> 2002 features                                           **
49     *> GC0410 Enhanced to make 2nd argument (buffer length)    **
=====

```

GCic for OSX Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 1

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/COBDUMP.cbl

Line Statement

Page: 2

```

=====
50      *>          optional                      **
51      *> GC0211 Ported to IBM Enterprise COBOL      **
52      *> GC0612 Updated for OpenCOBOL 2.0          **
53      *>*****
54      ENVIRONMENT DIVISION.
55      CONFIGURATION SECTION.
56      REPOSITORY.
57          FUNCTION ALL INTRINSIC.
58      DATA DIVISION.
59      WORKING-STORAGE SECTION.
60      01  WS-Addr-PTR                      USAGE POINTER.
61      01  WS-Addr-NUM REDEFINES WS-Addr-PTR
62                      USAGE BINARY-LONG.
63
64      01  WS-Addr-SUB                      USAGE BINARY-CHAR.
65
66      01  WS-Addr-Value-NUM                USAGE BINARY-LONG.
67
68      01  WS-Buffer-Byte-CHR.
69          05 WS-Buffer-Byte-NUM            USAGE BINARY-CHAR.
70
71      01  WS-Buffer-Length-NUM             USAGE BINARY-LONG.
72
73      01  WS-Buffer-SUB                    PIC 9(4) COMP-5.
74
75      01  WS-Hex-Digit-TXT VALUE '0123456789ABCDEF'.
76          05 WS-Hex-Digit-CHR              OCCURS 16 TIMES
77                      PIC X(1).
78
79      01  WS-Nibble-SUB                    PIC 9(1) COMP-5.
80
81      01  WS-Nibble-Left-SUB                PIC 9(1) COMP-5.
82
83      01  WS-Nibble-Right-SUB               PIC 9(1) COMP-5.
84
85      01  WS-Output-Detail-TXT.
86          05 WS-OD-Addr-TXT.
87              10 WS-OD-Addr-Hex-CHR        OCCURS 8 TIMES PIC X.
88              05 FILLER                     PIC X(1).
89              05 WS-OD-Relative-Byte-NUM    PIC Z(3)9.
90              05 FILLER                     PIC X(1).
91              05 WS-OD-Hex-TXT               OCCURS 16 TIMES.
92                  10 WS-OD-Hex-1-CHR        PIC X.
93                  10 WS-OD-Hex-2-CHR        PIC X.
94                  10 FILLER                 PIC X.
95          05 WS-OD-ASCII-Data-TXT.
96              10 WS-OD-ASCII-CHR            OCCURS 16 TIMES
97                      PIC X.
98
=====

```

GCic for OSX Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 2

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/COBDUMP.cbl

Line Statement Page: 3

```

=====
 99      01 WS-Output-SUB                                PIC 9(2) COMP-5.
100
101      >>SOURCE FORMAT IS FREE
102      01 WS-Output-Header-1-TXT.
103          05 VALUE '<-Addr-> Byte <----- Hexadecimal '-----> <---
- Char ---->' PIC X(80).
104
105      01 WS-Output-Header-2-TXT.
106          05 VALUE '===== ====='
=====
          PIC X(80).
107      >>SOURCE FORMAT IS FIXED
108
109      LINKAGE SECTION.
110      01 L-Buffer-TXT                                PIC X ANY LENGTH.
111
112      01 L-Buffer-Length-NUM                          USAGE BINARY-LONG.
113
114      PROCEDURE DIVISION USING L-Buffer-TXT,
115                                OPTIONAL L-Buffer-Length-NUM.
116      000-Main SECTION.
117          IF NUMBER-OF-CALL-PARAMETERS = 1
118              MOVE LENGTH(L-Buffer-TXT) TO WS-Buffer-Length-NUM
119          ELSE
120              MOVE L-Buffer-Length-NUM TO WS-Buffer-Length-NUM
121          END-IF
122          MOVE SPACES TO WS-Output-Detail-TXT
123          SET WS-Addr-PTR TO ADDRESS OF L-Buffer-TXT
124          PERFORM 100-Generate-Address
125          MOVE 0 TO WS-Output-SUB
126          DISPLAY WS-Output-Header-1-TXT UPON SYSERR
127          DISPLAY WS-Output-Header-2-TXT UPON SYSERR
128          PERFORM VARYING WS-Buffer-SUB FROM 1 BY 1
129              UNTIL WS-Buffer-SUB > WS-Buffer-Length-NUM
130              ADD 1 TO WS-Output-SUB
131              IF WS-Output-SUB = 1
132                  MOVE WS-Buffer-SUB TO WS-OD-Relative-Byte-NUM
133              END-IF
134              MOVE L-Buffer-TXT (WS-Buffer-SUB : 1)
135                  TO WS-OD-ASCII-CHR (WS-Output-SUB)
136                  WS-Buffer-Byte-CHR
137              DIVIDE WS-Buffer-Byte-NUM BY 16
138                  GIVING WS-Nibble-Left-SUB
139                  REMAINDER WS-Nibble-Right-SUB
140              ADD 1 TO WS-Nibble-Left-SUB
141                  WS-Nibble-Right-SUB
142              MOVE WS-Hex-Digit-CHR (WS-Nibble-Left-SUB)
143                  TO WS-OD-Hex-1-CHR (WS-Output-SUB)
144              MOVE WS-Hex-Digit-CHR (WS-Nibble-Right-SUB)
145                  TO WS-OD-Hex-2-CHR (WS-Output-SUB)
=====

```

GCic for OSX Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 3

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/COBDUMP.cbl

Line Statement Page: 4

```

=====
146             IF WS-Output-SUB = 16
147                 CALL "C$PRINTABLE" USING WS-OD-ASCII-Data-TXT
148                 DISPLAY WS-Output-Detail-TXT UPON SYSERR
149                 MOVE SPACES TO WS-Output-Detail-TXT
150                 MOVE 0 TO WS-Output-SUB
151                 SET WS-Addr-PTR UP BY 16
152                 PERFORM 100-Generate-Address
153             END-IF
154         END-PERFORM
155     IF WS-Output-SUB > 0
156         CALL "C$PRINTABLE" USING WS-OD-ASCII-Data-TXT
157         DISPLAY WS-Output-Detail-TXT UPON SYSERR
158     END-IF
159     EXIT PROGRAM
160     .
161 100-Generate-Address SECTION.
162     MOVE 8 TO WS-Addr-SUB
163     MOVE WS-Addr-NUM TO WS-Addr-Value-NUM
164     MOVE ALL '0' TO WS-OD-Addr-TXT
165     PERFORM WITH TEST BEFORE UNTIL WS-Addr-Value-NUM = 0
166         DIVIDE WS-Addr-Value-NUM BY 16
167             GIVING WS-Addr-Value-NUM
168             REMAINDER WS-Nibble-SUB
169     ADD 1 TO WS-Nibble-SUB
170     MOVE WS-Hex-Digit-CHR (WS-Nibble-SUB)
171         TO WS-OD-Addr-Hex-CHR (WS-Addr-SUB)
172     SUBTRACT 1 FROM WS-Addr-SUB
173     END-PERFORM
174     .
=====

```

GCic for OSX Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 4

GNU COBOL 2.1 23NOV2013 Cross-Reference Listing					2014/03/27		
C:/Users/tda010/Documents/Programs/Samples/COBDUMP.cbl					Page: 5		
PROGRAM-ID	Identifier/Register/Function	Defn	Where Defined	References			
COBDUMP	000-Main	116	PROCEDURE				
COBDUMP	100-Generate-Address	161	PROCEDURE	124	152		
COBDUMP	L-Buffer-Length-NUM	112	LINKAGE	115	120		
COBDUMP	L-Buffer-TXT	110	LINKAGE	114	118	123	
				134			
COBDUMP	NUMBER-OF-CALL-PARAMETERS		PROCEDURE	117			
COBDUMP	WS-Addr-NUM	61	WORKING-STORAGE	163			
COBDUMP	WS-Addr-PTR	60	WORKING-STORAGE	61	123*	151*	
COBDUMP	WS-Addr-SUB	64	WORKING-STORAGE	162*	171	172	
COBDUMP	WS-Addr-Value-NUM	66	WORKING-STORAGE	163*	165	166	
				167*			
COBDUMP	WS-Buffer-Byte-CHR	68	WORKING-STORAGE	136			
COBDUMP	WS-Buffer-Byte-NUM	69	WORKING-STORAGE	137			
COBDUMP	WS-Buffer-Length-NUM	71	WORKING-STORAGE	118*	120*	129	
COBDUMP	WS-Buffer-SUB	73	WORKING-STORAGE	128*	129	132	
				134			
COBDUMP	WS-Hex-Digit-CHR	76	WORKING-STORAGE	142	144	170	
COBDUMP	WS-Hex-Digit-TXT	75	WORKING-STORAGE				
COBDUMP	WS-Nibble-Left-SUB	81	WORKING-STORAGE	138*	140*	142	
COBDUMP	WS-Nibble-Right-SUB	83	WORKING-STORAGE	139*	141*	144	
COBDUMP	WS-Nibble-SUB	79	WORKING-STORAGE	168*	169*	170	
COBDUMP	WS-OD-Addr-Hex-CHR	87	WORKING-STORAGE	171*			
COBDUMP	WS-OD-Addr-TXT	86	WORKING-STORAGE	164*			
COBDUMP	WS-OD-ASCII-CHR	96	WORKING-STORAGE	135*			
COBDUMP	WS-OD-ASCII-Data-TXT	95	WORKING-STORAGE	147C	156C		
COBDUMP	WS-OD-Hex-1-CHR	92	WORKING-STORAGE	143*			
COBDUMP	WS-OD-Hex-2-CHR	93	WORKING-STORAGE	145*			
COBDUMP	WS-OD-Hex-TXT	91	WORKING-STORAGE				
COBDUMP	WS-OD-Relative-Byte-NUM	89	WORKING-STORAGE	132*			
COBDUMP	WS-Output-Detail-TXT	85	WORKING-STORAGE	122*	148	149*	
				157			
COBDUMP	WS-Output-Header-1-TXT	102	WORKING-STORAGE	126			
COBDUMP	WS-Output-Header-2-TXT	105	WORKING-STORAGE	127			
COBDUMP	WS-Output-SUB	99	WORKING-STORAGE	125*	130*	131	
				135	143	145	
				146	150*	155	

3. Colors

Colors is a handy little GnuCOBOL utility program that will produce a screen showing all possible combinations of:

- FOREGROUND-COLOR
- BACKGROUND-COLOR
- BLINKING (or absence of BLINKING)
- HIGHLIGHT, LOWLIGHT or absence of either (i.e. "Normal")
- REVERSE-VIDEO

Here is a sample of the screen generated by this program:



The program source and cross-reference listing, produced using the GnuCOBOL Interactive Compiler front-end (GCic.cbl, one of the sample programs included here), begins on the next page.

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/colors.cbl

Line Statement Page: 1

```

=====
1          >>SOURCE FREE
2 IDENTIFICATION DIVISION.
3 PROGRAM-ID. colors.
4 DATA DIVISION.
5 SCREEN SECTION.
6 01 S-COLORTST-SCR BACKGROUND-COLOR 0 FOREGROUND-COLOR 7 BLANK SCREEN.
7 05 LINE 01.
8 10 COL 1 VALUE ' LOWLIGHT  ----- HIGHLIGHT  LOWLIGHT  ----- HIGHLIGHT'.
9 05 LINE + 1.
10 10 COL 1 VALUE ' -----  -----  -----  -----  -----  -----'.
11 05 LINE + 1.
12 10 COL 1 VALUE ' -----  -----  -----  REVERSE  REVERSE  REVERSE'.
13 05 LINE + 1.
14 10 COL 1 VALUE ' 01234567 01234567 01234567 01234567 01234567 01234567'.
15 05 LINE + 1.
16 10 COL 1 VALUE '0          0          0          0          0          0          '.
17 05 LINE + 1.
18 10 COL 1 VALUE '1          1          1          1          1          1          '.
19 05 LINE + 1.
20 10 COL 1 VALUE '2          2          2          2          2          2          '.
21 05 LINE + 1.
22 10 COL 1 VALUE '3      1      3      2      3      3      3      4      3      5      3      6      '.
23 05 LINE + 1.
24 10 COL 1 VALUE '4          4          4          4          4          4          '.
25 05 LINE + 1.
26 10 COL 1 VALUE '5          5          5          5          5          5          '.
27 05 LINE + 1.
28 10 COL 1 VALUE '6          6          6          6          6          6          '.
29 05 LINE + 1.
30 10 COL 1 VALUE '7          7          7          7          7          7          '.
31 05 LINE + 1.
32 10 COL 1 VALUE ' LOWLIGHT  ----- HIGHLIGHT  LOWLIGHT  ----- HIGHLIGHT'.
33 05 LINE + 1.
34 10 COL 1 VALUE '          BLINK      BLINK      BLINK      BLINK      BLINK      BLINK'.
35 05 LINE + 1.
36 10 COL 1 VALUE ' -----  -----  -----  REVERSE  REVERSE  REVERSE'.
37 05 LINE + 1.
38 10 COL 1 VALUE ' 01234567 01234567 01234567 01234567 01234567 01234567'.
39 05 LINE + 1.
40 10 COL 1 VALUE '0          0          0          0          0          0          '.
41 05 LINE + 1.
42 10 COL 1 VALUE '1          1          1          1          1          1          '.
43 05 LINE + 1.
44 10 COL 1 VALUE '2          2          2          2          2          2          '.
45 05 LINE + 1.
46 10 COL 1 VALUE '3      7      3      8      3      9      3      10      3      11      3      12      '.
47 05 LINE + 1.
48 10 COL 1 VALUE '4          4          4          4          4          4          '.
49 05 LINE + 1.
=====

```

GCic for OSX Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 1

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/colors.cbl

Line Statement

Page: 2

```

=====
50 10 COL 1 VALUE '5          5          5          5          5          5          '
51 05 LINE + 1.
52 10 COL 1 VALUE '6          6          6          6          6          6          '
53 05 LINE + 1.
54 10 COL 1 VALUE '7          7          7          7          7          7          '
55 *> #1
56 05 LINE 05.
57 10 COL 2  BACKGROUND-COLOR 0 FOREGROUND-COLOR 0 LOWLIGHT VALUE 'X'.
58 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 1 LOWLIGHT VALUE 'X'.
59 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 2 LOWLIGHT VALUE 'X'.
60 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 3 LOWLIGHT VALUE 'X'.
61 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 4 LOWLIGHT VALUE 'X'.
62 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 5 LOWLIGHT VALUE 'X'.
63 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 6 LOWLIGHT VALUE 'X'.
64 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 7 LOWLIGHT VALUE 'X'.
65 05 LINE + 1.
66 10 COL 2  BACKGROUND-COLOR 1 FOREGROUND-COLOR 0 LOWLIGHT VALUE 'X'.
67 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 1 LOWLIGHT VALUE 'X'.
68 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 2 LOWLIGHT VALUE 'X'.
69 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 3 LOWLIGHT VALUE 'X'.
70 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 4 LOWLIGHT VALUE 'X'.
71 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 5 LOWLIGHT VALUE 'X'.
72 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 6 LOWLIGHT VALUE 'X'.
73 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 7 LOWLIGHT VALUE 'X'.
74 05 LINE + 1.
75 10 COL 2  BACKGROUND-COLOR 2 FOREGROUND-COLOR 0 LOWLIGHT VALUE 'X'.
76 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 1 LOWLIGHT VALUE 'X'.
77 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 2 LOWLIGHT VALUE 'X'.
78 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 3 LOWLIGHT VALUE 'X'.
79 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 4 LOWLIGHT VALUE 'X'.
80 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 5 LOWLIGHT VALUE 'X'.
81 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 6 LOWLIGHT VALUE 'X'.
82 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 7 LOWLIGHT VALUE 'X'.
83 05 LINE + 1.
84 10 COL 2  BACKGROUND-COLOR 3 FOREGROUND-COLOR 0 LOWLIGHT VALUE 'X'.
85 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 1 LOWLIGHT VALUE 'X'.
86 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 2 LOWLIGHT VALUE 'X'.
87 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 3 LOWLIGHT VALUE 'X'.
88 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 4 LOWLIGHT VALUE 'X'.
89 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 5 LOWLIGHT VALUE 'X'.
90 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 6 LOWLIGHT VALUE 'X'.
91 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 7 LOWLIGHT VALUE 'X'.
92 05 LINE + 1.
93 10 COL 2  BACKGROUND-COLOR 4 FOREGROUND-COLOR 0 LOWLIGHT VALUE 'X'.
94 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 1 LOWLIGHT VALUE 'X'.
95 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 2 LOWLIGHT VALUE 'X'.
96 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 3 LOWLIGHT VALUE 'X'.
97 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 4 LOWLIGHT VALUE 'X'.
98 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 5 LOWLIGHT VALUE 'X'.
=====

```

GCic for OSX Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 2

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/colors.cbl

Line Statement

Page: 3

```

=====
  99 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 6 LOWLIGHT VALUE 'X'.
 100 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 7 LOWLIGHT VALUE 'X'.
 101 05 LINE + 1.
 102 10 COL 2 BACKGROUND-COLOR 5 FOREGROUND-COLOR 0 LOWLIGHT VALUE 'X'.
 103 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 1 LOWLIGHT VALUE 'X'.
 104 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 2 LOWLIGHT VALUE 'X'.
 105 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 3 LOWLIGHT VALUE 'X'.
 106 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 4 LOWLIGHT VALUE 'X'.
 107 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 5 LOWLIGHT VALUE 'X'.
 108 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 6 LOWLIGHT VALUE 'X'.
 109 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 7 LOWLIGHT VALUE 'X'.
 110 05 LINE + 1.
 111 10 COL 2 BACKGROUND-COLOR 6 FOREGROUND-COLOR 0 LOWLIGHT VALUE 'X'.
 112 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 1 LOWLIGHT VALUE 'X'.
 113 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 2 LOWLIGHT VALUE 'X'.
 114 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 3 LOWLIGHT VALUE 'X'.
 115 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 4 LOWLIGHT VALUE 'X'.
 116 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 5 LOWLIGHT VALUE 'X'.
 117 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 6 LOWLIGHT VALUE 'X'.
 118 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 7 LOWLIGHT VALUE 'X'.
 119 05 LINE + 1.
 120 10 COL 2 BACKGROUND-COLOR 7 FOREGROUND-COLOR 0 LOWLIGHT VALUE 'X'.
 121 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 1 LOWLIGHT VALUE 'X'.
 122 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 2 LOWLIGHT VALUE 'X'.
 123 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 3 LOWLIGHT VALUE 'X'.
 124 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 4 LOWLIGHT VALUE 'X'.
 125 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 5 LOWLIGHT VALUE 'X'.
 126 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 6 LOWLIGHT VALUE 'X'.
 127 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 7 LOWLIGHT VALUE 'X'.
 128 *> #2
 129 05 LINE 05.
 130 10 COL 12 BACKGROUND-COLOR 0 FOREGROUND-COLOR 0 VALUE 'X'.
 131 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 1 VALUE 'X'.
 132 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 2 VALUE 'X'.
 133 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 3 VALUE 'X'.
 134 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 4 VALUE 'X'.
 135 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 5 VALUE 'X'.
 136 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 6 VALUE 'X'.
 137 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 7 VALUE 'X'.
 138 05 LINE + 1.
 139 10 COL 12 BACKGROUND-COLOR 1 FOREGROUND-COLOR 0 VALUE 'X'.
 140 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 1 VALUE 'X'.
 141 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 2 VALUE 'X'.
 142 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 3 VALUE 'X'.
 143 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 4 VALUE 'X'.
 144 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 5 VALUE 'X'.
 145 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 6 VALUE 'X'.
 146 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 7 VALUE 'X'.
 147 05 LINE + 1.
=====

```

GCic for OSX Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 3

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/colors.cbl

Line Statement Page: 4

```

=====
148 10 COL 12 BACKGROUND-COLOR 2 FOREGROUND-COLOR 0 VALUE 'X'.
149 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 1 VALUE 'X'.
150 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 2 VALUE 'X'.
151 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 3 VALUE 'X'.
152 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 4 VALUE 'X'.
153 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 5 VALUE 'X'.
154 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 6 VALUE 'X'.
155 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 7 VALUE 'X'.
156 05 LINE + 1.
157 10 COL 12 BACKGROUND-COLOR 3 FOREGROUND-COLOR 0 VALUE 'X'.
158 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 1 VALUE 'X'.
159 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 2 VALUE 'X'.
160 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 3 VALUE 'X'.
161 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 4 VALUE 'X'.
162 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 5 VALUE 'X'.
163 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 6 VALUE 'X'.
164 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 7 VALUE 'X'.
165 05 LINE + 1.
166 10 COL 12 BACKGROUND-COLOR 4 FOREGROUND-COLOR 0 VALUE 'X'.
167 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 1 VALUE 'X'.
168 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 2 VALUE 'X'.
169 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 3 VALUE 'X'.
170 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 4 VALUE 'X'.
171 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 5 VALUE 'X'.
172 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 6 VALUE 'X'.
173 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 7 VALUE 'X'.
174 05 LINE + 1.
175 10 COL 12 BACKGROUND-COLOR 5 FOREGROUND-COLOR 0 VALUE 'X'.
176 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 1 VALUE 'X'.
177 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 2 VALUE 'X'.
178 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 3 VALUE 'X'.
179 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 4 VALUE 'X'.
180 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 5 VALUE 'X'.
181 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 6 VALUE 'X'.
182 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 7 VALUE 'X'.
183 05 LINE + 1.
184 10 COL 12 BACKGROUND-COLOR 6 FOREGROUND-COLOR 0 VALUE 'X'.
185 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 1 VALUE 'X'.
186 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 2 VALUE 'X'.
187 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 3 VALUE 'X'.
188 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 4 VALUE 'X'.
189 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 5 VALUE 'X'.
190 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 6 VALUE 'X'.
191 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 7 VALUE 'X'.
192 05 LINE + 1.
193 10 COL 12 BACKGROUND-COLOR 7 FOREGROUND-COLOR 0 VALUE 'X'.
194 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 1 VALUE 'X'.
195 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 2 VALUE 'X'.
196 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 3 VALUE 'X'.
=====

```

GCic for OSX Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 4

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/colors.cbl

Line Statement

Page: 5

```

=====
197 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 4 VALUE 'X'.
198 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 5 VALUE 'X'.
199 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 6 VALUE 'X'.
200 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 7 VALUE 'X'.
201 *> #3
202 05 LINE 05.
203 10 COL 22 BACKGROUND-COLOR 0 FOREGROUND-COLOR 0 HIGHLIGHT VALUE 'X'.
204 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 1 HIGHLIGHT VALUE 'X'.
205 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 2 HIGHLIGHT VALUE 'X'.
206 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 3 HIGHLIGHT VALUE 'X'.
207 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 4 HIGHLIGHT VALUE 'X'.
208 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 5 HIGHLIGHT VALUE 'X'.
209 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 6 HIGHLIGHT VALUE 'X'.
210 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 7 HIGHLIGHT VALUE 'X'.
211 05 LINE + 1.
212 10 COL 22 BACKGROUND-COLOR 1 FOREGROUND-COLOR 0 HIGHLIGHT VALUE 'X'.
213 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 1 HIGHLIGHT VALUE 'X'.
214 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 2 HIGHLIGHT VALUE 'X'.
215 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 3 HIGHLIGHT VALUE 'X'.
216 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 4 HIGHLIGHT VALUE 'X'.
217 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 5 HIGHLIGHT VALUE 'X'.
218 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 6 HIGHLIGHT VALUE 'X'.
219 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 7 HIGHLIGHT VALUE 'X'.
220 05 LINE + 1.
221 10 COL 22 BACKGROUND-COLOR 2 FOREGROUND-COLOR 0 HIGHLIGHT VALUE 'X'.
222 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 1 HIGHLIGHT VALUE 'X'.
223 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 2 HIGHLIGHT VALUE 'X'.
224 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 3 HIGHLIGHT VALUE 'X'.
225 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 4 HIGHLIGHT VALUE 'X'.
226 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 5 HIGHLIGHT VALUE 'X'.
227 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 6 HIGHLIGHT VALUE 'X'.
228 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 7 HIGHLIGHT VALUE 'X'.
229 05 LINE + 1.
230 10 COL 22 BACKGROUND-COLOR 3 FOREGROUND-COLOR 0 HIGHLIGHT VALUE 'X'.
231 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 1 HIGHLIGHT VALUE 'X'.
232 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 2 HIGHLIGHT VALUE 'X'.
233 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 3 HIGHLIGHT VALUE 'X'.
234 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 4 HIGHLIGHT VALUE 'X'.
235 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 5 HIGHLIGHT VALUE 'X'.
236 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 6 HIGHLIGHT VALUE 'X'.
237 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 7 HIGHLIGHT VALUE 'X'.
238 05 LINE + 1.
239 10 COL 22 BACKGROUND-COLOR 4 FOREGROUND-COLOR 0 HIGHLIGHT VALUE 'X'.
240 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 1 HIGHLIGHT VALUE 'X'.
241 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 2 HIGHLIGHT VALUE 'X'.
242 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 3 HIGHLIGHT VALUE 'X'.
243 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 4 HIGHLIGHT VALUE 'X'.
244 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 5 HIGHLIGHT VALUE 'X'.
245 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 6 HIGHLIGHT VALUE 'X'.
=====

```

GCic for OSX Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 5

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/colors.cbl

Line Statement Page: 6

```

=====
246 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 7 HIGHLIGHT VALUE 'X'.
247 05 LINE + 1.
248 10 COL 22 BACKGROUND-COLOR 5 FOREGROUND-COLOR 0 HIGHLIGHT VALUE 'X'.
249 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 1 HIGHLIGHT VALUE 'X'.
250 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 2 HIGHLIGHT VALUE 'X'.
251 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 3 HIGHLIGHT VALUE 'X'.
252 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 4 HIGHLIGHT VALUE 'X'.
253 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 5 HIGHLIGHT VALUE 'X'.
254 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 6 HIGHLIGHT VALUE 'X'.
255 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 7 HIGHLIGHT VALUE 'X'.
256 05 LINE + 1.
257 10 COL 22 BACKGROUND-COLOR 6 FOREGROUND-COLOR 0 HIGHLIGHT VALUE 'X'.
258 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 1 HIGHLIGHT VALUE 'X'.
259 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 2 HIGHLIGHT VALUE 'X'.
260 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 3 HIGHLIGHT VALUE 'X'.
261 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 4 HIGHLIGHT VALUE 'X'.
262 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 5 HIGHLIGHT VALUE 'X'.
263 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 6 HIGHLIGHT VALUE 'X'.
264 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 7 HIGHLIGHT VALUE 'X'.
265 05 LINE + 1.
266 10 COL 22 BACKGROUND-COLOR 7 FOREGROUND-COLOR 0 HIGHLIGHT VALUE 'X'.
267 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 1 HIGHLIGHT VALUE 'X'.
268 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 2 HIGHLIGHT VALUE 'X'.
269 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 3 HIGHLIGHT VALUE 'X'.
270 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 4 HIGHLIGHT VALUE 'X'.
271 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 5 HIGHLIGHT VALUE 'X'.
272 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 6 HIGHLIGHT VALUE 'X'.
273 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 7 HIGHLIGHT VALUE 'X'.
274 *> #4
275 05 LINE 05.
276 10 COL 32 BACKGROUND-COLOR 0 FOREGROUND-COLOR 0 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
277 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 1 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
278 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 2 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
279 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 3 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
280 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 4 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
281 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 5 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
282 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 6 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
283 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 7 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
284 05 LINE + 1.
285 10 COL 32 BACKGROUND-COLOR 1 FOREGROUND-COLOR 0 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
286 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 1 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
287 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 2 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
288 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 3 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
289 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 4 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
290 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 5 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
291 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 6 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
292 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 7 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
293 05 LINE + 1.
294 10 COL 32 BACKGROUND-COLOR 2 FOREGROUND-COLOR 0 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
=====

```

GCic for OSX Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 6

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/colors.cbl

Line Statement

Page: 7

```

=====
295 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 1 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
296 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 2 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
297 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 3 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
298 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 4 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
299 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 5 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
300 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 6 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
301 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 7 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
302 05 LINE + 1.
303 10 COL 32 BACKGROUND-COLOR 3 FOREGROUND-COLOR 0 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
304 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 1 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
305 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 2 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
306 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 3 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
307 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 4 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
308 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 5 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
309 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 6 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
310 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 7 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
311 05 LINE + 1.
312 10 COL 32 BACKGROUND-COLOR 4 FOREGROUND-COLOR 0 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
313 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 1 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
314 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 2 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
315 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 3 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
316 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 4 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
317 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 5 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
318 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 6 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
319 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 7 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
320 05 LINE + 1.
321 10 COL 32 BACKGROUND-COLOR 5 FOREGROUND-COLOR 0 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
322 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 1 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
323 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 2 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
324 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 3 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
325 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 4 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
326 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 5 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
327 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 6 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
328 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 7 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
329 05 LINE + 1.
330 10 COL 32 BACKGROUND-COLOR 6 FOREGROUND-COLOR 0 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
331 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 1 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
332 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 2 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
333 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 3 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
334 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 4 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
335 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 5 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
336 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 6 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
337 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 7 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
338 05 LINE + 1.
339 10 COL 32 BACKGROUND-COLOR 7 FOREGROUND-COLOR 0 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
340 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 1 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
341 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 2 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
342 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 3 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
343 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 4 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
=====

```

GCic for OSX Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 7

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/colors.cbl

Line Statement Page: 8

```

=====
344 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 5 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
345 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 6 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
346 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 7 LOWLIGHT REVERSE-VIDEO VALUE 'X'.
347 *> #5
348 05 LINE 05.
349 10 COL 42 BACKGROUND-COLOR 0 FOREGROUND-COLOR 0 REVERSE-VIDEO VALUE 'X'.
350 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 1 REVERSE-VIDEO VALUE 'X'.
351 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 2 REVERSE-VIDEO VALUE 'X'.
352 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 3 REVERSE-VIDEO VALUE 'X'.
353 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 4 REVERSE-VIDEO VALUE 'X'.
354 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 5 REVERSE-VIDEO VALUE 'X'.
355 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 6 REVERSE-VIDEO VALUE 'X'.
356 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 7 REVERSE-VIDEO VALUE 'X'.
357 05 LINE + 1.
358 10 COL 42 BACKGROUND-COLOR 1 FOREGROUND-COLOR 0 REVERSE-VIDEO VALUE 'X'.
359 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 1 REVERSE-VIDEO VALUE 'X'.
360 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 2 REVERSE-VIDEO VALUE 'X'.
361 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 3 REVERSE-VIDEO VALUE 'X'.
362 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 4 REVERSE-VIDEO VALUE 'X'.
363 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 5 REVERSE-VIDEO VALUE 'X'.
364 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 6 REVERSE-VIDEO VALUE 'X'.
365 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 7 REVERSE-VIDEO VALUE 'X'.
366 05 LINE + 1.
367 10 COL 42 BACKGROUND-COLOR 2 FOREGROUND-COLOR 0 REVERSE-VIDEO VALUE 'X'.
368 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 1 REVERSE-VIDEO VALUE 'X'.
369 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 2 REVERSE-VIDEO VALUE 'X'.
370 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 3 REVERSE-VIDEO VALUE 'X'.
371 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 4 REVERSE-VIDEO VALUE 'X'.
372 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 5 REVERSE-VIDEO VALUE 'X'.
373 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 6 REVERSE-VIDEO VALUE 'X'.
374 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 7 REVERSE-VIDEO VALUE 'X'.
375 05 LINE + 1.
376 10 COL 42 BACKGROUND-COLOR 3 FOREGROUND-COLOR 0 REVERSE-VIDEO VALUE 'X'.
377 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 1 REVERSE-VIDEO VALUE 'X'.
378 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 2 REVERSE-VIDEO VALUE 'X'.
379 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 3 REVERSE-VIDEO VALUE 'X'.
380 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 4 REVERSE-VIDEO VALUE 'X'.
381 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 5 REVERSE-VIDEO VALUE 'X'.
382 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 6 REVERSE-VIDEO VALUE 'X'.
383 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 7 REVERSE-VIDEO VALUE 'X'.
384 05 LINE + 1.
385 10 COL 42 BACKGROUND-COLOR 4 FOREGROUND-COLOR 0 REVERSE-VIDEO VALUE 'X'.
386 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 1 REVERSE-VIDEO VALUE 'X'.
387 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 2 REVERSE-VIDEO VALUE 'X'.
388 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 3 REVERSE-VIDEO VALUE 'X'.
389 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 4 REVERSE-VIDEO VALUE 'X'.
390 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 5 REVERSE-VIDEO VALUE 'X'.
391 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 6 REVERSE-VIDEO VALUE 'X'.
392 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 7 REVERSE-VIDEO VALUE 'X'.
=====

```

GCic for OSX Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 8

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/colors.cbl

Line Statement

Page: 9

```

=====
393 05 LINE + 1.
394 10 COL 42 BACKGROUND-COLOR 5 FOREGROUND-COLOR 0 REVERSE-VIDEO VALUE 'X'.
395 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 1 REVERSE-VIDEO VALUE 'X'.
396 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 2 REVERSE-VIDEO VALUE 'X'.
397 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 3 REVERSE-VIDEO VALUE 'X'.
398 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 4 REVERSE-VIDEO VALUE 'X'.
399 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 5 REVERSE-VIDEO VALUE 'X'.
400 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 6 REVERSE-VIDEO VALUE 'X'.
401 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 7 REVERSE-VIDEO VALUE 'X'.
402 05 LINE + 1.
403 10 COL 42 BACKGROUND-COLOR 6 FOREGROUND-COLOR 0 REVERSE-VIDEO VALUE 'X'.
404 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 1 REVERSE-VIDEO VALUE 'X'.
405 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 2 REVERSE-VIDEO VALUE 'X'.
406 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 3 REVERSE-VIDEO VALUE 'X'.
407 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 4 REVERSE-VIDEO VALUE 'X'.
408 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 5 REVERSE-VIDEO VALUE 'X'.
409 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 6 REVERSE-VIDEO VALUE 'X'.
410 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 7 REVERSE-VIDEO VALUE 'X'.
411 05 LINE + 1.
412 10 COL 42 BACKGROUND-COLOR 7 FOREGROUND-COLOR 0 REVERSE-VIDEO VALUE 'X'.
413 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 1 REVERSE-VIDEO VALUE 'X'.
414 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 2 REVERSE-VIDEO VALUE 'X'.
415 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 3 REVERSE-VIDEO VALUE 'X'.
416 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 4 REVERSE-VIDEO VALUE 'X'.
417 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 5 REVERSE-VIDEO VALUE 'X'.
418 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 6 REVERSE-VIDEO VALUE 'X'.
419 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 7 REVERSE-VIDEO VALUE 'X'.
420 *> #6
421 05 LINE 05.
422 10 COL 52 BACKGROUND-COLOR 0 FOREGROUND-COLOR 0 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
423 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 1 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
424 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 2 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
425 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 3 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
426 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 4 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
427 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 5 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
428 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 6 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
429 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 7 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
430 05 LINE + 1.
431 10 COL 52 BACKGROUND-COLOR 1 FOREGROUND-COLOR 0 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
432 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 1 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
433 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 2 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
434 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 3 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
435 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 4 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
436 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 5 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
437 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 6 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
438 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 7 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
439 05 LINE + 1.
440 10 COL 52 BACKGROUND-COLOR 2 FOREGROUND-COLOR 0 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
441 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 1 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
=====

```

GCic for OSX Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 9

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/colors.cbl

Line Statement Page: 10

```

=====
442 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 2 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
443 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 3 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
444 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 4 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
445 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 5 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
446 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 6 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
447 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 7 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
448 05 LINE + 1.
449 10 COL 52 BACKGROUND-COLOR 3 FOREGROUND-COLOR 0 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
450 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 1 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
451 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 2 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
452 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 3 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
453 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 4 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
454 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 5 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
455 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 6 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
456 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 7 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
457 05 LINE + 1.
458 10 COL 52 BACKGROUND-COLOR 4 FOREGROUND-COLOR 0 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
459 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 1 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
460 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 2 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
461 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 3 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
462 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 4 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
463 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 5 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
464 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 6 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
465 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 7 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
466 05 LINE + 1.
467 10 COL 52 BACKGROUND-COLOR 5 FOREGROUND-COLOR 0 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
468 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 1 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
469 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 2 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
470 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 3 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
471 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 4 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
472 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 5 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
473 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 6 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
474 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 7 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
475 05 LINE + 1.
476 10 COL 52 BACKGROUND-COLOR 6 FOREGROUND-COLOR 0 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
477 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 1 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
478 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 2 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
479 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 3 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
480 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 4 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
481 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 5 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
482 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 6 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
483 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 7 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
484 05 LINE + 1.
485 10 COL 52 BACKGROUND-COLOR 7 FOREGROUND-COLOR 0 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
486 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 1 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
487 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 2 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
488 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 3 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
489 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 4 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
490 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 5 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 10

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/colors.cbl

Line Statement Page: 11

```

=====
491 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 6 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
492 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 7 HIGHLIGHT REVERSE-VIDEO VALUE 'X'.
493 *> #7
494 05 LINE 17.
495 10 COL 02 BACKGROUND-COLOR 0 FOREGROUND-COLOR 0 LOWLIGHT BLINK VALUE 'X'.
496 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 1 LOWLIGHT BLINK VALUE 'X'.
497 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 2 LOWLIGHT BLINK VALUE 'X'.
498 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 3 LOWLIGHT BLINK VALUE 'X'.
499 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 4 LOWLIGHT BLINK VALUE 'X'.
500 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 5 LOWLIGHT BLINK VALUE 'X'.
501 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 6 LOWLIGHT BLINK VALUE 'X'.
502 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 7 LOWLIGHT BLINK VALUE 'X'.
503 05 LINE + 1.
504 10 COL 02 BACKGROUND-COLOR 1 FOREGROUND-COLOR 0 LOWLIGHT BLINK VALUE 'X'.
505 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 1 LOWLIGHT BLINK VALUE 'X'.
506 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 2 LOWLIGHT BLINK VALUE 'X'.
507 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 3 LOWLIGHT BLINK VALUE 'X'.
508 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 4 LOWLIGHT BLINK VALUE 'X'.
509 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 5 LOWLIGHT BLINK VALUE 'X'.
510 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 6 LOWLIGHT BLINK VALUE 'X'.
511 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 7 LOWLIGHT BLINK VALUE 'X'.
512 05 LINE + 1.
513 10 COL 02 BACKGROUND-COLOR 2 FOREGROUND-COLOR 0 LOWLIGHT BLINK VALUE 'X'.
514 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 1 LOWLIGHT BLINK VALUE 'X'.
515 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 2 LOWLIGHT BLINK VALUE 'X'.
516 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 3 LOWLIGHT BLINK VALUE 'X'.
517 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 4 LOWLIGHT BLINK VALUE 'X'.
518 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 5 LOWLIGHT BLINK VALUE 'X'.
519 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 6 LOWLIGHT BLINK VALUE 'X'.
520 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 7 LOWLIGHT BLINK VALUE 'X'.
521 05 LINE + 1.
522 10 COL 02 BACKGROUND-COLOR 3 FOREGROUND-COLOR 0 LOWLIGHT BLINK VALUE 'X'.
523 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 1 LOWLIGHT BLINK VALUE 'X'.
524 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 2 LOWLIGHT BLINK VALUE 'X'.
525 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 3 LOWLIGHT BLINK VALUE 'X'.
526 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 4 LOWLIGHT BLINK VALUE 'X'.
527 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 5 LOWLIGHT BLINK VALUE 'X'.
528 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 6 LOWLIGHT BLINK VALUE 'X'.
529 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 7 LOWLIGHT BLINK VALUE 'X'.
530 05 LINE + 1.
531 10 COL 02 BACKGROUND-COLOR 4 FOREGROUND-COLOR 0 LOWLIGHT BLINK VALUE 'X'.
532 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 1 LOWLIGHT BLINK VALUE 'X'.
533 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 2 LOWLIGHT BLINK VALUE 'X'.
534 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 3 LOWLIGHT BLINK VALUE 'X'.
535 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 4 LOWLIGHT BLINK VALUE 'X'.
536 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 5 LOWLIGHT BLINK VALUE 'X'.
537 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 6 LOWLIGHT BLINK VALUE 'X'.
538 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 7 LOWLIGHT BLINK VALUE 'X'.
539 05 LINE + 1.
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 11

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/colors.cbl

Line Statement

Page: 12

```

=====
540 10 COL 02 BACKGROUND-COLOR 5 FOREGROUND-COLOR 0 LOWLIGHT BLINK VALUE 'X'.
541 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 1 LOWLIGHT BLINK VALUE 'X'.
542 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 2 LOWLIGHT BLINK VALUE 'X'.
543 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 3 LOWLIGHT BLINK VALUE 'X'.
544 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 4 LOWLIGHT BLINK VALUE 'X'.
545 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 5 LOWLIGHT BLINK VALUE 'X'.
546 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 6 LOWLIGHT BLINK VALUE 'X'.
547 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 7 LOWLIGHT BLINK VALUE 'X'.
548 05 LINE + 1.
549 10 COL 02 BACKGROUND-COLOR 6 FOREGROUND-COLOR 0 LOWLIGHT BLINK VALUE 'X'.
550 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 1 LOWLIGHT BLINK VALUE 'X'.
551 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 2 LOWLIGHT BLINK VALUE 'X'.
552 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 3 LOWLIGHT BLINK VALUE 'X'.
553 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 4 LOWLIGHT BLINK VALUE 'X'.
554 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 5 LOWLIGHT BLINK VALUE 'X'.
555 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 6 LOWLIGHT BLINK VALUE 'X'.
556 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 7 LOWLIGHT BLINK VALUE 'X'.
557 05 LINE + 1.
558 10 COL 02 BACKGROUND-COLOR 7 FOREGROUND-COLOR 0 LOWLIGHT BLINK VALUE 'X'.
559 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 1 LOWLIGHT BLINK VALUE 'X'.
560 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 2 LOWLIGHT BLINK VALUE 'X'.
561 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 3 LOWLIGHT BLINK VALUE 'X'.
562 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 4 LOWLIGHT BLINK VALUE 'X'.
563 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 5 LOWLIGHT BLINK VALUE 'X'.
564 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 6 LOWLIGHT BLINK VALUE 'X'.
565 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 7 LOWLIGHT BLINK VALUE 'X'.
566 *> #8
567 05 LINE 17.
568 10 COL 12 BACKGROUND-COLOR 0 FOREGROUND-COLOR 0 BLINK VALUE 'X'.
569 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 1 BLINK VALUE 'X'.
570 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 2 BLINK VALUE 'X'.
571 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 3 BLINK VALUE 'X'.
572 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 4 BLINK VALUE 'X'.
573 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 5 BLINK VALUE 'X'.
574 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 6 BLINK VALUE 'X'.
575 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 7 BLINK VALUE 'X'.
576 05 LINE + 1.
577 10 COL 12 BACKGROUND-COLOR 1 FOREGROUND-COLOR 0 BLINK VALUE 'X'.
578 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 1 BLINK VALUE 'X'.
579 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 2 BLINK VALUE 'X'.
580 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 3 BLINK VALUE 'X'.
581 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 4 BLINK VALUE 'X'.
582 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 5 BLINK VALUE 'X'.
583 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 6 BLINK VALUE 'X'.
584 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 7 BLINK VALUE 'X'.
585 05 LINE + 1.
586 10 COL 12 BACKGROUND-COLOR 2 FOREGROUND-COLOR 0 BLINK VALUE 'X'.
587 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 1 BLINK VALUE 'X'.
588 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 2 BLINK VALUE 'X'.
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 12

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/colors.cbl

Line Statement

Page: 13

```

=====
589 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 3 BLINK VALUE 'X'.
590 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 4 BLINK VALUE 'X'.
591 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 5 BLINK VALUE 'X'.
592 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 6 BLINK VALUE 'X'.
593 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 7 BLINK VALUE 'X'.
594 05 LINE + 1.
595 10 COL 12 BACKGROUND-COLOR 3 FOREGROUND-COLOR 0 BLINK VALUE 'X'.
596 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 1 BLINK VALUE 'X'.
597 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 2 BLINK VALUE 'X'.
598 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 3 BLINK VALUE 'X'.
599 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 4 BLINK VALUE 'X'.
600 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 5 BLINK VALUE 'X'.
601 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 6 BLINK VALUE 'X'.
602 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 7 BLINK VALUE 'X'.
603 05 LINE + 1.
604 10 COL 12 BACKGROUND-COLOR 4 FOREGROUND-COLOR 0 BLINK VALUE 'X'.
605 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 1 BLINK VALUE 'X'.
606 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 2 BLINK VALUE 'X'.
607 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 3 BLINK VALUE 'X'.
608 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 4 BLINK VALUE 'X'.
609 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 5 BLINK VALUE 'X'.
610 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 6 BLINK VALUE 'X'.
611 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 7 BLINK VALUE 'X'.
612 05 LINE + 1.
613 10 COL 12 BACKGROUND-COLOR 5 FOREGROUND-COLOR 0 BLINK VALUE 'X'.
614 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 1 BLINK VALUE 'X'.
615 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 2 BLINK VALUE 'X'.
616 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 3 BLINK VALUE 'X'.
617 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 4 BLINK VALUE 'X'.
618 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 5 BLINK VALUE 'X'.
619 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 6 BLINK VALUE 'X'.
620 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 7 BLINK VALUE 'X'.
621 05 LINE + 1.
622 10 COL 12 BACKGROUND-COLOR 6 FOREGROUND-COLOR 0 BLINK VALUE 'X'.
623 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 1 BLINK VALUE 'X'.
624 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 2 BLINK VALUE 'X'.
625 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 3 BLINK VALUE 'X'.
626 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 4 BLINK VALUE 'X'.
627 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 5 BLINK VALUE 'X'.
628 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 6 BLINK VALUE 'X'.
629 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 7 BLINK VALUE 'X'.
630 05 LINE + 1.
631 10 COL 12 BACKGROUND-COLOR 7 FOREGROUND-COLOR 0 BLINK VALUE 'X'.
632 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 1 BLINK VALUE 'X'.
633 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 2 BLINK VALUE 'X'.
634 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 3 BLINK VALUE 'X'.
635 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 4 BLINK VALUE 'X'.
636 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 5 BLINK VALUE 'X'.
637 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 6 BLINK VALUE 'X'.
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 13

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/colors.cbl

Line Statement

Page: 14

```

=====
638 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 7 BLINK VALUE 'X'.
639 *> #9
640 05 LINE 17.
641 10 COL 22 BACKGROUND-COLOR 0 FOREGROUND-COLOR 0 HIGHLIGHT BLINK VALUE 'X'.
642 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 1 HIGHLIGHT BLINK VALUE 'X'.
643 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 2 HIGHLIGHT BLINK VALUE 'X'.
644 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 3 HIGHLIGHT BLINK VALUE 'X'.
645 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 4 HIGHLIGHT BLINK VALUE 'X'.
646 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 5 HIGHLIGHT BLINK VALUE 'X'.
647 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 6 HIGHLIGHT BLINK VALUE 'X'.
648 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 7 HIGHLIGHT BLINK VALUE 'X'.
649 05 LINE + 1.
650 10 COL 22 BACKGROUND-COLOR 1 FOREGROUND-COLOR 0 HIGHLIGHT BLINK VALUE 'X'.
651 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 1 HIGHLIGHT BLINK VALUE 'X'.
652 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 2 HIGHLIGHT BLINK VALUE 'X'.
653 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 3 HIGHLIGHT BLINK VALUE 'X'.
654 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 4 HIGHLIGHT BLINK VALUE 'X'.
655 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 5 HIGHLIGHT BLINK VALUE 'X'.
656 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 6 HIGHLIGHT BLINK VALUE 'X'.
657 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 7 HIGHLIGHT BLINK VALUE 'X'.
658 05 LINE + 1.
659 10 COL 22 BACKGROUND-COLOR 2 FOREGROUND-COLOR 0 HIGHLIGHT BLINK VALUE 'X'.
660 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 1 HIGHLIGHT BLINK VALUE 'X'.
661 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 2 HIGHLIGHT BLINK VALUE 'X'.
662 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 3 HIGHLIGHT BLINK VALUE 'X'.
663 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 4 HIGHLIGHT BLINK VALUE 'X'.
664 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 5 HIGHLIGHT BLINK VALUE 'X'.
665 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 6 HIGHLIGHT BLINK VALUE 'X'.
666 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 7 HIGHLIGHT BLINK VALUE 'X'.
667 05 LINE + 1.
668 10 COL 22 BACKGROUND-COLOR 3 FOREGROUND-COLOR 0 HIGHLIGHT BLINK VALUE 'X'.
669 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 1 HIGHLIGHT BLINK VALUE 'X'.
670 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 2 HIGHLIGHT BLINK VALUE 'X'.
671 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 3 HIGHLIGHT BLINK VALUE 'X'.
672 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 4 HIGHLIGHT BLINK VALUE 'X'.
673 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 5 HIGHLIGHT BLINK VALUE 'X'.
674 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 6 HIGHLIGHT BLINK VALUE 'X'.
675 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 7 HIGHLIGHT BLINK VALUE 'X'.
676 05 LINE + 1.
677 10 COL 22 BACKGROUND-COLOR 4 FOREGROUND-COLOR 0 HIGHLIGHT BLINK VALUE 'X'.
678 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 1 HIGHLIGHT BLINK VALUE 'X'.
679 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 2 HIGHLIGHT BLINK VALUE 'X'.
680 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 3 HIGHLIGHT BLINK VALUE 'X'.
681 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 4 HIGHLIGHT BLINK VALUE 'X'.
682 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 5 HIGHLIGHT BLINK VALUE 'X'.
683 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 6 HIGHLIGHT BLINK VALUE 'X'.
684 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 7 HIGHLIGHT BLINK VALUE 'X'.
685 05 LINE + 1.
686 10 COL 22 BACKGROUND-COLOR 5 FOREGROUND-COLOR 0 HIGHLIGHT BLINK VALUE 'X'.
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 14

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/colors.cbl

Line Statement

Page: 15

```

=====
687 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 1 HIGHLIGHT BLINK VALUE 'X'.
688 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 2 HIGHLIGHT BLINK VALUE 'X'.
689 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 3 HIGHLIGHT BLINK VALUE 'X'.
690 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 4 HIGHLIGHT BLINK VALUE 'X'.
691 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 5 HIGHLIGHT BLINK VALUE 'X'.
692 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 6 HIGHLIGHT BLINK VALUE 'X'.
693 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 7 HIGHLIGHT BLINK VALUE 'X'.
694 05 LINE + 1.
695 10 COL 22 BACKGROUND-COLOR 6 FOREGROUND-COLOR 0 HIGHLIGHT BLINK VALUE 'X'.
696 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 1 HIGHLIGHT BLINK VALUE 'X'.
697 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 2 HIGHLIGHT BLINK VALUE 'X'.
698 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 3 HIGHLIGHT BLINK VALUE 'X'.
699 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 4 HIGHLIGHT BLINK VALUE 'X'.
700 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 5 HIGHLIGHT BLINK VALUE 'X'.
701 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 6 HIGHLIGHT BLINK VALUE 'X'.
702 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 7 HIGHLIGHT BLINK VALUE 'X'.
703 05 LINE + 1.
704 10 COL 22 BACKGROUND-COLOR 7 FOREGROUND-COLOR 0 HIGHLIGHT BLINK VALUE 'X'.
705 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 1 HIGHLIGHT BLINK VALUE 'X'.
706 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 2 HIGHLIGHT BLINK VALUE 'X'.
707 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 3 HIGHLIGHT BLINK VALUE 'X'.
708 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 4 HIGHLIGHT BLINK VALUE 'X'.
709 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 5 HIGHLIGHT BLINK VALUE 'X'.
710 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 6 HIGHLIGHT BLINK VALUE 'X'.
711 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 7 HIGHLIGHT BLINK VALUE 'X'.
712 *> #10
713 05 LINE 17.
714 10 COL 32 BACKGROUND-COLOR 0 FOREGROUND-COLOR 0 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
715 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 1 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
716 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 2 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
717 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 3 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
718 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 4 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
719 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 5 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
720 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 6 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
721 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 7 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
722 05 LINE + 1.
723 10 COL 32 BACKGROUND-COLOR 1 FOREGROUND-COLOR 0 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
724 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 1 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
725 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 2 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
726 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 3 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
727 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 4 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
728 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 5 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
729 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 6 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
730 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 7 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
731 05 LINE + 1.
732 10 COL 32 BACKGROUND-COLOR 2 FOREGROUND-COLOR 0 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
733 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 1 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
734 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 2 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
735 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 3 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 15

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/colors.cbl

Line Statement Page: 16

```

=====
736 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 4 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
737 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 5 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
738 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 6 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
739 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 7 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
740 05 LINE + 1.
741 10 COL 32 BACKGROUND-COLOR 3 FOREGROUND-COLOR 0 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
742 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 1 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
743 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 2 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
744 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 3 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
745 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 4 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
746 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 5 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
747 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 6 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
748 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 7 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
749 05 LINE + 1.
750 10 COL 32 BACKGROUND-COLOR 4 FOREGROUND-COLOR 0 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
751 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 1 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
752 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 2 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
753 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 3 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
754 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 4 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
755 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 5 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
756 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 6 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
757 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 7 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
758 05 LINE + 1.
759 10 COL 32 BACKGROUND-COLOR 5 FOREGROUND-COLOR 0 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
760 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 1 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
761 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 2 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
762 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 3 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
763 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 4 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
764 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 5 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
765 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 6 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
766 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 7 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
767 05 LINE + 1.
768 10 COL 32 BACKGROUND-COLOR 6 FOREGROUND-COLOR 0 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
769 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 1 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
770 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 2 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
771 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 3 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
772 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 4 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
773 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 5 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
774 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 6 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
775 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 7 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
776 05 LINE + 1.
777 10 COL 32 BACKGROUND-COLOR 7 FOREGROUND-COLOR 0 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
778 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 1 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
779 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 2 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
780 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 3 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
781 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 4 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
782 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 5 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
783 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 6 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
784 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 7 LOWLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 16

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/colors.cbl

Line Statement

Page: 17

```

=====
785 *> #11
786 05 LINE 17.
787 10 COL 42 BACKGROUND-COLOR 0 FOREGROUND-COLOR 0 BLINK REVERSE-VIDEO VALUE 'X'.
788 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 1 BLINK REVERSE-VIDEO VALUE 'X'.
789 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 2 BLINK REVERSE-VIDEO VALUE 'X'.
790 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 3 BLINK REVERSE-VIDEO VALUE 'X'.
791 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 4 BLINK REVERSE-VIDEO VALUE 'X'.
792 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 5 BLINK REVERSE-VIDEO VALUE 'X'.
793 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 6 BLINK REVERSE-VIDEO VALUE 'X'.
794 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 7 BLINK REVERSE-VIDEO VALUE 'X'.
795 05 LINE + 1.
796 10 COL 42 BACKGROUND-COLOR 1 FOREGROUND-COLOR 0 BLINK REVERSE-VIDEO VALUE 'X'.
797 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 1 BLINK REVERSE-VIDEO VALUE 'X'.
798 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 2 BLINK REVERSE-VIDEO VALUE 'X'.
799 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 3 BLINK REVERSE-VIDEO VALUE 'X'.
800 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 4 BLINK REVERSE-VIDEO VALUE 'X'.
801 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 5 BLINK REVERSE-VIDEO VALUE 'X'.
802 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 6 BLINK REVERSE-VIDEO VALUE 'X'.
803 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 7 BLINK REVERSE-VIDEO VALUE 'X'.
804 05 LINE + 1.
805 10 COL 42 BACKGROUND-COLOR 2 FOREGROUND-COLOR 0 BLINK REVERSE-VIDEO VALUE 'X'.
806 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 1 BLINK REVERSE-VIDEO VALUE 'X'.
807 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 2 BLINK REVERSE-VIDEO VALUE 'X'.
808 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 3 BLINK REVERSE-VIDEO VALUE 'X'.
809 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 4 BLINK REVERSE-VIDEO VALUE 'X'.
810 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 5 BLINK REVERSE-VIDEO VALUE 'X'.
811 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 6 BLINK REVERSE-VIDEO VALUE 'X'.
812 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 7 BLINK REVERSE-VIDEO VALUE 'X'.
813 05 LINE + 1.
814 10 COL 42 BACKGROUND-COLOR 3 FOREGROUND-COLOR 0 BLINK REVERSE-VIDEO VALUE 'X'.
815 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 1 BLINK REVERSE-VIDEO VALUE 'X'.
816 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 2 BLINK REVERSE-VIDEO VALUE 'X'.
817 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 3 BLINK REVERSE-VIDEO VALUE 'X'.
818 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 4 BLINK REVERSE-VIDEO VALUE 'X'.
819 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 5 BLINK REVERSE-VIDEO VALUE 'X'.
820 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 6 BLINK REVERSE-VIDEO VALUE 'X'.
821 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 7 BLINK REVERSE-VIDEO VALUE 'X'.
822 05 LINE + 1.
823 10 COL 42 BACKGROUND-COLOR 4 FOREGROUND-COLOR 0 BLINK REVERSE-VIDEO VALUE 'X'.
824 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 1 BLINK REVERSE-VIDEO VALUE 'X'.
825 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 2 BLINK REVERSE-VIDEO VALUE 'X'.
826 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 3 BLINK REVERSE-VIDEO VALUE 'X'.
827 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 4 BLINK REVERSE-VIDEO VALUE 'X'.
828 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 5 BLINK REVERSE-VIDEO VALUE 'X'.
829 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 6 BLINK REVERSE-VIDEO VALUE 'X'.
830 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 7 BLINK REVERSE-VIDEO VALUE 'X'.
831 05 LINE + 1.
832 10 COL 42 BACKGROUND-COLOR 5 FOREGROUND-COLOR 0 BLINK REVERSE-VIDEO VALUE 'X'.
833 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 1 BLINK REVERSE-VIDEO VALUE 'X'.
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 17

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/colors.cbl

Line Statement Page: 18

```

=====
834 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 2 BLINK REVERSE-VIDEO VALUE 'X'.
835 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 3 BLINK REVERSE-VIDEO VALUE 'X'.
836 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 4 BLINK REVERSE-VIDEO VALUE 'X'.
837 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 5 BLINK REVERSE-VIDEO VALUE 'X'.
838 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 6 BLINK REVERSE-VIDEO VALUE 'X'.
839 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 7 BLINK REVERSE-VIDEO VALUE 'X'.
840 05 LINE + 1.
841 10 COL 42 BACKGROUND-COLOR 6 FOREGROUND-COLOR 0 BLINK REVERSE-VIDEO VALUE 'X'.
842 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 1 BLINK REVERSE-VIDEO VALUE 'X'.
843 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 2 BLINK REVERSE-VIDEO VALUE 'X'.
844 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 3 BLINK REVERSE-VIDEO VALUE 'X'.
845 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 4 BLINK REVERSE-VIDEO VALUE 'X'.
846 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 5 BLINK REVERSE-VIDEO VALUE 'X'.
847 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 6 BLINK REVERSE-VIDEO VALUE 'X'.
848 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 7 BLINK REVERSE-VIDEO VALUE 'X'.
849 05 LINE + 1.
850 10 COL 42 BACKGROUND-COLOR 7 FOREGROUND-COLOR 0 BLINK REVERSE-VIDEO VALUE 'X'.
851 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 1 BLINK REVERSE-VIDEO VALUE 'X'.
852 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 2 BLINK REVERSE-VIDEO VALUE 'X'.
853 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 3 BLINK REVERSE-VIDEO VALUE 'X'.
854 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 4 BLINK REVERSE-VIDEO VALUE 'X'.
855 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 5 BLINK REVERSE-VIDEO VALUE 'X'.
856 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 6 BLINK REVERSE-VIDEO VALUE 'X'.
857 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 7 BLINK REVERSE-VIDEO VALUE 'X'.
858 *> #12
859 05 LINE 17.
860 10 COL 52 BACKGROUND-COLOR 0 FOREGROUND-COLOR 0 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
861 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 1 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
862 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 2 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
863 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 3 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
864 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 4 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
865 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 5 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
866 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 6 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
867 10 COL + 1 BACKGROUND-COLOR 0 FOREGROUND-COLOR 7 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
868 05 LINE + 1.
869 10 COL 52 BACKGROUND-COLOR 1 FOREGROUND-COLOR 0 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
870 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 1 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
871 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 2 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
872 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 3 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
873 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 4 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
874 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 5 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
875 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 6 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
876 10 COL + 1 BACKGROUND-COLOR 1 FOREGROUND-COLOR 7 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
877 05 LINE + 1.
878 10 COL 52 BACKGROUND-COLOR 2 FOREGROUND-COLOR 0 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
879 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 1 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
880 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 2 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
881 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 3 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
882 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 4 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 18

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/colors.cbl

Line Statement Page: 19

```

=====
883 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 5 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
884 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 6 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
885 10 COL + 1 BACKGROUND-COLOR 2 FOREGROUND-COLOR 7 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
886 05 LINE + 1.
887 10 COL 52 BACKGROUND-COLOR 3 FOREGROUND-COLOR 0 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
888 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 1 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
889 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 2 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
890 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 3 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
891 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 4 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
892 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 5 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
893 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 6 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
894 10 COL + 1 BACKGROUND-COLOR 3 FOREGROUND-COLOR 7 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
895 05 LINE + 1.
896 10 COL 52 BACKGROUND-COLOR 4 FOREGROUND-COLOR 0 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
897 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 1 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
898 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 2 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
899 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 3 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
900 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 4 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
901 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 5 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
902 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 6 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
903 10 COL + 1 BACKGROUND-COLOR 4 FOREGROUND-COLOR 7 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
904 05 LINE + 1.
905 10 COL 52 BACKGROUND-COLOR 5 FOREGROUND-COLOR 0 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
906 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 1 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
907 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 2 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
908 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 3 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
909 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 4 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
910 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 5 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
911 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 6 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
912 10 COL + 1 BACKGROUND-COLOR 5 FOREGROUND-COLOR 7 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
913 05 LINE + 1.
914 10 COL 52 BACKGROUND-COLOR 6 FOREGROUND-COLOR 0 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
915 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 1 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
916 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 2 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
917 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 3 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
918 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 4 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
919 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 5 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
920 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 6 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
921 10 COL + 1 BACKGROUND-COLOR 6 FOREGROUND-COLOR 7 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
922 05 LINE + 1.
923 10 COL 52 BACKGROUND-COLOR 7 FOREGROUND-COLOR 0 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
924 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 1 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
925 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 2 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
926 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 3 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
927 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 4 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
928 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 5 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
929 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 6 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
930 10 COL + 1 BACKGROUND-COLOR 7 FOREGROUND-COLOR 7 HIGHLIGHT BLINK REVERSE-VIDEO VALUE 'X'.
931 PROCEDURE DIVISION.
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 19

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/colors.cbl

Line Statement

Page: 20

```
=====
932 000-Main SECTION.
933 DISPLAY S-COLORTST-SCR
934 STOP RUN
935 .
```

```
=====
GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL
```

Page: 20

```

GNU COBOL 2.1 23NOV2013 Cross-Reference Listing
C:/Users/tda010/Documents/Programs/Samples/colors.cbl
2014/03/27
PROGRAM-ID      Identifier/Register/Function  Defn  Where Defined  References  Page: 21
=====
colors          000-Main                                932 PROCEDURE
colors          S-COLORTST-SCR                            6 SCREEN          933

```

4. DAY-FROM-DATE

DAY-FROM-DATE is a user-defined function that accepts a single numeric "USAGE DISPLAY" argument –æ either a 7-digit Julian date in the form *yyyyddd* or an 8-digit Gregorian date in the form *yyyymmdd*. This argument may be supplied either as a PIC 9(n) USAGE DISPLAY data item (n=7 or 8) or as a 7- or 8-digit numeric literal.

The subroutine will determine if the supplied date is a valid date in the year range 0000 through 9999 and what day of the week that date fell on.

The value returned will be zero if the date argument was invalid or an integer in the range 1-7, representing Sunday through Saturday.

In addition to general GnuCOBOL concepts, this program provides a useful demonstration of the following:

- Coding a GnuCOBOL user-defined function
- Using the "ANY LENGTH" data item attribute
- Using the "RETURNING" option in a subprogram
- Using the "DATE-OF-INTEGER" intrinsic function
- Using the "C\$PARAMSIZE" built-in system subroutine

The program source and cross-reference listing, produced using the GnuCOBOL Interactive Compiler front-end (GCic.cbl, one of the sample programs included here), begins on the next page.

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/DAY-FROM-DATE.cbl

Line Statement

Page: 1

```

=====
1      >>SOURCE FORMAT IS FIXED
2      IDENTIFICATION DIVISION.
3      FUNCTION-ID. DAY-FROM-DATE.
4      *>*****
5      *> This GNU COBOL user-defined function converts a Gregorian or **
6      *> Julian date into a numeric day of the week.                **
7      *>*****
8      *> Arguments:                                                  **
9      *>                                                            **
10     *> Calendar-Date      A PIC 9 data item or numeric literal which **
11     *>                                                            **
12     *>                                                            **
13     *>                                                            **
14     *>                    7-digit value: Interpreted as a Julian date **
15     *>                                                            **
16     *>                    8-digit value: Interpreted as a Gregorian **
17     *>                                                            **
18     *>                    date in the form yyyymmdd                **
19     *> The result returned will be one of the following:          **
20     *>                                                            **
21     *> 0: The supplied date is invalid                            **
22     *> 1: The supplied date is a Sunday                          **
23     *> 2: The supplied date is a Monday                          **
24     *> .                                                            **
25     *> .                                                            **
26     *> .                                                            **
27     *> 7: The supplied date is a Saturday                        **
28     *>*****
29     ENVIRONMENT DIVISION.
30     CONFIGURATION SECTION.
31     REPOSITORY.
32     FUNCTION ALL INTRINSIC.
33     DATA DIVISION.
34     WORKING-STORAGE SECTION.
35     01 WS-Input-Date-DT.
36         05 WS-ID-YYYY-NUM                PIC 9(4).
37         05 WS-ID-MM-NUM                   PIC 9(2).
38         05 WS-ID-DD-NUM                   PIC 9(2).
39     01 WS-Y-NUM                           BINARY-LONG.
40     01 WS-M-NUM                           BINARY-LONG.
41     01 WS-Temp-NUM                        BINARY-LONG.
42     LINKAGE SECTION.
43     01 L-Input-Date-DT                    PIC 9 ANY LENGTH.
44     01 L-Output-Day-NUM                   USAGE BINARY-LONG
45                                         SIGNED.
46     PROCEDURE DIVISION USING L-Input-Date-DT
47         RETURNING L-Output-Day-NUM.
48     000-Main SECTION.
49     CALL "C$PARAMSIZE" USING 1
=====

```

GCic for OSX Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 1

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/DAY-FROM-DATE.cbl

Line Statement

Page: 2

```

=====
50      EVALUATE RETURN-CODE
51      WHEN 7
52          IF TEST-DAY-YYYYDDD(L-Input-Date-DT) > 0
53              MOVE 0 TO L-Output-Day-NUM
54              GOBACK
55          END-IF
56          MOVE DATE-OF-INTEGER(INTEGER-OF-DAY(L-Input-Date-DT))
57              TO WS-Input-Date-DT
58      WHEN 8
59          IF TEST-DATE-YYYYMMDD(L-Input-Date-DT) > 0
60              MOVE 0 TO L-Output-Day-NUM
61              GOBACK
62          END-IF
63          MOVE L-Input-Date-DT TO WS-Input-Date-DT
64      WHEN OTHER
65          MOVE 0 TO L-Output-Day-NUM
66          GOBACK
67      END-EVALUATE
68      *> IF january OR february
69      *>     y = year - 1
70      *>     m = month + 10
71      *> ELSE
72      *>     y = year
73      *>     m = month - 2
74      *> END-IF
75      *> For Gregorian calendar:
76      *>     result = (day + y + y/4 - y/100 + y/400 + (31*m)/12) mod 7
77      *> (All divisions are integer divisions, discarding any remainder)
78      IF WS-ID-MM-NUM = 1 OR 2
79          SUBTRACT 1 FROM WS-ID-YYYY-NUM GIVING WS-Y-NUM
80          ADD WS-ID-MM-NUM, 10 GIVING WS-M-NUM
81      ELSE
82          MOVE WS-ID-YYYY-NUM TO WS-Y-NUM
83          SUBTRACT 2 FROM WS-ID-MM-NUM GIVING WS-M-NUM
84      END-IF
85      COMPUTE L-Output-Day-NUM =
86          WS-ID-DD-NUM
87          + WS-Y-NUM
88          + INTEGER(WS-Y-NUM/4)
89          - INTEGER(WS-Y-NUM/100)
90          + INTEGER(WS-Y-NUM/400)
91          + INTEGER((31*WS-M-NUM)/12)
92      DIVIDE L-Output-Day-NUM BY 7
93          GIVING WS-Temp-NUM
94      REMAINDER L-Output-Day-NUM
95      ADD 1 TO L-Output-Day-NUM
96      GOBACK
97      .
98
=====

```

GCic for OSX Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 2

GNU COBOL 2.1 23NOV2013 Cross-Reference Listing					2014/03/27	
C:/Users/tda010/Documents/Programs/Samples/DAY-FROM-DATE.cbl						
PROGRAM-ID	Identifier/Register/Function	Defn	Where Defined	References	Page: 3	
=====	=====	=====	=====	=====	=====	
DAY-FROM-DATE	000-Main	48	PROCEDURE			
DAY-FROM-DATE	L-Input-Date-DT	43	LINKAGE	46	52	56
				59	63	
DAY-FROM-DATE	L-Output-Day-NUM	44	LINKAGE	47	53*	60*
				65*	85*	92
				94*	95*	
DAY-FROM-DATE	RETURN-CODE		PROCEDURE	50		
DAY-FROM-DATE	WS-ID-DD-NUM	38	WORKING-STORAGE	86		
DAY-FROM-DATE	WS-ID-MM-NUM	37	WORKING-STORAGE	78	80	83
DAY-FROM-DATE	WS-ID-YYYY-NUM	36	WORKING-STORAGE	79	82	
DAY-FROM-DATE	WS-Input-Date-DT	35	WORKING-STORAGE	57*	63*	
DAY-FROM-DATE	WS-M-NUM	40	WORKING-STORAGE	80*	83*	91
DAY-FROM-DATE	WS-Temp-NUM	41	WORKING-STORAGE	93*		
DAY-FROM-DATE	WS-Y-NUM	39	WORKING-STORAGE	79*	82*	87
				88	89	90

5. GCic

This is MUCH more than a mere demonstration program –æ it's also a very practical utility! The "GCic" (GnuCOBOL Interactive Compiler) is a TUI (Textual User Interface) program that may be used as a full-screen interface to the "cobe" compiler. In addition, GCic can produce neat, concise and useful cross-reference listings of GnuCOBOL programs, showing not only where user-defined names and built-in registers and intrinsic functions are referenced, but also where user-defined data items ARE MODIFIED by program code!

The program is well documented (IMHO) and you should find it fairly easy to follow. The GCic.cbl program was written to work with a native Windows or Windows/MinGW build of GnuCOBOL as well as a Windows/Cygwin, UNIX or OS X build.

Source listings generated by GCic will show the original source code of your programs, with all indentation and comments preserved. Additionally, any COPYed code will be included in the listing immediately (in compressed form) following the COPY statement that triggered its inclusion into your program.

Cross-reference listings will show all user-defined data items and procedures as well as intrinsic function and special register references. In addition to showing the line numbers at which items were defined and referenced, those references that MODIFY the contents of the data item will have an asterisk appended to them.

In addition to general GnuCOBOL concepts, this program provides a useful demonstration of the following:

- Creating a GnuCOBOL compilation unit that consists of multiple programs
- Using CDF conditional compilation facilities
- Using the "SCREEN SECTION" and associated "ACCEPT" and "DISPLAY" statements
- Using "DECLARATIVES" to trap file I/O errors
- Using "FILE-STATUS"
- Using the "REPLACING" clause on a CDF "COPY" statement
- Using the following statements:
 - o "ACCEPT FROM COMMAND-LINE" statement
 - o "ACCEPT FROM DATE/TIME" statement
 - o "ACCEPT FROM ENVIRONMENT" statement
 - o "EXIT PERFORM" statement
 - o "EXIT SECTION" statement
 - o "INSPECT" statement
 - o "PERFORM FOREVER" statement
 - o "SEARCH ALL" statement
 - o "SET ENVIRONMENT" statement
 - o "SORT" statement
 - o "STRING" statement

- o "UNSTRING" statement
- Using the following built-in subroutines:
 - o "C\$JUSTIFY" built-in system subroutine
 - o "C\$SLEEP" built-in system subroutine
 - o "CBL_CHANGE_DIR" built-in system subroutine
 - o "CBL_CHECK_FILE_EXIST" built-in system subroutine
 - o "CBL_DELETE_FILE" built-in system subroutine
 - o "SYSTEM" built-in system subroutine
- Using the following intrinsic functions:
 - o "CONCATENATE" intrinsic function
 - o "LENGTH" intrinsic function
 - o "LOWER-CASE" intrinsic function
 - o "NUMVAL" intrinsic function
 - o "TRIM" intrinsic function
 - o "UPPER-CASE" intrinsic function
- Using the "COB-CRT-STATUS,Special Registers" special register
- Programmatically producing a report destined for either portrait or landscape printing

Here is a sample of the screen generated by this program:

```

GNU COBOL Compiler
GCic (2013/12/26 10:16) GNU COBOL 2.1 23NOV2013 Interactive Compilation
Filename: mathtest.cbl
Folder: E:\Programs\Samples
Set/Clr Switches Via F1-F9; Set Config Via F12; ENTER Key Compiles; ESC Quits
F1 Assume WITH DEBUGGING MODE F6 >"FUNCTION" Is Optional
F2 Procedure+Statement Trace F7 >Enable All Warnings
F3 Make a Library (DLL) F8 Source Is Free-Format
F4 Execute If Compilation OK F9 >No COMP/BINARY Truncation
F5 Produce Full Listing
Current Config: DEFAULT
Extra "cobc" Switches, If Any ("-save-temps=xxx" Prevents Listings):
Program Execution Arguments, If Any:
GCic for Windows/MinGW Copyright (C) 2009-2013, Gary L. Cutler, GPL

```

The program source and cross-reference listing, produced using this program, begins on the next page.

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement Page: 1

```

=====
1      >>SOURCE FORMAT IS FIXED
2      *> CONFIGURATION SETTINGS: Set these switches before compiling:
3      *>
4      *> LINEDRAW Set to:
5      *> 0 To use spaces (no lines)
6      *> 1 To use the line-drawing character set (PC codepage 437)
7      *> 2 To use conventional ASCII characters (+, -, |)
8      *>
9      *> OSX USERS - To use the linedrawing character set,
10     *> set your 'terminal' font to 'Lucida Console'
11     *>
12     *> OS Set to one of the following:
13     *> 'CYGWIN' For a Windows/Cygwin version
14     *> 'MINGW' For a Windows/MinGW version
15     *> 'OSX' For a Macintosh OSX version
16     *> 'UNIX' For a Unix/Linux version
17     *> 'WINDOWS' For a Native Windows version
18     *>
19     *> SELCHAR Set to the desired single character to be used as the red
20     *> 'feature selected' character on the screen.
21     *> SUGGESTIONS: '>', '*', '=', '+'
22     *>
23     *> LPP Set to maximum printable lines per page when the listing
24     *> should be generated for LANDSCAPE orientation (can be over-
25     *> ridden at execution time using the GCXREF_LINES environment
26     *> variable.
27     *>
28     *> LPPP Set to maximum printable lines per page when the listing
29     *> should be generated for PORTRAIT orientation (can be over-
30     *> ridden at execution time using the GCXREF_LINES_PORT
31     *> environment variable.
32     *>
33     *>*****
34     *>*** Change the settings in the copy book const-set-1.cpy to reflect
35     *> your system set up. This notes are also present there.
36     *> This is to reduce the need to amend these every time a update
37     *> for GCic occurs.
38     *>*****
39     *>
40     *> copy "const-set-1.cpy".
41     *>
42     *> -----
43     *> END CONFIGURATION SETTINGS

```

GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL

Page: 1

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 2

```

=====
45      IDENTIFICATION DIVISION.
46      PROGRAM-ID. GCic.
47      *>*****
48      *>      >NOTE<      >NOTE<      >NOTE<      >NOTE<      >NOTE<      >NOTE<      **
49      *>                                                              **
50      *> If this program is compiled with '-fdebugging-line', you      **
51      *> will need to pipe SYSERR to a text file when executing GCic **
52      *> (by adding the text '> filename' to the end of the GCic      **
53      *> command). You may also need to press the ENTER key when      **
54      *> GCic is finished.                                          **
55      *>*****
56      *> This program provides a Textual User Interface (TUI) to the **
57      *> process of compiling and (optionally) executing a GNU COBOL **
58      *> program.                                                  **
59      *>                                                              **
60      *> This programs execution syntax is as follows:              **
61      *>                                                              **
62      *> GCic <program-path-and-filename> [ <switch>... ]          **
63      *>                                                              **
64      *> Once executed, a display screen will be presented showing **
65      *> the compilation options that will be used. The user will **
66      *> have the opportunity to change options, specify new ones **
67      *> and specify any program execution arguments to be used if **
68      *> you select the 'Execute' option. When you press the Enter **
69      *> key the program will be compiled.                          **
70      *>                                                              **
71      *> The SCREEN SECTION contains an image of the screen.        **
72      *>                                                              **
73      *> The '010-Parse-Args' section in the PROCEDURE DIVISION has **
74      *> documentation on switches and their function.              **
75      *>*****
76      *>                                                              **
77      *> AUTHOR:          GARY L. CUTLER                             **
78      *>                  Copyright (C) 2009-2017, Gary L. Cutler, GPL **
79      *>                                                              **
80      *> DATE-WRITTEN: June 14, 2009                                  **
81      *>                                                              **
82      *>*****
83      *>  DATE  CHANGE DESCRIPTION                                     **
84      *> =====
85      *> GC0609 Don't display compiler messages file if compilation **
86      *> GLC   Is successful. Also don't display messages if the      **
87      *>          output file is busy (just put a message on the        **
88      *>          screen, leave the OC screen up & let the user fix      **
89      *>          the problem & resubmit.                                  **
90      *> GC0709 When 'EXECUTE' is selected, a 'FILE BUSY' error will **
91      *> CLC   still cause the (old) executable to be launched.        **
92      *>          Also, the 'EXTRA SWITCHES' field is being ignored.     **
93      *>          Changed the title bar to lowlighted reverse video & **
94      *>          the message area to highlighted reverse-video.         **
95      *> GC0809 Add a SPACE in front of command-line args when        **
96      *> GLC   executing users program. Add a SPACE after the          **
=====

```

GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL

Page: 2

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 3

```

=====
 97      *>      -ftraceall switch when building cobc command.      **
 98      *> GC0909 Convert to work on Cygwin/Linux as well as MinGW  **
 99      *> GC0310 Virtualized the key codes for S-F1 thru S-F7 as they **
100      *> GLC   differ depending upon whether PDCurses or NCurses is **
101      *>      being used.                                          **
102      *> GC0410 Introduced the cross-reference and source listing  **
103      *> GLC   features. Also fixed a bug in EXTRA switch proces- **
104      *>      sing where garbage will result if more than the      **
105      *>      EXTRA switch is specified.                          **
106      *> GC1010 Corrected several problems reported by Vince Coen: **
107      *> GLC   1) Listing/Xref wouldn't work if '-I' additional  **
108      *>      cobc switch specified.                                **
109      *>      2) Programs coded with lowercase reserved words did  **
110      *>      not get parsed properly when generating listing      **
111      *>      and/or xref reports.                                  **
112      *>      3) Reliance on a TEMP environment variable caused    **
113      *>      non-recoverable errors when generating listing      **
114      *>      and/or xref reports in a session that lacks a      **
115      *>      TEMP variable.                                        **
116      *>      As a result of this change, GCic no longer runs a    **
117      *>      second 'cobc' when generating listing and/or xref    **
118      *>      reports. A '-save-temps' (without 'dir') specified **
119      *>      in the EXTRA options field will be ignored. A      **
120      *>      '-save-temps=dir' specified in the EXTRA options    **
121      *>      field will negate both the XREF and SOURCE opts,    **
122      *>      if specified.                                          **
123      *> GC0711 Tailored for 29APR2011 version of GNU COBOL 2.0    **
124      *> GC0712 Replaced all switches with configuration settings; **
125      *> GLC   Tailored for 11FEB2012 version of GNU COBOL 2.0;    **
126      *>      Reformatted screen layout to fit a 24x80 screen      **
127      *>      rather than a 25x81 screen and to accommodate shell  **
128      *>      environments having only F1-F12 (like 'terminal' in   **
129      *>      OSX); Fully tested under OSX (required a few altera-   **
130      *>      tions); Expanded both extra-options and runtime-      **
131      *>      arguments areas to TWO lines (152 chars total) each; **
132      *>      Added support for MF/IBM/BS2000 listing-control      **
133      *>      directives EJECT,SKIP1,SKIP2,SKIP3 (any of these in  **
134      *>      copybooks will be ignored)                               **
135      *> GC0313 Expand the source code record from 80 chars to 256 **
136      *> GLC   to facilitate looking for "LINKAGE SECTION" in a    **
137      *>      free-format file.                                        **
138      *> GC1113 Edited to support the change of "OpenCOBOL" to "GNU **
139      *> GLC   COBOL"                                                  **
140      *> GC1213 Updated for 23NOV2013 version of GNU COBOL 2.1      **
141      *> GC0114 Introduce a "Press ENTER to Close" action after run- **
142      *> GLC   ning the compiled program in the compiler window (F4) **
143      *> VC0617 Remove the Blinking in meny screen as uncomfortable **
144      *> VBC   Update version printed to 2.2 30JUN2017.            **
145      *>      Move the system constant settings to a copy file      **
146      *>      const-set-1.cpy in case GCic is updated.              **
147      *>      Added SET ENVIRONMENT "COB_EXIT_WAIT" TO "0" to      **
148      *>      100-Initialization section.                            **
149      *> VC0717 Replaced compile param intrinsic=all with        **
=====

```

GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL

Page: 3

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 4

```

=====
150      *>  VBC    intrinstics=ALL. Changed mod detail inits for Gary  **
151      *>      from GCL to GLC.                                     **
152      *>      Update version printed to 2.2 20JUL2017.           **
153      *>      Should really get this from the compiler if avail?  **
154      *>*****
155      *>
156      ENVIRONMENT DIVISION.
157      CONFIGURATION SECTION.
158      REPOSITORY.
159          FUNCTION ALL INTRINSIC.
160      INPUT-OUTPUT SECTION.
161      FILE-CONTROL.
162 GC1010      SELECT F-Cobc-Output-FILE    ASSIGN TO WS-Listing-Filename-TXT
163                                         ORGANIZATION IS LINE SEQUENTIAL.
164
165          SELECT F-Source-Code-FILE    ASSIGN TO WS-File-Name-TXT
166                                         ORGANIZATION IS LINE SEQUENTIAL
167                                         FILE STATUS IS WS-FSM-Status-CD.
=====

```

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 5

=====

```

169      DATA DIVISION.
170      FILE SECTION.
171      FD  F-Cobc-Output-FILE.
172      01  F-Cobc-Output-REC          PIC X(256).
173
174      FD  F-Source-Code-FILE.
175 GC0313 01  F-Source-Code-REC      PIC X(256).
176
177      WORKING-STORAGE SECTION.
178      COPY screenio.
179      78 COB-COLOR-BLACK VALUE 0.
180      78 COB-COLOR-BLUE VALUE 1.
181      78 COB-COLOR-GREEN VALUE 2.
182      78 COB-COLOR-CYAN VALUE 3.
183      78 COB-COLOR-RED VALUE 4.
184      78 COB-COLOR-MAGENTA VALUE 5.
185      78 COB-COLOR-YELLOW VALUE 6.
186      78 COB-COLOR-WHITE VALUE 7.
187      78 COB-SCR-OK VALUE 0.
188      78 COB-SCR-F1 VALUE 1001.
189      78 COB-SCR-F2 VALUE 1002.
190      78 COB-SCR-F3 VALUE 1003.
191      78 COB-SCR-F4 VALUE 1004.
192      78 COB-SCR-F5 VALUE 1005.
193      78 COB-SCR-F6 VALUE 1006.
194      78 COB-SCR-F7 VALUE 1007.
195      78 COB-SCR-F8 VALUE 1008.
196      78 COB-SCR-F9 VALUE 1009.
197      78 COB-SCR-F10 VALUE 1010.
198      78 COB-SCR-F11 VALUE 1011.
199      78 COB-SCR-F12 VALUE 1012.
200      78 COB-SCR-F13 VALUE 1013.
201      78 COB-SCR-F14 VALUE 1014.
202      78 COB-SCR-F15 VALUE 1015.
203      78 COB-SCR-F16 VALUE 1016.
204      78 COB-SCR-F17 VALUE 1017.
205      78 COB-SCR-F18 VALUE 1018.
206      78 COB-SCR-F19 VALUE 1019.
207      78 COB-SCR-F20 VALUE 1020.
208      78 COB-SCR-F21 VALUE 1021.
209      78 COB-SCR-F22 VALUE 1022.
210      78 COB-SCR-F23 VALUE 1023.
211      78 COB-SCR-F24 VALUE 1024.
212      78 COB-SCR-F25 VALUE 1025.
213      78 COB-SCR-F26 VALUE 1026.
214      78 COB-SCR-F27 VALUE 1027.
215      78 COB-SCR-F28 VALUE 1028.
216      78 COB-SCR-F29 VALUE 1029.
217      78 COB-SCR-F30 VALUE 1030.
218      78 COB-SCR-F31 VALUE 1031.
219      78 COB-SCR-F32 VALUE 1032.
220      78 COB-SCR-F33 VALUE 1033.

```

GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL

Page: 5

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 6

```

=====
78 COB-SCR-F34 VALUE 1034.
78 COB-SCR-F35 VALUE 1035.
78 COB-SCR-F36 VALUE 1036.
78 COB-SCR-F37 VALUE 1037.
78 COB-SCR-F38 VALUE 1038.
78 COB-SCR-F39 VALUE 1039.
78 COB-SCR-F40 VALUE 1040.
78 COB-SCR-F41 VALUE 1041.
78 COB-SCR-F42 VALUE 1042.
78 COB-SCR-F43 VALUE 1043.
78 COB-SCR-F44 VALUE 1044.
78 COB-SCR-F45 VALUE 1045.
78 COB-SCR-F46 VALUE 1046.
78 COB-SCR-F47 VALUE 1047.
78 COB-SCR-F48 VALUE 1048.
78 COB-SCR-F49 VALUE 1049.
78 COB-SCR-F50 VALUE 1050.
78 COB-SCR-F51 VALUE 1051.
78 COB-SCR-F52 VALUE 1052.
78 COB-SCR-F53 VALUE 1053.
78 COB-SCR-F54 VALUE 1054.
78 COB-SCR-F55 VALUE 1055.
78 COB-SCR-F56 VALUE 1056.
78 COB-SCR-F57 VALUE 1057.
78 COB-SCR-F58 VALUE 1058.
78 COB-SCR-F59 VALUE 1059.
78 COB-SCR-F60 VALUE 1060.
78 COB-SCR-F61 VALUE 1061.
78 COB-SCR-F62 VALUE 1062.
78 COB-SCR-F63 VALUE 1063.
78 COB-SCR-F64 VALUE 1064.
78 COB-SCR-PAGE_UP VALUE 2001.
78 COB-SCR-PAGE_DOWN VALUE 2002.
78 COB-SCR-KEY-UP VALUE 2003.
78 COB-SCR-KEY-DOWN VALUE 2004.
78 COB-SCR-ESC VALUE 2005.
78 COB-SCR-PRINT VALUE 2006.
78 COB-SCR-NO-FIELD VALUE 8000.
78 COB-SCR-TIME-OUT VALUE 8001.
78 COB-SCR-FATAL VALUE 9000.
78 COB-SCR-MAX-FIELD VALUE 9001.
179
180 GC0712 01 WS-Compilation-Switches-TXT.
181 GC0712 05 WS-CS-Args-TXT VALUE SPACES.
182 GC0712 10 WS-CS-Arg-H1-TXT PIC X(76).
183 GC0712 10 WS-CS-Arg-H2-TXT PIC X(76).
184 GC0712 05 WS-CS-Filenames-TXT.
185 GC0712 10 VALUE 'BS2000' PIC X(9).
186 GC0712 10 VALUE 'COBOL85' PIC X(9).
187 GC0712 10 VALUE 'COBOL2002' PIC X(9).
188 GC0712 10 VALUE 'DEFAULT' PIC X(9).
189 GC0712 10 VALUE 'IBM' PIC X(9).
190 GC0712 10 VALUE 'MF' PIC X(9).
=====

```

GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL

Page: 6

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 7

```

=====
191 GC0712      10 VALUE 'MVS'                                PIC X(9).
192 GC0712      05 WS-CS-FileNames-Table-TXT REDEFINES WS-CS-FileNames-TXT.
193 GC0712      10 WS-CS-Filename-TXT                          OCCURS 7 TIMES
194 GC0712      10 WS-CS-Filename-TXT                          PIC X(9).
195 GC0712 >>IF F12 < 1
196 GC0712      05 WS-CS-Config-NUM      VALUE 4      PIC 9(1).
197 GC0712 >>ELIF F12 > 7
198 GC0712      05 WS-CS-Config-NUM      VALUE 4      PIC 9(1).
199 GC0712 >>ELSE
200 GC0712      05 WS-CS-Config-NUM      VALUE F12     PIC 9(1).
201 GC0712 >>END-IF
202 GC0712      05 WS-CS-Extra-TXT VALUE SPACES.
203 GC0712      10 WS-CS-Extra-H1-TXT      PIC X(76).
204 GC0712      10 WS-CS-Extra-H2-TXT      PIC X(76).
205 GC0712      05 WS-CS-Switch-Defaults-TXT.
206 GC0712      10 VALUE F1                PIC 9(1). *> WS-CS-DEBUG-CHR
207 GC0712      10 VALUE F4                PIC 9(1). *> WS-CS-EXECUTE-CHR
208 GC0712      10 VALUE F8                PIC 9(1). *> WS-CS-FREE-CHR
209 GC0712      10 VALUE F3                PIC 9(1). *> WS-CS-LIBRARY-CHR
210 GC0712      10 VALUE F5                PIC 9(1). *> WS-CS-LISTING-CHR
211 GC0712      10 VALUE F6                PIC 9(1). *> WS-CS-NOFUNC-CHR
212 GC0712      10 VALUE F9                PIC 9(1). *> WS-CS-NOTRUNC-CHR
213 GC0712      10 VALUE F2                PIC 9(1). *> WS-CS-TRACEALL-CHR
214 GC0712      10 VALUE F7                PIC 9(1). *> WS-CS-WARNALL-CHR
215 GC0712      05 WS-CS-All-Switches-TXT REDEFINES
216 GC0712      WS-CS-Switch-Defaults-TXT.
217 GC0712      10 WS-CS-DEBUG-CHR          PIC X(1).
218 GC0712      10 WS-CS-EXECUTE-CHR        PIC X(1).
219 GC0712      10 WS-CS-FREE-CHR            PIC X(1).
220 GC0712      10 WS-CS-LIBRARY-CHR        PIC X(1).
221 GC0712      10 WS-CS-LISTING-CHR        PIC X(1).
222 GC0712      10 WS-CS-NOFUNC-CHR         PIC X(1).
223 GC0712      10 WS-CS-NOTRUNC-CHR         PIC X(1).
224 GC0712      10 WS-CS-TRACEALL-CHR       PIC X(1).
225 GC0712      10 WS-CS-WARNALL-CHR        PIC X(1).
226
227 GC0909 01 WS-Cmd-TXT                                PIC X(512).
228
229 GC0712 01 WS-Cmd-Args-TXT                            PIC X(256).
230
231 GC0712 01 WS-Cmd-End-Quote-CHR                        PIC X(1).
232
233 GC0712 01 WS-Cmd-SUB                                    USAGE BINARY-LONG.
234
235      01 WS-Cobc-Cmd-TXT                                PIC X(256).
236
237      01 WS-Config-Fn-TXT                                PIC X(12).
238
239 GC1113 01 WS-Delete-Fn-TXT                            PIC X(256).
240
241      01 WS-File-Name-TXT.
242      05 WS-FN-CHR                                        OCCURS 256 TIMES
243      10 WS-FN-CHR                                        PIC X(1).
=====

```

GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL

Page: 7

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 8

```

=====
244
245      01 WS-File-Status-Message-TXT.
246          05 VALUE 'Status Code: '          PIC X(13).
247          05 WS-FSM-Status-CD              PIC 9(2).
248          05 VALUE ', Meaning: '          PIC X(11).
249          05 WS-FSM-Msg-TXT                PIC X(25).
250
251 GC0909 01 WS-Horizontal-Line-TXT          PIC X(80).
252 GC0909
253      01 WS-I-SUB                          USAGE BINARY-LONG.
254
255      01 WS-J-SUB                          USAGE BINARY-LONG.
256
257 GC1213 01 WS-Listing-CD VALUE F5          PIC 9(1).
258
259 GC0712 01 WS-Listing-Filename-TXT         PIC X(256).
260
261 GC1213 01 WS-Listing-TXT VALUE SPACES     PIC X(27).
262
263      01 WS-OC-Compile-DT                  PIC XXXX/XX/XXBXX/XX.
264
265 GC0712 >>IF OS = 'CYGWIN'
266 GC0712 01 WS-OS-Dir-CHR                   VALUE '/'          PIC X(1).
267 GC0712 78 WS-OS-Exe-Ext-CONST             VALUE '.exe'.
268 GC0712 78 WS-OS-Lib-Ext-CONST             VALUE '.dll'.
269 GC0712 78 WS-OS-Lib-Type-CONST            VALUE 'DLL)'.
270 GC0712 01 WS-OS-Type-CD                   VALUE 2          PIC 9(1).
271 GC0712 >>ELIF OS = 'MINGW'
272 GC0712 01 WS-OS-Dir-CHR                   VALUE '\\'         PIC X(1).
273 GC0712 78 WS-OS-Exe-Ext-CONST             VALUE '.exe'.
274 GC0712 78 WS-OS-Lib-Ext-CONST             VALUE '.dll'.
275 GC0712 78 WS-OS-Lib-Type-CONST            VALUE 'DLL)'.
276 GC0712 01 WS-OS-Type-CD                   VALUE 5          PIC 9(1).
277 GC0712 >>ELIF OS = 'OSX'
278 GC0712 01 WS-OS-Dir-CHR                   VALUE '/'          PIC X(1).
279 GC0712 78 WS-OS-Exe-Ext-CONST             VALUE ' '.
280 GC0712 78 WS-OS-Lib-Ext-CONST             VALUE '.dylib'.
281 GC0712 78 WS-OS-Lib-Type-CONST            VALUE 'DYLIB)'.
282 GC0712 01 WS-OS-Type-CD                   VALUE 4          PIC 9(1).
283 GC0712 >>ELIF OS = 'UNIX'
284 GC0712 01 WS-OS-Dir-CHR                   VALUE '/'          PIC X(1).
285 GC0712 78 WS-OS-Exe-Ext-CONST             VALUE ' '.
286 GC0712 78 WS-OS-Lib-Ext-CONST             VALUE '.so'.
287 GC0712 78 WS-OS-Lib-Type-CONST            VALUE 'SO)'.
288 GC0712 01 WS-OS-Type-CD                   VALUE 3          PIC 9(1).
289 GC0712 >>ELIF OS = 'WINDOWS'
290 GC0712 01 WS-OS-Dir-CHR                   VALUE '\\'         PIC X(1).
291 GC0712 78 WS-OS-Exe-Ext-CONST             VALUE '.exe'.
292 GC0712 78 WS-OS-Lib-Ext-CONST             VALUE '.dll'.
293 GC0712 78 WS-OS-Lib-Type-CONST            VALUE 'DLL)'.
294 GC0712 01 WS-OS-Type-CD                   VALUE 1          PIC 9(1).
295 GC0712 >>END-IF
296 GC0909      88 WS-OS-Windows-BOOL VALUE 1, 5.
=====

```

GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL

Page: 8

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 9

```

=====
297 GC0909      88 WS-OS-Cygwin-BOOL  VALUE 2.
298 GC0712      88 WS-OS-UNIX-BOOL   VALUE 3, 4.
299 GC0712      88 WS-OS-OSX-BOOL    VALUE 4.
300
301          01 WS-OS-Type-FILLER-TXT.
302              05 VALUE 'Windows'          PIC X(14).
303              05 VALUE 'Windows/Cygwin'    PIC X(14).
304              05 VALUE 'UNIX/Linux'       PIC X(14).
305              05 VALUE 'OSX'              PIC X(14).
306              05 VALUE 'Windows/MinGW'    PIC X(14).
307          01 WS-OS-Types-TXT REDEFINES WS-OS-Type-FILLER-TXT.
308              05 WS-OS-Type-TXT          OCCURS 5 TIMES
309                                      PIC X(14).
310
311          01 WS-Output-Msg-TXT          PIC X(80).
312
313          01 WS-Path-Delimiter-CHR      PIC X(1).
314
315          01 WS-Prog-Extension-TXT      PIC X(256).
316
317          01 WS-Prog-Folder-TXT         PIC X(256).
318
319 GC0712 01 WS-Prog-File-Name-TXT.
320 GC0712      05 WS-PFN-CHR              OCCURS 256 TIMES
321 GC0712                                      PIC X(1).
322
323 GC0712 01 WS-Pgm-Nm-TXT                PIC X(31).
324
325          01 WS-Runtime-Switches-TXT.
326              05 WS-RS-Compile-OK-CHR    PIC X(1).
327                  88 WS-RS-Compile-OK-BOOL VALUE 'Y'.
328 GC0909      88 WS-RS-Compile-OK-Warn-BOOL VALUE 'W'.
329                  88 WS-RS-Compile-Failed-BOOL VALUE 'N'.
330 GC0609      05 WS-RS-Complete-CHR       PIC X(1).
331 GC0609      88 WS-RS-Complete-BOOL      VALUE 'Y'.
332 GC0609      88 WS-RS-Not-Complete-BOOL  VALUE 'N'.
333 GC0712      05 WS-RS-Quote-CHR          PIC X(1).
334 GC0712      88 WS-RS-Double-Quote-Used-BOOL VALUE 'Y' FALSE 'N'.
335 GC0809      05 WS-RS-IDENT-DIV-CHR      PIC X(1).
336 GC0809      88 WS-RS-1st-Prog-Complete-BOOL VALUE 'Y'.
337 GC0809      88 WS-RS-More-To-1st-Prog-BOOL VALUE 'N'.
338          05 WS-RS-No-Switch-Chgs-CHR    PIC X(1).
339              88 WS-RS-No-Switch-Changes-BOOL VALUE 'Y'.
340              88 WS-RS-Switch-Changes-BOOL VALUE 'N'.
341 GC0709      05 WS-RS-Output-File-Busy-CHR PIC X(1).
342 GC0709      88 WS-RS-Output-File-Busy-BOOL VALUE 'Y'.
343 GC0709      88 WS-RS-Output-File-Avail-BOOL VALUE 'N'.
344 GC0809      05 WS-RS-Source-Record-Type-CHR PIC X(1).
345 GC0809      88 WS-RS-Source-Rec-Linkage-BOOL VALUE 'L'.
346 GC0809      88 WS-RS-Source-Rec-Ident-BOOL VALUE 'I'.
347 GC0712      88 WS-RS-Source-Rec-Ignored-BOOL VALUE ' '.
348          05 WS-RS-Switch-Error-CHR      PIC X(1).
349              88 WS-RS-Switch-Is-Bad-BOOL VALUE 'Y'.
=====

```

GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL

Page: 9

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 10

```
=====
350          88 WS-RS-Switch-Is-Good-BOOL      VALUE 'N'.
351
352      01  WS-Tally-QTY                        USAGE BINARY-LONG.
```

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 11

```

=====
354      SCREEN SECTION.
355      *>
356      *> Here is the layout of the GCic screen.
357      *>
358      *> The sample screen below shows how the screen would look if the LINEDRAW
359      *> configuration setting is set to a value of 2
360      *>
361      *> The following sample screen layout shows how the screen looks with line-drawing
362      *> characters disabled.
363      *>
364      *>          1          2          3          4          5          6          7          8
365      *>1234567890123456789012345678901234567890123456789012345678901234567890
366      *>=====
367      01 *> GCic (2011/07/11 08:52) - GNU COBOL V2.1 23NOV2013 Interactive Compilation
368      02 *>+-----+
369      03 *>| Folder:   E:\GNU COBOL\Samples                               |
370      04 *>| Filename: GCic.cbl                                           |
371      05 *>+-----+
372      06 *> Set/Clr Switches Via F1-F9; Set Config Via F12; ENTER Key Compiles; ESC Quits
373      07 *>+-----+
374      08 *>| F1  Assume WITH DEBUGGING MODE  F6  "FUNCTION" Is Optional      | Current |
375      09 *>| F2  Procedure+Statement Trace   F7  Enable All Warnings         | Config: |
376      10 *>| F3  Make A Library (DLL)        F8  Source Is Free-Format      | XXXXXXXX|
377      11 *>| F4  Execute If Compilation OK   F9  No COMP/BINARY Truncation   |         |
378      12 *>| F5  >Produce Listing (Landscape)                               |         |
379      13 *>+-----+
380      14 *> Extra "cobc" Switches, If Any ("-save-temps=xxx" Prevents Listings):
381      15 *>+-----+
382      16 *>| _____|
383      17 *>| _____|
384      18 *>+-----+
385      19 *> Program Execution Arguments, If Any:
386      20 *>+-----+
387      21 *>| _____|
388      22 *>| _____|
389      23 *>+-----+
390      24 *> GCic Copyright (C) 2009-2017, Gary L. Cutler, GPL
391      *>=====
392      *>1234567890123456789012345678901234567890123456789012345678901234567890
393      *>          1          2          3          4          5          6          7          8
394      *>
395      *> If this program is run on Windows, it must run with codepage 437 activated to
396      *> display the line-drawing characters. With a native Windows build or a
397      *> Windows/MinGW build, one could use the command 'chcp 437' to set that codepage
398      *> for display within a Windows console window (that should be the default though).
399      *> With a Windows/Cygwin build, set the environment variable CYGWIN to a value of
400      *> 'codepage:oem' (this cannot be done from within the program though - you will
401      *> have to use the 'Computer/Advanced System Settings/Environment Variables' (Vista
402      *> or Windows 7) function to define the variable. XP Users: use 'My Computer/
403      *> Properties/Advanced/Environment Variables'.
404      *>
405      *> OSX users may use line drawing characters in this and any GNU COBOL program
=====

```

GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL

Page: 11

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 12

```

=====
406      *> simply by setting their 'terminal' application's font to "Lucida Console".
407      *>
408      >>IF LINEDRAW IS EQUAL TO 0
409          78 LD-UL-Corner          VALUE ' '.
410          78 LD-LL-Corner          VALUE ' '.
411          78 LD-UR-Corner          VALUE ' '.
412          78 LD-LR-Corner          VALUE ' '.
413          78 LD-Upper-T            VALUE ' '.
414          78 LD-Lower-T            VALUE ' '.
415          78 LD-Horiz-Line         VALUE ' '.
416          78 LD-Vert-Line          VALUE ' '.
417      >>ELIF LINEDRAW IS EQUAL TO 1
418          78 LD-UL-Corner          VALUE X'DA'.
419          78 LD-LL-Corner          VALUE X'CO'.
420          78 LD-UR-Corner          VALUE X'BF'.
421          78 LD-LR-Corner          VALUE X'D9'.
422          78 LD-Upper-T            VALUE X'C2'.
423          78 LD-Lower-T            VALUE X'C1'.
424          78 LD-Horiz-Line         VALUE X'C4'.
425          78 LD-Vert-Line          VALUE X'B3'.
426      >>ELSE
427          78 LD-UL-Corner          VALUE '+'.
428          78 LD-LL-Corner          VALUE '+'.
429          78 LD-UR-Corner          VALUE '+'.
430          78 LD-LR-Corner          VALUE '+'.
431          78 LD-Upper-T            VALUE '+'.
432          78 LD-Lower-T            VALUE '+'.
433          78 LD-Horiz-Line         VALUE '-'.
434          78 LD-Vert-Line          VALUE '|'.
435      >>END-IF
436
437      01 S-Blank-SCR LINE 1 COLUMN 1 BLANK SCREEN.
438
439      01 S-Switches-SCR BACKGROUND-COLOR COB-COLOR-BLACK
440                          FOREGROUND-COLOR COB-COLOR-WHITE AUTO.
441      *>
442      *> GENERAL SCREEN FRAMEWORK
443      *>
444          03 BACKGROUND-COLOR COB-COLOR-BLACK
445              FOREGROUND-COLOR COB-COLOR-GREEN HIGHLIGHT.
446 GC0712      05 LINE 02 COL 01          VALUE LD-UL-Corner.
447 GC0712      05          COL 02 PIC X(78) FROM WS-Horizontal-Line-TXT.
448          05          COL 80          VALUE LD-UR-Corner.
449
450 GC0712      05 LINE 03 COL 01          VALUE LD-Vert-Line.
451          05          COL 80          VALUE LD-Vert-Line.
452
453 GC0712      05 LINE 04 COL 01          VALUE LD-Vert-Line.
454          05          COL 80          VALUE LD-Vert-Line.
455
456 GC0712      05 LINE 05 COL 01          VALUE LD-LL-Corner.
457 GC0712      05          COL 02 PIC X(78) FROM WS-Horizontal-Line-TXT.
458          05          COL 80          VALUE LD-LR-Corner.
=====

```

GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL

Page: 12

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 13

```

=====
459
460 GC0712      05 LINE 07 COL 01      VALUE LD-UL-Corner.
461 GC0712      05          COL 02 PIC X(65) FROM WS-Horizontal-Line-TXT.
462 GC0712      05          COL 67      VALUE LD-Upper-T.
463 GC0712      05          COL 68 PIC X(12) FROM WS-Horizontal-Line-TXT.
464            05          COL 80      VALUE LD-UR-Corner.
465
466 GC0712      05 LINE 08 COL 01      VALUE LD-Vert-Line.
467 GC0712      05          COL 67      VALUE LD-Vert-Line.
468            05          COL 80      VALUE LD-Vert-Line.
469
470 GC0712      05 LINE 09 COL 01      VALUE LD-Vert-Line.
471 GC0712      05          COL 67      VALUE LD-Vert-Line.
472            05          COL 80      VALUE LD-Vert-Line.
473
474 GC0712      05 LINE 10 COL 01      VALUE LD-Vert-Line.
475 GC0712      05          COL 67      VALUE LD-Vert-Line.
476            05          COL 80      VALUE LD-Vert-Line.
477
478 GC0712      05 LINE 11 COL 01      VALUE LD-Vert-Line.
479 GC0712      05          COL 67      VALUE LD-Vert-Line.
480            05          COL 80      VALUE LD-Vert-Line.
481
482 GC0712      05 LINE 12 COL 01      VALUE LD-Vert-Line.
483 GC0712      05          COL 67      VALUE LD-Vert-Line.
484            05          COL 80      VALUE LD-Vert-Line.
485
486 GC0712      05 LINE 13 COL 01      VALUE LD-LL-Corner.
487 GC0712      05          COL 02 PIC X(65) FROM WS-Horizontal-Line-TXT.
488 GC0712      05          COL 67      VALUE LD-Lower-T.
489 GC0712      05          COL 68 PIC X(12) FROM WS-Horizontal-Line-TXT.
490            05          COL 80      VALUE LD-LR-Corner.
491
492 GC0712      05 LINE 15 COL 01      VALUE LD-UL-Corner.
493 GC0712      05          COL 02 PIC X(78) FROM WS-Horizontal-Line-TXT.
494            05          COL 80      VALUE LD-UR-Corner.
495
496 GC0712      05 LINE 16 COL 01      VALUE LD-Vert-Line.
497            05          COL 80      VALUE LD-Vert-Line.
498
499 GC0712      05 LINE 17 COL 01      VALUE LD-Vert-Line.
500            05          COL 80      VALUE LD-Vert-Line.
501
502 GC0712      05 LINE 18 COL 01      VALUE LD-LL-Corner.
503 GC0712      05          COL 02 PIC X(78) FROM WS-Horizontal-Line-TXT.
504            05          COL 80      VALUE LD-LR-Corner.
505
506 GC0712      05 LINE 20 COL 01      VALUE LD-UL-Corner.
507 GC0712      05          COL 02 PIC X(78) FROM WS-Horizontal-Line-TXT.
508            05          COL 80      VALUE LD-UR-Corner.
509
510 GC0712      05 LINE 21 COL 01      VALUE LD-Vert-Line.
511            05          COL 80      VALUE LD-Vert-Line.
=====

```

GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL

Page: 13

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 14

```

=====
512
513 GC0712      05 LINE 22 COL 01      VALUE LD-Vert-Line.
514            05          COL 80      VALUE LD-Vert-Line.
515
516 GC0712      05 LINE 23 COL 01      VALUE LD-LL-Corner.
517 GC0712      05          COL 02 PIC X(78) FROM WS-Horizontal-Line-TXT.
518            05          COL 80      VALUE LD-LR-Corner.
519      *>
520      *> TOP AND BOTTOM LINES
521      *>
522 GC0712      03 BACKGROUND-COLOR COB-COLOR-BLUE
523            FOREGROUND-COLOR COB-COLOR-WHITE HIGHLIGHT.
524 GC0410      05 LINE 01 COL 01 VALUE ' GCic ('.
525 GC0410      05          COL 08 PIC X(16) FROM WS-OC-Compile-DT.
526 GC1213      05          COL 24 VALUE ') GNUCOBOL 2.2 20JUL2017 ' &
527 GC0410            'Interactive Compilation          '.
528 VC0617      03 BACKGROUND-COLOR COB-COLOR-RED
529 GC0712      FOREGROUND-COLOR COB-COLOR-WHITE HIGHLIGHT.
530 GC0712      05 LINE 24 COL 01 PIC X(80) FROM WS-Output-Msg-TXT.
531      *>
532      *> LABELS
533      *>
534      03 BACKGROUND-COLOR COB-COLOR-BLACK
535            FOREGROUND-COLOR COB-COLOR-CYAN  HIGHLIGHT.
536 GC0712      05 LINE 06 COL 02 VALUE 'Set/Clr Switches Via F1-F9; ' &
537 GC0712            'Set Config Via F12; Enter Key ' &
538 GC0712            'Compiles; Esc Quits'.
539 GC0712      05 LINE 14 COL 02 VALUE 'Extra "cobc" Switches, If Any ' &
540 GC0712            '("-save-temps=xxx" Prevents ' &
541 GC0712            'Listings):'.
542 GC0712      05 LINE 19 COL 02 VALUE 'Program Execution Arguments, ' &
543 GC0712            'If Any:'.
544 GC0712      03 BACKGROUND-COLOR COB-COLOR-BLACK
545 GC0712      FOREGROUND-COLOR COB-COLOR-WHITE HIGHLIGHT.
546 GC0712      05 LINE 06 COL 23 VALUE 'F1'.
547 GC0712      05          COL 26 VALUE 'F9'.
548 GC0712      05          COL 45 VALUE 'F12'.
549 GC0712      05          COL 50 VALUE 'ENTER'.
550 GC0712      05          COL 70 VALUE 'ESC'.
551      *>
552      *> TOP SECTION BACKGROUND
553      *>
554      03 BACKGROUND-COLOR COB-COLOR-BLACK
555            FOREGROUND-COLOR COB-COLOR-WHITE HIGHLIGHT.
556 GC0712      05 LINE 03 COL 62 VALUE 'Enter'.
557 GC0712      05 LINE 04 COL 62 VALUE 'Esc'.
558
559      03 BACKGROUND-COLOR COB-COLOR-BLACK
560            FOREGROUND-COLOR COB-COLOR-GREEN HIGHLIGHT.
561 GC0712      05 LINE 04 COL 03 VALUE 'Folder: '.
562 GC0712      05 LINE 03 COL 03 VALUE 'Filename: '.
563
564 GC0712      05 LINE 03 COL 67 VALUE ': Compile '.
=====

```

GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL

Page: 14

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 15

```

=====
565 GC0712      05 LINE 04 COL 65 VALUE ': Quit      '.
566      *>
567      *> TOP SECTION PROGRAM INFO
568      *>
569      03 BACKGROUND-COLOR COB-COLOR-BLACK
570      FOREGROUND-COLOR COB-COLOR-WHITE HIGHLIGHT.
571 GC0712      05 LINE 03 COL 13 PIC X(66) FROM WS-Prog-File-Name-TXT.
572 GC0712      05 LINE 04 COL 13 PIC X(66) FROM WS-Prog-Folder-TXT.
573      *>
574      *> MIDDLE LEFT SECTION F-KEYS
575      *>
576      03 BACKGROUND-COLOR COB-COLOR-BLACK
577      FOREGROUND-COLOR COB-COLOR-WHITE HIGHLIGHT.
578 GC0712      05 LINE 08 COL 03 VALUE 'F1'.
579 GC0712      05 LINE 09 COL 03 VALUE 'F2'.
580 GC0712      05 LINE 10 COL 03 VALUE 'F3'.
581 GC0712      05 LINE 11 COL 03 VALUE 'F4'.
582 GC0712      05 LINE 12 COL 03 VALUE 'F5'.
583
584 GC0712      05 LINE 08 COL 35 VALUE 'F6'.
585 GC0712      05 LINE 09 COL 35 VALUE 'F7'.
586 GC0712      05 LINE 10 COL 35 VALUE 'F8'.
587 GC0712      05 LINE 11 COL 35 VALUE 'F9'.
588      *>
589      *> MIDDLE LEFT SECTION SWITCHES
590      *>
591      03 BACKGROUND-COLOR COB-COLOR-BLACK
592      FOREGROUND-COLOR COB-COLOR-RED HIGHLIGHT.
593 GC0712      05 LINE 08 COL 06 PIC X(1) FROM WS-CS-DEBUG-CHR.
594 GC0712      05 LINE 09 COL 06 PIC X(1) FROM WS-CS-TRACEALL-CHR.
595 GC0712      05 LINE 10 COL 06 PIC X(1) FROM WS-CS-LIBRARY-CHR.
596 GC0712      05 LINE 11 COL 06 PIC X(1) FROM WS-CS-EXECUTE-CHR.
597 GC0712      05 LINE 12 COL 06 PIC X(1) FROM WS-CS-LISTING-CHR.
598
599 GC0712      05 LINE 08 COL 38 PIC X(1) FROM WS-CS-NOFUNC-CHR.
600 GC0712      05 LINE 09 COL 38 PIC X(1) FROM WS-CS-WARNALL-CHR.
601 GC0712      05 LINE 10 COL 38 PIC X(1) FROM WS-CS-FREE-CHR.
602 GC0712      05 LINE 11 COL 38 PIC X(1) FROM WS-CS-NOTRUNC-CHR.
603      *>
604      *> MIDDLE LEFT SECTION BACKGROUND
605      *>
606      03 BACKGROUND-COLOR COB-COLOR-BLACK
607      FOREGROUND-COLOR COB-COLOR-GREEN HIGHLIGHT.
608 GC0712      05 LINE 08 COL 07 VALUE 'Assume WITH DEBUGGING MODE'.
609 GC0712      05 LINE 09 COL 07 VALUE 'Procedure+Statement Trace '.
610 GC0712      05 LINE 10 COL 07 VALUE 'Make a Library ('.
611 GC0712      05 COL 23 VALUE WS-OS-Lib-Type-CONST.
612 GC0712      05 LINE 11 COL 07 VALUE 'Execute If Compilation OK '.
613 GC1213      05 LINE 12 COL 07 FROM WS-Listing-TXT.
614
615 GC0712      05 LINE 08 COL 39 VALUE '"FUNCTION" Is Optional '.
616 GC0712      05 LINE 09 COL 39 VALUE 'Enable All Warnings '.
617 GC0712      05 LINE 10 COL 39 VALUE 'Source Is Free-Format '.
=====

```

GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL

Page: 15

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 16

```

=====
618 GC0712      05 LINE 11 COL 39 VALUE 'No COMP/BINARY Truncation '.
619      *>
620      *> MIDDLE RIGHT SECTION Text
621      *>
622      03 BACKGROUND-COLOR COB-COLOR-BLACK
623      FOREGROUND-COLOR COB-COLOR-GREEN HIGHLIGHT.
624 GC0712      05 LINE 08 COL 69 VALUE 'Current'.
625 GC0712      05 LINE 09 COL 69 VALUE 'Config:'.
626      *>
627      *> MIDDLE RIGHT SECTION CONFIG FILE
628      *>
629      03 BACKGROUND-COLOR COB-COLOR-BLACK
630      FOREGROUND-COLOR COB-COLOR-WHITE HIGHLIGHT.
631 GC0712      05 LINE 10 COL 69 PIC X(10)
632 GC0712      FROM WS-CS-Filename-TXT (WS-CS-Config-NUM).
633      *>
634      *> FREE-FORM OPTIONS FIELDS
635      *>
636      03 BACKGROUND-COLOR COB-COLOR-BLACK
637      FOREGROUND-COLOR COB-COLOR-WHITE HIGHLIGHT.
638 GC0712      05 LINE 16 COL 03 PIC X(76) USING WS-CS-Extra-H1-TXT.
639 GC0712      05 LINE 17 COL 03 PIC X(76) USING WS-CS-Extra-H2-TXT.
640 GC0712      05 LINE 21 COL 03 PIC X(76) USING WS-CS-Arg-H1-TXT.
641 GC0712      05 LINE 22 COL 03 PIC X(76) USING WS-CS-Arg-H2-TXT.
=====

```

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 17

```

=====
643      PROCEDURE DIVISION.
644      *>*****
645      *> Legend to procedure names:                **
646      *>                                           **
647      *> 00x-xxx  All MAIN driver procedures        **
648      *> 0xx-xxx  All GLOBAL UTILITY procedures    **
649      *> 1xx-xxx  All INITIALIZATION procedures    **
650      *> 2xx-xxx  All CORE PROCESSING procedures   **
651      *> 9xx-xxx  All TERMINATION procedures       **
652      *>*****
653      DECLARATIVES.
654      000-File-Error SECTION.
655          USE AFTER STANDARD ERROR PROCEDURE ON F-Source-Code-FILE.
656          COPY FileStat-Msgs
657              REPLACING STATUS BY WS-FSM-Status-CD
658              MSG      BY WS-FSM-Msg-TXT.
        EVALUATE WS-FSM-Status-CD
        WHEN 00 MOVE 'SUCCESS'                ' TO WS-FSM-Msg-TXT
        WHEN 02 MOVE 'SUCCESS DUPLICATE'      ' TO WS-FSM-Msg-TXT
        WHEN 04 MOVE 'SUCCESS INCOMPLETE'     ' TO WS-FSM-Msg-TXT
        WHEN 05 MOVE 'SUCCESS OPTIONAL'       ' TO WS-FSM-Msg-TXT
        WHEN 07 MOVE 'SUCCESS NO UNIT'        ' TO WS-FSM-Msg-TXT
        WHEN 10 MOVE 'END OF FILE'            ' TO WS-FSM-Msg-TXT
        WHEN 14 MOVE 'OUT OF KEY RANGE'       ' TO WS-FSM-Msg-TXT
        WHEN 21 MOVE 'KEY INVALID'            ' TO WS-FSM-Msg-TXT
        WHEN 22 MOVE 'KEY EXISTS'             ' TO WS-FSM-Msg-TXT
        WHEN 23 MOVE 'KEY NOT EXISTS'         ' TO WS-FSM-Msg-TXT
        WHEN 30 MOVE 'PERMANENT ERROR'        ' TO WS-FSM-Msg-TXT
        WHEN 31 MOVE 'INCONSISTENT FILENAME'  ' TO WS-FSM-Msg-TXT
        WHEN 34 MOVE 'BOUNDARY VIOLATION'     ' TO WS-FSM-Msg-TXT
        WHEN 35 MOVE 'FILE NOT FOUND'        ' TO WS-FSM-Msg-TXT
        WHEN 37 MOVE 'PERMISSION DENIED'      ' TO WS-FSM-Msg-TXT
        WHEN 38 MOVE 'CLOSED WITH LOCK'      ' TO WS-FSM-Msg-TXT
        WHEN 39 MOVE 'CONFLICT ATTRIBUTE'     ' TO WS-FSM-Msg-TXT
        WHEN 41 MOVE 'ALREADY OPEN'          ' TO WS-FSM-Msg-TXT
        WHEN 42 MOVE 'NOT OPEN'              ' TO WS-FSM-Msg-TXT
        WHEN 43 MOVE 'READ NOT DONE'         ' TO WS-FSM-Msg-TXT
        WHEN 44 MOVE 'RECORD OVERFLOW'       ' TO WS-FSM-Msg-TXT
        WHEN 46 MOVE 'READ ERROR'            ' TO WS-FSM-Msg-TXT
        WHEN 47 MOVE 'INPUT DENIED'          ' TO WS-FSM-Msg-TXT
        WHEN 48 MOVE 'OUTPUT DENIED'         ' TO WS-FSM-Msg-TXT
        WHEN 49 MOVE 'I/O DENIED'            ' TO WS-FSM-Msg-TXT
        WHEN 51 MOVE 'RECORD LOCKED'         ' TO WS-FSM-Msg-TXT
        WHEN 52 MOVE 'END-OF-PAGE'           ' TO WS-FSM-Msg-TXT
        WHEN 57 MOVE 'I/O LINAGE'            ' TO WS-FSM-Msg-TXT
        WHEN 61 MOVE 'FILE SHARING FAILURE'  ' TO WS-FSM-Msg-TXT
        WHEN 91 MOVE 'FILE NOT AVAILABLE'    ' TO WS-FSM-Msg-TXT
        END-EVALUATE.
659      MOVE SPACES TO WS-Output-Msg-TXT
660      IF WS-FSM-Status-CD = 35
661          DISPLAY
662              'File not found: ''
=====

```

GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL

Page: 17

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 18

```

=====
663          TRIM(WS-File-Name-TXT,TRAILING)
664          ', '
665      ELSE
666          DISPLAY
667          'Error accessing file: '
668          TRIM(WS-File-Name-TXT,TRAILING)
669          ', '
670      END-IF
671      GOBACK
672      .
673  END DECLARATIVES.
674
675  000-Main SECTION.
676      PERFORM 100-Initialization
677  GC0609      SET WS-RS-Not-Complete-BOOL TO TRUE
678  GC0609      PERFORM UNTIL WS-RS-Complete-BOOL
679  GC0609          PERFORM 200-Let-User-Set-Switches
680  GC0609          PERFORM 210-Run-Compiler
681  GC0410          IF (WS-RS-Compile-OK-BOOL OR WS-RS-Compile-OK-Warn-BOOL)
682  GC0712              AND (WS-CS-LISTING-CHR > SPACE)
683  GC0712                  DISPLAY S-Blank-SCR
684  GC0410                  PERFORM 220-Make-Listing
685  GC0410          END-IF
686  GC0709          IF (WS-CS-EXECUTE-CHR NOT = SPACES)
687  GC0709              AND (WS-RS-Output-File-Avail-BOOL)
688  GC0609                  PERFORM 230-Run-Program
689  GC0609          END-IF
690  GC0712          PERFORM 250-Autoload-Listing
691  GC0609      END-PERFORM
692      PERFORM 900-Terminate
693      * -- Control will NOT return
694      .
=====

```

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 19

```

=====
696      *>*****
697      *> Perform all program-wide initialization operations      **
698      *>*****
699      100-Initialization SECTION.
700      *>*****
701      *> Make sure full screen-handling is in effect      **
702      *>*****
703      SET ENVIRONMENT 'COB_SCREEN_EXCEPTIONS' TO 'Y'
704      SET ENVIRONMENT 'COB_SCREEN_ESC' TO 'Y'
705 VC0617 SET ENVIRONMENT "COB_EXIT_WAIT" TO "0".
706      *>*****
707      *> Get GCic Compilation Date/Time      **
708      *>*****
709      MOVE WHEN-COMPILED (1:12) TO WS-OC-Compile-DT
710      INSPECT WS-OC-Compile-DT
711      REPLACING ALL '/' BY ':'
712      AFTER INITIAL SPACE
713      *>*****
714      *> Convert WS-CS-All-Switches-TXT to Needed Alphanumeric Values**
715      *>*****
716      INSPECT WS-CS-All-Switches-TXT
717      REPLACING ALL '0' BY SPACE
718      ALL '1' BY SELCHAR
719 GC1213 ALL '2' BY SELCHAR
720      *>*****
721      *> Process filename (the only command-line argument)      **
722      *>*****
723 GC0712 ACCEPT WS-Cmd-Args-TXT FROM COMMAND-LINE
724 GC0712 MOVE 1 TO WS-Cmd-SUB
725 GC0712 IF WS-Cmd-Args-TXT(WC-Cmd-SUB:1) = '"' OR '"'
726 GC0712 MOVE WS-Cmd-Args-TXT(WC-Cmd-SUB:1)
727 GC0712 TO WS-Cmd-End-Quote-CHR
728 GC0712 ADD 1 TO WS-Cmd-SUB
729 GC0712 UNSTRING WS-Cmd-Args-TXT
730 GC0712 DELIMITED BY WS-Cmd-End-Quote-CHR
731 GC0712 INTO WS-File-Name-TXT
732 GC0712 WITH POINTER WS-Cmd-SUB
733 GC0712 ELSE
734 GC0712 UNSTRING WS-Cmd-Args-TXT
735 GC0712 DELIMITED BY ALL SPACES
736 GC0712 INTO WS-File-Name-TXT
737 GC0712 WITH POINTER WS-Cmd-SUB
738 GC0712 END-IF
739 IF WS-File-Name-TXT = SPACES
740 GC0712 DISPLAY 'No program filename was specified'
741 PERFORM 900-Terminate
742 * ----- Control will NOT return
743 END-IF
744      *>*****
745      *> Determine if 'Make A Library' feature should be forced 'ON' **
746      *>*****
747      PERFORM 240-Find-LINKAGE-SECTION
=====

```

GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL

Page: 19

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 20

```

=====
748      *>*****
749      *> Split 'WS-File-Name-TXT' into 'WS-Prog-Folder-TXT' and      **
750      *> 'WS-Prog-File-Name-TXT'                                     **
751      *>*****
752 GC0909      IF WS-OS-Cygwin-BOOL AND WS-File-Name-TXT (2:1) = ':'
753 GC0712          MOVE '\' TO WS-OS-Dir-CHR
754 GC0909      END-IF
755 GC0712      MOVE LENGTH(WS-File-Name-TXT) TO WS-I-SUB
756 GC0712      PERFORM UNTIL WS-I-SUB = 0
757 GC0712          OR WS-FN-CHR (WS-I-SUB) = WS-OS-Dir-CHR
758              SUBTRACT 1 FROM WS-I-SUB
759      END-PERFORM
760      IF WS-I-SUB = 0
761          MOVE SPACES      TO WS-Prog-Folder-TXT
762          MOVE WS-File-Name-TXT TO WS-Prog-File-Name-TXT
763      ELSE
764          MOVE '*' TO WS-FN-CHR (WS-I-SUB)
765          UNSTRING WS-File-Name-TXT DELIMITED BY '*'
766              INTO WS-Prog-Folder-TXT
767                  WS-Prog-File-Name-TXT
768 GC0712      MOVE WS-OS-Dir-CHR TO WS-FN-CHR (WS-I-SUB)
769      END-IF
770      IF WS-Prog-Folder-TXT = SPACES
771          ACCEPT WS-Prog-Folder-TXT FROM ENVIRONMENT 'CD'
772 GC0909      ELSE
773 GC0909          CALL 'CBL_CHANGE_DIR'
774 GC0909              USING TRIM(WS-Prog-Folder-TXT,TRAILING)
775      END-IF
776 GC0909      IF WS-OS-Cygwin-BOOL AND WS-File-Name-TXT (2:1) = ':'
777 GC0712          MOVE '/' TO WS-OS-Dir-CHR
778 GC0909      END-IF
779      *>*****
780      *> Split 'WS-Prog-File-Name-TXT' into 'WS-Pgm-Nm-TXT' &      **
781      *> 'WS-Prog-Extension-TXT'                                     **
782      *>*****
783 GC0712      MOVE LENGTH(WS-Prog-File-Name-TXT) TO WS-I-SUB
784 GC0712      PERFORM UNTIL WS-I-SUB = 0
785 GC0712          OR WS-PFN-CHR (WS-I-SUB) = '.'
786 GC0712              SUBTRACT 1 FROM WS-I-SUB
787 GC0712      END-PERFORM
788 GC0712      IF WS-I-SUB = 0
789 GC0712          MOVE WS-Prog-File-Name-TXT TO WS-Pgm-Nm-TXT
790 GC0712          MOVE SPACES      TO WS-Prog-Extension-TXT
791 GC0712      ELSE
792 GC0712          MOVE '*' TO WS-PFN-CHR (WS-I-SUB)
793 GC0712          UNSTRING WS-Prog-File-Name-TXT DELIMITED BY '*'
794 GC0712              INTO WS-Pgm-Nm-TXT
795 GC0712                  WS-Prog-Extension-TXT
796 GC0712          MOVE '.' TO WS-PFN-CHR (WS-I-SUB)
797 GC0712      END-IF
798      *>*****
799      *> Build initial Line 24 Message                                **
800      *>*****
=====

```

GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL

Page: 20

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 21

```

=====
801 GC0909      MOVE ALL LD-Horiz-Line TO WS-Horizontal-Line-TXT.
802 GC0410      MOVE CONCATENATE(' GCic for '
803 GC0410                        TRIM(WS-OS-Type-TXT(WS-OS-Type-CD),Trailing)
804 GC1213                        ' Copyright (C) 2009-2017, Gary L. '
805 GC0410                        'Cutler, GPL')
806 GC0410      TO WS-Output-Msg-TXT.
807 GC0909
=====

```

```

=====
GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL

```

Page: 21

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 22

```

=====
809      *>*****
810      *> Show the user the current switch settings and allow them to **
811      *> be changed.                                          **
812      *>*****
813      200-Let-User-Set-Switches SECTION.
814          SET WS-RS-Switch-Changes-BOOL TO TRUE
815          PERFORM UNTIL WS-RS-No-Switch-Changes-BOOL
816 GC1213      EVALUATE WS-Listing-CD
817 GC1213      WHEN 0
818 GC1213          MOVE 'Listing Off'          TO WS-Listing-TXT
819 GC1213          MOVE SPACE                  TO WS-CS-LISTING-CHR
820 GC1213      WHEN 1
821 GC1213          MOVE 'Listing On (Landscape)' TO WS-Listing-TXT
822 GC1213          MOVE SELCHAR                TO WS-CS-LISTING-CHR
823 GC1213      WHEN 2
824 GC1213          MOVE 'Listing On (Portrait)' TO WS-Listing-TXT
825 GC1213          MOVE SELCHAR                TO WS-CS-LISTING-CHR
826 GC1213      END-EVALUATE
827      ACCEPT S-Switches-SCR
828      IF COB-CRT-STATUS > 0
829          EVALUATE COB-CRT-STATUS
830              WHEN COB-SCR-F1
831                  IF WS-CS-DEBUG-CHR = SPACE
832 GC0712      MOVE SELCHAR TO WS-CS-DEBUG-CHR
833                  ELSE
834                      MOVE ' ' TO WS-CS-DEBUG-CHR
835                  END-IF
836 GC0712      WHEN COB-SCR-F2
837 GC0712          IF WS-CS-TRACEALL-CHR = SPACE
838 GC0712      MOVE SELCHAR TO WS-CS-TRACEALL-CHR
839 GC0712          ELSE
840 GC0712      MOVE ' ' TO WS-CS-TRACEALL-CHR
841 GC0712          END-IF
842      WHEN COB-SCR-F3
843 GC0712          IF WS-CS-LIBRARY-CHR = SPACE
844 GC0712      MOVE SELCHAR TO WS-CS-LIBRARY-CHR
845          ELSE
846 GC0712      MOVE ' ' TO WS-CS-LIBRARY-CHR
847          END-IF
848      WHEN COB-SCR-F4
849          IF WS-CS-EXECUTE-CHR = SPACE
850 GC0712      MOVE SELCHAR TO WS-CS-EXECUTE-CHR
851          ELSE
852          MOVE ' ' TO WS-CS-EXECUTE-CHR
853          END-IF
854 GC0712      WHEN COB-SCR-F5
855 GC1213      ADD 1 TO WS-Listing-CD
856 GC1213      IF WS-Listing-CD > 2
857 GC1213      MOVE 0 TO WS-Listing-CD
858 GC1213      END-IF
859 GC0712      WHEN COB-SCR-F6
860 GC0712      IF WS-CS-NOFUNC-CHR = SPACE

```

GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL

Page: 22

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 23

```

=====
861 GC0712          MOVE SELCHAR TO WS-CS-NOFUNC-CHR
862 GC0712          ELSE
863 GC0712          MOVE ' ' TO WS-CS-NOFUNC-CHR
864 GC0712          END-IF
865 GC0712          WHEN COB-SCR-F7
866 GC0712          IF WS-CS-WARNALL-CHR = SPACE
867 GC0712          MOVE SELCHAR TO WS-CS-WARNALL-CHR
868 GC0712          ELSE
869 GC0712          MOVE ' ' TO WS-CS-WARNALL-CHR
870 GC0712          END-IF
871 GC0712          WHEN COB-SCR-F8
872 GC0712          IF WS-CS-FREE-CHR = SPACE
873 GC0712          MOVE SELCHAR TO WS-CS-FREE-CHR
874 GC0712          ELSE
875 GC0712          MOVE ' ' TO WS-CS-FREE-CHR
876 GC0712          END-IF
877 GC0712          WHEN COB-SCR-F9
878 GC0712          IF WS-CS-NOTRUNC-CHR = SPACE
879 GC0712          MOVE SELCHAR TO WS-CS-NOTRUNC-CHR
880 GC0712          ELSE
881 GC0712          MOVE ' ' TO WS-CS-NOTRUNC-CHR
882 GC0712          END-IF
883          WHEN COB-SCR-ESC
884          PERFORM 900-Terminate
885          * ----- Control will NOT return
886 GC0712          WHEN COB-SCR-F12
887 GC0712          ADD 1 TO WS-CS-Config-NUM
888 GC0712          IF WS-CS-Config-NUM > 7
889 GC0712          MOVE 1 TO WS-CS-Config-NUM
890 GC0712          END-IF
891          WHEN OTHER
892          MOVE 'An unsupported key was pressed'
893          TO WS-Output-Msg-TXT
894          END-EVALUATE
895          ELSE
896          SET WS-RS-No-Switch-Changes-BOOL TO TRUE
897          END-IF
898          END-PERFORM
899          .
=====

```

GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL

Page: 23

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 24

```

=====
901      *>*****
902      *> Run the compiler using the switch settings we've prepared.  **
903      *>*****
904      210-Run-Compiler SECTION.
905          MOVE SPACES TO WS-Cmd-TXT
906              WS-Cobc-Cmd-TXT
907              WS-Output-Msg-TXT
908      DISPLAY S-Switches-SCR
909      MOVE 1 TO WS-I-SUB
910 GC0712      MOVE LOWER-CASE(WS-CS-Filename-TXT (WS-CS-Config-NUM))
911 GC0712      TO WS-Config-Fn-TXT
912      *>*****
913      *> Build the 'cobc' command **
914      *>*****
915 GC0909      MOVE SPACES TO WS-Cobc-Cmd-TXT
916 GC0909      STRING 'cobc -v -std='
917 GC0909          TRIM(WS-Config-Fn-TXT,TRAILING)
918 GC0909          ' '
919 GC0909          INTO WS-Cobc-Cmd-TXT
920 GC0909          WITH POINTER WS-I-SUB
921      IF WS-CS-LIBRARY-CHR NOT = ' '
922          STRING '-m '
923              DELIMITED SIZE INTO WS-Cobc-Cmd-TXT
924              WITH POINTER WS-I-SUB
925      ELSE
926          STRING '-x '
927              DELIMITED SIZE INTO WS-Cobc-Cmd-TXT
928              WITH POINTER WS-I-SUB
929      END-IF
930      IF WS-CS-DEBUG-CHR NOT = ' '
931          STRING '-fdebugging-line '
932              DELIMITED SIZE INTO WS-Cobc-Cmd-TXT
933              WITH POINTER WS-I-SUB
934      END-IF
935      IF WS-CS-NOTRUNC-CHR NOT = ' '
936          STRING '-fnotrunc '
937              DELIMITED SIZE INTO WS-Cobc-Cmd-TXT
938              WITH POINTER WS-I-SUB
939      END-IF
940      IF WS-CS-TRACEALL-CHR NOT = ' '
941 GC0809      STRING '-ftraceall '
942              DELIMITED SIZE INTO WS-Cobc-Cmd-TXT
943              WITH POINTER WS-I-SUB
944      END-IF
945 GC0712      IF WS-CS-NOFUNC-CHR NOT = ' '
946 VC0717      STRING '-fintrinsics=ALL '
947 GC0712          DELIMITED SIZE INTO WS-Cobc-Cmd-TXT
948 GC0712          WITH POINTER WS-I-SUB
949 GC0712      END-IF
950 GC0712      IF WS-CS-WARNALL-CHR NOT = ' '
951 GC0712          STRING '-Wall '
952 GC0712          DELIMITED SIZE INTO WS-Cobc-Cmd-TXT
=====

```

GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL

Page: 24

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 25

```

=====
 953 GC0712          WITH POINTER WS-I-SUB
 954 GC0712      END-IF
 955 GC0712      IF WS-CS-FREE-CHR NOT = ' '
 956 GC0712          STRING '-free '
 957 GC0712          DELIMITED SIZE INTO WS-Cobc-Cmd-TXT
 958 GC0712          WITH POINTER WS-I-SUB
 959 GC0712      ELSE
 960 GC0712          STRING '-fixed '
 961 GC0712          DELIMITED SIZE INTO WS-Cobc-Cmd-TXT
 962 GC0712          WITH POINTER WS-I-SUB
 963 GC0712      END-IF
 964
 965 GC0712      MOVE 0 TO WS-Tally-QTY
 966 GC0712      INSPECT WS-CS-Extra-TXT
 967 GC0712          TALLYING WS-Tally-QTY FOR ALL '-save-temps'
 968 GC0712      IF WS-CS-LISTING-CHR > SPACE
 969 GC0712      AND WS-Tally-QTY > 0
 970 GC0712          MOVE SPACE TO WS-CS-LISTING-CHR *> Can't generate listing if -save-temps u
          sed
 971 GC0712      END-IF
 972 GC0712      IF WS-CS-LISTING-CHR > SPACE
 973 GC1010          STRING '-save-temps '
 974 GC1010          DELIMITED SIZE INTO WS-Cobc-Cmd-TXT
 975 GC1010          WITH POINTER WS-I-SUB
 976 GC1010      END-IF
 977
 978 GC0709      IF WS-CS-Extra-TXT > SPACES
 979 GC0709          STRING ' '
 980 GC0709          TRIM(WS-CS-Extra-TXT,TRAILING)
 981 GC0709          ' '
 982 GC0709          DELIMITED SIZE INTO WS-Cobc-Cmd-TXT
 983 GC0709          WITH POINTER WS-I-SUB
 984 GC0709      END-IF
 985 GC0909      STRING TRIM(WS-Prog-File-Name-TXT,TRAILING)
 986 GC0909          DELIMITED SIZE INTO WS-Cobc-Cmd-TXT
 987 GC0909          WITH POINTER WS-I-SUB
 988      *>*****
 989      *> Prepare the compilation listing file **
 990      *>*****
 991 GC1113      MOVE CONCATENATE(TRIM(WS-Pgm-Nm-TXT,Trailing),'.gclst')
 992 GC0712          TO WS-Listing-Filename-TXT
 993 GC0712      CALL 'CBL_DELETE_FILE' USING WS-Listing-Filename-TXT
 994      *>*****
 995      *> Now execute the 'cobc' command **
 996      *>*****
 997 GC0410      MOVE ' Compiling...' TO WS-Output-Msg-TXT
 998 GC0410      DISPLAY S-Switches-SCR
 999 GC0609      SET WS-RS-Output-File-Avail-BOOL TO TRUE
1000      MOVE SPACES TO WS-Cmd-TXT
1001      STRING TRIM(WS-Cobc-Cmd-TXT,TRAILING)
1002 GC0712          ' >' WS-Listing-Filename-TXT
1003 GC0712          ' 2>&1'
1004          DELIMITED SIZE
=====

```

GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL

Page: 25

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 26

```

=====
1005          INTO WS-Cmd-TXT
1006 DEBUG D   DISPLAY WS-Cmd-TXT UPON SYSERR
1007          CALL 'SYSTEM' USING TRIM(WS-Cmd-TXT,TRAILING)
1008 GC0712     OPEN EXTEND F-Cobc-Output-FILE
1009 GC0712     WRITE F-Cobc-Output-REC FROM SPACES
1010 GC0712     IF RETURN-CODE = 0
1011 GC0712         SET WS-RS-Compile-OK-BOOL TO TRUE
1012 GC0712         MOVE ' Compilation Was Successful' TO WS-Output-Msg-TXT
1013 GC0712         MOVE CONCATENATE('GNU COBOL',WS-Output-Msg-TXT)
1014 GC0712             TO F-Cobc-Output-REC
1015 GC0712         WRITE F-Cobc-Output-REC
1016 GC0712         SET WS-RS-Complete-BOOL TO TRUE
1017 GC0712     ELSE
1018 GC0712         SET WS-RS-Compile-Failed-BOOL TO TRUE
1019 GC0712         MOVE CONCATENATE(' Compilation Failed - See ',
1020             TRIM(WS-Listing-Filename-TXT,Trailing))
1021 GC0712             TO WS-Output-Msg-TXT
1022 GC0712         MOVE 'GNU COBOL Compilation HAS FAILED - See Above'
1023 GC0712             TO F-Cobc-Output-REC
1024 GC0712         WRITE F-Cobc-Output-REC
1025 GC0712     END-IF
1026 GC0712     CLOSE F-Cobc-Output-FILE
1027 GC0712     DISPLAY S-Switches-SCR
1028 GC0712     CALL 'C$SLEEP' USING 2
1029 GC0712     MOVE SPACES TO WS-Output-Msg-TXT
1030     IF WS-RS-Compile-Failed-BOOL
1031 GC0712         PERFORM 250-Autoload-Listing
1032         PERFORM 900-Terminate
1033     *> ----- Control will not return
1034     END-IF
1035     .
=====

```

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 27

```

=====
1037      *>*****
1038      *> Generate a source + xref listing using 'LISTING' subroutine **
1039      *>*****
1040 GC0410 220-Make-Listing SECTION.
1041 GC0410      MOVE ' Generating listing...' TO WS-Output-Msg-TXT
1042 GC0410      DISPLAY S-Switches-SCR
1043 GC0410      MOVE 0 TO RETURN-CODE
1044      *>*****
1045      *> Create the listing **
1046      *>*****
1047 GC0410      MOVE SPACES TO WS-Output-Msg-TXT
1048 GC0410      CALL 'LISTING' USING WS-Listing-Filename-TXT
1049 GC0712      WS-File-Name-TXT
1050 GC0712      WS-OS-Type-CD
1051 GC1213      LPP
1052 GC1213      LPPP
1053 GC1213      WS-Listing-CD
1054 GC0410      ON EXCEPTION
1055 GC0410      MOVE ' LISTING module is not available'
1056 GC0410      TO WS-Output-Msg-TXT
1057 GC0410      MOVE 1 TO RETURN-CODE
1058 GC0410      END-CALL
1059 GC0410      IF RETURN-CODE = 0
1060 GC0712      MOVE ' Source+Xref listing generated '
1061 GC0712      TO WS-Output-Msg-TXT
1062 GC0410      END-IF
1063 GC0712      DISPLAY S-Switches-SCR
1064 GC0712      CALL 'C$SLEEP' USING 2
1065 GC0712      PERFORM 250-Autoload-Listing
1066 GC0410      .

```

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 28

```

=====
1068      *>*****
1069      *> Run the compiled program                      **
1070      *>*****
1071      230-Run-Program SECTION.
1072 GC0114      MOVE ' Preparing to run program ... press ENTER to close '
1073 GC0114      TO WS-Output-Msg-TXT
1074 GC0114      DISPLAY S-Switches-SCR
1075 GC0114      CALL 'C$SLEEP' USING 3
1076 GC0909      MOVE SPACES TO WS-Cmd-TXT
1077 GC0909      MOVE 1 TO WS-I-SUB
1078      *>*****
1079      *> If necessary, start with 'cobcrun' command      **
1080      *>*****
1081 GC0712      IF WS-CS-LIBRARY-CHR NOT = ' '
1082              STRING 'cobcrun ' DELIMITED SIZE
1083              INTO WS-Cmd-TXT
1084              WITH POINTER WS-I-SUB
1085      END-IF
1086      *>*****
1087      *> Add any necessary path prefix                  **
1088      *>*****
1089 GC0712      SET WS-RS-Double-Quote-Used-BOOL TO FALSE
1090      IF WS-Prog-Folder-TXT NOT = SPACES
1091 GC0909      IF WS-OS-Cygwin-BOOL AND WS-Prog-Folder-TXT (2:1) = ':'
1092 GC0909      STRING '/cygdrive/'
1093 GC0909      INTO WS-Cmd-TXT
1094 GC0909      WITH POINTER WS-I-SUB
1095 GC0909      STRING LOWER-CASE(WS-Prog-Folder-TXT (1:1))
1096 GC0909      INTO WS-Cmd-TXT
1097 GC0909      WITH POINTER WS-I-SUB
1098 GC0909      PERFORM
1099 GC0909      VARYING WS-J-SUB FROM 3 BY 1
1100 GC0909      UNTIL WS-J-SUB > LENGTH(TRIM(WS-Prog-Folder-TXT))
1101 GC0909      IF WS-Prog-Folder-TXT (WS-J-SUB:1) = '\'
1102 GC0909      STRING '/'
1103 GC0909      INTO WS-Cmd-TXT
1104 GC0909      WITH POINTER WS-I-SUB
1105 GC0909      ELSE
1106 GC0909      STRING WS-Prog-Folder-TXT (WS-J-SUB:1)
1107 GC0909      INTO WS-Cmd-TXT
1108 GC0909      WITH POINTER WS-I-SUB
1109 GC0909      END-IF
1110 GC0909      END-PERFORM
1111 GC0909      ELSE
1112 GC0410      STRING '"' TRIM(WS-Prog-Folder-TXT,TRAILING)
1113 GC0909      INTO WS-Cmd-TXT
1114 GC0909      WITH POINTER WS-I-SUB
1115 GC0712      SET WS-RS-Double-Quote-Used-BOOL TO TRUE
1116 GC0909      END-IF
1117 GC0712      STRING WS-OS-Dir-CHR
1118 GC0909      INTO WS-Cmd-TXT
1119 GC0909      WITH POINTER WS-I-SUB
=====

```

GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL

Page: 28

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 29

```

=====
1120 GC0909      ELSE
1121 GC0909          IF WS-OS-Cygwin-BOOL OR WS-OS-UNIX-BOOL
1122 GC0909              STRING './'
1123 GC0909              INTO WS-Cmd-TXT
1124 GC0909              WITH POINTER WS-I-SUB
1125 GC0909          END-IF
1126 GC0909      END-IF
1127      *>*****
1128      *> Insert program filename **
1129      *>*****
1130 GC0909      STRING TRIM(WS-Pgm-Nm-TXT,TRAILING)
1131 GC0909          INTO WS-Cmd-TXT
1132 GC0909          WITH POINTER WS-I-SUB
1133      *>*****
1134      *> Insert proper extension **
1135      *>*****
1136 GC0712      IF WS-CS-LIBRARY-CHR = ' '
1137 GC0712          IF WS-OS-Exe-Ext-CONST > ' '
1138 GC0712              STRING WS-OS-Exe-Ext-CONST DELIMITED SPACE
1139 GC0712              INTO WS-Cmd-TXT
1140 GC0712              WITH POINTER WS-I-SUB
1141 GC0712          END-IF
1142 GC0712      ELSE
1143 GC0712          IF WS-OS-Lib-Ext-CONST > ' '
1144 GC0712              STRING WS-OS-Lib-Ext-CONST DELIMITED SPACE
1145 GC0712              INTO WS-Cmd-TXT
1146 GC0712              WITH POINTER WS-I-SUB
1147 GC0712          END-IF
1148 GC0712      END-IF
1149 GC0712      IF WS-RS-Double-Quote-Used-BOOL
1150 GC0712          STRING ''' DELIMITED SIZE
1151 GC0712          INTO WS-Cmd-TXT
1152 GC0712          WITH POINTER WS-I-SUB
1153 GC0712      END-IF
1154 GC0712      IF WS-CS-Args-TXT NOT = SPACES
1155 GC0809          STRING ' ' TRIM(WS-CS-Args-TXT,TRAILING)
1156 GC0809          INTO WS-Cmd-TXT
1157 GC0809          WITH POINTER WS-I-SUB
1158 GC0809      END-IF
1159      *>*****
1160      *> Run the program **
1161      *>*****
1162 GC0114      CALL X'E4'
1163 GC0114          CALL 'SYSTEM' USING TRIM(WS-Cmd-TXT,TRAILING)
1164 GC0114          MOVE SPACES TO WS-Output-Msg-TXT
1165 GC0114          ACCEPT WS-Output-Msg-TXT(1:1) AT 0101
1166 GC0114          PERFORM 900-Terminate
1167      * -- Control will NOT return
1168      .
=====

```

GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL

Page: 29

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 30

=====

```

1170      *>*****
1171      *> Determine if the program being compiled is a MAIN program  **
1172      *>*****
1173      240-Find-LINKAGE-SECTION SECTION.
1174      OPEN INPUT F-Source-Code-FILE
1175 GC0712  MOVE ' ' TO WS-CS-LIBRARY-CHR
1176      SET WS-RS-More-To-1st-Prog-BOOL TO TRUE
1177      PERFORM UNTIL WS-RS-1st-Prog-Complete-BOOL
1178          READ F-Source-Code-FILE AT END
1179          CLOSE F-Source-Code-FILE
1180          EXIT SECTION
1181      END-READ
1182 GC0712  CALL 'CHECKSRC'
1183 GC0712      USING BY CONTENT  F-Source-Code-REC
1184 GC0712          BY REFERENCE WS-RS-Source-Record-Type-CHR
1185      IF WS-RS-Source-Rec-Ident-BOOL
1186          SET WS-RS-1st-Prog-Complete-BOOL TO TRUE
1187      END-IF
1188      END-PERFORM
1189 GC0712  SET WS-RS-Source-Rec-Ignored-BOOL TO TRUE
1190      PERFORM UNTIL WS-RS-Source-Rec-Linkage-BOOL
1191          OR WS-RS-Source-Rec-Ident-BOOL
1192          READ F-Source-Code-FILE AT END
1193          CLOSE F-Source-Code-FILE
1194          EXIT SECTION
1195      END-READ
1196 GC0712  CALL 'CHECKSRC'
1197 GC0712      USING BY CONTENT  F-Source-Code-REC
1198 GC0712          BY REFERENCE WS-RS-Source-Record-Type-CHR
1199      END-PERFORM
1200      CLOSE F-Source-Code-FILE
1201      IF WS-RS-Source-Rec-Linkage-BOOL
1202 GC0712  MOVE SELCHAR TO WS-CS-LIBRARY-CHR
1203      END-IF
1204      .

```

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 31

=====

```

1206 GC0712*>*****
1207 GC0712*> Attempt to open the listing file as a command. This will - **
1208 GC1113*> if the user has associated filetype/extension 'gclst' with **
1209 GC0712*> an application - invoke the appropriate application to **
1210 GC0712*> allow the user to view the listing. **
1211 GC0712*>*****
1212 GC0712 250-Autoload-Listing SECTION.
1213 GC0712      EVALUATE TRUE
1214 GC0712          WHEN WS-OS-Windows-BOOL OR WS-OS-Cygwin-BOOL
1215 GC0712              MOVE SPACES TO WS-Cmd-TXT
1216 GC0712              STRING
1217 GC0712                  'cmd /c '
1218 GC0712                  TRIM(WS-Listing-Filename-TXT,TRAILING)
1219 GC0712                  DELIMITED SIZE INTO WS-Cmd-TXT
1220 GC0712                  CALL 'SYSTEM' USING TRIM(WS-Cmd-TXT,TRAILING)
1221 GC0712          WHEN WS-OS-OSX-BOOL
1222 GC0712              MOVE SPACES TO WS-Cmd-TXT
1223 GC0712              STRING
1224 GC0712                  'open -t '
1225 GC0712                  TRIM(WS-Listing-Filename-TXT,TRAILING)
1226 GC0712                  DELIMITED SIZE INTO WS-Cmd-TXT
1227 GC0712                  CALL 'SYSTEM' USING TRIM(WS-Cmd-TXT,TRAILING)
1228 GC0712      END-EVALUATE
1229 GC0712*> *****
1230 GC0712*> ** Since we had to do our own '-save-temps' when we **
1231 GC0712*> ** compiled (in order to generate the cross-reference **
1232 GC0712*> ** listing) we now need to clean up after ourselves. **
1233 GC0712*> *****
1234 GC1112      DISPLAY S-Blank-SCR
1235 GC0712      IF WS-OS-Windows-BOOL
1236 GC0712          MOVE CONCATENATE('del ',TRIM(WS-Pgm-Nm-TXT,TRAILING))
1237 GC0712              TO WS-Cmd-TXT
1238 GC0712      ELSE
1239 GC0712          MOVE CONCATENATE('rm ',TRIM(WS-Pgm-Nm-TXT,TRAILING))
1240 GC0712              TO WS-Cmd-TXT
1241 GC0712      END-IF
1242 GC0712      CALL 'SYSTEM'
1243 GC0712          USING CONCATENATE(TRIM(WS-Cmd-TXT,TRAILING),'.c')
1244 GC0712      CALL 'SYSTEM'
1245 GC0712          USING CONCATENATE(TRIM(WS-Cmd-TXT,TRAILING),'.c.h')
1246 GC0712      CALL 'SYSTEM'
1247 GC0712          USING CONCATENATE(TRIM(WS-Cmd-TXT,TRAILING),'.c.l*.h')
1248 GC0712      CALL 'SYSTEM'
1249 GC0712          USING CONCATENATE(TRIM(WS-Cmd-TXT,TRAILING),'.i')
1250 GC0712      CALL 'SYSTEM'
1251 GC0712          USING CONCATENATE(TRIM(WS-Cmd-TXT,TRAILING),'.o')
1252
1253 GC0712      .

```

```

=====
GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL
Page: 31

```


GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 32

=====

```
1255      *>*****
1256      *> Display a message and halt the program          **
1257      *>*****
1258      900-Terminate SECTION.
1259 GC0909      IF WS-Output-Msg-TXT > SPACES
1260 GC0909          DISPLAY S-Switches-SCR
1261 GC0909          CALL 'C$SLEEP' USING 2
1262 GC0909      END-IF
1263          DISPLAY S-Blank-SCR
1264          STOP RUN
1265          .
1266
1267      END PROGRAM GCic.
```

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 33

```

=====
1269      IDENTIFICATION DIVISION.
1270      PROGRAM-ID. CHECKSRC.
1271      *>*****
1272      *> This subprogram will scan a line of source code it is given **
1273      *> looking for 'LINKAGE SECTION' or 'IDENTIFICATION DIVISION'. **
1274      *> **
1275      *> ****NOTE**** ****NOTE**** ****NOTE**** ****NOTE*** **
1276      *> **
1277      *> These two strings must be found IN THEIR ENTIRETY within **
1278      *> the 1st 80 columns of program source records, and cannot **
1279      *> follow either a '>' sequence OR a '*' in col 7. **
1280      *>*****
1281      *> DATE CHANGE DESCRIPTION **
1282      *> ===== **
1283      *> GC0809 Initial coding. **
1284      *>*****
1285      ENVIRONMENT DIVISION.
1286      CONFIGURATION SECTION.
1287      REPOSITORY.
1288      FUNCTION ALL INTRINSIC.
1289      DATA DIVISION.
1290      WORKING-STORAGE SECTION.
1291      01 WS-Compressed-Src-TXT.
1292          05 WS-CS-CHR OCCURS 80 TIMES
1293                      PIC X(1).
1294
1295      01 WS-Runtime-Switches-TXT.
1296          05 WS-RS-Found-SPACE-CHR PIC X(1).
1297          88 WS-RS-Skipping-SPACE-BOOL VALUE 'Y'.
1298          88 WS-RS-Not-Skipping-SPACE-BOOL VALUE 'N'.
1299
1300      01 WS-I-SUB USAGE BINARY-CHAR.
1301
1302      01 WS-J-SUB USAGE BINARY-CHAR.
1303      LINKAGE SECTION.
1304      01 L-Argument-1-TXT.
1305          02 L-A1-CHR OCCURS 80 TIMES
1306                  PIC X(1).
1307
1308      01 L-Argument-2-CHR PIC X(1).
1309          88 L-A2-LINKAGE-SECTION-BOOL VALUE 'L'.
1310          88 L-A2-IDENT-DIVISION-BOOL VALUE 'I'.
1311          88 L-A2-Nothing-Special-BOOL VALUE ' '.

```

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 34

```

=====
1313 GC0712 PROCEDURE DIVISION USING BY VALUE      L-Argument-1-TXT
1314 GC0712                                     BY REFERENCE L-Argument-2-CHR.
1315         000-Main SECTION.
1316             SET L-A2-Nothing-Special-BOOL TO TRUE
1317             IF L-A1-CHR (7) = '*'
1318                 GOBACK
1319             END-IF
1320         .
1321     *>
1322     *> Compress multiple consecutive spaces
1323     *>
1324         SET WS-RS-Not-Skipping-SPACE-BOOL TO TRUE
1325         MOVE 0 TO WS-J-SUB
1326         MOVE SPACES TO WS-Compressed-Src-TXT
1327         PERFORM VARYING WS-I-SUB FROM 1 BY 1
1328             UNTIL WS-I-SUB > 80
1329             IF L-A1-CHR (WS-I-SUB) = SPACE
1330                 IF WS-RS-Not-Skipping-SPACE-BOOL
1331                     ADD 1 TO WS-J-SUB
1332                     MOVE UPPER-CASE(L-A1-CHR (WS-I-SUB))
1333                     TO WS-CS-CHR (WS-J-SUB)
1334                     SET WS-RS-Skipping-SPACE-BOOL TO TRUE
1335                 END-IF
1336             ELSE
1337                 SET WS-RS-Not-Skipping-SPACE-BOOL TO TRUE
1338                 ADD 1 TO WS-J-SUB
1339                 MOVE L-A1-CHR (WS-I-SUB) TO WS-CS-CHR (WS-J-SUB)
1340             END-IF
1341         END-PERFORM
1342     *>
1343     *> Scan the compressed source line
1344     *>
1345         PERFORM VARYING WS-I-SUB FROM 1 BY 1
1346             UNTIL WS-I-SUB > 66
1347         EVALUATE TRUE
1348             WHEN WS-CS-CHR (WS-I-SUB) = '*'
1349                 IF WS-Compressed-Src-TXT (WS-I-SUB : 2) = '*>'
1350                     GOBACK
1351                 END-IF
1352             WHEN (WS-CS-CHR (WS-I-SUB) = 'L') AND (WS-I-SUB < 66)
1353                 IF WS-Compressed-Src-TXT (WS-I-SUB : 15)
1354                     = 'LINKAGE SECTION'
1355                     SET L-A2-LINKAGE-SECTION-BOOL TO TRUE
1356                     GOBACK
1357                 END-IF
1358             WHEN (WS-CS-CHR (WS-I-SUB) = 'I') AND (WS-I-SUB < 58)
1359                 IF WS-Compressed-Src-TXT (WS-I-SUB : 23)
1360                     = 'IDENTIFICATION DIVISION'
1361                     SET L-A2-IDENT-DIVISION-BOOL TO TRUE
1362                     GOBACK
1363                 END-IF
1364         END-EVALUATE
=====

```

GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL

Page: 34

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 35

```

=====
1365         END-PERFORM
1366     *>
1367     *> If we get to here, we never found anything!
1368     *>
1369 +         GOBACK
1370     .
1371     END PROGRAM CHECKSRC.
1372
1373     IDENTIFICATION DIVISION.
1374     PROGRAM-ID. LISTING.
1375     *>*****
1376     *> This subprogram generates a cross-reference listing of an **
1377     *> GNU COBOL program. **
1378     *>*****
1379     *> **
1380     *> AUTHOR:          GARY L. CUTLER **
1381     *>                Copyright (C) 2010, Gary L. Cutler, GPL **
1382     *> **
1383     *> DATE-WRITTEN: April 1, 2010 **
1384     *> **
1385     *>*****
1386     *>  DATE  CHANGE DESCRIPTION **
1387     *> ===== **
1388     *> GC0410 Initial coding **
1389     *> GC0711 Updates to accommodate the 12MAR2010 version of OC **
1390     *> GC0710 Handle duplicate data names (i.e. 'CORRESPONDING' or **
1391     *>        qualified items) better; ignore 'END PROGRAM' recs **
1392     *>        so program name doesn't appear in listing. **
1393     *> GC0313 Fix problem where the first procedure name defined **
1394     *>        in the PROCEDURE DIVISION lacks a "Defined" line **
1395     *>        number. **
1396     *> GC1213 Updated for 23NOV2013 version of GNU COBOL 2.1; Stop **
1397     *>        showing functions as if they were identifiers in the **
1398     *>        xref listing; Flag all CALL argument references with **
1399     *>        a "C" rather than "*" because they aren't necessari- **
1400     *>        ly altered; Fixed assorted formatting bugs; DOWN- **
1401     *>        WARD COMPATIBLE WITH GNU COBOL 2.0 SYNTAX **
1402     *> GC0314 Fix problem where 1st char of 1st token on a line is **
1403     *>        lost if >>SOURCE MODE IS FREE is in effect and the **
1404     *>        1st character is non-blank. **
1405     *>*****
1406     ENVIRONMENT DIVISION.
1407     CONFIGURATION SECTION.
1408     REPOSITORY.
1409     FUNCTION ALL INTRINSIC.
1410     INPUT-OUTPUT SECTION.
1411     FILE-CONTROL.
1412         SELECT F-Expanded-Src-FILE ASSIGN TO WS-Expanded-Src-Fn-TXT
1413         ORGANIZATION IS LINE SEQUENTIAL.
1414 GC0712     SELECT F-Listing-FILE   ASSIGN TO L-Listing-Fn-TXT
1415         ORGANIZATION IS LINE SEQUENTIAL.
1416         SELECT F-Original-Src-FILE ASSIGN TO L-Src-Fn-TXT
1417         ORGANIZATION IS LINE SEQUENTIAL.
=====

```

GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL

Page: 35

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 36

```

=====
1418          SELECT F-Sort-Work-FILE      ASSIGN TO DISK.
1419          DATA DIVISION.
1420          FILE SECTION.
1421          FD  F-Expanded-Src-FILE.
1422          01  F-Expanded-Src-REC.
1423              05 F-ES-1-CHR                      PIC X.
1424              05 F-ES-2-256-TXT-256              PIC X(256).
1425 GC0712 01  F-Expanded-Src2-REC.
1426 GC0712 05 F-ES-1-7-TXT                      PIC X(7).
1427 GC0712 05 F-ES-8-256-TXT                    PIC X(249).
1428
1429 GC0712 FD  F-Listing-FILE.
1430 GC1213 01  F-Listing-96-REC                  PIC X(96).
1431 GC1213 01  F-Listing-135-REC                PIC X(135).
1432          01  F-Listing-REC                  PIC X(135).
1433
1434          FD  F-Original-Src-FILE.
1435          01  F-Original-Src-REC.
1436 GC0410 05 F-OS-1-128-TXT.
1437 GC0410 10 FILLER                          PIC X(6).
1438 GC0410 10 F-OS-7-CHR                      PIC X(1).
1439 GC0712 10 F-OS-8-72-TXT                    PIC X(65).
1440 GC0712 10 FILLER                          PIC X(56).
1441          05 F-OS-129-256-TXT                PIC X(128).
1442
1443          SD  F-Sort-Work-FILE.
1444          01  F-Sort-Work-REC.
1445              05 F-SW-Prog-ID-TXT              PIC X(15).
1446              05 F-SW-Token-Uc-TXT            PIC X(32).
1447              05 F-SW-Token-TXT              PIC X(32).
1448              05 F-SW-Section-TXT            PIC X(15).
1449              05 F-SW-Def-Line-NUM          PIC 9(6).
1450              05 F-SW-Reference-TXT.
1451                  10 F-SW-Ref-Line-NUM      PIC 9(6).
1452                  10 F-SW-Ref-Flag-CHR      PIC X(1).
1453
1454          WORKING-STORAGE SECTION.
1455 GC1213 01  WS-Copyright-TXT                PIC X(86).
1456
1457          01  WS-Curr-CHR                    PIC X(1).
1458              88 WS-Curr-Char-Is-Punct-BOOL  VALUE '=' , '(' , ')' ,
1459                  '*' , '/' , '&' ,
1460                  ';' , ',' , '<' ,
1461                  '>' , ':' .
1462              88 WS-Curr-Char-Is-Quote-BOOL  VALUE '"' , "'" .
1463              88 WS-Curr-Char-Is-X-BOOL      VALUE 'x' , 'X' .
1464              88 WS-Curr-Char-Is-Z-BOOL      VALUE 'z' , 'Z' .
1465
1466          01  WS-Curr-Division-TXT            PIC X(1).
1467 GC1010 88 WS-CD-In-IDENT-DIV-BOOL          VALUE 'i' , 'I' , '?.
1468 GC1010 88 WS-CD-In-ENV-DIV-BOOL            VALUE 'e' , 'E' .
1469 GC1010 88 WS-CD-In-DATA-DIV-BOOL           VALUE 'd' , 'D' .
1470 GC1010 88 WS-CD-In-PROC-DIV-BOOL           VALUE 'p' , 'P' .
=====

```

GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL

Page: 36

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 37

```

=====
1471
1472      01  WS-Curr-Line-NUM                      PIC 9(6).
1473
1474      01  WS-Curr-Prog-ID-TXT.
1475          05  FILLER                          PIC X(12).
1476          05  WS-CPI-13-15-TXT                 PIC X(3).
1477 GC0712  05  WS-CPI-16-CHR                     PIC X(1).
1478
1479      01  WS-Curr-Section-TXT.
1480          05  WS-CS-1-CHR                       PIC X(1).
1481          05  WS-CS-2-14-TXT.
1482              10  FILLER                      PIC X(10).
1483              10  WS-CS-11-14-TXT              PIC X(3).
1484          05  WS-CS-15-CHR                     PIC X(1).
1485
1486      01  WS-Curr-Verb-TXT                      PIC X(12).
1487
1488      01  WS-Delim-TXT                          PIC X(2).
1489
1490      01  WS-Dummy-TXT                          PIC X(1).
1491
1492      01  WS-Expanded-Src-Fn-TXT                PIC X(256).
1493
1494      01  WS-Filename-TXT                      PIC X(256).
1495
1496 GC1213  01  WS-Flags-TXT.
1497 GC1213  05  WS-Suppress-FF-CHR                PIC X(1).
1498
1499 GC1213  01  WS-Formatted-DT                   PIC 9999/99/99.
1500
1501      01  WS-Group-Indicators-TXT.
1502          05  WS-GI-Prog-ID-TXT                 PIC X(15).
1503          05  WS-GI-Token-TXT                   PIC X(32).
1504
1505      01  WS-Held-Reference-TXT                 PIC X(100).
1506
1507      01  WS-I-SUB                             USAGE BINARY-LONG.
1508
1509      01  WS-J-SUB                             USAGE BINARY-LONG.
1510
1511      01  WS-Lines-Left-NUM                     USAGE BINARY-LONG.
1512
1513      01  WS-Lines-Per-Page-NUM                 USAGE BINARY-LONG.
1514
1515      01  WS-Lines-Per-Page-Env-TXT             PIC X(256).
1516
1517 GC1010  01  WS-Main-Module-Name-TXT           PIC X(256).
1518
1519      01  WS-Next-CHR                           PIC X(1).
1520          88  WS-Next-Char-Is-Quote-BOOL        VALUE '"', "'".
1521
1522      01  WS-OS-Type-FILLER-TXT.
1523          05  VALUE 'Windows'                   PIC X(14).
=====

```

GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL

Page: 37

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 38

```

=====
1524          05 VALUE 'Windows/Cygwin'          PIC X(14).
1525          05 VALUE 'UNIX/Linux'             PIC X(14).
1526          05 VALUE 'OSX'                     PIC X(14).
1527          05 VALUE 'Windows/MinGW'           PIC X(14).
1528      01 WS-OS-Types-TXT REDEFINES WS-OS-Type-FILLER-TXT.
1529          05 WS-OS-Type-TXT                   PIC X(14)
1530                                         OCCURS 5 TIMES .
1531
1532 GC0712 01 WS-Page-NUM                        USAGE BINARY-LONG.
1533
1534 GC0712 01 WS-Page-No-TXT.
1535 GC0712          05 WS-PN-Literal-TXT          PIC X(6).
1536 GC0712          05 WS-PN-Page-NUM             PIC Z(3)9.
1537
1538 GC1213 01 WS-Program-Path-TXT                PIC X(135).
1539
1540      01 WS-Reserved-Words-TXT.
1541          05 VALUE '          ' PIC X(33).
1542 GC1213          05 VALUE 'FABS' PIC X(33).
1543          05 VALUE 'VACCEPT' PIC X(33).
1544          05 VALUE 'ACCESS' PIC X(33).
1545 GC1213          05 VALUE 'FACOS' PIC X(33).
1546          05 VALUE 'ACTIVE-CLASS' PIC X(33). UNIMPLEMENTED
1547          05 VALUE 'VADD' PIC X(33).
1548          05 VALUE 'ADDRESS' PIC X(33).
1549          05 VALUE 'ADVANCING' PIC X(33).
1550          05 VALUE 'KAFTER' PIC X(33).
1551          05 VALUE 'ALIGNED' PIC X(33). UNIMPLEMENTED
1552          05 VALUE 'ALL' PIC X(33).
1553          05 VALUE 'VALLOCATE' PIC X(33).
1554          05 VALUE 'ALPHABET' PIC X(33).
1555          05 VALUE 'ALPHABETIC' PIC X(33).
1556          05 VALUE 'ALPHABETIC-LOWER' PIC X(33).
1557          05 VALUE 'ALPHABETIC-UPPER' PIC X(33).
1558          05 VALUE 'ALPHANUMERIC' PIC X(33).
1559          05 VALUE 'ALPHANUMERIC-EDITED' PIC X(33).
1560          05 VALUE 'ALSO' PIC X(33).
1561          05 VALUE 'VALTER' PIC X(33).
1562          05 VALUE 'ALTERNATE' PIC X(33).
1563          05 VALUE 'AND' PIC X(33).
1564 GC1213          05 VALUE 'FANNUITY' PIC X(33).
1565          05 VALUE 'ANY' PIC X(33).
1566          05 VALUE 'ANYCASE' PIC X(33). UNIMPLEMENTED
1567          05 VALUE 'ARE' PIC X(33).
1568          05 VALUE 'AREA' PIC X(33).
1569          05 VALUE 'AREAS' PIC X(33).
1570          05 VALUE 'ARGUMENT-NUMBER' PIC X(33).
1571          05 VALUE 'ARGUMENT-VALUE' PIC X(33).
1572          05 VALUE 'ARITHMETIC' PIC X(33). UNIMPLEMENTED
1573          05 VALUE 'AS' PIC X(33).
1574          05 VALUE 'ASCENDING' PIC X(33).
1575          05 VALUE 'ASCII' PIC X(33).
1576 GC1213          05 VALUE 'FASIN' PIC X(33).
=====

```

GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL

Page: 38

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 39

```

=====
1577      05 VALUE ' ASSIGN          ' PIC X(33).
1578      05 VALUE ' AT              ' PIC X(33).
1579 GC1213 05 VALUE ' FATAN          ' PIC X(33).
1580 GC0711 05 VALUE ' ATTRIBUTE      ' PIC X(33).
1581      05 VALUE ' AUTHOR           ' PIC X(33).      OBSOLETE
1582      05 VALUE ' AUTO             ' PIC X(33).
1583      05 VALUE ' AUTO-SKIP         ' PIC X(33).
1584      05 VALUE ' AUTOMATIC         ' PIC X(33).
1585      05 VALUE ' AUTOTERMINATE     ' PIC X(33).
1586      05 VALUE ' AWAY-FROM-ZERO    ' PIC X(33).
1587      05 VALUE ' B-AND             ' PIC X(33).      UNIMPLEMENTED
1588      05 VALUE ' B-NOT             ' PIC X(33).      UNIMPLEMENTED
1589      05 VALUE ' B-OR              ' PIC X(33).      UNIMPLEMENTED
1590      05 VALUE ' B-XOR             ' PIC X(33).      UNIMPLEMENTED
1591      05 VALUE ' BACKGROUND-COLOR  ' PIC X(33).
1592      05 VALUE ' BACKGROUND-COLOUR ' PIC X(33).
1593      05 VALUE ' BASED             ' PIC X(33).
1594      05 VALUE ' BEEP              ' PIC X(33).
1595      05 VALUE ' BEFORE            ' PIC X(33).
1596      05 VALUE ' BELL              ' PIC X(33).
1597      05 VALUE ' BINARY            ' PIC X(33).
1598      05 VALUE ' BINARY-C-LONG     ' PIC X(33).
1599      05 VALUE ' BINARY-CHAR       ' PIC X(33).
1600      05 VALUE ' BINARY-DOUBLE    ' PIC X(33).
1601      05 VALUE ' BINARY-INT       ' PIC X(33).
1602      05 VALUE ' BINARY-LONG      ' PIC X(33).
1603      05 VALUE ' BINARY-LONG-LONG ' PIC X(33).
1604      05 VALUE ' BINARY-SHORT     ' PIC X(33).
1605      05 VALUE ' BIT               ' PIC X(33).      UNIMPLEMENTED
1606      05 VALUE ' BLANK             ' PIC X(33).
1607      05 VALUE ' BLINK            ' PIC X(33).
1608      05 VALUE ' BLOCK            ' PIC X(33).
1609      05 VALUE ' BOOLEAN           ' PIC X(33).      UNIMPLEMENTED
1610 GC1213 05 VALUE ' FBOOLEAN-OF-INTEGER ' PIC X(33).      UNIMPLEMENTED
1611      05 VALUE ' BOTTOM            ' PIC X(33).
1612      05 VALUE ' YBY              ' PIC X(33).
1613 GC1213 05 VALUE ' FBYTE-LENGTH  ' PIC X(33).
1614      05 VALUE ' MC01             ' PIC X(33).
1615      05 VALUE ' MC02             ' PIC X(33).
1616      05 VALUE ' MC03             ' PIC X(33).
1617      05 VALUE ' MC04             ' PIC X(33).
1618      05 VALUE ' MC05             ' PIC X(33).
1619      05 VALUE ' MC06             ' PIC X(33).
1620      05 VALUE ' MC07             ' PIC X(33).
1621      05 VALUE ' MC08             ' PIC X(33).
1622      05 VALUE ' MC09             ' PIC X(33).
1623      05 VALUE ' MC10             ' PIC X(33).
1624      05 VALUE ' MC11             ' PIC X(33).
1625      05 VALUE ' MC12             ' PIC X(33).
1626      05 VALUE ' VCALL            ' PIC X(33).
1627      05 VALUE ' MCALL-CONVENTION ' PIC X(33).
1628      05 VALUE ' VCANCEL           ' PIC X(33).
1629      05 VALUE ' CAPACITY         ' PIC X(33).      UNIMPLEMENTED
=====

```

GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL

Page: 39

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 40

```

=====
1630          05 VALUE ' CD                      ' PIC X(33).      OBSOLETE
1631          05 VALUE ' CENTER                  ' PIC X(33).      UNIMPLEMENTED
1632          05 VALUE ' CF                      ' PIC X(33).
1633          05 VALUE ' CH                      ' PIC X(33).
1634          05 VALUE ' CHAIN                   ' PIC X(33).      UNIMPLEMENTED
1635          05 VALUE ' CHAINING                 ' PIC X(33).
1636 GC1213    05 VALUE ' FCHAR                   ' PIC X(33).
1637 GC1213    05 VALUE ' FCHAR-NATIONAL          ' PIC X(33).      UNIMPLEMENTED
1638          05 VALUE ' CHARACTER                ' PIC X(33).
1639          05 VALUE ' CHARACTERS               ' PIC X(33).
1640          05 VALUE ' CLASS                    ' PIC X(33).
1641          05 VALUE ' CLASS-ID                 ' PIC X(33).      UNIMPLEMENTED
1642 GC0711    05 VALUE ' CLASSIFICATION          ' PIC X(33).
1643          05 VALUE ' VCLOSE                   ' PIC X(33).
1644 GC1213    05 VALUE ' FCOB-CRT-STATUS          ' PIC X(33).
1645          05 VALUE ' CODE                     ' PIC X(33).
1646          05 VALUE ' CODE-SET                 ' PIC X(33).
1647          05 VALUE ' COL                     ' PIC X(33).
1648          05 VALUE ' COLLATING                ' PIC X(33).
1649          05 VALUE ' COLS                    ' PIC X(33).
1650          05 VALUE ' COLUMN                   ' PIC X(33).
1651          05 VALUE ' COLUMNS                  ' PIC X(33).
1652 GC1213    05 VALUE ' FCOMBINED-DATETIME       ' PIC X(33).
1653          05 VALUE ' COMMA                   ' PIC X(33).
1654          05 VALUE ' COMMAND-LINE             ' PIC X(33).
1655          05 VALUE ' VCOMMIT                  ' PIC X(33).
1656          05 VALUE ' COMMON                   ' PIC X(33).
1657          05 VALUE ' COMMUNICATION            ' PIC X(33).      OBSOLETE
1658          05 VALUE ' COMP                     ' PIC X(33).
1659          05 VALUE ' COMP-1                   ' PIC X(33).
1660          05 VALUE ' COMP-2                   ' PIC X(33).
1661          05 VALUE ' COMP-3                   ' PIC X(33).
1662          05 VALUE ' COMP-4                   ' PIC X(33).
1663          05 VALUE ' COMP-5                   ' PIC X(33).
1664          05 VALUE ' COMP-6                   ' PIC X(33).
1665          05 VALUE ' COMP-X                   ' PIC X(33).
1666          05 VALUE ' COMPUTATIONAL            ' PIC X(33).
1667          05 VALUE ' COMPUTATIONAL-1          ' PIC X(33).
1668          05 VALUE ' COMPUTATIONAL-2          ' PIC X(33).
1669          05 VALUE ' COMPUTATIONAL-3          ' PIC X(33).
1670          05 VALUE ' COMPUTATIONAL-4          ' PIC X(33).
1671          05 VALUE ' COMPUTATIONAL-5          ' PIC X(33).
1672          05 VALUE ' COMPUTATIONAL-X          ' PIC X(33).
1673          05 VALUE ' VCOMPUTE                 ' PIC X(33).
1674 GC1213    05 VALUE ' FCONCATENATE            ' PIC X(33).
1675 GC0712    05 VALUE ' CONDITION               ' PIC X(33).
1676          05 VALUE ' KCONFIGURATION           ' PIC X(33).
1677          05 VALUE ' MCONSOLE                 ' PIC X(33).
1678          05 VALUE ' CONSTANT                 ' PIC X(33).
1679          05 VALUE ' CONTAINS                 ' PIC X(33).
1680 GC0712    05 VALUE ' ACONTENT                ' PIC X(33).
1681          05 VALUE ' VCONTINUE                ' PIC X(33).
1682          05 VALUE ' CONTROL                  ' PIC X(33).
=====

```

GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL

Page: 40

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 41

```

=====
1683          05 VALUE ' CONTROLS          ' PIC X(33).
1684 GC0711    05 VALUE ' CONVERSION        ' PIC X(33).
1685          05 VALUE ' KCONVERTING        ' PIC X(33).
1686          05 VALUE ' COPY                ' PIC X(33).
1687          05 VALUE ' CORR                ' PIC X(33).
1688          05 VALUE ' CORRESPONDING       ' PIC X(33).
1689 GC1213     05 VALUE ' FCOS              ' PIC X(33).
1690          05 VALUE ' KCOUNT             ' PIC X(33).
1691          05 VALUE ' CRT                 ' PIC X(33).
1692          05 VALUE ' CRT-UNDER           ' PIC X(33).
1693          05 VALUE ' MCSP                ' PIC X(33).
1694          05 VALUE ' CURRENCY            ' PIC X(33).
1695 GC1213     05 VALUE ' FCURRENCY-SYMBOL   ' PIC X(33).
1696 GC1213     05 VALUE ' FCURRENT-DATE     ' PIC X(33).
1697          05 VALUE ' CURSOR              ' PIC X(33).
1698          05 VALUE ' CYCLE               ' PIC X(33).
1699          05 VALUE ' KDATA               ' PIC X(33).
1700          05 VALUE ' DATA-POINTER       ' PIC X(33).      UNIMPLEMENTED
1701          05 VALUE ' DATE                ' PIC X(33).
1702          05 VALUE ' DATE-COMPILED       ' PIC X(33).      OBSOLETE
1703          05 VALUE ' DATE-MODIFIED       ' PIC X(33).      OBSOLETE
1704 GC1213     05 VALUE ' FDATE-OF-INTEGER   ' PIC X(33).
1705 GC1213     05 VALUE ' FDATE-TO-YYYYMMDD ' PIC X(33).
1706          05 VALUE ' DATE-WRITTEN        ' PIC X(33).      OBSOLETE
1707          05 VALUE ' DAY                 ' PIC X(33).
1708 GC1213     05 VALUE ' FDAY-OF-INTEGER    ' PIC X(33).
1709          05 VALUE ' DAY-OF-WEEK          ' PIC X(33).
1710 GC1213     05 VALUE ' IDAY-TO-YYYYDDD    ' PIC X(33).
1711          05 VALUE ' DE                  ' PIC X(33).
1712 GC0712     05 VALUE ' IDEBUG-CONTENTS    ' PIC X(33).
1713 GC0712     05 VALUE ' IDEBUG-ITEM       ' PIC X(33).
1714 GC0712     05 VALUE ' IDEBUG-LINE       ' PIC X(33).
1715 GC0712     05 VALUE ' IDEBUG-NAME       ' PIC X(33).
1716 GC0712     05 VALUE ' IDEBUG-SUB-1      ' PIC X(33).
1717 GC0712     05 VALUE ' IDEBUG-SUB-2      ' PIC X(33).
1718 GC0712     05 VALUE ' IDEBUG-SUB-3      ' PIC X(33).
1719          05 VALUE ' DEBUGGING           ' PIC X(33).
1720          05 VALUE ' DECIMAL-POINT        ' PIC X(33).
1721          05 VALUE ' DECLARATIVES        ' PIC X(33).
1722          05 VALUE ' DEFAULT             ' PIC X(33).
1723          05 VALUE ' VDELETE             ' PIC X(33).
1724          05 VALUE ' DELIMITED           ' PIC X(33).
1725          05 VALUE ' KDELIMITER          ' PIC X(33).
1726          05 VALUE ' DEPENDING           ' PIC X(33).
1727          05 VALUE ' DESCENDING           ' PIC X(33).
1728          05 VALUE ' DESTINATION          ' PIC X(33).      UNIMPLEMENTED
1729          05 VALUE ' DETAIL              ' PIC X(33).
1730 GC0711     05 VALUE ' DISC              ' PIC X(33).
1731          05 VALUE ' DISK                ' PIC X(33).
1732          05 VALUE ' VDISPLAY             ' PIC X(33).
1733 GC1213     05 VALUE ' FDISPLAY-OF        ' PIC X(33).      UNIMPLEMENTED
1734          05 VALUE ' VDIVIDE             ' PIC X(33).
1735          05 VALUE ' KDIVISION            ' PIC X(33).
=====

```

GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL

Page: 41

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 42

```

=====
1736          05 VALUE 'KDOWN                ' PIC X(33).
1737          05 VALUE ' DUPLICATES          ' PIC X(33).
1738          05 VALUE ' DYNAMIC              ' PIC X(33).
1739 GC1213    05 VALUE 'FE                  ' PIC X(33).
1740          05 VALUE ' EBCDIC                ' PIC X(33).
1741 GC0712    05 VALUE ' EC                  ' PIC X(33).
1742          05 VALUE ' EGI                   ' PIC X(33).      OBSOLETE
1743          05 VALUE ' VELSE                ' PIC X(33).
1744          05 VALUE ' EMI                   ' PIC X(33).      OBSOLETE
1745          05 VALUE ' EMPTY-CHECK          ' PIC X(33).
1746          05 VALUE ' VENABLE              ' PIC X(33).      OBSOLETE
1747 GC0710    05 VALUE 'KEND                ' PIC X(33).
1748          05 VALUE ' END-ACCEPT            ' PIC X(33).
1749          05 VALUE ' END-ADD               ' PIC X(33).
1750          05 VALUE ' END-CALL              ' PIC X(33).
1751          05 VALUE ' END-CHAIN            ' PIC X(33).      UNIMPLEMENTED
1752          05 VALUE ' END-COMPUTE          ' PIC X(33).
1753          05 VALUE ' END-DELETE            ' PIC X(33).
1754          05 VALUE ' END-DISPLAY          ' PIC X(33).
1755          05 VALUE ' END-DIVIDE           ' PIC X(33).
1756          05 VALUE ' END-EVALUATE         ' PIC X(33).
1757          05 VALUE ' END-IF                ' PIC X(33).
1758          05 VALUE ' END-MULTIPLY          ' PIC X(33).
1759          05 VALUE ' END-OF-PAGE           ' PIC X(33).
1760          05 VALUE ' END-PERFORM           ' PIC X(33).
1761          05 VALUE ' END-READ              ' PIC X(33).
1762          05 VALUE ' END-RECEIVE           ' PIC X(33).      OBSOLETE
1763          05 VALUE ' END-RETURN            ' PIC X(33).
1764          05 VALUE ' END-REWRITE           ' PIC X(33).
1765          05 VALUE ' END-SEARCH            ' PIC X(33).
1766          05 VALUE ' END-START             ' PIC X(33).
1767          05 VALUE ' END-STRING            ' PIC X(33).
1768          05 VALUE ' END-SUBTRACT          ' PIC X(33).
1769          05 VALUE ' END-UNSTRING          ' PIC X(33).
1770          05 VALUE ' END-WRITE            ' PIC X(33).
1771          05 VALUE ' VENTRY                ' PIC X(33).
1772          05 VALUE ' ENTRY-CONVENTION      ' PIC X(33).      UNIMPLEMENTED
1773          05 VALUE ' KENVIRONMENT          ' PIC X(33).
1774          05 VALUE ' ENVIRONMENT-NAME      ' PIC X(33).
1775          05 VALUE ' ENVIRONMENT-VALUE     ' PIC X(33).
1776          05 VALUE ' EO                   ' PIC X(33).      UNIMPLEMENTED
1777          05 VALUE ' EOL                   ' PIC X(33).
1778          05 VALUE ' EOP                   ' PIC X(33).
1779          05 VALUE ' EOS                   ' PIC X(33).
1780          05 VALUE ' EQUAL                 ' PIC X(33).
1781          05 VALUE ' KEQUALS               ' PIC X(33).
1782          05 VALUE ' ERASE                 ' PIC X(33).
1783          05 VALUE ' ERROR                 ' PIC X(33).
1784          05 VALUE ' ESCAPE                 ' PIC X(33).
1785          05 VALUE ' ESI                   ' PIC X(33).      OBSOLETE
1786          05 VALUE ' VEVALUATE             ' PIC X(33).
1787          05 VALUE ' EXCEPTION              ' PIC X(33).
1788 GC1213    05 VALUE ' FEXCEPTION-FILE      ' PIC X(33).
=====

```

GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL

Page: 42

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Page: 43

Line	Statement			
1789	GC1213	05 VALUE 'FEXCEPTION-FILE-N	' PIC X(33).	UNIMPLEMENTED
1790	GC1213	05 VALUE 'FEXCEPTION-LOCATION	' PIC X(33).	
1791	GC1213	05 VALUE 'FEXCEPTION-LOCATION-N	' PIC X(33).	UNIMPLEMENTED
1792		05 VALUE ' EXCEPTION-OBJECT	' PIC X(33).	UNIMPLEMENTED
1793	GC1213	05 VALUE 'FEXCEPTION-STATEMENT	' PIC X(33).	
1794	GC1213	05 VALUE 'FEXCEPTION-STATUS	' PIC X(33).	
1795		05 VALUE ' EXCLUSIVE	' PIC X(33).	
1796		05 VALUE ' VEXIT	' PIC X(33).	
1797	GC1213	05 VALUE ' FEXP	' PIC X(33).	
1798	GC1213	05 VALUE ' FEXP10	' PIC X(33).	
1799		05 VALUE ' EXPANDS	' PIC X(33).	UNIMPLEMENTED
1800		05 VALUE ' EXTEND	' PIC X(33).	
1801		05 VALUE ' EXTERNAL	' PIC X(33).	
1802	GC1213	05 VALUE ' FFACTORIAL	' PIC X(33).	
1803		05 VALUE ' FACTORY	' PIC X(33).	UNIMPLEMENTED
1804		05 VALUE ' FALSE	' PIC X(33).	
1805		05 VALUE ' KFD	' PIC X(33).	
1806		05 VALUE ' KFILE	' PIC X(33).	
1807		05 VALUE ' FILE-CONTROL	' PIC X(33).	
1808		05 VALUE ' FILE-ID	' PIC X(33).	
1809	GC1113	05 VALUE ' FILLER	' PIC X(33).	
1810		05 VALUE ' FINAL	' PIC X(33).	
1811		05 VALUE ' FIRST	' PIC X(33).	
1812	GC0712	05 VALUE ' FLOAT-BINARY-128	' PIC X(33).	UNIMPLEMENTED
1813	GC0712	05 VALUE ' FLOAT-BINARY-32	' PIC X(33).	UNIMPLEMENTED
1814	GC0712	05 VALUE ' FLOAT-BINARY-64	' PIC X(33).	UNIMPLEMENTED
1815		05 VALUE ' FLOAT-DECIMAL-16	' PIC X(33).	
1816		05 VALUE ' FLOAT-DECIMAL-34	' PIC X(33).	
1817		05 VALUE ' FLOAT-EXTENDED	' PIC X(33).	UNIMPLEMENTED
1818	GC0712	05 VALUE ' FLOAT-INFINITY	' PIC X(33).	UNIMPLEMENTED
1819		05 VALUE ' FLOAT-LONG	' PIC X(33).	
1820	GC0712	05 VALUE ' FLOAT-NOT-A-NUMBER	' PIC X(33).	UNIMPLEMENTED
1821		05 VALUE ' FLOAT-SHORT	' PIC X(33).	
1822		05 VALUE ' FOOTING	' PIC X(33).	
1823		05 VALUE ' FOR	' PIC X(33).	
1824		05 VALUE ' FOREGROUND-COLOR	' PIC X(33).	
1825		05 VALUE ' FOREGROUND-COLOUR	' PIC X(33).	
1826	GC0711	05 VALUE ' FOREVER	' PIC X(33).	
1827		05 VALUE ' FORMAT	' PIC X(33).	UNIMPLEMENTED
1828	GC1213	05 VALUE ' FFORMATTED-CURRENT-DATE	' PIC X(33).	UNIMPLEMENTED
1829	GC1213	05 VALUE ' FFORMATTED-DATE	' PIC X(33).	UNIMPLEMENTED
1830	GC1213	05 VALUE ' FFORMATTED-DATETIME	' PIC X(33).	UNIMPLEMENTED
1831	GC1213	05 VALUE ' FFORMATTED-TIME	' PIC X(33).	UNIMPLEMENTED
1832		05 VALUE ' MFORMFEED	' PIC X(33).	
1833	GC1213	05 VALUE ' FFRACTION-PART	' PIC X(33).	
1834		05 VALUE ' VFREE	' PIC X(33).	
1835		05 VALUE ' FROM	' PIC X(33).	
1836		05 VALUE ' FULL	' PIC X(33).	
1837		05 VALUE ' FUNCTION	' PIC X(33).	
1838	GC0712	05 VALUE ' KFUNCTION-ID	' PIC X(33).	
1839		05 VALUE ' FUNCTION-POINTER	' PIC X(33).	UNIMPLEMENTED
1840		05 VALUE ' VGENERATE	' PIC X(33).	
1841		05 VALUE ' GET	' PIC X(33).	UNIMPLEMENTED

GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL

Page: 43

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 44

```

=====
1842          05 VALUE 'KGIVING                ' PIC X(33).
1843          05 VALUE ' GLOBAL                ' PIC X(33).
1844          05 VALUE ' VGO                    ' PIC X(33).
1845          05 VALUE ' VGOBACK                ' PIC X(33).
1846          05 VALUE ' GREATER                ' PIC X(33).
1847          05 VALUE ' GROUP                  ' PIC X(33).
1848          05 VALUE ' GROUP-USAGE            ' PIC X(33).      UNIMPLEMENTED
1849          05 VALUE ' HEADING                ' PIC X(33).
1850          05 VALUE ' HIGH-VALUE             ' PIC X(33).
1851          05 VALUE ' HIGH-VALUES            ' PIC X(33).
1852 GC1213    05 VALUE ' FHIGHEST-ALGEBRAIC    ' PIC X(33).
1853          05 VALUE ' HIGHLIGHT              ' PIC X(33).
1854          05 VALUE ' I-O                    ' PIC X(33).
1855          05 VALUE ' I-O-CONTROL            ' PIC X(33).
1856          05 VALUE ' KID                    ' PIC X(33).
1857          05 VALUE ' KIDENTIFICATION        ' PIC X(33).
1858          05 VALUE ' VIF                    ' PIC X(33).
1859          05 VALUE ' IGNORE                  ' PIC X(33).
1860          05 VALUE ' IGNORING                ' PIC X(33).
1861          05 VALUE ' IMPLEMENTS              ' PIC X(33).      UNIMPLEMENTED
1862          05 VALUE ' IN                      ' PIC X(33).
1863          05 VALUE ' INDEX                   ' PIC X(33).
1864          05 VALUE ' KINDEXED                ' PIC X(33).
1865          05 VALUE ' INDICATE                ' PIC X(33).
1866          05 VALUE ' INDIRECT                ' PIC X(33).      UNIMPLEMENTED
1867          05 VALUE ' INHERITS                ' PIC X(33).      UNIMPLEMENTED
1868          05 VALUE ' INITIAL                ' PIC X(33).
1869          05 VALUE ' VINITIALISE             ' PIC X(33).
1870          05 VALUE ' INITIALISED            ' PIC X(33).
1871          05 VALUE ' VINITIALIZE             ' PIC X(33).
1872          05 VALUE ' INITIALIZED            ' PIC X(33).
1873          05 VALUE ' VINITIAATE             ' PIC X(33).
1874          05 VALUE ' INPUT                   ' PIC X(33).
1875          05 VALUE ' KINPUT-OUTPUT           ' PIC X(33).
1876          05 VALUE ' VINSPECT                ' PIC X(33).
1877          05 VALUE ' INSTALLATION            ' PIC X(33).      OBSOLETE
1878 GC1213    05 VALUE ' FINTEGER               ' PIC X(33).
1879 GC1213    05 VALUE ' FINTEGER-OF-BOOLEAN    ' PIC X(33).      UNIMPLEMENTED
1880 GC1213    05 VALUE ' FINTEGER-OF-DATE      ' PIC X(33).
1881 GC1213    05 VALUE ' FINTEGER-OF-DAY        ' PIC X(33).
1882 GC1213    05 VALUE ' FINTEGER-OF-FORMATTED-DATE ' PIC X(33).      UNIMPLEMENTED
1883 GC1213    05 VALUE ' FINTEGER-PART          ' PIC X(33).
1884          05 VALUE ' INTERFACE                ' PIC X(33).      UNIMPLEMENTED
1885          05 VALUE ' INTERFACE-ID             ' PIC X(33).      UNIMPLEMENTED
1886          05 VALUE ' INTERMEDIATE            ' PIC X(33).      UNIMPLEMENTED
1887          05 VALUE ' KINTO                    ' PIC X(33).
1888          05 VALUE ' INTRINSIC                ' PIC X(33).
1889          05 VALUE ' INVALID                  ' PIC X(33).
1890          05 VALUE ' INVOKE                    ' PIC X(33).      UNIMPLEMENTED
1891          05 VALUE ' IS                       ' PIC X(33).
1892          05 VALUE ' JUST                      ' PIC X(33).
1893          05 VALUE ' JUSTIFIED                ' PIC X(33).
1894          05 VALUE ' KEPT                     ' PIC X(33).
=====

```

GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL

Page: 44

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 45

```

=====
1895          05 VALUE ' KEY                      ' PIC X(33).
1896          05 VALUE ' KEYBOARD                  ' PIC X(33).
1897          05 VALUE ' LABEL                      ' PIC X(33).
1898          05 VALUE ' LAST                      ' PIC X(33).
1899          05 VALUE ' LC_ALL                    ' PIC X(33).      UNIMPLEMENTED
1900          05 VALUE ' LC_COLLATE                ' PIC X(33).      UNIMPLEMENTED
1901          05 VALUE ' LC_CTYPE                  ' PIC X(33).      UNIMPLEMENTED
1902          05 VALUE ' LC_MESSAGES                ' PIC X(33).      UNIMPLEMENTED
1903          05 VALUE ' LC_MONETARY                ' PIC X(33).      UNIMPLEMENTED
1904          05 VALUE ' LC_NUMERIC                ' PIC X(33).      UNIMPLEMENTED
1905          05 VALUE ' LC_TIME                    ' PIC X(33).      UNIMPLEMENTED
1906          05 VALUE ' LEADING                    ' PIC X(33).
1907          05 VALUE ' LEFT                      ' PIC X(33).
1908          05 VALUE ' LEFT-JUSTIFY                ' PIC X(33).      UNIMPLEMENTED
1909          05 VALUE ' LEFTLINE                    ' PIC X(33).
1910 GC1213    05 VALUE ' FLENGTH                    ' PIC X(33).
1911 GC1213    05 VALUE ' FLENGTH-AN                ' PIC X(33).
1912          05 VALUE ' LENGTH-CHECK                ' PIC X(33).
1913          05 VALUE ' LESS                      ' PIC X(33).
1914          05 VALUE ' LIMIT                      ' PIC X(33).
1915          05 VALUE ' LIMITS                      ' PIC X(33).
1916          05 VALUE ' LINAGE                      ' PIC X(33).
1917          05 VALUE ' ILINAGE-COUNTER              ' PIC X(33).
1918          05 VALUE ' LINE                      ' PIC X(33).
1919 GC1213    05 VALUE ' ILINE-COUNTER              ' PIC X(33).
1920          05 VALUE ' LINES                      ' PIC X(33).
1921          05 VALUE ' KLINKAGE                    ' PIC X(33).
1922          05 VALUE ' KLOCAL-STORAGE                ' PIC X(33).
1923          05 VALUE ' LOCALE                      ' PIC X(33).
1924 GC1213    05 VALUE ' FLOCALE-COMPARE              ' PIC X(33).
1925 GC1213    05 VALUE ' FLOCALE-DATE                ' PIC X(33).
1926 GC1213    05 VALUE ' FLOCALE-TIME                ' PIC X(33).
1927 GC1213    05 VALUE ' FLOCALE-TIME-FROM-SECONDS ' PIC X(33).
1928          05 VALUE ' LOCK                      ' PIC X(33).
1929 GC1213    05 VALUE ' FLOG                      ' PIC X(33).
1930 GC1213    05 VALUE ' FLOG10                    ' PIC X(33).
1931          05 VALUE ' LOW-VALUE                    ' PIC X(33).
1932          05 VALUE ' LOW-VALUES                  ' PIC X(33).
1933          05 VALUE ' LOWER                      ' PIC X(33).
1934 GC1213    05 VALUE ' FLOWER-CASE                ' PIC X(33).
1935 GC1213    05 VALUE ' FLOWEST-ALGEBRAIC            ' PIC X(33).
1936          05 VALUE ' LOWLIGHT                    ' PIC X(33).
1937          05 VALUE ' MANUAL                      ' PIC X(33).
1938 GC1213    05 VALUE ' FMAX                      ' PIC X(33).
1939 GC1213    05 VALUE ' FMEAN                      ' PIC X(33).
1940 GC1213    05 VALUE ' FMEDIAN                    ' PIC X(33).
1941          05 VALUE ' MEMORY                      ' PIC X(33).
1942          05 VALUE ' VMERGE                      ' PIC X(33).
1943          05 VALUE ' MESSAGE                      ' PIC X(33).      OBSOLETE
1944          05 VALUE ' METHOD                      ' PIC X(33).      UNIMPLEMENTED
1945          05 VALUE ' METHOD-ID                    ' PIC X(33).      UNIMPLEMENTED
1946 GC1213    05 VALUE ' FMIDRANGE                  ' PIC X(33).
1947 GC1213    05 VALUE ' FMIN                      ' PIC X(33).
=====

```

GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL

Page: 45

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 46

```

=====
1948          05 VALUE ' MINUS                ' PIC X(33).
1949 GC1213    05 VALUE ' FMOD                  ' PIC X(33).
1950          05 VALUE ' MODE                    ' PIC X(33).
1951 GC1213    05 VALUE ' FMODULE-CALLER-ID      ' PIC X(33).
1952 GC1213    05 VALUE ' FMODULE-DATE          ' PIC X(33).
1953 GC1213    05 VALUE ' FMODULE-FORMATTED-DATE ' PIC X(33).
1954 GC1213    05 VALUE ' FMODULE-ID            ' PIC X(33).
1955 GC1213    05 VALUE ' FMODULE-PATH          ' PIC X(33).
1956 GC1213    05 VALUE ' FMODULE-SOURCE        ' PIC X(33).
1957 GC1213    05 VALUE ' FMODULE-TIME          ' PIC X(33).
1958 GC1213    05 VALUE ' FMONETARY-DECIMAL-POINT ' PIC X(33).
1959 GC1213    05 VALUE ' FMONETARY-THOUSANDS-SEPARATOR ' PIC X(33).
1960          05 VALUE ' VMOVE                    ' PIC X(33).
1961          05 VALUE ' MULTIPLE                  ' PIC X(33).
1962          05 VALUE ' VMULTIPLY                  ' PIC X(33).
1963 GC0711     05 VALUE ' NAME                    ' PIC X(33).
1964          05 VALUE ' NATIONAL                  ' PIC X(33).
1965          05 VALUE ' NATIONAL-EDITED          ' PIC X(33).
1966 GC1213    05 VALUE ' FNATIONAL-OF            ' PIC X(33).      UNIMPLEMENTED
1967          05 VALUE ' NATIVE                    ' PIC X(33).
1968          05 VALUE ' NEAREST-AWAY-FROM-ZERO    ' PIC X(33).
1969          05 VALUE ' NEAREST-EVEN              ' PIC X(33).
1970          05 VALUE ' NEAREST-TOWARD-ZERO      ' PIC X(33).
1971          05 VALUE ' NEGATIVE                  ' PIC X(33).
1972          05 VALUE ' NESTED                    ' PIC X(33).      UNIMPLEMENTED
1973          05 VALUE ' VNEXT                      ' PIC X(33).
1974          05 VALUE ' NO                        ' PIC X(33).
1975          05 VALUE ' NO-ECHO                  ' PIC X(33).
1976          05 VALUE ' NONE                      ' PIC X(33).      UNIMPLEMENTED
1977          05 VALUE ' NORMAL                  ' PIC X(33).
1978          05 VALUE ' NOT                      ' PIC X(33).
1979          05 VALUE ' NULL                     ' PIC X(33).
1980          05 VALUE ' NULLS                    ' PIC X(33).
1981          05 VALUE ' NUMBER                   ' PIC X(33).
1982          05 VALUE ' INUMBER-OF-CALL-PARAMETERS ' PIC X(33).
1983          05 VALUE ' NUMBERS                   ' PIC X(33).
1984          05 VALUE ' NUMERIC                   ' PIC X(33).
1985 GC1213    05 VALUE ' FNUMERIC-DECIMAL-POINT ' PIC X(33).
1986          05 VALUE ' NUMERIC-EDITED          ' PIC X(33).
1987 GC1213    05 VALUE ' FNUMERIC-THOUSANDS-SEPARATOR ' PIC X(33).
1988 GC1213    05 VALUE ' FNUMVAL                 ' PIC X(33).
1989 GC1213    05 VALUE ' FNUMVAL-C               ' PIC X(33).
1990 GC1213    05 VALUE ' FNUMVAL-F              ' PIC X(33).
1991          05 VALUE ' OBJECT                    ' PIC X(33).      UNIMPLEMENTED
1992          05 VALUE ' OBJECT-COMPUTER          ' PIC X(33).
1993          05 VALUE ' OBJECT-REFERENCE          ' PIC X(33).      UNIMPLEMENTED
1994          05 VALUE ' OCCURS                   ' PIC X(33).
1995          05 VALUE ' OF                      ' PIC X(33).
1996          05 VALUE ' OFF                      ' PIC X(33).
1997          05 VALUE ' OMITTED                  ' PIC X(33).
1998          05 VALUE ' ON                      ' PIC X(33).
1999          05 VALUE ' ONLY                     ' PIC X(33).
2000          05 VALUE ' VOPEN                    ' PIC X(33).
=====

```

GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL

Page: 46

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 47

```

=====
2001          05 VALUE ' OPTIONAL          ' PIC X(33).
2002          05 VALUE ' OPTIONS           ' PIC X(33).      UNIMPLEMENTED
2003          05 VALUE ' OR                ' PIC X(33).
2004 GC1213    05 VALUE ' FORD              ' PIC X(33).
2005 GC1213    05 VALUE ' FORD-MAX         ' PIC X(33).
2006 GC1213    05 VALUE ' FORD-MIN        ' PIC X(33).
2007          05 VALUE ' ORDER             ' PIC X(33).
2008          05 VALUE ' ORGANISATION      ' PIC X(33).
2009          05 VALUE ' ORGANIZATION     ' PIC X(33).
2010          05 VALUE ' OTHER             ' PIC X(33).
2011          05 VALUE ' OUTPUT            ' PIC X(33).
2012          05 VALUE ' OVERFLOW         ' PIC X(33).
2013          05 VALUE ' OVERLINE         ' PIC X(33).
2014          05 VALUE ' OVERRIDE         ' PIC X(33).
2015          05 VALUE ' PACKED-DECIMAL   ' PIC X(33).
2016          05 VALUE ' PADDING          ' PIC X(33).
2017          05 VALUE ' PAGE              ' PIC X(33).
2018 GC1213    05 VALUE ' IPAGE-COUNTER    ' PIC X(33).
2019          05 VALUE ' PARAGRAPH         ' PIC X(33).
2020          05 VALUE ' VPERFORM          ' PIC X(33).
2021          05 VALUE ' PF                ' PIC X(33).
2022          05 VALUE ' PH                ' PIC X(33).
2023 GC1213    05 VALUE ' FPI              ' PIC X(33).
2024          05 VALUE ' KPIC              ' PIC X(33).
2025          05 VALUE ' KPICTURE          ' PIC X(33).
2026          05 VALUE ' PLUS              ' PIC X(33).
2027          05 VALUE ' KPOINTER          ' PIC X(33).
2028          05 VALUE ' POSITION            ' PIC X(33).
2029          05 VALUE ' POSITIVE           ' PIC X(33).
2030          05 VALUE ' PREFIXED          ' PIC X(33).      UNIMPLEMENTED
2031          05 VALUE ' PRESENT           ' PIC X(33).
2032 GC1213    05 VALUE ' FPRESENT-VALUE   ' PIC X(33).
2033          05 VALUE ' PREVIOUS           ' PIC X(33).
2034          05 VALUE ' MPRINTER          ' PIC X(33).
2035          05 VALUE ' PRINTING          ' PIC X(33).
2036          05 VALUE ' KPROCEDURE        ' PIC X(33).
2037          05 VALUE ' PROCEDURE-POINTER ' PIC X(33).
2038          05 VALUE ' PROCEDURES        ' PIC X(33).
2039          05 VALUE ' PROCEED           ' PIC X(33).
2040          05 VALUE ' PROGRAM           ' PIC X(33).
2041          05 VALUE ' KPROGRAM-ID        ' PIC X(33).
2042          05 VALUE ' PROGRAM-POINTER    ' PIC X(33).
2043          05 VALUE ' PROHIBITED        ' PIC X(33).
2044          05 VALUE ' PROMPT             ' PIC X(33).
2045          05 VALUE ' PROPERTY           ' PIC X(33).      UNIMPLEMENTED
2046          05 VALUE ' PROTOTYPE         ' PIC X(33).      UNIMPLEMENTED
2047          05 VALUE ' PURGE             ' PIC X(33).      OBSOLETE
2048          05 VALUE ' QUEUE             ' PIC X(33).      OBSOLETE
2049          05 VALUE ' QUOTE             ' PIC X(33).
2050          05 VALUE ' QUOTES            ' PIC X(33).
2051          05 VALUE ' RAISE              ' PIC X(33).      UNIMPLEMENTED
2052          05 VALUE ' RAISING            ' PIC X(33).      UNIMPLEMENTED
2053 GC1213    05 VALUE ' FRANDOM          ' PIC X(33).
=====

```

GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL

Page: 47

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 48

```

=====
2054 GC1213      05 VALUE 'FRANGE          ' PIC X(33).
2055 GC1213      05 VALUE 'KRD            ' PIC X(33).
2056              05 VALUE 'VREAD          ' PIC X(33).
2057              05 VALUE 'VREADY         ' PIC X(33).
2058              05 VALUE 'VRECEIVE       ' PIC X(33).      OBSOLETE
2059              05 VALUE 'RECORD          ' PIC X(33).
2060              05 VALUE 'RECORDING       ' PIC X(33).
2061              05 VALUE 'RECORDS         ' PIC X(33).
2062              05 VALUE 'RECURSIVE       ' PIC X(33).
2063              05 VALUE 'KREDEFINES      ' PIC X(33).
2064              05 VALUE 'REEL            ' PIC X(33).
2065 GC0712      05 VALUE 'AREFERENCE       ' PIC X(33).
2066              05 VALUE 'REFERENCES      ' PIC X(33).
2067              05 VALUE 'RELATION        ' PIC X(33).      UNIMPLEMENTED
2068              05 VALUE 'RELATIVE        ' PIC X(33).
2069              05 VALUE 'VRELEASE        ' PIC X(33).
2070 GC1213      05 VALUE 'FREM             ' PIC X(33).
2071              05 VALUE 'REMAINDER       ' PIC X(33).
2072              05 VALUE 'REMARKS         ' PIC X(33).      OBSOLETE
2073              05 VALUE 'REMOVAL         ' PIC X(33).
2074              05 VALUE 'KRENAMES        ' PIC X(33).
2075              05 VALUE 'REPLACE         ' PIC X(33).
2076              05 VALUE 'KREPLACING      ' PIC X(33).
2077              05 VALUE 'KREPORT         ' PIC X(33).
2078              05 VALUE 'REPORTING       ' PIC X(33).
2079              05 VALUE 'REPORTS         ' PIC X(33).
2080              05 VALUE 'REPOSITORY       ' PIC X(33).
2081              05 VALUE 'REQUIRED        ' PIC X(33).
2082              05 VALUE 'RESERVE         ' PIC X(33).
2083              05 VALUE 'VRESET          ' PIC X(33).
2084              05 VALUE 'RESUME          ' PIC X(33).      UNIMPLEMENTED
2085              05 VALUE 'RETRY           ' PIC X(33).      UNIMPLEMENTED
2086              05 VALUE 'VRETURN         ' PIC X(33).
2087              05 VALUE 'IRETURN-CODE    ' PIC X(33).
2088              05 VALUE 'KRETURNING      ' PIC X(33).
2089 GC1213      05 VALUE 'FREVERSE         ' PIC X(33).
2090              05 VALUE 'REVERSE-VIDEO   ' PIC X(33).
2091              05 VALUE 'REVERSED        ' PIC X(33).
2092              05 VALUE 'REWIND          ' PIC X(33).
2093              05 VALUE 'VREWRITE        ' PIC X(33).
2094              05 VALUE 'RF              ' PIC X(33).
2095              05 VALUE 'RH              ' PIC X(33).
2096              05 VALUE 'RIGHT           ' PIC X(33).
2097              05 VALUE 'RIGHT-JUSTIFY   ' PIC X(33).      UNIMPLEMENTED
2098              05 VALUE 'VROLLBACK       ' PIC X(33).
2099              05 VALUE 'ROUNDED         ' PIC X(33).
2100              05 VALUE 'ROUNDING        ' PIC X(33).      UNIMPLEMENTED
2101              05 VALUE 'RUN             ' PIC X(33).
2102              05 VALUE 'SAME            ' PIC X(33).
2103              05 VALUE 'KSCREEN          ' PIC X(33).
2104              05 VALUE 'SCROLL          ' PIC X(33).
2105              05 VALUE 'KSD             ' PIC X(33).
2106              05 VALUE 'VSEARCH         ' PIC X(33).
=====

```

GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL

Page: 48

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 49

```

=====
2107          05 VALUE ' SECONDS          ' PIC X(33).      UNIMPLEMENTED
2108 GC1213    05 VALUE 'FSECONDS-FROM-FORMATTED-TIME ' PIC X(33).
2109 GC1213    05 VALUE 'FSECONDS-PAST-MIDNIGHT ' PIC X(33).
2110          05 VALUE 'KSECTION          ' PIC X(33).
2111          05 VALUE ' SECURE            ' PIC X(33).
2112          05 VALUE ' SECURITY          ' PIC X(33).      OBSOLETE
2113          05 VALUE ' SEGMENT           ' PIC X(33).      OBSOLETE
2114          05 VALUE ' SEGMENT-LIMIT     ' PIC X(33).
2115          05 VALUE ' SELECT            ' PIC X(33).
2116          05 VALUE ' SELF              ' PIC X(33).      UNIMPLEMENTED
2117          05 VALUE ' VSEND             ' PIC X(33).      OBSOLETE
2118          05 VALUE ' SENTENCE          ' PIC X(33).
2119          05 VALUE ' SEPARATE          ' PIC X(33).
2120          05 VALUE ' SEQUENCE          ' PIC X(33).
2121          05 VALUE ' SEQUENTIAL        ' PIC X(33).
2122          05 VALUE ' VSET              ' PIC X(33).
2123          05 VALUE ' SHARING           ' PIC X(33).
2124 GC1213    05 VALUE ' FSIGN            ' PIC X(33).
2125          05 VALUE ' SIGNED             ' PIC X(33).
2126          05 VALUE ' SIGNED-INT        ' PIC X(33).
2127          05 VALUE ' SIGNED-LONG       ' PIC X(33).
2128          05 VALUE ' SIGNED-SHORT      ' PIC X(33).
2129 GC1213    05 VALUE ' FSIN             ' PIC X(33).
2130          05 VALUE ' SIZE              ' PIC X(33).
2131          05 VALUE ' VSORT              ' PIC X(33).
2132          05 VALUE ' SORT-MERGE        ' PIC X(33).
2133          05 VALUE ' ISORT-RETURN      ' PIC X(33).
2134          05 VALUE ' SOURCE            ' PIC X(33).
2135          05 VALUE ' SOURCE-COMPUTER    ' PIC X(33).
2136          05 VALUE ' SOURCES           ' PIC X(33).      UNIMPLEMENTED
2137          05 VALUE ' SPACE            ' PIC X(33).
2138          05 VALUE ' SPACE-FILL        ' PIC X(33).      UNIMPLEMENTED
2139          05 VALUE ' SPACES            ' PIC X(33).
2140          05 VALUE ' SPECIAL-NAMES     ' PIC X(33).
2141 GC1213    05 VALUE ' FSQRT            ' PIC X(33).
2142          05 VALUE ' STANDARD          ' PIC X(33).
2143          05 VALUE ' STANDARD-1        ' PIC X(33).
2144          05 VALUE ' STANDARD-2        ' PIC X(33).
2145          05 VALUE ' STANDARD-BINARY   ' PIC X(33).      UNIMPLEMENTED
2146 GC1213    05 VALUE ' FSTANDARD-COMPARE ' PIC X(33).      UNIMPLEMENTED
2147          05 VALUE ' STANDARD-DECIMAL  ' PIC X(33).      UNIMPLEMENTED
2148 GC1213    05 VALUE ' FSTANDARD-DEVIATION ' PIC X(33).
2149          05 VALUE ' VSTART            ' PIC X(33).
2150          05 VALUE ' STATEMENT          ' PIC X(33).      UNIMPLEMENTED
2151          05 VALUE ' STATIC            ' PIC X(33).
2152          05 VALUE ' STATUS            ' PIC X(33).
2153          05 VALUE ' STDCALL           ' PIC X(33).
2154          05 VALUE ' MSTDERR           ' PIC X(33).
2155          05 VALUE ' MSTDIN            ' PIC X(33).
2156          05 VALUE ' MSTDOUT           ' PIC X(33).
2157          05 VALUE ' STEP              ' PIC X(33).
2158          05 VALUE ' VSTOP             ' PIC X(33).
2159 GC1213    05 VALUE ' FSTORED-CHAR-LENGTH ' PIC X(33).
=====

```

GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL

Page: 49

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 50

```

=====
2160          05 VALUE 'VSTRING'                ' PIC X(33).
2161          05 VALUE 'STRONG'                  ' PIC X(33).      UNIMPLEMENTED
2162          05 VALUE 'SUB-QUEUE-1'              ' PIC X(33).      OBSOLETE
2163          05 VALUE 'SUB-QUEUE-2'              ' PIC X(33).      OBSOLETE
2164          05 VALUE 'SUB-QUEUE-3'              ' PIC X(33).      OBSOLETE
2165 GC1213    05 VALUE 'FSUBSTITUTE'              ' PIC X(33).
2166 GC1213    05 VALUE 'FSUBSTITUTE-CASE'          ' PIC X(33).
2167          05 VALUE 'VSUBTRACT'                ' PIC X(33).
2168 GC1213    05 VALUE 'FSUM'                    ' PIC X(33).
2169          05 VALUE 'SUPER'                     ' PIC X(33).      UNIMPLEMENTED
2170          05 VALUE 'VSUPPRESS'                 ' PIC X(33).
2171          05 VALUE 'MSW0'                      ' PIC X(33).
2172          05 VALUE 'MSW1'                      ' PIC X(33).
2173          05 VALUE 'MSW10'                     ' PIC X(33).
2174          05 VALUE 'MSW11'                     ' PIC X(33).
2175          05 VALUE 'MSW12'                     ' PIC X(33).
2176          05 VALUE 'MSW13'                     ' PIC X(33).
2177          05 VALUE 'MSW14'                     ' PIC X(33).
2178          05 VALUE 'MSW15'                     ' PIC X(33).
2179          05 VALUE 'MSW2'                      ' PIC X(33).
2180          05 VALUE 'MSW3'                      ' PIC X(33).
2181          05 VALUE 'MSW4'                      ' PIC X(33).
2182          05 VALUE 'MSW5'                      ' PIC X(33).
2183          05 VALUE 'MSW6'                      ' PIC X(33).
2184          05 VALUE 'MSW7'                      ' PIC X(33).
2185          05 VALUE 'MSW8'                      ' PIC X(33).
2186          05 VALUE 'MSW9'                      ' PIC X(33).
2187          05 VALUE 'MSWITCH-0'                 ' PIC X(33).
2188          05 VALUE 'MSWITCH-1'                 ' PIC X(33).
2189          05 VALUE 'MSWITCH-10'                 ' PIC X(33).
2190          05 VALUE 'MSWITCH-11'                 ' PIC X(33).
2191          05 VALUE 'MSWITCH-12'                 ' PIC X(33).
2192          05 VALUE 'MSWITCH-13'                 ' PIC X(33).
2193          05 VALUE 'MSWITCH-14'                 ' PIC X(33).
2194          05 VALUE 'MSWITCH-15'                 ' PIC X(33).
2195          05 VALUE 'MSWITCH-2'                 ' PIC X(33).
2196          05 VALUE 'MSWITCH-3'                 ' PIC X(33).
2197          05 VALUE 'MSWITCH-4'                 ' PIC X(33).
2198          05 VALUE 'MSWITCH-5'                 ' PIC X(33).
2199          05 VALUE 'MSWITCH-6'                 ' PIC X(33).
2200          05 VALUE 'MSWITCH-7'                 ' PIC X(33).
2201          05 VALUE 'MSWITCH-8'                 ' PIC X(33).
2202          05 VALUE 'MSWITCH-9'                 ' PIC X(33).
2203          05 VALUE 'SYMBOL'                     ' PIC X(33).      UNIMPLEMENTED
2204          05 VALUE 'SYMBOLIC'                   ' PIC X(33).
2205          05 VALUE 'SYNC'                       ' PIC X(33).
2206          05 VALUE 'SYNCHRONISED'              ' PIC X(33).
2207          05 VALUE 'SYNCHRONIZED'              ' PIC X(33).
2208          05 VALUE 'MSYSERR'                   ' PIC X(33).
2209          05 VALUE 'MSYSIN'                     ' PIC X(33).
2210          05 VALUE 'MSYSIPT'                    ' PIC X(33).
2211          05 VALUE 'MSYSLIST'                   ' PIC X(33).
2212          05 VALUE 'MSYSLST'                   ' PIC X(33).
=====

```

GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL

Page: 50

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 51

```

=====
2213          05 VALUE 'MSYSOUT          ' PIC X(33).
2214          05 VALUE ' SYSTEM-DEFAULT  ' PIC X(33).
2215          05 VALUE ' TABLE          ' PIC X(33).      UNIMPLEMENTED
2216          05 VALUE 'KTALLYING        ' PIC X(33).
2217 GC1213    05 VALUE 'FTAN            ' PIC X(33).
2218          05 VALUE ' TAPE             ' PIC X(33).
2219          05 VALUE ' TERMINAL         ' PIC X(33).      OBSOLETE
2220          05 VALUE 'VTERMINATE        ' PIC X(33).
2221          05 VALUE ' TEST             ' PIC X(33).
2222 GC1213    05 VALUE 'FTEST-DATE-YYYYMMDD ' PIC X(33).
2223 GC1213    05 VALUE 'FTEST-DAY-YYYYDDD  ' PIC X(33).
2224 GC1213    05 VALUE 'FTEST-FORMATTED-DATETIME ' PIC X(33).      UNIMPLEMENTED
2225 GC1213    05 VALUE 'FTEST-NUMVAL      ' PIC X(33).
2226 GC1213    05 VALUE 'FTEST-NUMVAL-C    ' PIC X(33).
2227 GC1213    05 VALUE 'FTEST-NUMVAL-F    ' PIC X(33).
2228          05 VALUE ' TEXT            ' PIC X(33).      OBSOLETE
2229          05 VALUE ' THAN             ' PIC X(33).
2230          05 VALUE ' THEN             ' PIC X(33).
2231          05 VALUE ' THROUGH          ' PIC X(33).
2232          05 VALUE ' THRU            ' PIC X(33).
2233          05 VALUE ' TIME            ' PIC X(33).
2234 GC0711    05 VALUE ' TIME-OUT        ' PIC X(33).
2235 GC0711    05 VALUE ' TIMEOUT        ' PIC X(33).
2236          05 VALUE ' TIMES           ' PIC X(33).
2237          05 VALUE 'KTO              ' PIC X(33).
2238          05 VALUE ' TOP              ' PIC X(33).
2239          05 VALUE ' TOWARD-GREATER    ' PIC X(33).
2240          05 VALUE ' TOWARD-LESSER     ' PIC X(33).
2241          05 VALUE ' TRAILING         ' PIC X(33).
2242          05 VALUE ' TRAILING-SIGN     ' PIC X(33).      UNIMPLEMENTED
2243          05 VALUE 'VTRANSFORM        ' PIC X(33).
2244 GC1213    05 VALUE 'FTRIM           ' PIC X(33).
2245          05 VALUE ' TRUE            ' PIC X(33).
2246          05 VALUE ' TRUNCATION       ' PIC X(33).
2247          05 VALUE ' TYPE            ' PIC X(33).
2248          05 VALUE ' TYPEDEF          ' PIC X(33).      UNIMPLEMENTED
2249          05 VALUE ' UCS-4            ' PIC X(33).      UNIMPLEMENTED
2250          05 VALUE ' UNDERLINE        ' PIC X(33).
2251          05 VALUE ' UNIT            ' PIC X(33).
2252          05 VALUE ' UNIVERSAL        ' PIC X(33).      UNIMPLEMENTED
2253          05 VALUE 'VUNLOCK           ' PIC X(33).
2254          05 VALUE ' UNSIGNED         ' PIC X(33).
2255          05 VALUE ' UNSIGNED-INT     ' PIC X(33).
2256          05 VALUE ' UNSIGNED-LONG   ' PIC X(33).
2257          05 VALUE ' UNSIGNED-SHORT  ' PIC X(33).
2258          05 VALUE 'VUNSTRING         ' PIC X(33).
2259          05 VALUE ' UNTIL           ' PIC X(33).
2260          05 VALUE 'KUP              ' PIC X(33).
2261          05 VALUE ' UPDATE           ' PIC X(33).
2262          05 VALUE ' UPON            ' PIC X(33).
2263          05 VALUE ' UPPER           ' PIC X(33).
2264 GC1213    05 VALUE 'FUPPER-CASE      ' PIC X(33).
2265          05 VALUE ' USAGE           ' PIC X(33).
=====

```

GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL

Page: 51

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 52

```

=====
2266          05 VALUE 'VUSE                      ' PIC X(33).
2267 GC0711    05 VALUE ' USER                      ' PIC X(33).
2268          05 VALUE ' USER-DEFAULT                ' PIC X(33).
2269          05 VALUE ' KUSING                      ' PIC X(33).
2270          05 VALUE ' UTF-16                      ' PIC X(33).      UNIMPLEMENTED
2271          05 VALUE ' UTF-8                      ' PIC X(33).      UNIMPLEMENTED
2272          05 VALUE ' VAL-STATUS                  ' PIC X(33).      UNIMPLEMENTED
2273          05 VALUE ' VALID                      ' PIC X(33).      UNIMPLEMENTED
2274          05 VALUE ' VALIDATE                    ' PIC X(33).      UNIMPLEMENTED
2275          05 VALUE ' VALIDATE-STATUS              ' PIC X(33).      UNIMPLEMENTED
2276 GC0712    05 VALUE ' AVALUE                      ' PIC X(33).
2277          05 VALUE ' VALUES                      ' PIC X(33).
2278 GC1213    05 VALUE ' FVARIANCE                  ' PIC X(33).
2279          05 VALUE ' KVARYING                    ' PIC X(33).
2280          05 VALUE ' VDISABLE                      ' PIC X(33).      UNIMPLEMENTED
2281          05 VALUE ' WAIT                      ' PIC X(33).
2282          05 VALUE ' VWHEN                      ' PIC X(33).
2283 GC1213    05 VALUE ' FWHEN-COMPILED              ' PIC X(33).
2284          05 VALUE ' WITH                      ' PIC X(33).
2285          05 VALUE ' WORDS                      ' PIC X(33).
2286          05 VALUE ' KWORKING-STORAGE              ' PIC X(33).
2287          05 VALUE ' VWRITE                      ' PIC X(33).
2288 GC1213    05 VALUE ' FYEAR-TO-YYYY              ' PIC X(33).
2289          05 VALUE ' YYYYDDD                    ' PIC X(33).
2290          05 VALUE ' YYYYMMDD                    ' PIC X(33).
2291          05 VALUE ' ZERO                      ' PIC X(33).
2292          05 VALUE ' ZERO-FILL                    ' PIC X(33).      UNIMPLEMENTED
2293          05 VALUE ' ZEROES                      ' PIC X(33).
2294          05 VALUE ' ZEROS                      ' PIC X(33).
2295          01 WS-Reserved-Word-Table-TXT REDEFINES WS-Reserved-Words-TXT.
2296 GC1113    05 WS-Reserved-Word-TXT OCCURS 754 TIMES
2297                                     ASCENDING KEY
2298                                     WS-RW-Word-TXT
2299                                     INDEXED WS-RW-IDX.
2300          10 WS-RW-Type-CD                      PIC X(1).
2301          10 WS-RW-Word-TXT                      PIC X(32).
2302
2303          01 WS-Runtime-Switches.
2304 GC0710    05 WS-RS-Duplicate-CHR                PIC X(1).
2305          05 WS-RS-In-Which-Pgm-CHR              PIC X(1).
2306          88 WS-RS-In-Main-Module-BOOL            VALUE 'M'.
2307          88 WS-RS-In-Copybook-BOOL              VALUE 'C'.
2308          05 WS-RS-Last-Token-Ended-Sent-CHR      PIC X(1).
2309          05 WS-RS-Processing-PICTURE-CHR         PIC X(1).
2310          05 WS-RS-Token-Ended-Sentence-CHR       PIC X(1).
2311 GC0710    05 WS-RS-Verb-Has-Been-Found-CHR      PIC X(1).
2312
2313          01 WS-Saved-Section-TXT                  PIC X(15).
2314
2315 GC1213 01 WS-Src-Dashes-TXT.
2316 GC0712    05 VALUE '===== ' PIC X(7).
2317 GC0712    05 VALUE ALL '=' PIC X(128).
2318
=====

```

GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL

Page: 52

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 53

```

=====
2319      01  WS-Src-Detail-Line-TXT.
2320          05 WS-SDL-Line-NUM          PIC ZZZZZ9.
2321          05 FILLER                    PIC X(1).
2322          05 WS-SDL-Statement-TXT      PIC X(256).
2323
2324 GC1213 01  WS-Src-Hold-TXT          PIC X(256).
2325
2326          01  WS-Src-Line-NUM          PIC 9(6).
2327
2328 GC1213 01  WS-Src-Lines-NUM          USAGE BINARY-LONG.
2329
2330          01  WS-Src-SUB                USAGE BINARY-LONG.
2331
2332          01  WS-Tally-QTY              USAGE BINARY-LONG.
2333
2334          01  WS-Temp-10-Chars-TXT     PIC X(10).
2335
2336          01  WS-Temp-32-Chars-1-TXT   PIC X(32).
2337
2338 GC0711 01  WS-Temp-32-Chars-2-TXT     PIC X(32).
2339
2340 GC0711 01  WS-Temp-32-Chars-3-TXT     PIC X(32).
2341
2342 GC0712 01  WS-Temp-65-Chars-TXT      PIC X(65).
2343
2344          01  WS-Temp-256-Chars-TXT    PIC X(256).
2345
2346          01  WS-Today-DT              PIC 9(8).
2347
2348          01  WS-Token-Curr-TXT        PIC X(32).
2349
2350          01  WS-Token-Curr-Uc-TXT     PIC X(32).
2351
2352          01  WS-Token-Prev-TXT        PIC X(32).
2353
2354          01  WS-Token-Search-TXT      PIC X(32).
2355
2356          01  WS-Token-Type-CD         PIC X(1).
2357 GC0712      88 WS-TT-Token-Is-Argtype-BOOL  VALUE 'A'.
2358          88 WS-TT-Token-Is-EOF-BOOL      VALUE HIGH-VALUES.
2359 GC1213      88 WS-TT-Token-Is-Function-BOOL VALUE 'F'.
2360          88 WS-TT-Token-Is-Identifier-BOOL VALUE 'I'.
2361 GC0712      88 WS-TT-Token-Is-Keyword-BOOL  VALUE 'K', 'V', 'A'.
2362          88 WS-TT-Token-Is-Lit-Alpha-BOOL  VALUE 'L'.
2363          88 WS-TT-Token-Is-Lit-Number-BOOL  VALUE 'N'.
2364          88 WS-TT-Token-Is-Verb-BOOL      VALUE 'V'.
2365 GC1213      88 WS-TT-Token-Is-Reserved-Wd-BOOL  VALUE ' ', 'F'.
2366
2367          01  WS-Usernames-QTY          USAGE BINARY-LONG.
2368
2369          01  WS-Version-TXT            PIC X(23).
2370
2371          01  WS-Xref-Detail-Line-TXT.
=====

```

GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL

Page: 53

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 54

```

=====
2372          05 WS-XDL-Prog-ID-TXT          PIC X(15).
2373          05 FILLER                      PIC X(1).
2374          05 WS-XDL-Token-TXT            PIC X(32).
2375          05 FILLER                      PIC X(1).
2376          05 WS-XDL-Def-Line-NUM         PIC ZZZZZ9.
2377          05 FILLER                      PIC X(1).
2378          05 WS-XDL-Section-TXT          PIC X(15).
2379          05 FILLER                      PIC X(1).
2380          05 WS-XDL-Reference-TXT        OCCURS 8 TIMES.
2381              10 WS-XDL-Ref-Line-NUM     PIC ZZZZZ9.
2382              10 WS-XDL-Ref-Flag-CHR     PIC X(1).
2383              10 FILLER                  PIC X(1).
2384
2385 GC1213 01  WS-Xref-Lines-Per-Rec-NUM     PIC 9(1).
2386
2387          LINKAGE SECTION.
2388 GC0712 01  L-Listing-Fn-TXT              PIC X(256).
2389
2390          01  L-Src-Fn-TXT                 PIC X(256).
2391
2392 GC0712 01  L-OS-Type-CD                  PIC 9(1).
2393
2394 GC1213 01  L-LPP-NUM                     USAGE BINARY-LONG.
2395
2396 GC1213 01  L-LPP-Port-NUM                USAGE BINARY-LONG.
2397
2398 GC1213 01  L-Listing-CD                  PIC 9(1).
=====

```

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 55

=====

```

2400 GC0712 PROCEDURE DIVISION USING L-Listing-Fn-TXT
2401 GC0712                      L-Src-Fn-TXT
2402 GC0712                      L-OS-Type-CD
2403 GC1213                      L-LPP-NUM
2404 GC1213                      L-LPP-Port-NUM
2405 GC1213                      L-Listing-CD.
2406      000-Main SECTION.
2407      PERFORM 100-Initialization
2408 GC0712      OPEN OUTPUT F-Listing-FILE
2409 GC0712      PERFORM 500-Produce-Source-Listing
2410 GC0712      SORT F-Sort-Work-FILE
2411 GC0712          ASCENDING KEY      F-SW-Prog-ID-TXT
2412 GC0712          F-SW-Token-Uc-TXT
2413 GC0712          F-SW-Ref-Line-NUM
2414 GC0712          INPUT PROCEDURE  300-Tokenize-Source
2415 GC0712          OUTPUT PROCEDURE 400-Produce-Xref-Listing
2416 GC0712      CLOSE F-Listing-FILE
2417      GOBACK
2418      .

```

=====
GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL

Page: 55

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 56

```

=====
2420      *>*****
2421      *> Perform all program-wide initialization operations      **
2422      *>*****
2423      100-Initialization SECTION.
2424 GC1213      MOVE 0 TO WS-Page-NUM
2425 GC1213      MOVE 'N' TO WS-Suppress-FF-CHR
2426 GC1213      MOVE SPACES TO WS-Copyright-TXT
2427 GC1213      STRING 'GCic for '                DELIMITED SIZE
2428 GC1213              WS-OS-Type-TXT(L-OS-Type-CD) DELIMITED SPACE
2429 GC1213              ' Copyright (C) 2009-2017, Gary L. Cutler, GPL'
2430 GC1213              DELIMITED SIZE
2431 GC1213              INTO WS-Copyright-TXT
2432 GC1213      MOVE 'GNUCOBOL 2.2 20JUL2017' TO WS-Version-TXT
2433      MOVE TRIM(L-Src-Fn-TXT,Leading) TO L-Src-Fn-TXT
2434 GC1010      PERFORM VARYING WS-I-SUB FROM LENGTH(L-Src-Fn-TXT) BY -1 *> Locate last direct
               ory delimiter character so that the filename can be extracted
2435 GC1010              UNTIL L-Src-Fn-TXT(WS-I-SUB:1) = '/' OR '\',
2436 GC1010              OR WS-I-SUB = 0
2437 GC1010      END-PERFORM
2438 GC1010      IF WS-I-SUB = 0
2439 GC1010          MOVE UPPER-CASE(L-Src-Fn-TXT) TO WS-Main-Module-Name-TXT *> No directory d
               elimiter, whole thing is filename
2440 GC1010      ELSE
2441 GC1010          ADD 1 TO WS-I-SUB
2442 GC1010          MOVE UPPER-CASE(L-Src-Fn-TXT(WS-I-SUB:))
2443 GC1010              TO WS-Main-Module-Name-TXT *> Extract filename
2444 GC1010      END-IF
2445 GC1213      IF L-Listing-CD = 1 *> LANDSCAPE
2446 GC1213          MOVE 8 TO WS-Xref-Lines-Per-Rec-NUM
2447 GC1213          ACCEPT WS-Lines-Per-Page-Env-TXT
2448 GC1213              FROM ENVIRONMENT 'GCXREF_LINES'
2449 GC1213      ELSE *> PORTRAIT
2450 GC1213          MOVE 3 TO WS-Xref-Lines-Per-Rec-NUM
2451 GC1213          ACCEPT WS-Lines-Per-Page-Env-TXT
2452 GC1213              FROM ENVIRONMENT 'GCXREF_LINES_PORT'
2453 GC1213      END-IF
2454      INSPECT L-Src-Fn-TXT REPLACING ALL '\ ' BY '/'
2455      MOVE L-Src-Fn-TXT TO WS-Program-Path-TXT
2456      CALL 'C$JUSTIFY' USING WS-Program-Path-TXT, 'Right'
2457      MOVE LENGTH(TRIM(L-Src-Fn-TXT,Trailing)) TO WS-I-SUB
2458      MOVE 0 TO WS-J-SUB
2459      PERFORM UNTIL L-Src-Fn-TXT(WS-I-SUB:1) = '/'
2460              OR WS-I-SUB = 0
2461          SUBTRACT 1 FROM WS-I-SUB
2462          ADD 1 TO WS-J-SUB
2463      END-PERFORM
2464      UNSTRING L-Src-Fn-TXT((WS-I-SUB + 1):WS-J-SUB)
2465          DELIMITED BY '.'
2466          INTO WS-Filename-TXT
2467          WS-Dummy-TXT
2468 GC1010      STRING
2469 GC1010          TRIM(WS-Filename-TXT,Trailing)
=====

```

GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL

Page: 56

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 57

```

=====
2470 GC1010          '.i'
2471 GC1010          DELIMITED SIZE
2472 GC1010          INTO WS-Expanded-Src-Fn-TXT
2473 GC1010          CALL 'CBL_CHECK_FILE_EXIST' USING WS-Expanded-Src-Fn-TXT
2474 GC1010                               WS-Temp-256-Chars-TXT
2475 GC1010          IF RETURN-CODE NOT = 0
2476 GC1010              GOBACK
2477 GC1010          END-IF
2478          IF WS-Lines-Per-Page-Env-TXT NOT = SPACES
2479              MOVE NUMVAL(WS-Lines-Per-Page-Env-TXT)
2480                  TO WS-Lines-Per-Page-NUM
2481          ELSE
2482 GC1213              IF L-LISTING-CD = 1 *> LANDSCAPE
2483 GC1213                  MOVE L-LPP-NUM TO WS-Lines-Per-Page-NUM
2484 GC1213              ELSE
2485 GC1213                  MOVE L-LPP-Port-NUM TO WS-Lines-Per-Page-NUM
2486 GC1213              END-IF
2487          END-IF
2488 GC1213          SUBTRACT 3 FROM WS-Lines-Per-Page-NUM *> FOR PAGE FOOTER
2489          ACCEPT WS-Today-DT FROM DATE YYYYMMDD
2490 GC1213          MOVE WS-Today-DT TO WS-Formatted-DT
2491          MOVE '?????????????...' TO WS-Curr-Prog-ID-TXT
2492          MOVE SPACES              TO WS-Curr-Verb-TXT
2493                               WS-Held-Reference-TXT
2494          .
=====

```

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 58

```

=====
2496      300-Tokenize-Source SECTION.
2497      OPEN INPUT F-Expanded-Src-FILE
2498      MOVE SPACES TO F-Expanded-Src-REC
2499      MOVE 256 TO WS-Src-SUB
2500      MOVE 0 TO WS-Usernames-QTY
2501      WS-Curr-Line-NUM
2502      MOVE '?' TO WS-Curr-Division-TXT
2503 GC0710  MOVE 'N' TO WS-RS-Verb-Has-Been-Found-CHR
2504      PERFORM FOREVER
2505          PERFORM 310-Get-Token
2506          IF WS-TT-Token-Is-EOF-BOOL
2507              EXIT PERFORM
2508          END-IF
2509          MOVE UPPER-CASE(WS-Token-Curr-TXT)
2510              TO WS-Token-Curr-Uc-TXT
2511 GC1010  IF WS-TT-Token-Is-Keyword-BOOL
2512 GC1010  OR WS-TT-Token-Is-Reserved-Wd-BOOL
2513 GC1010  MOVE WS-Token-Curr-Uc-TXT TO WS-Token-Curr-TXT
2514 GC1010  END-IF
2515      IF WS-TT-Token-Is-Verb-BOOL
2516          MOVE WS-Token-Curr-Uc-TXT TO WS-Curr-Verb-TXT
2517          WS-Token-Prev-TXT
2518          IF WS-Held-Reference-TXT NOT = SPACES
2519              MOVE WS-Held-Reference-TXT TO F-Sort-Work-REC
2520              MOVE SPACES TO WS-Held-Reference-TXT
2521              RELEASE F-Sort-Work-REC
2522          END-IF
2523      END-IF
2524      EVALUATE TRUE
2525      WHEN WS-CD-In-IDENT-DIV-BOOL
2526          PERFORM 320-IDENTIFICATION-DIVISION
2527      WHEN WS-CD-In-ENV-DIV-BOOL
2528          PERFORM 330-ENVIRONMENT-DIVISION
2529      WHEN WS-CD-In-DATA-DIV-BOOL
2530          PERFORM 340-DATA-DIVISION
2531      WHEN WS-CD-In-PROC-DIV-BOOL
2532          PERFORM 350-PROCEDURE-DIVISION
2533      END-EVALUATE
2534      IF WS-TT-Token-Is-Keyword-BOOL
2535          MOVE WS-Token-Curr-Uc-TXT TO WS-Token-Prev-TXT
2536      END-IF
2537      IF WS-RS-Token-Ended-Sentence-CHR = 'Y'
2538      AND WS-Curr-Division-TXT NOT = 'I'
2539          MOVE SPACES TO WS-Token-Prev-TXT
2540          WS-Curr-Verb-TXT
2541      END-IF
2542
2543      END-PERFORM
2544      CLOSE F-Expanded-Src-FILE
2545      .
=====

```

GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL

Page: 58

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 59

```

=====
2547      310-Get-Token SECTION.
2548      *>-- Position to 1st non-blank character
2549          MOVE WS-RS-Token-Ended-Sentence-CHR
2550              TO WS-RS-Last-Token-Ended-Sent-CHR
2551          MOVE 'N' TO WS-RS-Token-Ended-Sentence-CHR
2552          PERFORM UNTIL F-Expanded-Src-REC(WS-Src-SUB : 1) NOT = SPACE
2553              IF WS-Src-SUB > 255
2554                  READ F-Expanded-Src-FILE AT END
2555                  IF WS-Held-Reference-TXT NOT = SPACES
2556                      MOVE WS-Held-Reference-TXT TO F-Sort-Work-REC
2557                      MOVE SPACES TO WS-Held-Reference-TXT
2558                      RELEASE F-Sort-Work-REC
2559                  END-IF
2560                  SET WS-TT-Token-Is-EOF-BOOL TO TRUE
2561                  MOVE 0 TO WS-Curr-Line-NUM
2562                  EXIT SECTION
2563              END-READ
2564 GC0712          IF F-ES-1-7-TXT NOT = '#DEFLIT'
2565 GC0712              IF F-ES-1-CHR = '#'
2566 GC0712                  PERFORM 311-Control-Record
2567 GC0712              ELSE
2568 GC0712                  PERFORM 312-Expanded-Src-Record
2569 GC0712              END-IF
2570 GC0712          END-IF
2571              ELSE
2572                  ADD 1 TO WS-Src-SUB
2573              END-IF
2574          END-PERFORM
2575      *>-- Extract token string
2576          MOVE F-Expanded-Src-REC(WS-Src-SUB : 1)
2577              TO WS-Curr-CHR
2578          MOVE F-Expanded-Src-REC(WS-Src-SUB + 1: 1)
2579              TO WS-Next-CHR
2580          IF WS-Curr-CHR = '.'
2581              ADD 1 TO WS-Src-SUB
2582              MOVE WS-Curr-CHR TO WS-Token-Curr-TXT
2583              MOVE SPACE TO WS-Token-Type-CD
2584              MOVE 'Y' TO WS-RS-Token-Ended-Sentence-CHR
2585              EXIT SECTION
2586          END-IF
2587          IF WS-Curr-Char-Is-Punct-BOOL
2588              AND WS-Curr-CHR = '='
2589              AND WS-Curr-Division-TXT = 'P'
2590              ADD 1 TO WS-Src-SUB
2591              MOVE 'EQUALS' TO WS-Token-Curr-TXT
2592              MOVE 'K' TO WS-Token-Type-CD
2593              EXIT SECTION
2594          END-IF
2595          IF WS-Curr-Char-Is-Punct-BOOL *> So subscripts don't get flagged w/ '*'
2596              AND WS-Curr-CHR = '('
2597              AND WS-Curr-Division-TXT = 'P'
2598              MOVE SPACES TO WS-Token-Prev-TXT
=====

```

GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL

Page: 59

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 60

```

=====
2599         END-IF
2600         IF WS-Curr-Char-Is-Punct-BOOL
2601             ADD 1 TO WS-Src-SUB
2602             MOVE WS-Curr-CHR TO WS-Token-Curr-TXT
2603             MOVE SPACE TO WS-Token-Type-CD
2604             EXIT SECTION
2605         END-IF
2606         IF WS-Curr-Char-Is-Quote-BOOL
2607             ADD 1 TO WS-Src-SUB
2608             UNSTRING F-Expanded-Src-REC
2609                 DELIMITED BY WS-Curr-CHR
2610                 INTO WS-Token-Curr-TXT
2611                 WITH POINTER WS-Src-SUB
2612             IF F-Expanded-Src-REC(WS-Src-SUB : 1) = '.'
2613                 MOVE 'Y' TO WS-RS-Token-Ended-Sentence-CHR
2614                 ADD 1 TO WS-Src-SUB
2615             END-IF
2616             SET WS-TT-Token-Is-Lit-Alpha-BOOL TO TRUE
2617             EXIT SECTION
2618         END-IF
2619         IF WS-Curr-Char-Is-X-BOOL AND WS-Next-Char-Is-Quote-BOOL
2620             ADD 2 TO WS-Src-SUB
2621             UNSTRING F-Expanded-Src-REC
2622                 DELIMITED BY WS-Next-CHR
2623                 INTO WS-Token-Curr-TXT
2624                 WITH POINTER WS-Src-SUB
2625             IF F-Expanded-Src-REC(WS-Src-SUB : 1) = '.'
2626                 MOVE 'Y' TO WS-RS-Token-Ended-Sentence-CHR
2627                 ADD 1 TO WS-Src-SUB
2628             END-IF
2629             SET WS-TT-Token-Is-Lit-Number-BOOL TO TRUE
2630             EXIT SECTION
2631         END-IF
2632         IF WS-Curr-Char-Is-Z-BOOL AND WS-Next-Char-Is-Quote-BOOL
2633             ADD 2 TO WS-Src-SUB
2634             UNSTRING F-Expanded-Src-REC
2635                 DELIMITED BY WS-Next-CHR
2636                 INTO WS-Token-Curr-TXT
2637                 WITH POINTER WS-Src-SUB
2638             IF F-Expanded-Src-REC(WS-Src-SUB : 1) = '.'
2639                 MOVE 'Y' TO WS-RS-Token-Ended-Sentence-CHR
2640                 ADD 1 TO WS-Src-SUB
2641             END-IF
2642             SET WS-TT-Token-Is-Lit-Alpha-BOOL TO TRUE
2643             EXIT SECTION
2644         END-IF
2645         IF WS-RS-Processing-PICTURE-CHR = 'Y'
2646             UNSTRING F-Expanded-Src-REC
2647                 DELIMITED BY ' ' OR ' '
2648                 INTO WS-Token-Curr-TXT
2649                 DELIMITER IN WS-Delim-TXT
2650                 WITH POINTER WS-Src-SUB
2651             IF WS-Delim-TXT = ' '
=====

```

GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL

Page: 60

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 61

```

=====
2652             MOVE 'Y' TO WS-RS-Token-Ended-Sentence-CHR
2653             ADD 1 TO WS-Src-SUB
2654             END-IF
2655             IF UPPER-CASE(WS-Token-Curr-TXT) = 'IS'
2656                 MOVE SPACE TO WS-Token-Type-CD
2657                 EXIT SECTION
2658             ELSE
2659                 MOVE 'N' TO WS-RS-Processing-PICTURE-CHR
2660                 MOVE SPACE TO WS-Token-Type-CD
2661                 EXIT SECTION
2662             END-IF
2663         END-IF
2664         UNSTRING F-Expanded-Src-REC
2665             DELIMITED BY ' . ' OR ' ' OR '=' OR '(' OR ')' OR '*'
2666                 OR '/' OR '&' OR ';' OR ',' OR '<'
2667                 OR '>' OR ':'
2668             INTO WS-Token-Curr-TXT
2669             DELIMITER IN WS-Delim-TXT
2670             WITH POINTER WS-Src-SUB
2671         IF WS-Delim-TXT = ' . '
2672             MOVE 'Y' TO WS-RS-Token-Ended-Sentence-CHR
2673         END-IF
2674         IF WS-Delim-TXT NOT = ' . ' AND ' '
2675             SUBTRACT 1 FROM WS-Src-SUB
2676         END-IF
2677         *>-- Classify Token
2678         MOVE UPPER-CASE(WS-Token-Curr-TXT) TO WS-Token-Search-TXT
2679         IF WS-Token-Search-TXT = 'EQUAL' OR 'EQUALS'
2680             MOVE 'EQUALS' TO WS-Token-Curr-TXT
2681             MOVE 'K'      TO WS-Token-Type-CD
2682             EXIT SECTION
2683         END-IF
2684         SEARCH ALL WS-Reserved-Word-TXT
2685             WHEN WS-RW-Word-TXT (WS-RW-IDX) = WS-Token-Search-TXT
2686                 MOVE WS-RW-Type-CD (WS-RW-IDX) TO WS-Token-Type-CD
2687 GC0710         IF WS-TT-Token-Is-Verb-BOOL
2688 GC0710             MOVE 'Y' TO WS-RS-Verb-Has-Been-Found-CHR
2689 GC0710         END-IF
2690             EXIT SECTION
2691         END-SEARCH
2692         *>-- Not a reserved word, must be a user name
2693         SET WS-TT-Token-Is-Identifier-BOOL TO TRUE
2694         PERFORM 313-Check-For-Numeric-Token
2695         IF WS-TT-Token-Is-Lit-Number-BOOL
2696             IF (WS-RS-Last-Token-Ended-Sent-CHR = 'Y')
2697                 AND (WS-Curr-Division-TXT = 'D')
2698                 MOVE 'LEVEL #' TO WS-Token-Curr-TXT
2699                 MOVE 'K'      TO WS-Token-Type-CD
2700             EXIT SECTION
2701         ELSE
2702             EXIT SECTION
2703         END-IF
2704     END-IF
=====

```

GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL

Page: 61

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 62

```
=====
2705      .
```

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 63

=====

```

2707      311-Control-Record SECTION.
2708      UNSTRING F-ES-2-256-TXT-256
2709          DELIMITED BY '''
2710      INTO WS-Temp-10-Chars-TXT
2711          WS-Temp-256-Chars-TXT
2712          WS-Dummy-TXT
2713      INSPECT WS-Temp-10-Chars-TXT REPLACING ALL ''' BY SPACE
2714 GC0712  IF WS-Temp-10-Chars-TXT(1:4) = 'line'
2715 GC0712      MOVE SPACES TO WS-Temp-10-Chars-TXT(1:4)
2716 GC0712  END-IF
2717      COMPUTE WS-I-SUB = NUMVAL(WS-Temp-10-Chars-TXT) - 1
2718 GC1010  IF UPPER-CASE(TRIM(WS-Temp-256-Chars-TXT,Trailing)) =
2719 GC1010      TRIM(WS-Main-Module-Name-TXT)
2720      MOVE WS-I-SUB TO WS-Curr-Line-NUM
2721      SET WS-RS-In-Main-Module-BOOL TO TRUE
2722      IF WS-Saved-Section-TXT NOT = SPACES
2723          MOVE WS-Saved-Section-TXT TO WS-Curr-Section-TXT
2724      END-IF
2725  ELSE
2726      SET WS-RS-In-Copybook-BOOL TO TRUE
2727      IF WS-Saved-Section-TXT = SPACES
2728          MOVE WS-Curr-Section-TXT TO WS-Saved-Section-TXT
2729      END-IF
2730      MOVE LENGTH(TRIM(WS-Temp-256-Chars-TXT,Trailing))
2731      TO WS-I-SUB
2732      MOVE 0 TO WS-J-SUB
2733      PERFORM UNTIL WS-Temp-256-Chars-TXT(WS-I-SUB:1) = '/'
2734          OR WS-I-SUB = 0
2735          SUBTRACT 1 FROM WS-I-SUB
2736          ADD 1 TO WS-J-SUB
2737      END-PERFORM
2738      UNSTRING WS-Temp-256-Chars-TXT((WS-I-SUB + 1):WS-J-SUB)
2739          DELIMITED BY ','
2740      INTO WS-Filename-TXT
2741          WS-Dummy-TXT
2742      MOVE '[' TO WS-CS-1-CHR
2743      MOVE WS-Filename-TXT TO WS-CS-2-14-TXT
2744      IF WS-CS-11-14-TXT NOT = SPACES
2745          MOVE '...' TO WS-CS-11-14-TXT
2746      END-IF
2747      MOVE ']' TO WS-CS-15-CHR
2748  END-IF
2749      MOVE SPACES TO F-Expanded-Src-REC *> Force another READ
2750      MOVE 256 TO WS-Src-SUB
2751      .

```

```

=====
GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL
Page: 63

```


GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 64

=====

```
2753      312-Expanded-Src-Record SECTION.
2754 GC0314      IF F-Expanded-Src-REC(1:1) = SPACE
2755 GC0314          MOVE 2 TO WS-Src-SUB
2756 GC0314      ELSE
2757 GC0314          MOVE 1 TO WS-Src-SUB
2758 GC0314      END-IF
2759      IF WS-RS-In-Main-Module-BOOL
2760          ADD 1 To WS-Curr-Line-NUM
2761      END-IF
2762      .
```

=====

GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL

Page: 64

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 65

```

=====
2764      313-Check-For-Numeric-Token SECTION.
2765      MOVE WS-Token-Curr-TXT TO WS-Temp-32-Chars-1-TXT
2766      INSPECT WS-Temp-32-Chars-1-TXT
2767 GC0711      CONVERTING '0123456789' TO SPACES
2768 GC0711      IF WS-Temp-32-Chars-1-TXT = SPACES                *> Simple Unsigned Integer
2769      SET WS-TT-Token-Is-Lit-Number-BOOL TO TRUE
2770      EXIT SECTION
2771      END-IF
2772 GC0711      MOVE SPACES TO WS-Temp-32-Chars-2-TXT
2773 GC0711      WS-Temp-32-Chars-3-TXT
2774 GC0711      WS-Dummy-TXT
2775 GC0711      UNSTRING WS-Temp-32-Chars-1-TXT
2776 GC0711      DELIMITED BY 'e' OR 'E'
2777 GC0711      INTO WS-Temp-32-Chars-2-TXT
2778 GC0711      WS-Temp-32-Chars-3-TXT
2779 GC0711      WS-Dummy-TXT
2780 GC0711      IF WS-Dummy-TXT NOT = SPACES                      *> More than one 'E' - Not Numeric
2781 GC0711      EXIT SECTION
2782 GC0711      END-IF
2783 GC0711      IF WS-Temp-32-Chars-2-TXT(1:1) = '+' OR '-'
2784 GC0711      MOVE SPACE TO WS-Temp-32-Chars-2-TXT(1:1)
2785 GC0711      END-IF
2786 GC0711      IF WS-Temp-32-Chars-3-TXT(1:1) = '+' OR '-'
2787 GC0711      MOVE SPACE TO WS-Temp-32-Chars-3-TXT(1:1)
2788 GC0711      END-IF
2789      MOVE 0 TO WS-Tally-QTY
2790 GC0711      INSPECT WS-Temp-32-Chars-2-TXT
2791      TALLYING WS-Tally-QTY FOR ALL '.'
2792      IF WS-Tally-QTY = 1
2793 GC0711      INSPECT WS-Temp-32-Chars-2-TXT REPLACING ALL '.' BY SPACE
2794      END-IF
2795 GC0711      INSPECT WS-Temp-32-Chars-3-TXT
2796 GC0711      TALLYING WS-Tally-QTY FOR ALL '.'
2797 GC0711      IF WS-Tally-QTY = 1
2798 GC0711      INSPECT WS-Temp-32-Chars-3-TXT REPLACING ALL '.' BY SPACE
2799 GC0711      END-IF
2800 GC0711      IF WS-Temp-32-Chars-2-TXT = SPACES AND WS-Temp-32-Chars-3-TXT = SPACES
2801      SET WS-TT-Token-Is-Lit-Number-BOOL TO TRUE
2802      EXIT SECTION
2803      END-IF
2804      .
=====

```

GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL

Page: 65

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 66

=====

```

2806      320-IDENTIFICATION-DIVISION SECTION.
2807 GC0712      IF WS-TT-Token-Is-Argtype-BOOL
2808 GC0712          SET WS-TT-Token-Is-Reserved-Wd-BOOL TO TRUE
2809 GC0712      END-IF
2810 GC0710      MOVE 'N' TO WS-RS-Verb-Has-Been-Found-CHR
2811              IF WS-TT-Token-Is-Keyword-BOOL
2812                  AND WS-Token-Curr-TXT = 'DIVISION'
2813                      MOVE WS-Token-Prev-TXT TO WS-Curr-Division-TXT
2814                      EXIT SECTION
2815              END-IF
2816 GC0712      IF WS-Token-Prev-TXT = 'PROGRAM-ID' OR 'FUNCTION-ID'
2817                  MOVE SPACES TO WS-Token-Prev-TXT
2818                  MOVE WS-Token-Curr-TXT TO WS-Curr-Prog-ID-TXT
2819 GC0712      IF WS-CPI-16-CHR NOT = SPACES
2820                  MOVE '...' TO WS-CPI-13-15-TXT
2821              END-IF
2822              EXIT SECTION
2823      END-IF
2824      .

```

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 67

```

=====
2826      330-ENVIRONMENT-DIVISION SECTION.
2827 GC0712      IF WS-TT-Token-Is-Argtype-BOOL
2828 GC0712          SET WS-TT-Token-Is-Reserved-Wd-BOOL TO TRUE
2829 GC0712      END-IF
2830      IF WS-TT-Token-Is-Keyword-BOOL
2831      AND WS-Token-Curr-TXT = 'DIVISION'
2832          MOVE WS-Token-Prev-TXT TO WS-Curr-Division-TXT
2833          EXIT SECTION
2834      END-IF
2835      IF WS-TT-Token-Is-Keyword-BOOL
2836      AND WS-Token-Curr-TXT = 'SECTION'
2837          MOVE WS-Token-Prev-TXT TO WS-Curr-Section-TXT
2838          EXIT SECTION
2839      END-IF
2840      IF WS-TT-Token-Is-Identifier-BOOL
2841 GC0712          IF WS-Token-Prev-TXT = 'FUNCTION'
2842 GC0712              PERFORM 360-Release-Def
2843 GC0712          ELSE
2844 GC0712              PERFORM 361-Release-Ref
2845 GC0712          END-IF
2846      END-IF
2847 GC1213      IF WS-TT-Token-Is-Function-BOOL
2848 GC1213          PERFORM 361-Release-Ref
2849 GC1213      END-IF
2850      .

```

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 68

```

=====
2852      340-DATA-DIVISION SECTION.
2853 GC0712      IF WS-TT-Token-Is-Argtype-BOOL
2854 GC0712          SET WS-TT-Token-Is-Reserved-Wd-BOOL TO TRUE
2855 GC0712      END-IF
2856          IF WS-TT-Token-Is-Keyword-BOOL
2857      AND WS-Token-Curr-TXT = 'DIVISION'
2858          MOVE WS-Token-Prev-TXT TO WS-Curr-Division-TXT
2859          EXIT SECTION
2860      END-IF
2861          IF WS-TT-Token-Is-Keyword-BOOL
2862      AND WS-Token-Curr-TXT = 'SECTION'
2863          MOVE WS-Token-Prev-TXT TO WS-Curr-Section-TXT
2864          EXIT SECTION
2865      END-IF
2866          IF (WS-Token-Curr-TXT = 'PIC' OR 'PICTURE')
2867      AND (WS-TT-Token-Is-Keyword-BOOL)
2868          MOVE 'Y' TO WS-RS-Processing-PICTURE-CHR
2869          EXIT SECTION
2870      END-IF
2871 GC0710      IF WS-TT-Token-Is-Reserved-Wd-BOOL
2872 GC0710      AND WS-Token-Prev-TXT = 'LEVEL #'
2873 GC0710          MOVE SPACES TO WS-Token-Prev-TXT
2874 GC0710          EXIT SECTION
2875 GC0710      END-IF
2876          IF WS-TT-Token-Is-Identifier-BOOL
2877      EVALUATE WS-Token-Prev-TXT
2878          WHEN 'FD'
2879              PERFORM 360-Release-Def
2880              MOVE SPACES TO WS-Token-Prev-TXT
2881 GC1213          WHEN 'RD'
2882 GC1213              PERFORM 360-Release-Def
2883 GC1213              MOVE SPACES TO WS-Token-Prev-TXT
2884          WHEN 'SD'
2885              PERFORM 360-Release-Def
2886              MOVE SPACES TO WS-Token-Prev-TXT
2887          WHEN 'LEVEL #'
2888              PERFORM 360-Release-Def
2889              MOVE SPACES TO WS-Token-Prev-TXT
2890          WHEN 'INDEXED'
2891              PERFORM 360-Release-Def
2892              MOVE SPACES TO WS-Token-Prev-TXT
2893          WHEN 'USING'
2894              PERFORM 362-Release-Upd
2895              MOVE SPACES TO WS-Token-Prev-TXT
2896          WHEN 'INTO'
2897              PERFORM 362-Release-Upd
2898              MOVE SPACES TO WS-Token-Prev-TXT
2899          WHEN OTHER
2900 GC1213              IF WS-Token-Curr-TXT NOT = 'SUM'
2901 GC1213                  PERFORM 361-Release-Ref
2902 GC1213              END-IF
2903          END-EVALUATE
=====

```

GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL

Page: 68

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 69

```
=====
2904          EXIT SECTION
2905          END-IF
2906          .
=====
```

```
=====
GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL
```

Page: 69

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 70

```

=====
2908      350-PROCEDURE-DIVISION SECTION.
2909      IF WS-Curr-Section-TXT NOT = 'PROCEDURE'
2910          MOVE 'PROCEDURE' TO WS-Curr-Section-TXT
2911      END-IF
2912 GC0710  IF WS-Token-Curr-Uc-TXT = 'PROGRAM'
2913 GC0710  AND WS-Token-Prev-TXT = 'END'
2914 GC0710  MOVE '?' TO WS-Curr-Division-TXT
2915 GC0710  EXIT SECTION
2916 GC0710  END-IF
2917      IF WS-TT-Token-Is-Keyword-BOOL
2918      AND WS-Token-Curr-TXT = 'DIVISION'
2919          MOVE WS-Token-Prev-TXT TO WS-Curr-Division-TXT
2920      EXIT SECTION
2921      END-IF
2922 GC0313  IF WS-TT-Token-Is-Identifier-BOOL
2923 GC0313  AND WS-Token-Prev-TXT = SPACES
2924 GC0313  AND WS-Curr-Verb-TXT = SPACES
2925 GC0313*> ----- Definition of a Paragraph or Section
2926 GC0313  PERFORM 360-Release-Def
2927 GC0313  MOVE SPACES TO WS-Token-Prev-TXT
2928 GC0313  EXIT SECTION
2929 GC0313  END-IF
2930      IF NOT WS-TT-Token-Is-Identifier-BOOL
2931      EXIT SECTION
2932      END-IF
2933      EVALUATE WS-Curr-Verb-TXT
2934      WHEN 'ACCEPT'
2935          PERFORM 351-ACCEPT
2936      WHEN 'ADD'
2937          PERFORM 351-ADD
2938      WHEN 'ALLOCATE'
2939          PERFORM 351-ALLOCATE
2940      WHEN 'CALL'
2941          PERFORM 351-CALL
2942      WHEN 'COMPUTE'
2943          PERFORM 351-COMPUTE
2944      WHEN 'DIVIDE'
2945          PERFORM 351-DIVIDE
2946      WHEN 'FREE'
2947          PERFORM 351-FREE
2948 GC1213  WHEN 'GENERATE'
2949 GC1213  PERFORM 351-GENERATE
2950      WHEN 'INITIALIZE'
2951          PERFORM 351-INITIALIZE
2952 GC1213  WHEN 'INITIATE'
2953 GC1213  PERFORM 351-GENERATE
2954      WHEN 'INSPECT'
2955          PERFORM 351-INSPECT
2956      WHEN 'MOVE'
2957          PERFORM 351-MOVE
2958      WHEN 'MULTIPLY'
2959          PERFORM 351-MULTIPLY
=====

```

GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL

Page: 70

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 71

```

=====
2960          WHEN 'PERFORM'
2961              PERFORM 351-PERFORM
2962          WHEN 'SET'
2963              PERFORM 351-SET
2964          WHEN 'STRING'
2965              PERFORM 351-STRING
2966          WHEN 'SUBTRACT'
2967              PERFORM 351-SUBTRACT
2968 GC1213     WHEN 'TERMINATE'
2969 GC1213     PERFORM 351-GENERATE
2970          WHEN 'TRANSFORM'
2971              PERFORM 351-TRANSFORM
2972          WHEN 'UNSTRING'
2973              PERFORM 351-UNSTRING
2974          WHEN OTHER
2975              PERFORM 361-Release-Ref
2976          END-EVALUATE
2977          .
=====

```

```

=====
GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL

```

Page: 71

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 72

```

=====
2979      351-ACCEPT SECTION.
2980          EVALUATE WS-Token-Prev-TXT
2981          WHEN 'ACCEPT'
2982              PERFORM 362-Release-Upd
2983              MOVE SPACES TO WS-Token-Prev-TXT
2984          WHEN OTHER
2985              PERFORM 361-Release-Ref
2986          END-EVALUATE
2987      .
2988
2989      351-ADD SECTION.
2990          EVALUATE WS-Token-Prev-TXT
2991          WHEN 'GIVING'
2992              PERFORM 362-Release-Upd
2993          WHEN 'TO'
2994              PERFORM 362-Release-Upd
2995          WHEN OTHER
2996              PERFORM 361-Release-Ref
2997          END-EVALUATE
2998      .
2999
3000      351-ALLOCATE SECTION.
3001          EVALUATE WS-Token-Prev-TXT
3002          WHEN 'ALLOCATE'
3003              PERFORM 362-Release-Upd
3004              MOVE SPACES TO WS-Token-Prev-TXT
3005          WHEN 'RETURNING'
3006              PERFORM 362-Release-Upd
3007          WHEN OTHER
3008              PERFORM 361-Release-Ref
3009          END-EVALUATE
3010      .
3011
3012      351-CALL SECTION.
3013          EVALUATE WS-Token-Prev-TXT
3014          WHEN 'RETURNING'
3015              PERFORM 362-Release-Upd
3016          WHEN 'GIVING'
3017              PERFORM 362-Release-Upd
3018          WHEN OTHER
3019 GC1213      PERFORM 365-Release-Arg
3020          END-EVALUATE
3021      .
3022
3023      351-COMPUTE SECTION.
3024          EVALUATE WS-Token-Prev-TXT
3025          WHEN 'COMPUTE'
3026              PERFORM 362-Release-Upd
3027          WHEN OTHER
3028              PERFORM 361-Release-Ref
3029          END-EVALUATE
3030      .
=====

```

GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL

Page: 72

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 73

```

=====
3031
3032     351-DIVIDE SECTION.
3033         EVALUATE WS-Token-Prev-TXT
3034         WHEN 'INTO'
3035             PERFORM 363-Set-Upd
3036             MOVE F-Sort-Work-REC TO WS-Held-Reference-TXT
3037         WHEN 'GIVING'
3038             IF WS-Held-Reference-TXT NOT = SPACES
3039                 MOVE WS-Held-Reference-TXT To F-Sort-Work-REC
3040                 MOVE SPACES          To WS-Held-Reference-TXT
3041                 F-SW-Ref-Flag-CHR
3042             RELEASE F-Sort-Work-REC
3043         END-IF
3044         PERFORM 362-Release-Upd
3045         WHEN 'REMAINDER'
3046             PERFORM 362-Release-Upd
3047         WHEN OTHER
3048             PERFORM 361-Release-Ref
3049         END-EVALUATE
3050     .
3051
3052     351-FREE SECTION.
3053         PERFORM 362-Release-Upd
3054     .
3055
3056 GC1213 351-GENERATE SECTION.
3057 GC1213     PERFORM 362-Release-Upd
3058 GC1213     .
3059
3060     351-INITIALIZE SECTION.
3061         EVALUATE WS-Token-Prev-TXT
3062         WHEN 'INITIALIZE'
3063             PERFORM 362-Release-Upd
3064         WHEN 'REPLACING'
3065             PERFORM 361-Release-Ref
3066         END-EVALUATE
3067     .
3068
3069 GC1213 351-INITIATE SECTION.
3070 GC1213     PERFORM 362-Release-Upd
3071 GC1213     .
3072
3073     351-INSPECT SECTION.
3074         EVALUATE WS-Token-Prev-TXT
3075         WHEN 'INSPECT'
3076             PERFORM 364-Set-Ref
3077             MOVE SPACES TO WS-Held-Reference-TXT
3078             MOVE SPACES TO WS-Token-Prev-TXT
3079         WHEN 'TALLYING'
3080             PERFORM 362-Release-Upd
3081             MOVE SPACES TO WS-Token-Prev-TXT
3082         WHEN 'REPLACING'
3083             IF WS-Held-Reference-TXT NOT = SPACES
=====

```

GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL

Page: 73

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 74

```

=====
3084             MOVE WS-Held-Reference-TXT TO F-Sort-Work-REC
3085             MOVE SPACES          TO WS-Held-Reference-TXT
3086             MOVE '*'              TO F-SW-Ref-Flag-CHR
3087             RELEASE F-Sort-Work-REC
3088             END-IF
3089             MOVE SPACES TO WS-Token-Prev-TXT
3090             WHEN 'CONVERTING'
3091                 IF WS-Held-Reference-TXT NOT = SPACES
3092                     MOVE WS-Held-Reference-TXT TO F-Sort-Work-REC
3093                     MOVE SPACES          TO WS-Held-Reference-TXT
3094                     MOVE '*'              TO F-SW-Ref-Flag-CHR
3095                     RELEASE F-Sort-Work-REC
3096                     END-IF
3097                     MOVE SPACES TO WS-Token-Prev-TXT
3098             WHEN OTHER
3099                 PERFORM 361-Release-Ref
3100             END-EVALUATE
3101             .
3102
3103             351-MOVE SECTION.
3104                 EVALUATE WS-Token-Prev-TXT
3105                 WHEN 'TO'
3106                     PERFORM 362-Release-Upd
3107                 WHEN OTHER
3108                     PERFORM 361-Release-Ref
3109                 END-EVALUATE
3110                 .
3111
3112             351-MULTIPLY SECTION.
3113                 EVALUATE WS-Token-Prev-TXT
3114                 WHEN 'BY'
3115                     PERFORM 363-Set-Upd
3116                     MOVE F-Sort-Work-REC TO WS-Held-Reference-TXT
3117                 WHEN 'GIVING'
3118                     MOVE WS-Held-Reference-TXT TO F-Sort-Work-REC
3119                     MOVE SPACES          TO WS-Held-Reference-TXT
3120                                     F-SW-Ref-Flag-CHR
3121                     RELEASE F-Sort-Work-REC
3122                     PERFORM 362-Release-Upd
3123                 WHEN OTHER
3124                     PERFORM 361-Release-Ref
3125                 END-EVALUATE
3126                 .
3127
3128             351-PERFORM SECTION.
3129                 EVALUATE WS-Token-Prev-TXT
3130                 WHEN 'VARYING'
3131                     PERFORM 362-Release-Upd
3132                     MOVE SPACES TO WS-Token-Prev-TXT
3133                 WHEN 'AFTER'
3134                     PERFORM 362-Release-Upd
3135                     MOVE SPACES TO WS-Token-Prev-TXT
3136                 WHEN OTHER

```

GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL

Page: 74

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 75

```

=====
3137             PERFORM 361-Release-Ref
3138             END-EVALUATE
3139             .
3140
3141         351-SET SECTION.
3142             EVALUATE WS-Token-Prev-TXT
3143             WHEN 'SET'
3144                 PERFORM 362-Release-Upd
3145             WHEN OTHER
3146                 PERFORM 361-Release-Ref
3147             END-EVALUATE
3148             .
3149
3150         351-STRING SECTION.
3151             EVALUATE WS-Token-Prev-TXT
3152             WHEN 'INTO'
3153                 PERFORM 362-Release-Upd
3154             WHEN 'POINTER'
3155                 PERFORM 362-Release-Upd
3156             WHEN OTHER
3157                 PERFORM 361-Release-Ref
3158             END-EVALUATE
3159             .
3160
3161         351-SUBTRACT SECTION.
3162             EVALUATE WS-Token-Prev-TXT
3163             WHEN 'GIVING'
3164                 PERFORM 362-Release-Upd
3165             WHEN 'FROM'
3166                 PERFORM 362-Release-Upd
3167             WHEN OTHER
3168                 PERFORM 361-Release-Ref
3169             END-EVALUATE
3170             .
3171
3172 GC1213 351-TERMINATE SECTION.
3173 GC1213     PERFORM 362-Release-Upd
3174 GC1213     .
3175
3176         351-TRANSFORM SECTION.
3177             EVALUATE WS-Token-Prev-TXT
3178             WHEN 'TRANSFORM'
3179                 PERFORM 362-Release-Upd
3180             MOVE SPACES TO WS-Token-Prev-TXT
3181             WHEN OTHER
3182                 PERFORM 361-Release-Ref
3183             END-EVALUATE
3184             .
3185
3186         351-UNSTRING SECTION.
3187             EVALUATE WS-Token-Prev-TXT
3188             WHEN 'INTO'
3189                 PERFORM 362-Release-Upd
=====

```

GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL

Page: 75

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 76

```

=====
3190      WHEN 'DELIMITER'
3191          PERFORM 362-Release-Upd
3192      WHEN 'COUNT'
3193          PERFORM 362-Release-Upd
3194      WHEN 'POINTER'
3195          PERFORM 362-Release-Upd
3196      WHEN 'TALLYING'
3197          PERFORM 362-Release-Upd
3198      WHEN OTHER
3199          PERFORM 361-Release-Ref
3200      END-EVALUATE
3201      .
3202
3203      360-Release-Def SECTION.
3204          MOVE SPACES                TO F-Sort-Work-REC
3205          MOVE WS-Curr-Prog-ID-TXT   TO F-SW-Prog-ID-TXT
3206          MOVE WS-Token-Curr-Uc-TXT  TO F-SW-Token-Uc-TXT
3207          MOVE WS-Token-Curr-TXT     TO F-SW-Token-TXT
3208          MOVE WS-Curr-Section-TXT   TO F-SW-Section-TXT
3209          MOVE WS-Curr-Line-NUM      TO F-SW-Def-Line-NUM
3210          MOVE 0                    TO F-SW-Ref-Line-NUM
3211          RELEASE F-Sort-Work-REC
3212      .
3213
3214      361-Release-Ref SECTION.
3215          PERFORM 364-Set-Ref
3216          RELEASE F-Sort-Work-REC
3217      .
3218
3219      362-Release-Upd SECTION.
3220          PERFORM 363-Set-Upd
3221          RELEASE F-Sort-Work-REC
3222      .
3223
3224      363-Set-Upd SECTION.
3225          MOVE SPACES                TO F-Sort-Work-REC
3226          MOVE WS-Curr-Prog-ID-TXT   TO F-SW-Prog-ID-TXT
3227          MOVE WS-Token-Curr-Uc-TXT  TO F-SW-Token-Uc-TXT
3228          MOVE WS-Token-Curr-TXT     TO F-SW-Token-TXT
3229          MOVE WS-Curr-Section-TXT   TO F-SW-Section-TXT
3230          MOVE WS-Curr-Line-NUM      TO F-SW-Ref-Line-NUM
3231          MOVE '*'                   TO F-SW-Ref-Flag-CHR
3232      .
3233
3234      364-Set-Ref SECTION.
3235          MOVE SPACES                TO F-Sort-Work-REC
3236          MOVE WS-Curr-Prog-ID-TXT   TO F-SW-Prog-ID-TXT
3237          MOVE WS-Token-Curr-Uc-TXT  TO F-SW-Token-Uc-TXT
3238          MOVE WS-Token-Curr-TXT     TO F-SW-Token-TXT
3239          MOVE WS-Curr-Section-TXT   TO F-SW-Section-TXT
3240          MOVE WS-Curr-Line-NUM      TO F-SW-Ref-Line-NUM
3241      .
3242
=====

```

GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL

Page: 76

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 77

```

=====
3243 GC1213 365-Release-Arg SECTION.
3244 GC1213      PERFORM 366-Set-Arg
3245 GC1213      RELEASE F-Sort-Work-REC
3246 GC1213      .
3247
3248 GC1213 366-Set-Arg SECTION.
3249 GC1213      MOVE SPACES              TO F-Sort-Work-REC
3250 GC1213      MOVE WS-Curr-Prog-ID-TXT TO F-SW-Prog-ID-TXT
3251 GC1213      MOVE WS-Token-Curr-Uc-TXT TO F-SW-Token-Uc-TXT
3252 GC1213      MOVE WS-Token-Curr-TXT   TO F-SW-Token-TXT
3253 GC1213      MOVE WS-Curr-Section-TXT TO F-SW-Section-TXT
3254 GC1213      MOVE WS-Curr-Line-NUM     TO F-SW-Ref-Line-NUM
3255 GC1213      MOVE 'C'                  TO F-SW-Ref-Flag-CHR
3256 GC1213      .
3257

```

```

=====
GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL

```

Page: 77

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 78

```

=====
3259      400-Produce-Xref-Listing SECTION.
3260      MOVE SPACES          TO WS-Xref-Detail-Line-TXT
3261      WS-Group-Indicators-TXT
3262      MOVE 0                TO WS-I-SUB
3263      WS-Lines-Left-NUM
3264 GC0710  MOVE 'N'          TO WS-RS-Duplicate-CHR
3265      PERFORM FOREVER
3266      RETURN F-Sort-Work-FILE AT END
3267 GC1213      IF WS-Xref-Detail-Line-TXT NOT = SPACES
3268 GC1213      PERFORM 410-Generate-Report-Line
3269 GC1213      END-IF
3270 GC1213      MOVE SPACES TO WS-Xref-Detail-Line-TXT
3271 GC1213      PERFORM 410-Generate-Report-Line
3272 GC1213      UNTIL WS-Lines-Left-NUM = 0
3273 GC1213      MOVE 'Y' TO WS-Suppress-FF-CHR
3274 GC1213      PERFORM 420-Generate-Xref-Footer
3275      EXIT PERFORM
3276      END-RETURN
3277      IF F-SW-Prog-ID-TXT NOT = WS-GI-Prog-ID-TXT
3278      OR F-SW-Token-Uc-TXT NOT = WS-GI-Token-TXT
3279 GC0710      MOVE 'N' TO WS-RS-Duplicate-CHR
3280      IF WS-Xref-Detail-Line-TXT NOT = SPACES
3281      PERFORM 410-Generate-Report-Line
3282      END-IF
3283      IF F-SW-Prog-ID-TXT NOT = WS-GI-Prog-ID-TXT
3284 GC1213      MOVE SPACES TO WS-Xref-Detail-Line-TXT
3285 GC1213      PERFORM 410-Generate-Report-Line
3286 GC1213      UNTIL WS-Lines-Left-NUM = 0
3287      END-IF
3288      MOVE F-SW-Prog-ID-TXT TO WS-GI-Prog-ID-TXT
3289      MOVE F-SW-Token-Uc-TXT TO WS-GI-Token-TXT
3290      END-IF
3291 GC0710      IF F-SW-Token-Uc-TXT = WS-GI-Token-TXT
3292 GC0710      AND F-SW-Def-Line-NUM NOT = SPACES
3293 GC0710      AND WS-Xref-Detail-Line-TXT NOT = SPACES
3294 GC0710      MOVE 'Y' TO WS-RS-Duplicate-CHR
3295 GC0710      PERFORM 410-Generate-Report-Line
3296 GC0710      MOVE 0 TO WS-I-SUB
3297 GC0710      MOVE F-SW-Prog-ID-TXT TO WS-XDL-Prog-ID-TXT
3298 GC0710      MOVE ' (Duplicate Definition)' TO WS-XDL-Token-TXT
3299 GC0710      MOVE F-SW-Section-TXT TO WS-XDL-Section-TXT
3300 GC0710      MOVE F-SW-Def-Line-NUM TO WS-XDL-Def-Line-NUM
3301 GC0710      EXIT PERFORM CYCLE
3302 GC0710      END-IF
3303 GC0710      IF F-SW-Token-Uc-TXT = WS-GI-Token-TXT
3304 GC0710      AND F-SW-Def-Line-NUM = SPACES
3305 GC0710      AND WS-RS-Duplicate-CHR = 'Y'
3306 GC0710      MOVE 'N' TO WS-RS-Duplicate-CHR
3307 GC0710      PERFORM 410-Generate-Report-Line
3308 GC0710      MOVE 0 TO WS-I-SUB
3309 GC0710      MOVE F-SW-Prog-ID-TXT TO WS-XDL-Prog-ID-TXT
3310 GC0710      MOVE ' (Duplicate References)' TO WS-XDL-Token-TXT
=====

```

GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL

Page: 78

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 79

```

=====
3311 GC0710          END-IF
3312                IF WS-Xref-Detail-Line-TXT = SPACES
3313                    MOVE F-SW-Prog-ID-TXT TO WS-XDL-Prog-ID-TXT
3314                    MOVE F-SW-Token-TXT TO WS-XDL-Token-TXT
3315                    MOVE F-SW-Section-TXT TO WS-XDL-Section-TXT
3316                    IF F-SW-Def-Line-NUM NOT = SPACES
3317                        MOVE F-SW-Def-Line-NUM TO WS-XDL-Def-Line-NUM
3318                    END-IF
3319                END-IF
3320                IF F-SW-Reference-TXT > '000000'
3321                    ADD 1 TO WS-I-SUB
3322                    IF WS-I-SUB > WS-Xref-Lines-Per-Rec-NUM
3323                        PERFORM 410-Generate-Report-Line
3324                        MOVE 1 TO WS-I-SUB
3325                    END-IF
3326                    MOVE F-SW-Ref-Line-NUM
3327                        TO WS-XDL-Ref-Line-NUM (WS-I-SUB)
3328                    MOVE F-SW-Ref-Flag-CHR
3329                        TO WS-XDL-Ref-Flag-CHR (WS-I-SUB)
3330                END-IF
3331            END-PERFORM
3332            IF WS-Xref-Detail-Line-TXT NOT = SPACES
3333                PERFORM 410-Generate-Report-Line
3334            END-IF
3335            .
=====

```


GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 80

```

=====
3337      410-Generate-Report-Line SECTION.
3338      IF WS-Lines-Left-NUM < 1
3339 GC1213      PERFORM 420-Generate-Xref-Footer
3340 GC1213      ADD 1 TO WS-Page-NUM
3341 GC1213      MOVE 'Page:' TO WS-PN-Literal-TXT
3342 GC1213      MOVE WS-Page-NUM TO WS-PN-Page-NUM
3343 GC1213      CALL 'C$JUSTIFY' USING WS-PN-Page-NUM, 'Left'
3344 GC1213      CALL 'C$JUSTIFY' USING WS-Page-No-TXT, 'Right'
3345 GC1213      IF L-Listing-CD = 1 *> LANDSCAPE
3346 GC1213          MOVE WS-Version-TXT
3347 GC1213              TO F-Listing-135-REC
3348 GC1213          MOVE 'Cross-Reference Listing'
3349 GC1213              TO F-Listing-135-REC(25:23)
3350 GC1213          MOVE WS-Formatted-DT
3351 GC1213              TO F-Listing-135-REC(126:10)
3352 GC1213          WRITE F-Listing-135-REC BEFORE 1 *> Page Header Line #1
3353 GC1213          MOVE WS-Program-Path-TXT
3354 GC1213              TO F-Listing-135-REC
3355 GC1213          WRITE F-Listing-135-REC BEFORE 1 *> Page Header Line #2
3356 GC1213          MOVE 'PROGRAM-ID Identifier/Register/Function' &
3357 GC1213              ' Defn Where Defined References'
3358 GC1213              TO F-Listing-135-REC
3359 GC1213          MOVE WS-Page-No-TXT
3360 GC1213              TO F-Listing-135-REC(126:10)
3361 GC1213          WRITE F-Listing-135-REC BEFORE 1 *> Page Header Line #3
3362 GC1213          MOVE ALL '=' TO F-Listing-135-REC
3363 GC1213          MOVE SPACE TO F-Listing-135-REC(16:1)
3364 GC1213              F-Listing-135-REC(49:1)
3365 GC1213              F-Listing-135-REC(56:1)
3366 GC1213              F-Listing-135-REC(72:1)
3367 GC1213          WRITE F-Listing-135-REC BEFORE 1 *> Page Header Line #4
3368 GC1213      ELSE *> PORTRAIT
3369 GC1213          MOVE WS-Version-TXT
3370 GC1213              TO F-Listing-96-REC
3371 GC1213          MOVE 'Cross-Reference Listing'
3372 GC1213              TO F-Listing-96-REC(25:23)
3373 GC1213          MOVE WS-Formatted-DT
3374 GC1213              TO F-Listing-96-REC(87:10)
3375 GC1213          WRITE F-Listing-96-REC BEFORE 1 *> Page Header Line #1
3376 GC1213          MOVE WS-Program-Path-TXT(40:96)
3377 GC1213              TO F-Listing-96-REC
3378 GC1213          WRITE F-Listing-96-REC BEFORE 1 *> Page Header Line #2
3379 GC1213          MOVE 'PROGRAM-ID Identifier/Register/Function' &
3380 GC1213              ' Defn Where Defined References'
3381 GC1213              TO F-Listing-96-REC
3382 GC1213          MOVE WS-Page-No-TXT
3383 GC1213              TO F-Listing-96-REC(87:10)
3384 GC1213          WRITE F-Listing-96-REC BEFORE 1 *> Page Header Line #3
3385 GC1213          MOVE ALL '=' TO F-Listing-96-REC
3386 GC1213          MOVE SPACE TO F-Listing-96-REC(16:1)
3387 GC1213              F-Listing-96-REC(49:1)
3388 GC1213              F-Listing-96-REC(56:1)
=====

```

GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL

Page: 80

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 81

```

=====
3389 GC1213          F-Listing-96-REC(72:1)
3390 GC1213          WRITE F-Listing-96-REC BEFORE 1 *> Page Header Line #4
3391 GC1213          END-IF
3392 GC1213          COMPUTE WS-Lines-Left-NUM = WS-Lines-Per-Page-NUM - 4
3393          END-IF
3394 GC1213          IF L-Listing-CD = 1 *> LANDSCAPE
3395 GC1213              WRITE F-Listing-135-REC FROM WS-Xref-Detail-Line-TXT
3396 GC1213              BEFORE 1
3397 GC1213          ELSE          *> PORTRAIT
3398 GC1213              WRITE F-Listing-96-REC FROM WS-Xref-Detail-Line-TXT
3399 GC1213              BEFORE 1
3400 GC1213          END-IF
3401          MOVE SPACES TO WS-Xref-Detail-Line-TXT
3402          MOVE 0 TO WS-I-SUB
3403          SUBTRACT 1 FROM WS-Lines-Left-NUM
3404          .
3405 GC1213 420-Generate-Xref-Footer SECTION.
3406 GC1213          IF L-Listing-CD = 1 *> LANDSCAPE
3407 GC1213              WRITE F-Listing-135-REC FROM SPACES BEFORE 1 *> Footer Line #1
3408 GC1213              MOVE ALL '='
3409 GC1213                  TO F-Listing-135-REC
3410 GC1213              WRITE F-Listing-135-REC BEFORE 1 *> Footer Line #2
3411 GC1213              MOVE WS-Copyright-TXT
3412 GC1213                  TO F-Listing-135-REC
3413 GC1213              MOVE WS-Page-No-TXT
3414 GC1213                  TO F-Listing-135-REC(126:10)
3415 GC1213              IF WS-Suppress-FF-CHR = 'Y'
3416 GC1213                  WRITE F-Listing-135-REC BEFORE 1 *> Footer Line #3
3417 GC1213              ELSE
3418 GC1213                  WRITE F-Listing-135-REC BEFORE PAGE *> Footer Line #3
3419 GC1213                  WRITE F-Listing-135-REC FROM SPACES BEFORE 1 *> Spaces After FF Charac
3420 GC1213              ter
3421 GC1213          ELSE          *> PORTRAIT
3422 GC1213              WRITE F-Listing-96-REC FROM SPACES BEFORE 1 *> Footer Line #1
3423 GC1213              MOVE ALL '='
3424 GC1213                  TO F-Listing-96-REC
3425 GC1213              WRITE F-Listing-96-REC BEFORE 1 *> Footer Line #2
3426 GC1213              MOVE WS-Copyright-TXT
3427 GC1213                  TO F-Listing-96-REC
3428 GC1213              MOVE WS-Page-No-TXT
3429 GC1213                  TO F-Listing-96-REC(87:10)
3430 GC1213              IF WS-Suppress-FF-CHR = 'Y'
3431 GC1213                  WRITE F-Listing-96-REC BEFORE 1 *> Footer Line #3
3432 GC1213              ELSE
3433 GC1213                  WRITE F-Listing-96-REC BEFORE PAGE *> Footer Line #3
3434 GC1213                  WRITE F-Listing-96-REC FROM SPACES BEFORE 1 *> Spaces After FF Charact
3435 GC1213              er
3436 GC1213          END-IF
3437 GC1213          .
=====

```

GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL

Page: 81

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 82

=====

```

3439      500-Produce-Source-Listing SECTION.
3440      OPEN INPUT F-Original-Src-FILE
3441              F-Expanded-Src-FILE
3442      MOVE 0 TO WS-Src-Line-NUM
3443      PERFORM FOREVER
3444              READ F-Expanded-Src-FILE AT END
3445 GC1213      MOVE SPACES TO WS-Src-Detail-Line-TXT
3446 GC1213      PERFORM 530-Generate-Source-Line
3447 GC1213      UNTIL WS-Lines-Left-NUM = 0
3448      EXIT PERFORM
3449      END-READ
3450 GC0712      IF F-ES-1-7-TXT NOT = '#DEFLIT'
3451 GC0712      IF F-ES-1-CHR = '#'
3452 GC0712      PERFORM 510-Control-Record
3453 GC0712      ELSE
3454 GC0712      PERFORM 520-Expanded-Src-Record
3455 GC0712      END-IF
3456 GC0712      END-IF
3457      END-PERFORM
3458      CLOSE F-Original-Src-FILE
3459              F-Expanded-Src-FILE
3460      .

```

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 83

=====

```

3462      510-Control-Record SECTION.
3463      UNSTRING F-ES-2-256-TXT-256
3464      DELIMITED BY ','
3465      INTO WS-Temp-10-Chars-TXT
3466      WS-Temp-256-Chars-TXT
3467      WS-Dummy-TXT
3468 GC1010  IF UPPER-CASE(TRIM(WS-Temp-256-Chars-TXT,Trailing)) =
3469 GC1010  TRIM(WS-Main-Module-Name-TXT) *> Main Pgm
3470      SET WS-RS-In-Main-Module-BOOL TO TRUE
3471      IF WS-Src-Line-NUM > 0
3472      READ F-Expanded-Src-FILE END-READ
3473      END-IF
3474      ELSE *> COPY
3475      SET WS-RS-In-Copybook-BOOL TO TRUE
3476      END-IF
3477      .

```

=====

GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL

Page: 83

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 84

```

=====
3479      520-Expanded-Src-Record SECTION.
3480      IF WS-RS-In-Main-Module-BOOL
3481          ADD 1 To WS-Curr-Line-NUM
3482 GC0712      READ F-Original-Src-FILE AT END CONTINUE END-READ
3483          ADD 1 TO WS-Src-Line-NUM
3484          MOVE SPACES TO WS-Src-Detail-Line-TXT
3485          MOVE WS-Src-Line-NUM TO WS-SDL-Line-NUM
3486 GC1213      MOVE F-Original-Src-REC TO WS-SDL-Statement-TXT
3487 GC0712      MOVE LOWER-CASE(TRIM(F-OS-8-72-TXT,LEADING))
3488 GC0712          TO WS-Temp-65-Chars-TXT
3489 GC0712      INSPECT WS-Temp-65-Chars-TXT REPLACING ALL '.' BY SPACE
3490 GC0712      EVALUATE TRUE
3491          WHEN F-OS-7-CHR = '/'
3492              MOVE SPACES TO WS-Src-Detail-Line-TXT
3493              PERFORM 530-Generate-Source-Line
3494              UNTIL WS-Lines-Left-NUM = 0
3495          WHEN WS-Temp-65-Chars-TXT = "eject"
3496              MOVE SPACES TO WS-Src-Detail-Line-TXT
3497              PERFORM 530-Generate-Source-Line
3498              UNTIL WS-Lines-Left-NUM = 0
3499          EXIT SECTION
3500          WHEN WS-Temp-65-Chars-TXT = "skip1"
3501              MOVE SPACES TO WS-Src-Detail-Line-TXT
3502              PERFORM 530-Generate-Source-Line
3503              EXIT SECTION
3504          WHEN WS-Temp-65-Chars-TXT = "skip2"
3505              MOVE SPACES TO WS-Src-Detail-Line-TXT
3506              PERFORM 530-Generate-Source-Line 2 TIMES
3507              EXIT SECTION
3508          WHEN WS-Temp-65-Chars-TXT = "skip3"
3509              MOVE SPACES TO WS-Src-Detail-Line-TXT
3510              PERFORM 530-Generate-Source-Line 3 TIMES
3511              EXIT SECTION
3512 GC0712      END-EVALUATE
3513          PERFORM 530-Generate-Source-Line
3514      ELSE
3515          IF F-Expanded-Src-REC NOT = SPACES
3516              MOVE SPACES TO WS-Src-Detail-Line-TXT
3517 GC1213      MOVE F-Expanded-Src-REC
3518          TO WS-SDL-Statement-TXT
3519 GC0712      MOVE LOWER-CASE(TRIM(F-OS-8-72-TXT,LEADING))
3520 GC0712          TO WS-Temp-65-Chars-TXT
3521 GC0712      INSPECT WS-Temp-65-Chars-TXT
3522 GC0712          REPLACING ALL '.' BY SPACE
3523 GC0712      EVALUATE TRUE
3524          WHEN WS-Temp-65-Chars-TXT = "eject"
3525              MOVE 0 TO WS-Lines-Left-NUM
3526              EXIT SECTION
3527          WHEN WS-Temp-65-Chars-TXT = "skip1"
3528              MOVE SPACES TO WS-Src-Detail-Line-TXT
3529              PERFORM 530-Generate-Source-Line
3530              EXIT SECTION
=====

```

GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL

Page: 84

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 85

```

=====
3531 GC0712          WHEN WS-Temp-65-Chars-TXT = "skip2"
3532 GC0712          MOVE SPACES TO WS-Src-Detail-Line-TXT
3533 GC0712          PERFORM 530-Generate-Source-Line 2 TIMES
3534 GC0712          EXIT SECTION
3535 GC0712          WHEN WS-Temp-65-Chars-TXT = "skip3"
3536 GC0712          MOVE SPACES TO WS-Src-Detail-Line-TXT
3537 GC0712          PERFORM 530-Generate-Source-Line 3 TIMES
3538 GC0712          EXIT SECTION
3539 GC0712          END-EVALUATE
3540                  PERFORM 530-Generate-Source-Line
3541                  END-IF
3542          END-IF
3543          .
=====

```

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 86

```

=====
3545      530-Generate-Source-Line SECTION.
3546 GC1213      MOVE 1 TO WS-Src-Lines-NUM
3547 GC1213      IF L-Listing-CD = 1 *> LANDSCAPE
3548 GC1213          IF WS-SDL-Statement-TXT(129:128) > SPACES
3549 GC1213              ADD 1 TO WS-Src-Lines-NUM
3550 GC1213          END-IF
3551 GC1213      ELSE                                *> PORTRAIT
3552 GC1213          IF WS-SDL-Statement-TXT(90:167) > SPACES
3553 GC1213              ADD 1 TO WS-Src-Lines-NUM
3554 GC1213          IF WS-SDL-Statement-TXT(179:78) > SPACES
3555 GC1213              ADD 1 TO WS-Src-Lines-NUM
3556 GC1213          END-IF
3557 GC1213      END-IF
3558 GC1213      END-IF
3559 GC1213      IF WS-Lines-Left-NUM < WS-Src-Lines-NUM
3560 GC1213          IF WS-Page-Num > 0 *> Don't print footer before page 1
3561 GC1213              IF L-Listing-CD = 1 *> LANDSCAPE
3562 GC1213                  IF WS-Src-Lines-NUM = 2
3563 GC1213                      WRITE F-Listing-135-REC FROM SPACES BEFORE 1 *> Blank Line
3564 GC1213                  END-IF
3565 GC1213                  WRITE F-Listing-135-REC FROM SPACES BEFORE 1 *> Footer Line #1
3566 GC1213                  MOVE ALL '='
3567 GC1213                      TO F-Listing-135-REC
3568 GC1213                  WRITE F-Listing-135-REC BEFORE 1 *> Footer Line #2
3569 GC1213                  MOVE WS-Copyright-TXT
3570 GC1213                      TO F-Listing-135-REC
3571 GC1213                  MOVE WS-Page-No-TXT
3572 GC1213                      TO F-Listing-135-REC(126:10)
3573 GC1213                  WRITE F-Listing-135-REC BEFORE PAGE *> Footer Line #3
3574 GC1213                  WRITE F-Listing-135-REC FROM SPACES BEFORE 1 *> Spaces After FF Ch
aracter
3575 GC1213          ELSE                                *> PORTRAIT
3576 GC1213              EVALUATE WS-Src-Lines-NUM
3577 GC1213                  WHEN 1 *> Need no extra blank lines
3578 GC1213                      CONTINUE
3579 GC1213                  WHEN 2 *> Need 1 extra blank line
3580 GC1213                      WRITE F-Listing-96-REC FROM SPACES BEFORE 1
3581 GC1213                  WHEN 3 *> Need 2 extra blank lines
3582 GC1213                      WRITE F-Listing-96-REC FROM SPACES BEFORE 1
3583 GC1213                      WRITE F-Listing-96-REC FROM SPACES BEFORE 1
3584 GC1213                  END-EVALUATE
3585 GC1213                  WRITE F-Listing-96-REC FROM SPACES BEFORE 1 *> Footer Line #1
3586 GC1213                  MOVE ALL '='
3587 GC1213                      TO F-Listing-96-REC
3588 GC1213                  WRITE F-Listing-96-REC BEFORE 1 *> Footer Line #2
3589 GC1213                  MOVE WS-Copyright-TXT
3590 GC1213                      TO F-Listing-96-REC
3591 GC1213                  MOVE WS-Page-No-TXT
3592 GC1213                      TO F-Listing-96-REC(87:10)
3593 GC1213                  WRITE F-Listing-96-REC BEFORE PAGE *> Footer Line #3
3594 GC1213                  WRITE F-Listing-96-REC FROM SPACES BEFORE 1 *> Spaces After FF Cha
racter
=====

```

GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL

Page: 86

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 87

```

=====
3595 GC1213          END-IF
3596 GC1213          END-IF
3597 GC1213          ADD 1          TO WS-Page-NUM
3598 GC1213          MOVE 'Page:'    TO WS-PN-Literal-TXT
3599 GC1213          MOVE WS-Page-NUM TO WS-PN-Page-NUM
3600 GC1213          CALL 'C$JUSTIFY' USING WS-PN-Page-NUM, 'Left'
3601 GC1213          CALL 'C$JUSTIFY' USING WS-Page-No-TXT, 'Right'
3602 GC1213          IF L-Listing-CD = 1 *> LANDSCAPE
3603 GC1213              MOVE WS-Version-TXT
3604 GC1213                  TO F-Listing-135-REC
3605 GC1213              MOVE 'Source Listing'
3606 GC1213                  TO F-Listing-135-REC(25:14)
3607 GC1213              MOVE WS-Formatted-DT
3608 GC1213                  TO F-Listing-135-REC(126:10)
3609 GC1213              WRITE F-Listing-135-REC BEFORE 1 *> Page Header Line #1
3610 GC1213              MOVE WS-Program-Path-TXT
3611 GC1213                  TO F-Listing-135-REC
3612 GC1213              WRITE F-Listing-135-REC BEFORE 1 *> Page Header Line #2
3613 GC1213              MOVE 'Line Statement'
3614 GC1213                  TO F-Listing-135-REC
3615 GC1213              MOVE WS-Page-No-TXT
3616 GC1213                  TO F-Listing-135-REC(126:10)
3617 GC1213              WRITE F-Listing-135-REC BEFORE 1 *> Page Header Line #3
3618 GC1213              MOVE WS-Src-Dashes-TXT
3619 GC1213                  TO F-Listing-135-REC
3620 GC1213              WRITE F-Listing-135-REC BEFORE 1 *> Page Header Line #4
3621 GC1213          ELSE          *> PORTRAIT
3622 GC1213              MOVE WS-Version-TXT
3623 GC1213                  TO F-Listing-96-REC
3624 GC1213              MOVE 'Source Listing'
3625 GC1213                  TO F-Listing-96-REC(25:14)
3626 GC1213              MOVE WS-Formatted-DT
3627 GC1213                  TO F-Listing-96-REC(87:10)
3628 GC1213              WRITE F-Listing-96-REC BEFORE 1 *> Page Header Line #1
3629 GC1213              MOVE WS-Program-Path-TXT(40:96)
3630 GC1213                  TO F-Listing-96-REC
3631 GC1213              WRITE F-Listing-96-REC BEFORE 1 *> Page Header Line #2
3632 GC1213              MOVE 'Line Statement'
3633 GC1213                  TO F-Listing-96-REC
3634 GC1213              MOVE WS-Page-No-TXT
3635 GC1213                  TO F-Listing-96-REC(87:10)
3636 GC1213              WRITE F-Listing-96-REC BEFORE 1 *> Page Header Line #3
3637 GC1213              MOVE WS-Src-Dashes-TXT
3638 GC1213                  TO F-Listing-96-REC
3639 GC1213              WRITE F-Listing-96-REC BEFORE 1 *> Page Header Line #4
3640 GC1213          END-IF
3641 GC1213          COMPUTE WS-Lines-Left-NUM = WS-Lines-Per-Page-NUM - 4
3642 GC1213          END-IF
3643 GC1213          IF L-Listing-CD = 1 *> LANDSCAPE
3644 GC1213              EVALUATE WS-Src-Lines-NUM
3645 GC1213              WHEN 1
3646 GC1213                  MOVE WS-Src-Detail-Line-TXT TO F-Listing-135-REC
3647 GC1213                  WRITE F-Listing-96-REC BEFORE 1
=====

```

GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL

Page: 87

GNUCOBOL 2.2 20JUL2017 Source Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

Line Statement

Page: 88

```

=====
3648 GC1213          SUBTRACT 1 FROM WS-Lines-Left-NUM
3649 GC1213          WHEN 2
3650 GC1213              MOVE WS-SDL-Statement-TXT TO WS-Src-Hold-TXT
3651 GC1213              MOVE WS-Src-Detail-Line-TXT TO F-Listing-135-REC
3652 GC1213              WRITE F-Listing-135-REC BEFORE 1 *> Prints chars 1-128 of stmtnt
3653 GC1213              MOVE SPACES TO WS-Src-Detail-Line-TXT
3654 GC1213              MOVE WS-Src-Hold-TXT(129:128) TO WS-SDL-Statement-TXT
3655 GC1213              MOVE WS-Src-Detail-Line-TXT TO F-Listing-135-REC
3656 GC1213              WRITE F-Listing-135-REC BEFORE 1 *> Prints chars 129-256 of stmtnt
3657 GC1213              SUBTRACT 2 FROM WS-Lines-Left-NUM
3658 GC1213          END-EVALUATE
3659 GC1213          ELSE          *> PORTRAIT
3660 GC1213              EVALUATE WS-Src-Lines-NUM
3661 GC1213              WHEN 1 *> Print only chars 1-89 of stmtnt
3662 GC1213                  WRITE F-Listing-96-REC FROM WS-Src-Detail-Line-TXT
3663 GC1213                      BEFORE 1
3664 GC1213                  SUBTRACT 1 FROM WS-Lines-Left-NUM
3665 GC1213              WHEN 2 *> Print only chars 1-89 and 90-178 of text
3666 GC1213                  MOVE WS-SDL-Statement-TXT TO WS-Src-Hold-TXT
3667 GC1213                  WRITE F-Listing-96-REC FROM WS-Src-Detail-Line-TXT
3668 GC1213                      BEFORE 1
3669 GC1213                  MOVE SPACES TO WS-Src-Detail-Line-TXT
3670 GC1213                  MOVE WS-Src-Hold-TXT(90:89) TO WS-SDL-Statement-TXT
3671 GC1213                  WRITE F-Listing-96-REC FROM WS-Src-Detail-Line-TXT
3672 GC1213                      BEFORE 1
3673 GC1213                  SUBTRACT 2 FROM WS-Lines-Left-NUM
3674 GC1213              WHEN 3 *> Print chars 1-89, 90-178 and 179-256 of stmtnt
3675 GC1213                  MOVE WS-SDL-Statement-TXT TO WS-Src-Hold-TXT
3676 GC1213                  WRITE F-Listing-96-REC FROM WS-Src-Detail-Line-TXT
3677 GC1213                      BEFORE 1
3678 GC1213                  MOVE SPACES TO WS-Src-Detail-Line-TXT
3679 GC1213                  MOVE WS-Src-Hold-TXT(90:89) TO WS-SDL-Statement-TXT
3680 GC1213                  WRITE F-Listing-96-REC FROM WS-Src-Detail-Line-TXT
3681 GC1213                      BEFORE 1
3682 GC1213                  MOVE SPACES TO WS-Src-Detail-Line-TXT
3683 GC1213                  MOVE WS-Src-Hold-TXT(179:78) TO WS-SDL-Statement-TXT
3684 GC1213                  WRITE F-Listing-96-REC FROM WS-Src-Detail-Line-TXT
3685 GC1213                      BEFORE 1
3686 GC1213                  SUBTRACT 3 FROM WS-Lines-Left-NUM
3687 GC1213              END-EVALUATE
3688 GC1213          END-IF
3689 GC1213          MOVE SPACES TO WS-Src-Detail-Line-TXT
3690 GC1213          .
3691 GC1213
3692 GC1213          END PROGRAM LISTING.
=====

```

GNUCOBOL 2.2 20JUL2017 Cross-Reference Listing				2017/07/22		
				/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl		
PROGRAM-ID	Identifier/Register/Function	Defn	Where Defined	References	Page: 89	
CHECKSRC	000-Main	1315	PROCEDURE			
CHECKSRC	L-A1-CHR	1305	LINKAGE	1317	1329	1332
				1339		
CHECKSRC	L-A2-IDENT-DIVISION-BOOL	1310	LINKAGE	1361*		
CHECKSRC	L-A2-LINKAGE-SECTION-BOOL	1309	LINKAGE	1355*		
CHECKSRC	L-A2-Nothing-Special-BOOL	1311	LINKAGE	1316*		
CHECKSRC	L-Argument-1-TXT	1304	LINKAGE	1313		
CHECKSRC	L-Argument-2-CHR	1308	LINKAGE	1314		
CHECKSRC	WS-Compressed-Src-TXT	1291	WORKING-STORAGE	1326*	1349	1353
				1359		
CHECKSRC	WS-CS-CHR	1292	WORKING-STORAGE	1333*	1339*	1348
				1352	1358	
CHECKSRC	WS-I-SUB	1300	WORKING-STORAGE	1327*	1328	1329
				1332	1339	1345*
				1346	1348	1349
				1352	1352	1353
				1358	1358	1359
CHECKSRC	WS-J-SUB	1302	WORKING-STORAGE	1325*	1331*	1333
				1338*	1339	
CHECKSRC	WS-RS-Found-SPACE-CHR	1296	WORKING-STORAGE			
CHECKSRC	WS-RS-Not-Skipping-SPACE-BOOL	1298	WORKING-STORAGE	1324*	1330	1337*
CHECKSRC	WS-RS-Skipping-SPACE-BOOL	1297	WORKING-STORAGE	1334*		
CHECKSRC	WS-Runtime-Switches-TXT	1295	WORKING-STORAGE			

GNUCOBOL 2.2 20JUL2017 Cross-Reference Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

PROGRAM-ID	Identifier/Register/Function	Defn	Where Defined	References	Page: 90	
GCic	000-File-Error	654	PROCEDURE			
GCic	000-Main	675	PROCEDURE			
GCic	100-Initialization	699	PROCEDURE	676		
GCic	200-Let-User-Set-Switches	813	PROCEDURE	679		
GCic	210-Run-Compiler	904	PROCEDURE	680		
GCic	220-Make-Listing	1040	PROCEDURE	684		
GCic	230-Run-Program	1071	PROCEDURE	688		
GCic	240-Find-LINKAGE-SECTION	1173	PROCEDURE	747		
GCic	250-Autoload-Listing	1212	PROCEDURE	690	1031	1065
GCic	900-Terminate	1258	PROCEDURE	692	741	884
				1032	1166	
GCic	COB-COLOR-BLACK	178	[screenio]	439	444	534
				544	554	559
				569	576	591
				606	622	629
				636		
GCic	COB-COLOR-BLUE	178	[screenio]	522		
GCic	COB-COLOR-CYAN	178	[screenio]	535		
GCic	COB-COLOR-GREEN	178	[screenio]	445	560	607
				623		
GCic	COB-COLOR-MAGENTA	178	[screenio]			
GCic	COB-COLOR-RED	178	[screenio]	528	592	
GCic	COB-COLOR-WHITE	178	[screenio]	440	523	529
				545	555	570
				577	630	637
GCic	COB-COLOR-YELLOW	178	[screenio]			
GCic	COB-SCR-ESC	178	[screenio]	883		
GCic	COB-SCR-F1	178	[screenio]	830		
GCic	COB-SCR-F10	178	[screenio]			
GCic	COB-SCR-F11	178	[screenio]			
GCic	COB-SCR-F12	178	[screenio]	886		
GCic	COB-SCR-F13	178	[screenio]			
GCic	COB-SCR-F14	178	[screenio]			
GCic	COB-SCR-F15	178	[screenio]			
GCic	COB-SCR-F16	178	[screenio]			
GCic	COB-SCR-F17	178	[screenio]			
GCic	COB-SCR-F18	178	[screenio]			
GCic	COB-SCR-F19	178	[screenio]			
GCic	COB-SCR-F2	178	[screenio]	836		
GCic	COB-SCR-F20	178	[screenio]			
GCic	COB-SCR-F21	178	[screenio]			
GCic	COB-SCR-F22	178	[screenio]			
GCic	COB-SCR-F23	178	[screenio]			
GCic	COB-SCR-F24	178	[screenio]			
GCic	COB-SCR-F25	178	[screenio]			
GCic	COB-SCR-F26	178	[screenio]			
GCic	COB-SCR-F27	178	[screenio]			
GCic	COB-SCR-F28	178	[screenio]			
GCic	COB-SCR-F29	178	[screenio]			
GCic	COB-SCR-F3	178	[screenio]	842		
GCic	COB-SCR-F30	178	[screenio]			
GCic	COB-SCR-F31	178	[screenio]			
GCic	COB-SCR-F32	178	[screenio]			

GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL

Page: 90

GNUCOBOL 2.2 20JUL2017 Cross-Reference Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

PROGRAM-ID	Identifier/Register/Function	Defn	Where Defined	References	Page: 91
=====					
GCic	COB-SCR-F33	178	[screenio]		
GCic	COB-SCR-F34	178	[screenio]		
GCic	COB-SCR-F35	178	[screenio]		
GCic	COB-SCR-F36	178	[screenio]		
GCic	COB-SCR-F37	178	[screenio]		
GCic	COB-SCR-F38	178	[screenio]		
GCic	COB-SCR-F39	178	[screenio]		
GCic	COB-SCR-F4	178	[screenio]	848	
GCic	COB-SCR-F40	178	[screenio]		
GCic	COB-SCR-F41	178	[screenio]		
GCic	COB-SCR-F42	178	[screenio]		
GCic	COB-SCR-F43	178	[screenio]		
GCic	COB-SCR-F44	178	[screenio]		
GCic	COB-SCR-F45	178	[screenio]		
GCic	COB-SCR-F46	178	[screenio]		
GCic	COB-SCR-F47	178	[screenio]		
GCic	COB-SCR-F48	178	[screenio]		
GCic	COB-SCR-F49	178	[screenio]		
GCic	COB-SCR-F5	178	[screenio]	854	
GCic	COB-SCR-F50	178	[screenio]		
GCic	COB-SCR-F51	178	[screenio]		
GCic	COB-SCR-F52	178	[screenio]		
GCic	COB-SCR-F53	178	[screenio]		
GCic	COB-SCR-F54	178	[screenio]		
GCic	COB-SCR-F55	178	[screenio]		
GCic	COB-SCR-F56	178	[screenio]		
GCic	COB-SCR-F57	178	[screenio]		
GCic	COB-SCR-F58	178	[screenio]		
GCic	COB-SCR-F59	178	[screenio]		
GCic	COB-SCR-F6	178	[screenio]	859	
GCic	COB-SCR-F60	178	[screenio]		
GCic	COB-SCR-F61	178	[screenio]		
GCic	COB-SCR-F62	178	[screenio]		
GCic	COB-SCR-F63	178	[screenio]		
GCic	COB-SCR-F64	178	[screenio]		
GCic	COB-SCR-F7	178	[screenio]	865	
GCic	COB-SCR-F8	178	[screenio]	871	
GCic	COB-SCR-F9	178	[screenio]	877	
GCic	COB-SCR-FATAL	178	[screenio]		
GCic	COB-SCR-KEY-DOWN	178	[screenio]		
GCic	COB-SCR-KEY-UP	178	[screenio]		
GCic	COB-SCR-MAX-FIELD	178	[screenio]		
GCic	COB-SCR-NO-FIELD	178	[screenio]		
GCic	COB-SCR-OK	178	[screenio]		
GCic	COB-SCR-PAGE_DOWN	178	[screenio]		
GCic	COB-SCR-PAGE_UP	178	[screenio]		
GCic	COB-SCR-PRINT	178	[screenio]		
GCic	COB-SCR-TIME-OUT	178	[screenio]		
GCic	F-Cobc-Output-FILE	171	FILE	162 1008 1026	
GCic	F-Cobc-Output-REC	172	FILE	1009 1014* 1015	
				1023* 1024	
GCic	F-Source-Code-FILE	174	FILE	165 655 1174	
				1178 1179 1192	

GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL

Page: 91

GNUCOBOL 2.2 20JUL2017 Cross-Reference Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

PROGRAM-ID	Identifier/Register/Function	Defn	Where Defined	References	Page: 92
GCic	F-Source-Code-REC	175	FILE	1193 1200 1183C 1197C	
GCic	F1		WORKING-STORAGE	206	
GCic	F12		WORKING-STORAGE	200	
GCic	F2		WORKING-STORAGE	213	
GCic	F3		WORKING-STORAGE	209	
GCic	F4		WORKING-STORAGE	207	
GCic	F5		WORKING-STORAGE	210	257
GCic	F6		WORKING-STORAGE	211	
GCic	F7		WORKING-STORAGE	214	
GCic	F8		WORKING-STORAGE	208	
GCic	F9		WORKING-STORAGE	212	
GCic	LD-Horiz-Line	433	SCREEN	801	
GCic	LD-LL-Corner	428	SCREEN	456 486 502	
				516	
GCic	LD-Lower-T	432	SCREEN	488	
GCic	LD-LR-Corner	430	SCREEN	458 490 504	
				518	
GCic	LD-UL-Corner	427	SCREEN	446 460 492	
				506	
GCic	LD-Upper-T	431	SCREEN	462	
GCic	LD-UR-Corner	429	SCREEN	448 464 494	
				508	
GCic	LD-Vert-Line	434	SCREEN	450 451 453	
				454 466 467	
				468 470 471	
				472 474 475	
				476 478 479	
				480 482 483	
				484 496 497	
				499 500 510	
				511 513 514	
GCic	LPP		PROCEDURE	1051C	
GCic	LPPP		PROCEDURE	1052C	
GCic	RETURN-CODE		PROCEDURE	1010 1043* 1057*	
				1059	
GCic	S-Blank-SCR	437	SCREEN	683 1234 1263	
GCic	S-Switches-SCR	439	SCREEN	827* 908 998	
				1027 1042 1063	
				1074 1260	
GCic	SELCHAR		PROCEDURE	719 822 825	
				832 838 844	
				850 861 867	
				873 879 1202	
GCic	WS-Cmd-Args-TXT	229	WORKING-STORAGE	723* 725 726	
				729 734	
GCic	WS-Cmd-End-Quote-CHR	231	WORKING-STORAGE	727* 730	
GCic	WS-Cmd-SUB	233	WORKING-STORAGE	724* 725 726	
				728* 732* 737*	
GCic	WS-Cmd-TXT	227	WORKING-STORAGE	905* 1000* 1005*	
				1007C 1076* 1083*	
				1093* 1096* 1103*	
				1107* 1113* 1118*	

GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL

Page: 92

GNUCOBOL 2.2 20JUL2017 Cross-Reference Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

PROGRAM-ID	Identifier/Register/Function	Defn	Where Defined	References	Page: 93
=====					
				1123* 1131* 1139*	
				1145* 1151* 1156*	
				1163C 1215* 1219*	
				1220C 1222* 1226*	
				1227C 1237* 1240*	
				1243C 1245C 1247C	
				1249C 1251C	
GCic	WS-Cobc-Cmd-TXT	235	WORKING-STORAGE	906* 915* 919*	
				923* 927* 932*	
				937* 942* 947*	
				952* 957* 961*	
				974* 982* 986*	
				1001	
GCic	WS-Compilation-Switches-TXT	180	WORKING-STORAGE		
GCic	WS-Config-Fn-TXT	237	WORKING-STORAGE	911* 917	
GCic	WS-CS-All-Switches-TXT	215	WORKING-STORAGE		
GCic	WS-CS-Arg-H1-TXT	182	WORKING-STORAGE	640*	
GCic	WS-CS-Arg-H2-TXT	183	WORKING-STORAGE	641*	
GCic	WS-CS-Args-TXT	181	WORKING-STORAGE	1154 1155	
GCic	WS-CS-Config-NUM	200	WORKING-STORAGE	632 887* 888	
				889* 910	
GCic	WS-CS-DEBUG-CHR	217	WORKING-STORAGE	593 831 832*	
				834* 930	
GCic	WS-CS-EXECUTE-CHR	218	WORKING-STORAGE	596 686 849	
				850* 852*	
GCic	WS-CS-Extra-H1-TXT	203	WORKING-STORAGE	638*	
GCic	WS-CS-Extra-H2-TXT	204	WORKING-STORAGE	639*	
GCic	WS-CS-Extra-TXT	202	WORKING-STORAGE	978 980	
GCic	WS-CS-Filename-TXT	193	WORKING-STORAGE	632 910	
GCic	WS-CS-Filenames-Table-TXT	192	WORKING-STORAGE		
GCic	WS-CS-Filenames-TXT	184	WORKING-STORAGE	192	
GCic	WS-CS-FREE-CHR	219	WORKING-STORAGE	601 872 873*	
				875* 955	
GCic	WS-CS-LIBRARY-CHR	220	WORKING-STORAGE	595 843 844*	
				846* 921 1081	
				1136 1175* 1202*	
GCic	WS-CS-LISTING-CHR	221	WORKING-STORAGE	597 682 819*	
				822* 825* 968	
				970* 972	
GCic	WS-CS-NOFUNC-CHR	222	WORKING-STORAGE	599 860 861*	
				863* 945	
GCic	WS-CS-NOTRUNC-CHR	223	WORKING-STORAGE	602 878 879*	
				881* 935	
GCic	WS-CS-Switch-Defaults-TXT	205	WORKING-STORAGE	216	
GCic	WS-CS-TRACEALL-CHR	224	WORKING-STORAGE	594 837 838*	
				840* 940	
GCic	WS-CS-WARNALL-CHR	225	WORKING-STORAGE	600 866 867*	
				869* 950	
GCic	WS-Delete-Fn-TXT	239	WORKING-STORAGE		
GCic	WS-File-Name-TXT	241	WORKING-STORAGE	165 663 668	
				731* 736* 739	
				752 755 762	
				765 776 1049C	

GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL

Page: 93

GNUCOBOL 2.2 20JUL2017 Cross-Reference Listing				2017/07/22		
				/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl		
PROGRAM-ID	Identifier/Register/Function	Defn	Where Defined	References	Page: 94	
GCic	WS-File-Status-Message-TXT	245	WORKING-STORAGE			
GCic	WS-FN-CHR	242	WORKING-STORAGE	757	764*	768*
GCic	WS-FSM-Msg-TXT	249	WORKING-STORAGE	658*	658*	658*
				658*	658*	658*
				658*	658*	658*
				658*	658*	658*
				658*	658*	658*
				658*	658*	658*
				658*	658*	658*
				658*	658*	658*
				658*	658*	658*
				658*	658*	658*
GCic	WS-FSM-Status-CD	247	WORKING-STORAGE	167	658	660
GCic	WS-Horizontal-Line-TXT	251	WORKING-STORAGE	447	457	461
				463	487	489
				493	503	507
				517	801*	
GCic	WS-I-SUB	253	WORKING-STORAGE	755*	756	757
				758	760	764
				768	783*	784
				785	786	788
				792	796	909*
				920*	924*	928*
				933*	938*	943*
				948*	953*	958*
				962*	975*	983*
				987*	1077*	1084*
				1094*	1097*	1104*
				1108*	1114*	1119*
				1124*	1132*	1140*
				1146*	1152*	1157*
GCic	WS-J-SUB	255	WORKING-STORAGE	1099*	1100	1101
				1106		
GCic	WS-Listing-CD	257	WORKING-STORAGE	816	855*	856
				857*	1053C	
GCic	WS-Listing-Filename-TXT	259	WORKING-STORAGE	162	992*	993C
				1002	1020	1048C
				1218	1225	
GCic	WS-Listing-TXT	261	WORKING-STORAGE	613	818*	821*
				824*		
GCic	WS-OC-Compile-DT	263	WORKING-STORAGE	525	709*	
GCic	WS-OS-Cygwin-BOOL	297	WORKING-STORAGE	752	776	1091
				1121	1214	
GCic	WS-OS-Dir-CHR	284	WORKING-STORAGE	753*	757	768
				777*	1117	
GCic	WS-OS-Exe-Ext-CONST	285	WORKING-STORAGE	1137	1138	
GCic	WS-OS-Lib-Ext-CONST	286	WORKING-STORAGE	1143	1144	
GCic	WS-OS-Lib-Type-CONST	287	WORKING-STORAGE	611		
GCic	WS-OS-OSX-BOOL	299	WORKING-STORAGE	1221		
GCic	WS-OS-Type-CD	288	WORKING-STORAGE	803	1050C	
GCic	WS-OS-Type-FILLER-TXT	301	WORKING-STORAGE	307		
GCic	WS-OS-Type-TXT	308	WORKING-STORAGE	803		
GCic	WS-OS-Types-TXT	307	WORKING-STORAGE			
=====						
GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL					Page: 94	

GNUCOBOL 2.2 20JUL2017 Cross-Reference Listing				2017/07/22		
				/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl		
PROGRAM-ID	Identifier/Register/Function	Defn	Where Defined	References	Page: 95	
GCic	WS-OS-UNIX-BOOL	298	WORKING-STORAGE	1121		
GCic	WS-OS-Windows-BOOL	296	WORKING-STORAGE	1214	1235	
GCic	WS-Output-Msg-TXT	311	WORKING-STORAGE	530	659*	806*
				893*	907*	997*
				1012*	1013	1021*
				1029*	1041*	1047*
				1056*	1061*	1073*
				1164*	1165*	1259
GCic	WS-Path-Delimiter-CHR	313	WORKING-STORAGE			
GCic	WS-PFN-CHR	320	WORKING-STORAGE	785	792*	796*
GCic	WS-Pgm-Nm-TXT	323	WORKING-STORAGE	789*	794*	991
				1130	1236	1239
GCic	WS-Prog-Extension-TXT	315	WORKING-STORAGE	790*	795*	
GCic	WS-Prog-File-Name-TXT	319	WORKING-STORAGE	571	762*	767*
				783	789	793
				985		
GCic	WS-Prog-Folder-TXT	317	WORKING-STORAGE	572	761*	766*
				770	771*	774C
				1090	1091	1095
				1100	1101	1106
				1112		
GCic	WS-RS-1st-Prog-Complete-BOOL	336	WORKING-STORAGE	1177	1186*	
GCic	WS-RS-Compile-Failed-BOOL	329	WORKING-STORAGE	1018*	1030	
GCic	WS-RS-Compile-OK-BOOL	327	WORKING-STORAGE	681	1011*	
GCic	WS-RS-Compile-OK-CHR	326	WORKING-STORAGE			
GCic	WS-RS-Compile-OK-Warn-BOOL	328	WORKING-STORAGE	681		
GCic	WS-RS-Complete-BOOL	331	WORKING-STORAGE	678	1016*	
GCic	WS-RS-Complete-CHR	330	WORKING-STORAGE			
GCic	WS-RS-Double-Quote-Used-BOOL	334	WORKING-STORAGE	1089*	1115*	1149
GCic	WS-RS-IDENT-DIV-CHR	335	WORKING-STORAGE			
GCic	WS-RS-More-To-1st-Prog-BOOL	337	WORKING-STORAGE	1176*		
GCic	WS-RS-No-Switch-Changes-BOOL	339	WORKING-STORAGE	815	896*	
GCic	WS-RS-No-Switch-Chgs-CHR	338	WORKING-STORAGE			
GCic	WS-RS-Not-Complete-BOOL	332	WORKING-STORAGE	677*		
GCic	WS-RS-Output-File-Avail-BOOL	343	WORKING-STORAGE	687	999*	
GCic	WS-RS-Output-File-Busy-BOOL	342	WORKING-STORAGE			
GCic	WS-RS-Output-File-Busy-CHR	341	WORKING-STORAGE			
GCic	WS-RS-Quote-CHR	333	WORKING-STORAGE			
GCic	WS-RS-Source-Rec-Ident-BOOL	346	WORKING-STORAGE	1185	1191	
GCic	WS-RS-Source-Rec-Ignored-BOOL	347	WORKING-STORAGE	1189*		
GCic	WS-RS-Source-Rec-Linkage-BOOL	345	WORKING-STORAGE	1190	1201	
GCic	WS-RS-Source-Record-Type-CHR	344	WORKING-STORAGE	1184C	1198C	
GCic	WS-RS-Switch-Changes-BOOL	340	WORKING-STORAGE	814*		
GCic	WS-RS-Switch-Error-CHR	348	WORKING-STORAGE			
GCic	WS-RS-Switch-Is-Bad-BOOL	349	WORKING-STORAGE			
GCic	WS-RS-Switch-Is-Good-BOOL	350	WORKING-STORAGE			
GCic	WS-Runtime-Switches-TXT	325	WORKING-STORAGE			
GCic	WS-Tally-QTY	352	WORKING-STORAGE	965*	967*	969

GNUCOBOL 2.2 20JUL2017 Cross-Reference Listing

2017/07/22

/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl

PROGRAM-ID	Identifier/Register/Function	Defn	Where Defined	References	Page: 96
LISTING	000-Main	2406	PROCEDURE		
LISTING	100-Initialization	2423	PROCEDURE	2407	
LISTING	300-Tokenize-Source	2496	PROCEDURE	2414	
LISTING	310-Get-Token	2547	PROCEDURE	2505	
LISTING	311-Control-Record	2707	PROCEDURE	2566	
LISTING	312-Expanded-Src-Record	2753	PROCEDURE	2568	
LISTING	313-Check-For-Numeric-Token	2764	PROCEDURE	2694	
LISTING	320-IDENTIFICATION-DIVISION	2806	PROCEDURE	2526	
LISTING	330-ENVIRONMENT-DIVISION	2826	PROCEDURE	2528	
LISTING	340-DATA-DIVISION	2852	PROCEDURE	2530	
LISTING	350-PROCEDURE-DIVISION	2908	PROCEDURE	2532	
LISTING	351-ACCEPT	2979	PROCEDURE	2935	
LISTING	351-ADD	2989	PROCEDURE	2937	
LISTING	351-ALLOCATE	3000	PROCEDURE	2939	
LISTING	351-CALL	3012	PROCEDURE	2941	
LISTING	351-COMPUTE	3023	PROCEDURE	2943	
LISTING	351-DIVIDE	3032	PROCEDURE	2945	
LISTING	351-FREE	3052	PROCEDURE	2947	
LISTING	351-GENERATE	3056	PROCEDURE	2949	2953 2969
LISTING	351-INITIALIZE	3060	PROCEDURE	2951	
LISTING	351-INITIATE	3069	PROCEDURE		
LISTING	351-INSPECT	3073	PROCEDURE	2955	
LISTING	351-MOVE	3103	PROCEDURE	2957	
LISTING	351-MULTIPLY	3112	PROCEDURE	2959	
LISTING	351-PERFORM	3128	PROCEDURE	2961	
LISTING	351-SET	3141	PROCEDURE	2963	
LISTING	351-STRING	3150	PROCEDURE	2965	
LISTING	351-SUBTRACT	3161	PROCEDURE	2967	
LISTING	351-TERMINATE	3172	PROCEDURE		
LISTING	351-TRANSFORM	3176	PROCEDURE	2971	
LISTING	351-UNSTRING	3186	PROCEDURE	2973	
LISTING	360-Release-Def	3203	PROCEDURE	2842	2879 2882
				2885	2888 2891
				2926	
LISTING	361-Release-Ref	3214	PROCEDURE	2844	2848 2901
				2975	2985 2996
				3008	3028 3048
				3065	3099 3108
				3124	3137 3146
				3157	3168 3182
				3199	
LISTING	362-Release-Upd	3219	PROCEDURE	2894	2897 2982
				2992	2994 3003
				3006	3015 3017
				3026	3044 3046
				3053	3057 3063
				3070	3080 3106
				3122	3131 3134
				3144	3153 3155
				3164	3166 3173
				3179	3189 3191
				3193	3195 3197
LISTING	363-Set-Upd	3224	PROCEDURE	3035	3115 3220

GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL

Page: 96

GNUCOBOL 2.2 20JUL2017 Cross-Reference Listing				2017/07/22		
				/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl		
PROGRAM-ID	Identifier/Register/Function	Defn	Where Defined	References	Page: 97	
LISTING	364-Set-Ref	3234	PROCEDURE	3076	3215	
LISTING	365-Release-Arg	3243	PROCEDURE	3019		
LISTING	366-Set-Arg	3248	PROCEDURE	3244		
LISTING	400-Produce-Xref-Listing	3259	PROCEDURE	2415		
LISTING	410-Generate-Report-Line	3337	PROCEDURE	3268	3271	3281
				3285	3295	3307
				3323	3333	
LISTING	420-Generate-Xref-Footer	3405	PROCEDURE	3274	3339	
LISTING	500-Produce-Source-Listing	3439	PROCEDURE	2409		
LISTING	510-Control-Record	3462	PROCEDURE	3452		
LISTING	520-Expanded-Src-Record	3479	PROCEDURE	3454		
LISTING	530-Generate-Source-Line	3545	PROCEDURE	3446	3493	3497
				3502	3506	3510
				3513	3529	3533
				3537	3540	
LISTING	F-ES-1-7-TXT	1426	FILE	2564	3450	
LISTING	F-ES-1-CHR	1423	FILE	2565	3451	
LISTING	F-ES-2-256-TXT-256	1424	FILE	2708	3463	
LISTING	F-ES-8-256-TXT	1427	FILE			
LISTING	F-Expanded-Src-FILE	1421	FILE	1412	2497	2544
				2554	3441	3444
				3459	3472	
LISTING	F-Expanded-Src-REC	1422	FILE	2498*	2552	2576
				2578	2608	2612
				2621	2625	2634
				2638	2646	2664
				2749*	2754	3515
				3517		
LISTING	F-Expanded-Src2-REC	1425	FILE			
LISTING	F-Listing-135-REC	1431	FILE	3347*	3349*	3351*
				3352	3354*	3355
				3358*	3360*	3361
				3362*	3363*	3364
				3365	3366	3367
				3395	3407	3409*
				3410	3412*	3414*
				3416	3418	3419
				3563	3565	3567*
				3568	3570*	3572*
				3573	3574	3604*
				3606*	3608*	3609
				3611*	3612	3614*
				3616*	3617	3619*
				3620	3646*	3651*
				3652	3655*	3656
LISTING	F-Listing-96-REC	1430	FILE	3370*	3372*	3374*
				3375	3377*	3378
				3381*	3383*	3384
				3385*	3386*	3387
				3388	3389	3390
				3398	3422	3424*
				3425	3427*	3429*
				3431	3433	3434

GNUCOBOL 2.2 20JUL2017 Cross-Reference Listing				2017/07/22		
				/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl		
PROGRAM-ID	Identifier/Register/Function	Defn	Where Defined	References	Page: 98	
=====				3580	3582	3583
				3585	3587*	3588
				3590*	3592*	3593
				3594	3623*	3625*
				3627*	3628	3630*
				3631	3633*	3635*
				3636	3638*	3639
				3647	3662	3667
				3671	3676	3680
				3684		
LISTING	F-Listing-FILE	1429	FILE	1414	2408	2416
LISTING	F-Listing-REC	1432	FILE			
LISTING	F-Original-Src-FILE	1434	FILE	1416	3440	3458
				3482		
				3486		
LISTING	F-Original-Src-REC	1435	FILE			
LISTING	F-OS-1-128-TXT	1436	FILE			
LISTING	F-OS-129-256-TXT	1441	FILE			
LISTING	F-OS-7-CHR	1438	FILE	3491		
LISTING	F-OS-8-72-TXT	1439	FILE	3487	3519	
LISTING	F-Sort-Work-FILE	1443	FILE	1418	2410	3266
LISTING	F-Sort-Work-REC	1444	FILE	2519*	2521	2556*
				2558	3036	3039*
				3042	3084*	3087
				3092*	3095	3116
				3118*	3121	3204*
				3211	3216	3221
				3225*	3235*	3245
				3249*		
LISTING	F-SW-Def-Line-NUM	1449	FILE	3209*	3292	3300
				3304	3316	3317
LISTING	F-SW-Prog-ID-TXT	1445	FILE	2411	3205*	3226*
				3236*	3250*	3277
				3283	3288	3297
				3309	3313	
LISTING	F-SW-Ref-Flag-CHR	1452	FILE	3041*	3086*	3094*
				3120*	3231*	3255*
				3328		
LISTING	F-SW-Ref-Line-NUM	1451	FILE	2413	3210*	3230*
				3240*	3254*	3326
LISTING	F-SW-Reference-TXT	1450	FILE	3320		
LISTING	F-SW-Section-TXT	1448	FILE	3208*	3229*	3239*
				3253*	3299	3315
LISTING	F-SW-Token-TXT	1447	FILE	3207*	3228*	3238*
				3252*	3314	
LISTING	F-SW-Token-Uc-TXT	1446	FILE	2412	3206*	3227*
				3237*	3251*	3278
				3289	3291	3303
LISTING	L-Listing-CD	2398	LINKAGE	2405	2445	2482
				3345	3394	3406
				3547	3561	3602
				3643		
LISTING	L-Listing-Fn-TXT	2388	LINKAGE	1414	2400	
LISTING	L-LPP-NUM	2394	LINKAGE	2403	2483	
=====						
GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL					Page: 98	

GNUCOBOL 2.2 20JUL2017 Cross-Reference Listing				2017/07/22		
				/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl		
PROGRAM-ID	Identifier/Register/Function	Defn	Where Defined	References	Page: 99	
LISTING	L-LPP-Port-NUM	2396	LINKAGE	2404	2485	
LISTING	L-OS-Type-CD	2392	LINKAGE	2402	2428	
LISTING	L-Src-Fn-TXT	2390	LINKAGE	1416	2401	2433
				2433*	2434	2435
				2439	2442	2455
				2457	2459	2464
LISTING	RETURN-CODE		PROCEDURE	2475		
LISTING	WS-CD-In-DATA-DIV-BOOL	1469	WORKING-STORAGE	2529		
LISTING	WS-CD-In-ENV-DIV-BOOL	1468	WORKING-STORAGE	2527		
LISTING	WS-CD-In-IDENT-DIV-BOOL	1467	WORKING-STORAGE	2525		
LISTING	WS-CD-In-PROC-DIV-BOOL	1470	WORKING-STORAGE	2531		
LISTING	WS-Copyright-TXT	1455	WORKING-STORAGE	2426*	2431*	3411
				3426	3569	3589
LISTING	WS-CPI-13-15-TXT	1476	WORKING-STORAGE	2820*		
LISTING	WS-CPI-16-CHR	1477	WORKING-STORAGE	2819		
LISTING	WS-CS-1-CHR	1480	WORKING-STORAGE	2742*		
LISTING	WS-CS-11-14-TXT	1483	WORKING-STORAGE	2744	2745*	
LISTING	WS-CS-15-CHR	1484	WORKING-STORAGE	2747*		
LISTING	WS-CS-2-14-TXT	1481	WORKING-STORAGE	2743*		
LISTING	WS-Curr-Char-Is-Punct-BOOL	1458	WORKING-STORAGE	2587	2595	2600
LISTING	WS-Curr-Char-Is-Quote-BOOL	1462	WORKING-STORAGE	2606		
LISTING	WS-Curr-Char-Is-X-BOOL	1463	WORKING-STORAGE	2619		
LISTING	WS-Curr-Char-Is-Z-BOOL	1464	WORKING-STORAGE	2632		
LISTING	WS-Curr-CHR	1457	WORKING-STORAGE	2577*	2580	2582
				2588	2596	2602
				2609		
LISTING	WS-Curr-Division-TXT	1466	WORKING-STORAGE	2502*	2538	2589
				2597	2697	2813*
				2832*	2858*	2914*
				2919*		
LISTING	WS-Curr-Line-NUM	1472	WORKING-STORAGE	2501*	2561*	2720*
				2760*	3209	3230
				3240	3254	3481*
LISTING	WS-Curr-Prog-ID-TXT	1474	WORKING-STORAGE	2491*	2818*	3205
				3226	3236	3250
LISTING	WS-Curr-Section-TXT	1479	WORKING-STORAGE	2723*	2728	2837*
				2863*	2909	2910*
				3208	3229	3239
				3253		
LISTING	WS-Curr-Verb-TXT	1486	WORKING-STORAGE	2492*	2516*	2540*
				2924	2933	
LISTING	WS-Delim-TXT	1488	WORKING-STORAGE	2649*	2651	2669*
				2671	2674	
LISTING	WS-Dummy-TXT	1490	WORKING-STORAGE	2467*	2712*	2741*
				2774*	2779*	2780
				3467*		
LISTING	WS-Expanded-Src-Fn-TXT	1492	WORKING-STORAGE	1412	2472*	2473C
LISTING	WS-Filename-TXT	1494	WORKING-STORAGE	2466*	2469	2740*
				2743		
LISTING	WS-Flags-TXT	1496	WORKING-STORAGE			
LISTING	WS-Formatted-DT	1499	WORKING-STORAGE	2490*	3350	3373
				3607	3626	
LISTING	WS-GI-Prog-ID-TXT	1502	WORKING-STORAGE	3277	3283	3288*
=====						
GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL					Page: 99	

GNUCOBOL 2.2 20JUL2017 Cross-Reference Listing				2017/07/22		
				/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl		
PROGRAM-ID	Identifier/Register/Function	Defn	Where Defined	References	Page: 100	
LISTING	WS-GI-Token-TXT	1503	WORKING-STORAGE	3278 3303	3289*	3291
LISTING	WS-Group-Indicators-TXT	1501	WORKING-STORAGE	3261*		
LISTING	WS-Held-Reference-TXT	1505	WORKING-STORAGE	2493*	2518	2519
				2520*	2555	2556
				2557*	3036*	3038
				3039	3040*	3077*
				3083	3084	3085*
				3091	3092	3093*
				3116*	3118	3119*
LISTING	WS-I-SUB	1507	WORKING-STORAGE	2434*	2435	2436
				2438	2441*	2442
				2457*	2459	2460
				2461	2464	2717*
				2720	2731*	2733
				2734	2735	2738
				3262*	3296*	3308*
				3321*	3322	3324*
				3327	3329	3402*
LISTING	WS-J-SUB	1509	WORKING-STORAGE	2458*	2462*	2464
				2732*	2736*	2738
LISTING	WS-Lines-Left-NUM	1511	WORKING-STORAGE	3263*	3272	3286
				3338	3392*	3403
				3447	3494	3498
				3525*	3559	3641*
				3648	3657	3664
				3673	3686	
LISTING	WS-Lines-Per-Page-Env-TXT	1515	WORKING-STORAGE	2447*	2451*	2478
				2479		
LISTING	WS-Lines-Per-Page-NUM	1513	WORKING-STORAGE	2480*	2483*	2485*
				2488	3392	3641
LISTING	WS-Main-Module-Name-TXT	1517	WORKING-STORAGE	2439*	2443*	2719
				3469		
LISTING	WS-Next-Char-Is-Quote-BOOL	1520	WORKING-STORAGE	2619	2632	
LISTING	WS-Next-CHR	1519	WORKING-STORAGE	2579*	2622	2635
LISTING	WS-OS-Type-FILLER-TXT	1522	WORKING-STORAGE	1528		
LISTING	WS-OS-Type-TXT	1529	WORKING-STORAGE	2428		
LISTING	WS-OS-Types-TXT	1528	WORKING-STORAGE			
LISTING	WS-Page-No-TXT	1534	WORKING-STORAGE	3344C	3359	3382
				3413	3428	3571
				3591	3601C	3615
				3634		
LISTING	WS-Page-NUM	1532	WORKING-STORAGE	2424*	3340*	3342
				3560	3597*	3599
LISTING	WS-PN-Literal-TXT	1535	WORKING-STORAGE	3341*	3598*	
LISTING	WS-PN-Page-NUM	1536	WORKING-STORAGE	3342*	3343C	3599*
				3600C		
LISTING	WS-Program-Path-TXT	1538	WORKING-STORAGE	2455*	2456C	3353
				3376	3610	3629
LISTING	WS-Reserved-Word-Table-TXT	2295	WORKING-STORAGE			
LISTING	WS-Reserved-Word-TXT	2296	WORKING-STORAGE	2684		
LISTING	WS-Reserved-Words-TXT	1540	WORKING-STORAGE	2295		
LISTING	WS-RS-Duplicate-CHR	2304	WORKING-STORAGE	3264*	3279*	3294*

GNUCOBOL 2.2 20JUL2017 Cross-Reference Listing				2017/07/22		
				/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl		
PROGRAM-ID	Identifier/Register/Function	Defn	Where Defined	References	Page: 101	
=====	=====	=====	=====	=====	=====	
				3305	3306*	
LISTING	WS-RS-In-Copybook-BOOL	2307	WORKING-STORAGE	2726*	3475*	
LISTING	WS-RS-In-Main-Module-BOOL	2306	WORKING-STORAGE	2721*	2759	3470*
				3480		
LISTING	WS-RS-In-Which-Pgm-CHR	2305	WORKING-STORAGE			
LISTING	WS-RS-Last-Token-Ended-Sent-CHR	2308	WORKING-STORAGE	2550*	2696	
LISTING	WS-RS-Processing-PICTURE-CHR	2309	WORKING-STORAGE	2645	2659*	2868*
LISTING	WS-RS-Token-Ended-Sentence-CHR	2310	WORKING-STORAGE	2537	2549	2551*
				2584*	2613*	2626*
				2639*	2652*	2672*
LISTING	WS-RS-Verb-Has-Been-Found-CHR	2311	WORKING-STORAGE	2503*	2688*	2810*
LISTING	WS-Runtime-Switches	2303	WORKING-STORAGE			
LISTING	WS-RW-IDX	2299	WORKING-STORAGE	2685	2686	
LISTING	WS-RW-Type-CD	2300	WORKING-STORAGE	2686		
LISTING	WS-RW-Word-TXT	2301	WORKING-STORAGE	2298	2685	
LISTING	WS-Saved-Section-TXT	2313	WORKING-STORAGE	2722	2723	2727
				2728*		
LISTING	WS-SDL-Line-NUM	2320	WORKING-STORAGE	3485*		
LISTING	WS-SDL-Statement-TXT	2322	WORKING-STORAGE	3486*	3518*	3548
				3552	3554	3650
				3654*	3666	3670*
				3675	3679*	3683*
LISTING	WS-Src-Dashes-TXT	2315	WORKING-STORAGE	3618	3637	
LISTING	WS-Src-Detail-Line-TXT	2319	WORKING-STORAGE	3445*	3484*	3492*
				3496*	3501*	3505*
				3509*	3516*	3528*
				3532*	3536*	3646
				3651	3653*	3655
				3662	3667	3669*
				3671	3676	3678*
				3680	3682*	3684
				3689*		
LISTING	WS-Src-Hold-TXT	2324	WORKING-STORAGE	3650*	3654	3666*
				3670	3675*	3679
				3683		
LISTING	WS-Src-Line-NUM	2326	WORKING-STORAGE	3442*	3471	3483*
				3485		
LISTING	WS-Src-Lines-NUM	2328	WORKING-STORAGE	3546*	3549*	3553*
				3555*	3559	3562
				3576	3644	3660
LISTING	WS-Src-SUB	2330	WORKING-STORAGE	2499*	2552	2553
				2572*	2576	2578
				2581*	2590*	2601*
				2607*	2611*	2612
				2614*	2620*	2624*
				2625	2627*	2633*
				2637*	2638	2640*
				2650*	2653*	2670*
				2675	2750*	2755*
				2757*		
LISTING	WS-Suppress-FF-CHR	1497	WORKING-STORAGE	2425*	3273*	3415
				3430		
LISTING	WS-Tally-QTY	2332	WORKING-STORAGE	2789*	2791*	2792
=====				=====		
GCic for UNIX/Linux Copyright (C) 2009-2017, Gary L. Cutler, GPL				Page: 101		

GNUCOBOL 2.2 20JUL2017 Cross-Reference Listing				2017/07/22		
				/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl		
PROGRAM-ID	Identifier/Register/Function	Defn	Where Defined	References	Page: 102	
=====	=====	=====	=====	=====	=====	
LISTING	WS-Temp-10-Chars-TXT	2334	WORKING-STORAGE	2796* 2710* 2717	2797 2714 3465*	2715*
LISTING	WS-Temp-256-Chars-TXT	2344	WORKING-STORAGE	2474C 2730 3466*	2711* 2733 3468	2718 2738
LISTING	WS-Temp-32-Chars-1-TXT	2336	WORKING-STORAGE	2765*	2768	2775
LISTING	WS-Temp-32-Chars-2-TXT	2338	WORKING-STORAGE	2772* 2784*	2777* 2800	2783
LISTING	WS-Temp-32-Chars-3-TXT	2340	WORKING-STORAGE	2773* 2787*	2778* 2800	2786
LISTING	WS-Temp-65-Chars-TXT	2342	WORKING-STORAGE	3488* 3504 3524 3535	3495 3508 3527	3500 3520* 3531
LISTING	WS-Today-DT	2346	WORKING-STORAGE	2489*	2490	
LISTING	WS-Token-Curr-TXT	2348	WORKING-STORAGE	2509 2591* 2623* 2655 2680* 2812 2836 2866 3207 3252	2513* 2602* 2636* 2668* 2698* 2818 2857 2900 3228	2582* 2610* 2648* 2678 2765 2831 2862 2918 3238
LISTING	WS-Token-Curr-Uc-TXT	2350	WORKING-STORAGE	2510* 2535 3227	2513 2912 3237	2516 3206 3251
LISTING	WS-Token-Prev-TXT	2352	WORKING-STORAGE	2517* 2598* 2817* 2841 2872 2880* 2889* 2898* 2923 2983* 3004* 3033 3078* 3097* 3129 3142 3177	2535* 2813 2832 2858 2873* 2883* 2892* 2913 2927* 2990 3013 3061 3081* 3104 3132* 3151 3180*	2539* 2816 2837 2863 2877 2886* 2895* 2919 2980 3001 3024 3074 3089* 3113 3135* 3162 3187
LISTING	WS-Token-Search-TXT	2354	WORKING-STORAGE	2678*	2679	2685
LISTING	WS-Token-Type-CD	2356	WORKING-STORAGE	2583* 2656* 2686*	2592* 2660* 2699*	2603* 2681*
LISTING	WS-TT-Token-Is-Argtype-BOOL	2357	WORKING-STORAGE	2807	2827	2853
LISTING	WS-TT-Token-Is-EOF-BOOL	2358	WORKING-STORAGE	2506	2560*	
LISTING	WS-TT-Token-Is-Function-BOOL	2359	WORKING-STORAGE	2847		

GNUCOBOL 2.2 20JUL2017 Cross-Reference Listing				2017/07/22		
				/home/vince/cobolsrc/Cobol-Tools/ocic/GCic.cbl		
PROGRAM-ID	Identifier/Register/Function	Defn	Where Defined	References	Page: 103	
LISTING	WS-TT-Token-Is-Identifier-BOOL	2360	WORKING-STORAGE	2693* 2922	2840 2930	2876
LISTING	WS-TT-Token-Is-Keyword-BOOL	2361	WORKING-STORAGE	2511 2830 2861	2534 2835 2867	2811 2856 2917
LISTING	WS-TT-Token-Is-Lit-Alpha-BOOL	2362	WORKING-STORAGE	2616*	2642*	
LISTING	WS-TT-Token-Is-Lit-Number-BOOL	2363	WORKING-STORAGE	2629* 2801*	2695	2769*
LISTING	WS-TT-Token-Is-Reserved-Wd-BOOL	2365	WORKING-STORAGE	2512 2854*	2808* 2871	2828*
LISTING	WS-TT-Token-Is-Verb-BOOL	2364	WORKING-STORAGE	2515	2687	
LISTING	WS-Usernames-QTY	2367	WORKING-STORAGE	2500*		
LISTING	WS-Version-TXT	2369	WORKING-STORAGE	2432* 3603	3346 3622	3369
LISTING	WS-XDL-Def-Line-NUM	2376	WORKING-STORAGE	3300*	3317*	
LISTING	WS-XDL-Prog-ID-TXT	2372	WORKING-STORAGE	3297*	3309*	3313*
LISTING	WS-XDL-Ref-Flag-CHR	2382	WORKING-STORAGE	3329*		
LISTING	WS-XDL-Ref-Line-NUM	2381	WORKING-STORAGE	3327*		
LISTING	WS-XDL-Reference-TXT	2380	WORKING-STORAGE			
LISTING	WS-XDL-Section-TXT	2378	WORKING-STORAGE	3299*	3315*	
LISTING	WS-XDL-Token-TXT	2374	WORKING-STORAGE	3298*	3310*	3314*
LISTING	WS-Xref-Detail-Line-TXT	2371	WORKING-STORAGE	3260* 3280 3312 3398	3267 3284* 3332 3401*	3270* 3293 3395
LISTING	WS-Xref-Lines-Per-Rec-NUM	2385	WORKING-STORAGE	2446*	2450*	3322

6. STREAMIO

STREAMIO is a utility I created to assist with handling stream I/O functions. I've used it to construct a number of useful little command-line utilities.

Usage of this subroutine is completely documented in the program comments. The program COPY's a copybook named STREAMIOcb, the format of which is described in the program comments.

Both STREAMIO.cbl and STREAMIOcb.cpy are included in the "samples" directory of any pre-built distributions of GnuCOBOL that I have created.

In addition to general GnuCOBOL concepts, this program provides a useful demonstration of the following:

- Coding a GnuCOBOL subroutine
- Using the "REPLACING" clause on a CDF "COPY" statement
- Using hexadecimal alphanumeric literals
- Using the following statements:
 - "ACCEPT FROM ENVIRONMENT" statement
 - "INSPECT" statement
 - "STRING" statement
- Using the following built-in subroutines:
 - "C\$PARAMSIZE" built-in system subroutine
 - "CBL_CLOSE_FILE" built-in system subroutine
 - "CBL_DELETE_FILE" built-in system subroutine
 - "CBL_EXIT_PROC" built-in system subroutine
 - "CBL_OPEN_FILE" built-in system subroutine
 - "CBL_READ_FILE" built-in system subroutine
 - "CBL_WRITE_FILE" built-in system subroutine
- Using the following intrinsic functions:
 - "RANDOM" intrinsic function
 - "TRIM" intrinsic function

First, here is the STREAMIOcb.cpy copybook:

```

05 SCB-Handle-NUM                PIC X(4) COMP-X.
05 SCB-Mode-CD                   PIC X(1).
    88 SCB-MODE-Input-BOOL       VALUE 'I', 'i'.
    88 SCB-MODE-Output-BOOL      VALUE 'O', 'o'.
    88 SCB-MODE-Both-BOOL        VALUE 'B', 'b'.
05 SCB-Function-CD               PIC X(2).
    88 SCB-Func-CLOSE-BOOL       VALUE 'C ', 'c '.
    88 SCB-Func-DELETE-BOOL      VALUE 'D ', 'd '.
    88 SCB-Func-OPEN-BOOL        VALUE 'O ', 'o '.
    88 SCB-Func-READ-BOOL        VALUE 'R ', 'r '.
    88 SCB-Func-READ-Delim-BOOL  VALUE 'RD', 'rd',
                                'rD', 'Rd'.
    88 SCB-Func-WRITE-BOOL       VALUE 'W ', 'w '.
    88 SCB-Func-WRITE-Delim-BOOL VALUE 'WD', 'wd',
                                'wD', 'Wd'.

05 SCB-Delimiter-Mode-CD         PIC X(1).
    88 SCB-DELIM-Unix-BOOL       VALUE 'U', 'u'.
    88 SCB-DELIM-Windows-BOOL    VALUE 'W', 'w'.
05 SCB-Offset-NUM                PIC X(8) COMP-X.
05 SCB-Error-Routine-PTR         USAGE PROGRAM-POINTER.
05 SCB-Error-Routine-NUM REDEFINES SCB-Error-Routine-PTR
                                USAGE BINARY-LONG.
05 SCB-Return-CD                 USAGE BINARY-LONG.
05 SCB-Filename-TXT              PIC X(256).

```

The program source and cross-reference listing, produced using the GnuCOBOL Interactive Compiler front-end (GCic.cbl, one of the sample programs included here), begins on the next page.

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/STREAMIO.cbl

Line Statement Page: 1

```

=====
1      >>SOURCE FORMAT IS FIXED
2      IDENTIFICATION DIVISION.
3      PROGRAM-ID. STREAMIO.
4      *>*****
5      *> Author: Gary L. Cutler **
6      *> **
7      *> This routine centralizes all bytestream file I/O functions **
8      *> into one routine. The manner in which this routine is **
9      *> CALLED is as follows: **
10     *> **
11     *> CALL "STREAMIO" USING control-block [ , arg2 ] **
12     *> **
13     *> where 'control-block' is defined by the "STREAMIOcb.cpy" **
14     *> copybook and 'arg2' will vary, depending upon the function **
15     *> specified in the control block. **
16     *> **
17     *> The STREAMIO routine has an advantage over the various **
18     *> "CBL_XXXXXX_FILE" routines in that: **
19     *> **
20     *> 1. It automates the establishment and on-going adjustment of **
21     *> the file-offset value in such a way as to simplify the **
22     *> sequential processing of a bytestream file (you may still **
23     *> specify a file-offset manually on each read or write, if **
24     *> you wish) **
25     *> **
26     *> 2. It auto-detects the size of the I/O buffer you supply to **
27     *> STREAMIO, using that as the byte-count of all read and **
28     *> write operations. **
29     *> **
30     *> 3. Not only does it support the raw input and output of data **
31     *> that the CBL_READ_FILE and CBL_WRITE_FILE routines do, **
32     *> but on input it is also capable of delivering just a **
33     *> single newline-delimited or carriage-return/newline de- **
34     *> limited record to the caller. **
35     *> **
36     *> 4. On output, STREAMIO can optionally append either a new- **
37     *> line or carriage-return/newline sequence (your choice) to **
38     *> the end of every record it writes. **
39     *> **
40     *> 5. STREAMIO can automatically generate filenames for output **
41     *> files if you wish, simplifying the process of creating **
42     *> scratch or work files. **
43     *> **
44     *> 6. The STREAMIO routine also allows you to (optionally) re- **
45     *> gister a general error-handling routine to be given con- **
46     *> trol should a fatal error be detected with STREAMIO. **
47     *> **
48     *> This routine can be "turned on" and "turned off" at will. **
49     *> **
=====

```

GCic for OSX Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 1

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/STREAMIO.cbl

Line Statement Page: 2

```

=====
50      *> The control block format is as follows. This structure must **
51      *> be defined under an 01-level data item of your creation and **
52      *> should be INITIALIZED before any items within it are used. **
53      *> **
54      *> 05 SCB-Handle-NUM          PIC X(4) COMP-X.          **
55      *> 05 SCB-Mode-CD            PIC X(1).                  **
56      *>     88 SCB-Mode-Input-BOOL  VALUE 'I', 'i'.          **
57      *>     88 SCB-Mode-Output-BOOL VALUE 'O', 'o'.          **
58      *>     88 SCB-Mode-Both-BOOL   VALUE 'B', 'b'.          **
59      *> 05 SCB-Function-CD         PIC X(2).                  **
60      *>     88 SCB-Func-CLOSE-BOOL  VALUE 'C ', 'c '.        **
61      *>     88 SCB-Func-DELETE-BOOL VALUE 'D ', 'd '.        **
62      *>     88 SCB-Func-OPEN-BOOL   VALUE 'O ', 'o '.        **
63      *>     88 SCB-Func-READ-BOOL   VALUE 'R ', 'r '.        **
64      *>     88 SCB-Func-READ-Delim-BOOL VALUE 'RD', 'rd',    **
65      *>                               'rD', 'Rd'.            **
66      *>     88 SCB-Func-WRITE-BOOL  VALUE 'W ', 'w '.        **
67      *>     88 SCB-Func-WRITE-Delim-BOOL VALUE 'WD', 'wd',    **
68      *>                               'wD', 'Wd'.            **
69      *> 05 SCB-Delimiter-Mode-CD   PIC X(1).                  **
70      *>     88 SCB-Delim-Unix-BOOL  VALUE 'U', 'u'.          **
71      *>     88 SCB-Delim-Windows-BOOL VALUE 'W', 'w'.        **
72      *> 05 SCB-Offset-NUM          PIC X(8) COMP-X.          **
73      *> 05 SCB-Error-Routine-PTR    USAGE PROGRAM-POINTER.   **
74      *> 05 SCB-Error-Routine-NUM REDEFINES SCB-Error-Routine-PTR **
75      *>                               USAGE BINARY-LONG.      **
76      *> 05 SCB-Return-CD            USAGE BINARY-LONG.      **
77      *> 05 SCB-Filename-TXT         PIC X(256).              **
78      *> **
79      *> Such a structure is defined for your use using the copybook **
80      *> "STREAMIOcb.cpy" (you may also define your own, provided it **
81      *> conforms to the above layout). **
82      *>-----**
83      *> SCB-Handle-NUM **
84      *>-----**
85      *> **
86      *> Serves as a file handle to the file once it has been opened **
87      *> (via the "SCB-Func-OPEN-BOOL" function). **
88      *> **
89      *>-----**
90      *> SCB-Mode-CD **
91      *>-----**
92      *> **
93      *> Prior to calling "STREAMIO" for the first time for a file, **
94      *> the appropriate subordinate level-88 must be set to TRUE to **
95      *> select an I/O mode. You may also simply move one of the **
96      *> string values listed on the level-88 items to "SCB-Mode-CD". **
97      *> **
98      *>-----**

```

GCic for OSX Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 2

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/STREAMIO.cbl

Line Statement

Page: 3

```

=====
 99      *> SCB-Function-CD                                **
100      *>-----**
101      *>                                                **
102      *> The appropriate subordinate level-88 must be set to TRUE to **
103      *> select a function you'd like to execute against a file. You **
104      *> may also simply move one of the string values listed on the **
105      *> level-88 items to "SCB-Function-CD".                **
106      *>                                                **
107      *> Available functions are as follows:                **
108      *>                                                **
109      *> SCB-Func-OPEN-BOOL                                **
110      *>                                                **
111      *>     This must be the function specified the first time you **
112      *>     call STREAMIO for any given file. It opens the file & **
113      *>     makes it available for use according to the      **
114      *>     "SCB-Mode-CD" specification.                    **
115      *>                                                **
116      *>     The filename being opened must be specified in the **
117      *>     "SCB-Filename-TXT" field.                        **
118      *>                                                **
119      *>     The SCB-Offset-NUM field will be initialized to ZERO. **
120      *>                                                **
121      *>     If "arg2" is specified in conjunction with this funct- **
122      *>     ion, it will be ignored.                          **
123      *>                                                **
124      *> SCB-Func-CLOSE-BOOL                                **
125      *>                                                **
126      *>     This function should be the one specified the LAST time **
127      *>     you call STREAMIO against a specific file. After this **
128      *>     function has been executed, you'll have to re-open the **
129      *>     file if you wish to use it with STREAMIO again.   **
130      *>                                                **
131      *>     The SCB-Handle-NUM item will be reset to ZERO.    **
132      *>                                                **
133      *>     If "arg2" is specified in conjunction with this funct- **
134      *>     ion, it will be ignored.                          **
135      *>                                                **
136      *> SCB-Func-DELETE-BOOL                                **
137      *>                                                **
138      *>     This function will delete the file specified in the **
139      *>     control block (see SCB-Filename-TXT).              **
140      *>                                                **
141      *>     This function should not be performed against a file **
142      *>     that is open.                                       **
143      *>                                                **
144      *>     If "arg2" is specified in conjunction with this funct- **
145      *>     ion, it will be ignored.                          **
146      *>                                                **
147      *> SCB-Func-READ-BOOL                                  **
=====

```

GCic for OSX Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 3

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/STREAMIO.cbl

Line Statement

Page: 4

```

=====
148      *>
149      *>      This function invokes a standard CBL_READ_FILE against **
150      *>      the file specified in the control block (see **
151      *>      SCB-Filename-TXT). **
152      *> **
153      *>      The buffer into which you wish to read data must be **
154      *>      supplied as "arg2". The size of that buffer, in bytes, **
155      *>      will define the "byte-count" value supplied to the **
156      *>      CBL_READ_FILE subroutine. The buffer data item will be **
157      *>      set to SPACES before the read takes place. **
158      *> **
159      *>      If the file-offset value (SCB-Offset-NUM) is greater **
160      *>      than the size of the file, a "no more data" return code **
161      *>      (01) will be passed back in SCB-Return-CD and the **
162      *>      buffer will have been set to SPACES. **
163      *> **
164      *>      At the conclusion of a successful SCB-Func-READ-BOOL, **
165      *>      the value of SCB-Offset-NUM will have been automati- **
166      *>      cally incremented by the byte-count size of "arg2". **
167      *> **
168      *> SCB-Func-WRITE-BOOL **
169      *> **
170      *>      This function invokes a standard CBL_WRITE_FILE against **
171      *>      the file specified in the control block (see **
172      *>      SCB-Filename-TXT). **
173      *> **
174      *>      The buffer from which data will be written to the file **
175      *>      must be supplied as "arg2". The size of that buffer, **
176      *>      in bytes, will define the "byte-count" value supplied **
177      *>      CBL_WRITE_FILE subroutine. The buffer data will be **
178      *>      written to the file-offset position defined by the **
179      *>      SCB-Offset-NUM value. You may specify "arg2" either **
180      *>      as an actual alphanumeric data item or as an alpha- **
181      *>      numeric literal. **
182      *> **
183      *>      If the file-offset value (SCB-Offset-NUM) is greater **
184      *>      than the size of the file, a "no more data" return code **
185      *>      will be passed back in SCB-Return-CD and the buffer **
186      *>      will have been set to SPACES. **
187      *> **
188      *>      At the conclusion of a successful SCB-Func-WRITE-BOOL **
189      *>      operation, the value of SCB-Offset-NUM will have been **
190      *>      automatically incremented by the byte-count size of **
191      *>      "arg2". **
192      *> **
193      *> SCB-Func-READ-Delim-BOOL **
194      *> **
195      *>      SCB-Func-READ-Delim-BOOL bahaves like the SCB-FUNC- **
196      *>      READ function, with the following behavioral dif- **
=====

```

GCic for OSX Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 4

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/STREAMIO.cbl

Line Statement

Page: 5

```

=====
197      *>      ferences:                                **
198      *>                                             **
199      *>      1. When data is read from the file, only that data read **
200      *>      up to BUT NOT INCLUDING an end-of-line delimiter **
201      *>      sequence (either a LF or CRLF) will be retained in **
202      *>      the buffer - the remainder of the buffer from the **
203      *>      end-of-line sequence onward will be reset to SPACES. **
204      *>      The file-offset value (SCB-Offset-NUM) will be in- **
205      *>      cremented ONLY by the amount of data transferred up **
206      *>      to AND INCLUDING the end-of-line sequence. **
207      *>                                             **
208      *>      2. When data is read from the file and an end-of-line **
209      *>      delimiter sequence (either a LF or a CRLF) cannot be **
210      *>      found within the buffer, the assumption is made that **
211      *>      the record is too long to fit within the buffer. In **
212      *>      these instances, an SCB-Return-CD value of 02 will **
213      *>      be returned and the SCB-Offset-NUM value will be **
214      *>      incremented past the next end-of-line sequence in **
215      *>      the file (this will involve at least one additional **
216      *>      call to CBL_READ_FILE to locate that eol sequence, **
217      *>      but any additional such reads will be done internal- **
218      *>      ly to STREAMIO and will be entirely transparent to **
219      *>      the caller of STREAMIO. **
220      *>                                             **
221      *>      DO NOT USE the Streamio-READ-Delim function if the **
222      *>      possibility exists that linefeed (X"0A") or carriage- **
223      *>      return (X"0D") characters could exist as actual data **
224      *>      characters in the file. **
225      *>                                             **
226      *>      SCB-Func-WRITE-Delim-BOOL **
227      *>                                             **
228      *>      SCB-Func-WRITE-Delim-BOOL acts like the Streamio- **
229      *>      FUNC-WRITE function, with the following difference: **
230      *>                                             **
231      *>      After the specified data is written to the file, an **
232      *>      end-of-line sequence will also be written to the file. **
233      *>      The file-offset value (SCB-Value) will be incremented **
234      *>      by the byte-count size of the data PLUS the size of the **
235      *>      end-of-line sequence. One of two possible end-of-line **
236      *>      sequences must be specified using the value of SCB- **
237      *>      Delimter-Mode. **
238      *>                                             **
239      *>-----**
240      *>      SCB-Delimiter-Mode-CD **
241      *>-----**
242      *>                                             **
243      *>      This data item is needed only when issuing the Streamio- **
244      *>      FUNC-WRITE-Delim function. In those circumstances, this **
245      *>      item defines what end-of-line delimiter sequence is to be **
=====

```

GCic for OSX Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 5

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/STREAMIO.cbl

Line Statement

Page: 6

```

=====
246      *> written:                                     **
247      *>                                             **
248      *> If SCB-Delim-Unix-BOOL is true, a linefeed character will **
249      *> be written.                                   **
250      *>                                             **
251      *> If SCB-Delim-Windows-BOOL is true, a carriage-return and **
252      *> linefeed sequence will be written.           **
253      *>                                             **
254      *>-----**
255      *> SCB-Offset-NUM                                **
256      *>-----**
257      *>                                             **
258      *> This data item specifies the next relative byte number with- **
259      *> in the file where the next read or write will start.       **
260      *>                                             **
261      *> SCB-Offset-NUM is automatically set to 0 (the first byte) **
262      *> when the file is opened, and is automatically incremented as **
263      *> the file is read or written via STREAMIO.         **
264      *>                                             **
265      *> You may also manually set this value as desired before any **
266      *> call to STREAMIO.                                   **
267      *>                                             **
268      *>-----**
269      *> SCB-Error-Routine-PTR                          **
270      *>-----**
271      *>                                             **
272      *> To specify a general error-handling routine for handling **
273      *> STREAMIO failures, Create the routine and define an entry- **
274      *> name for it via the ENTRY statement. Then use the following **
275      *> to set that routine up as the error handler:         **
276      *>                                             **
277      *>     SET SCB-Error-Routine-PTR TO ENTRY "entry-name"      **
278      *>                                             **
279      *> To "turn off" the error-routine:                   **
280      *>                                             **
281      *>     SET SCB-Error-Routine-PTR TO NULL                **
282      *>                                             **
283      *> If a fatal error occurs (any error not marked with a ">" in **
284      *> the SCB-Return-CD discussion), the error routine you spe- **
285      *> cified (if any) will be set up as an exit routine via the **
286      *> CBL_EXIT_PROC subroutine; the STREAMIO routine will then is- **
287      *> sue a STOP RUN to intentionally trigger your error routine. **
288      *> You will not be able to recover your program once your error **
289      *> routine triggers. If you wish to be able to recover from **
290      *> fatal STREAMIO errors, you should NOT use the SCB-Error- **
291      *> Routine feature but instead you should explicitly test the **
292      *> SCB-Return-CD value after every call to STREAMIO.       **
293      *>                                             **
294      *> A default error routine is defined by the "STREAMIOError.cpy" **
=====

```

GCic for OSX Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 6

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/STREAMIO.cbl

Line Statement

Page: 7

```

=====
295     *> copybook.                                **
296     *>                                           **
297     *>-----**
298     *> SCB-Return-CD                             **
299     *>-----**
300     *>                                           **
301     *> The following are the possible SCB-Return-CD values. The **
302     *> ones marked with a ">" will NOT trigger an error-routine, if **
303     *> one is currently registered via SCB-Error-Routine-PTR.    **
304     *>                                           **
305     *> 12 I/O error writing to file                 **
306     *> 11 File does not exist                     **
307     *> 10 File already OPEN or already CLOSEd      **
308     *> > 02 READ-Delim was truncated               **
309     *> > 01 No more data is available from the current **
310     *>      SCB-Offset-NUM                         **
311     *> > 00 OK - the operation was successful       **
312     *> -1 Invalid SCB-Function-CD                 **
313     *> -2 Invalid SCB-Mode-CD                     **
314     *> -3 CBL_XXXXX_FILE routine rejected operation **
315     *> -4 Invalid delimiter mode specified (Not U/W) **
316     *>                                           **
317     *>-----**
318     *> SCB-Filename-TXT                           **
319     *>-----**
320     *>                                           **
321     *> This is the name of the file you wish to access.      **
322     *>                                           **
323     *> If you are planning on reading the file, the file MUST exist **
324     *> at the time the SCB-Func-OPEN-BOOL is executed.      **
325     *>                                           **
326     *> If you are planning on writing to the file, the file need **
327     *> exist when the SCB-Func-OPEN-BOOL is issued.         **
328     *>                                           **
329     *> In general, the contents of SCB-Filename-TXT should re- **
330     *> flect the complete path to the file as well as the name of **
331     *> the file itself, unless the file is contained in whatever **
332     *> directory is current at the time the SCB-Func-OPEN-BOOL is **
333     *> executed.                                           **
334     *>                                           **
335     *> The following special values may be used for         **
336     *> SCB-Filename-TXT:                                   **
337     *>                                           **
338     *> SPACES If the filename is SPACES, a filename will be created **
339     *>      automatically for you in whatever directory is de- **
340     *>      fined by the TEMP environment variable. If there IS **
341     *>      no TEMP variable defined, the "/tmp" folder will be **
342     *>      assumed. The filename will be STREAMIO-nnnnnnnn.dat **
343     *>      where "nnnnnnnn" is a random number.           **
=====

```

GCic for OSX Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 7

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/STREAMIO.cbl

Line Statement

Page: 8

```

=====
344      *>
345      *> .      If you specify only a dot (period) as the filename, **
346      *>      the behavior will be the same as with a value of **
347      *>      SPACES except there will be no ".dat" at the end of **
348      *>      the generated filename. **
349      *> **
350      *> .ext  If you specify a filename extension prefixed with a **
351      *>      dot (period), the behavior will be the same as if a **
352      *>      value of SPACES were specified, except that the given **
353      *>      extension will be used instead of ".dat". Note that **
354      *>      if you are using a Unix/Cygwin implementation of **
355      *>      OpenCOBOL and you'd like to specify a hidden file in **
356      *>      the current directory as the SCB-Filename-TXT, you **
357      *>      MUST code the filename as "./.xxxxx" to avoid having **
358      *>      it treated as this special name. **
359      *> **
360      *>*****
361      ENVIRONMENT DIVISION.
362      CONFIGURATION SECTION.
363      REPOSITORY.
364          FUNCTION ALL INTRINSIC.
365      DATA DIVISION.
366      WORKING-STORAGE SECTION.
367          01 WS-Access-Mode-CD                PIC X(1) COMP-X.
368          01 WS-Arg-Length-NUM                PIC X(4) COMP-X.
369          01 WS-Buffer-TXT                    PIC X(256).
370          01 WS-Delim-Buffer-TXT              PIC X(2).
371          01 WS-Env-Temp-TXT                  PIC X(256).
372          01 WS-Slash-CHR                     PIC X(1).
373          01 WS-Tally-NUM                     USAGE BINARY-LONG.
374          01 WS-8-Digit-NUM                   PIC 9(8).
375          01 WS-256-Byte-TXT                  PIC X(256).
376      LINKAGE SECTION.
377          01 L-StreamIO-Control-Block-TXT.
378          COPY STREAMIOcb
379              REPLACING LEADING ==SCB== BY ==L-SCB==.
05 L-SCB-Handle-NUM PIC X(4) COMP-X.
05 L-SCB-Mode-CD PIC X(1).
88 L-SCB-MODE-Input-BOOL VALUE 'I' 'i'.
88 L-SCB-MODE-Output-BOOL VALUE 'O' 'o'.
88 L-SCB-MODE-Both-BOOL VALUE 'B' 'b'.
05 L-SCB-Function-CD PIC X(2).
88 L-SCB-Func-CLOSE-BOOL VALUE 'C' 'c'.
88 L-SCB-Func-DELETE-BOOL VALUE 'D' 'd'.
88 L-SCB-Func-OPEN-BOOL VALUE 'O' 'o'.
88 L-SCB-Func-READ-BOOL VALUE 'R' 'r'.
88 L-SCB-Func-READ-Delim-BOOL VALUE 'RD' 'rd'
'rD' 'Rd'.
88 L-SCB-Func-WRITE-BOOL VALUE 'W' 'w'.
=====

```

GCic for OSX Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 8

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/STREAMIO.cbl

Line Statement Page: 9

```

=====
      88 L-SCB-Func-WRITE-Delim-BOOL VALUE 'WD' 'wd'
      'WD' 'Wd'.
      05 L-SCB-Delimiter-Mode-CD PIC X(1).
      88 L-SCB-DELIM-Unix-BOOL VALUE 'U' 'u'.
      88 L-SCB-DELIM-Windows-BOOL VALUE 'W' 'w'.
      05 L-SCB-Offset-NUM PIC X(8) COMP-X.
      05 L-SCB-Error-Routine-PTR USAGE PROGRAM-POINTER.
      05 L-SCB-Error-Routine-NUM REDEFINES L-SCB-Error-Routine-PTR
      USAGE BINARY-LONG.
      05 L-SCB-Return-CD USAGE BINARY-LONG.
      05 L-SCB-Filename-TXT PIC X(256).
380      01 L-Arg2-TXT PIC X ANY LENGTH.
381      PROCEDURE DIVISION USING L-StreamIO-Control-Block-TXT,
382      L-Arg2-TXT.
383      000-Main SECTION.
384      MOVE 00 TO L-SCB-Return-CD
385      EVALUATE TRUE
386      WHEN L-SCB-Func-CLOSE-BOOL
387      PERFORM 030-Validate-Handle-NonZero
388      PERFORM 200-CLOSE
389      WHEN L-SCB-Func-DELETE-BOOL
390      CALL "CBL_DELETE_FILE" USING L-SCB-Filename-TXT
391      WHEN L-SCB-Func-OPEN-BOOL
392      PERFORM 020-Validate-Handle-Zero
393      PERFORM 100-OPEN
394      WHEN L-SCB-Func-READ-BOOL
395      PERFORM 030-Validate-Handle-NonZero
396      PERFORM 400-READ
397      WHEN L-SCB-Func-READ-Delim-BOOL
398      PERFORM 030-Validate-Handle-NonZero
399      PERFORM 500-READ-Delim
400      WHEN L-SCB-Func-WRITE-BOOL
401      PERFORM 030-Validate-Handle-NonZero
402      PERFORM 300-WRITE
403      WHEN L-SCB-Func-WRITE-Delim-BOOL
404      EVALUATE TRUE
405      WHEN L-SCB-Delim-Unix-BOOL
406      PERFORM 030-Validate-Handle-NonZero
407      PERFORM 300-WRITE
408      MOVE 1 TO WS-Arg-Length-NUM
409      MOVE X"0A" TO WS-Delim-Buffer-TXT
410      WHEN L-SCB-Delim-Windows-BOOL
411      PERFORM 030-Validate-Handle-NonZero
412      PERFORM 300-WRITE
413      MOVE 2 TO WS-Arg-Length-NUM
414      MOVE X"0D0A" TO WS-Delim-Buffer-TXT
415      WHEN OTHER
416      MOVE -4 TO L-SCB-Return-CD
417      PERFORM 099-ERROR-Return
=====

```

GCic for OSX Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 9

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/STREAMIO.cbl

Line Statement Page: 10

```

=====
418          END-EVALUATE
419          CALL "CBL_WRITE_FILE" USING L-SCB-Handle-NUM
420                                         L-SCB-Offset-NUM
421                                         WS-Arg-Length-NUM
422                                         0
423                                         WS-Delim-Buffer-TXT
424          PERFORM 040-Check-WRITE-SCB-Return-CD
425          ADD WS-Arg-Length-NUM TO L-SCB-Offset-NUM
426          WHEN OTHER
427              MOVE -1 TO L-SCB-Return-CD
428              PERFORM 099-ERROR-Return
429          END-EVALUATE
430          GOBACK
431          .
432      020-Validate-Handle-Zero SECTION.
433          IF L-SCB-Handle-NUM NOT = ZERO
434              MOVE 10 TO L-SCB-Return-CD
435              PERFORM 099-ERROR-Return
436          END-IF
437          .
438      030-Validate-Handle-NonZero SECTION.
439          IF L-SCB-Handle-NUM = ZERO
440              MOVE 10 TO L-SCB-Return-CD
441              PERFORM 099-ERROR-Return
442          END-IF
443          .
444      040-Check-WRITE-SCB-Return-CD SECTION.
445          IF RETURN-CODE < 0
446              MOVE -3 TO L-SCB-Return-CD
447              PERFORM 099-ERROR-Return
448          END-IF
449          IF RETURN-CODE = 30
450              MOVE 12 TO L-SCB-Return-CD
451              PERFORM 099-ERROR-Return
452          END-IF
453          MOVE 00 TO L-SCB-Return-CD
454          .
455      050-Check-READ-SCB-Return-CD SECTION.
456          IF RETURN-CODE < 0
457              MOVE -3 TO L-SCB-Return-CD
458              PERFORM 099-ERROR-Return
459          END-IF
460          IF RETURN-CODE = 10
461              MOVE 01 TO L-SCB-Return-CD
462              GOBACK
463          END-IF
464          MOVE 00 TO L-SCB-Return-CD
465          .
466      060-Identify-TEMP SECTION.
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 10

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/STREAMIO.cbl

Line Statement Page: 11

```

=====
467      ACCEPT WS-Env-Temp-TXT FROM ENVIRONMENT "TEMP"
468      EVALUATE TRUE
469          WHEN WS-Env-Temp-TXT (1:1) = "/"
470              MOVE "/" TO WS-Slash-CHR
471          WHEN WS-Env-Temp-TXT (2:1) = ":"
472              MOVE "\" TO WS-Slash-CHR
473          WHEN OTHER
474              MOVE "/tmp" TO WS-Env-Temp-TXT
475              MOVE "/" TO WS-Slash-CHR
476      END-EVALUATE
477      .
478      099-ERROR-Return SECTION.
479          IF L-SCB-Error-Routine-NUM NOT = 0
480              CALL "CBL_EXIT_PROC" USING 0, L-SCB-Error-Routine-PTR
481              STOP RUN
482          END-IF
483          GOBACK
484      .
485      100-OPEN SECTION.
486          IF (L-SCB-Mode-Input-BOOL OR L-SCB-Mode-Both-BOOL)
487          AND (L-SCB-Filename-TXT = SPACES OR LOW-VALUES)
488              MOVE 11 TO L-SCB-Return-CD
489              PERFORM 099-ERROR-Return
490          END-IF
491          EVALUATE TRUE
492              WHEN L-SCB-Filename-TXT = SPACES OR LOW-VALUES
493                  PERFORM 060-Identify-TEMP
494                  MOVE SPACES TO L-SCB-Filename-TXT
495                  COMPUTE
496                      WS-8-Digit-NUM =
497                      RANDOM(SECONDS-PAST-MIDNIGHT) * 100000000
498                  END-COMPUTE
499                  STRING
500                      TRIM(WS-Env-Temp-TXT,TRAILING)
501                      WS-Slash-CHR
502                      "STREAMIO-"
503                      WS-8-Digit-NUM
504                      ".dat"
505                      DELIMITED BY SIZE
506                      INTO L-SCB-Filename-TXT
507              WHEN L-SCB-Filename-TXT(1:1) = "."
508                  PERFORM 060-Identify-TEMP
509                  IF L-SCB-Filename-TXT(2:1) = SPACE
510                      MOVE SPACES TO WS-256-Byte-TXT
511                  ELSE
512                      MOVE L-SCB-Filename-TXT TO WS-256-Byte-TXT
513                  END-IF
514              MOVE SPACES TO L-SCB-Filename-TXT
515              COMPUTE WS-8-Digit-NUM =
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 11

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/STREAMIO.cbl

Line Statement

Page: 12

```

=====
516          RANDOM(SECONDS-PAST-MIDNIGHT) * 100000000
517          STRING
518          TRIM(WS-Env-Temp-TXT,TRAILING)
519          WS-Slash-CHR
520          "STREAMIO-"
521          WS-8-Digit-NUM
522          TRIM(WS-256-Byte-TXT,TRAILING)
523          DELIMITED BY SIZE
524          INTO L-SCB-Filename-TXT
525      END-EVALUATE
526      EVALUATE TRUE
527          WHEN L-SCB-Mode-Input-BOOL
528              MOVE 1 TO WS-Access-Mode-CD
529          WHEN L-SCB-Mode-Output-BOOL
530              MOVE 2 TO WS-Access-Mode-CD
531          WHEN L-SCB-Mode-Both-BOOL
532              MOVE 3 TO WS-Access-Mode-CD
533          WHEN OTHER
534              MOVE -2 TO L-SCB-Return-CD
535              PERFORM 099-ERROR-Return
536      END-EVALUATE
537      CALL "CBL_OPEN_FILE" USING TRIM(L-SCB-Filename-TXT,TRAILING)
538                               WS-Access-Mode-CD
539                               0
540                               0
541                               L-SCB-Handle-NUM
542      IF RETURN-CODE = 35
543          MOVE 11 TO L-SCB-Return-CD
544          PERFORM 099-ERROR-Return
545      END-IF
546      IF RETURN-CODE < 0
547          MOVE -2 TO L-SCB-Return-CD
548          PERFORM 099-ERROR-Return
549      END-IF
550      MOVE 00 TO L-SCB-Return-CD
551      MOVE 0 TO L-SCB-Offset-NUM
552      .
553      200-CLOSE SECTION.
554      CALL "CBL_CLOSE_FILE" USING L-SCB-Handle-NUM
555      IF RETURN-CODE < 0
556          MOVE -2 TO L-SCB-Return-CD
557          PERFORM 099-ERROR-Return
558      END-IF
559      MOVE 00 TO L-SCB-Return-CD
560      MOVE 0 TO L-SCB-Handle-NUM
561      .
562      300-WRITE SECTION.
563      CALL "C$PARAMSIZE" USING 2
564      MOVE RETURN-CODE TO WS-Arg-Length-NUM
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 12

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/STREAMIO.cbl

Line Statement

Page: 13

```

=====
565          CALL "CBL_WRITE_FILE" USING L-SCB-Handle-NUM
566                      L-SCB-Offset-NUM
567                      WS-Arg-Length-NUM
568                      0
569                      L-Arg2-TXT
570          PERFORM 040-Check-WRITE-SCB-Return-CD
571          ADD WS-Arg-Length-NUM TO L-SCB-Offset-NUM
572          .
573      400-READ SECTION.
574          CALL "C$PARAMSIZE" USING 2
575          MOVE RETURN-CODE TO WS-Arg-Length-NUM
576          MOVE SPACES TO L-Arg2-TXT(1:WS-Arg-Length-NUM)
577          CALL "CBL_READ_FILE" USING L-SCB-Handle-NUM
578                      L-SCB-Offset-NUM
579                      WS-Arg-Length-NUM
580                      0
581                      L-Arg2-TXT
582          PERFORM 050-Check-READ-SCB-Return-CD
583          ADD WS-Arg-Length-NUM TO L-SCB-Offset-NUM
584          .
585      500-READ-Delim SECTION.
586          CALL "C$PARAMSIZE" USING 2
587          MOVE RETURN-CODE TO WS-Arg-Length-NUM
588          MOVE SPACES TO L-Arg2-TXT(1:WS-Arg-Length-NUM)
589          CALL "CBL_READ_FILE" USING L-SCB-Handle-NUM
590                      L-SCB-Offset-NUM
591                      WS-Arg-Length-NUM
592                      0
593                      L-Arg2-TXT
594          PERFORM 050-Check-READ-SCB-Return-CD
595          MOVE 0 TO WS-Tally-NUM
596          INSPECT L-Arg2-TXT(1:WS-Arg-Length-NUM)
597              TALLYING WS-Tally-NUM FOR ALL X"OA"
598          IF WS-Tally-NUM = 0 >* No LF found - return truncated data and position past n
ext LF (if any)
599              IF L-Arg2-TXT(WS-Arg-Length-NUM:1) = X"OD"
600                  MOVE SPACE TO L-Arg2-TXT(WS-Arg-Length-NUM:1)
601              END-IF
602          ADD WS-Arg-Length-NUM TO L-SCB-Offset-NUM
603          MOVE 02 TO L-SCB-Return-CD
604          MOVE 256 TO WS-Arg-Length-NUM
605          PERFORM UNTIL 0 = 1
606              MOVE SPACES TO WS-Buffer-TXT
607              CALL "CBL_READ_FILE" USING L-SCB-Handle-NUM
608                      L-SCB-Offset-NUM
609                      WS-Arg-Length-NUM
610                      0
611                      WS-Buffer-TXT
612          IF RETURN-CODE < 0
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 13

GNU COBOL 2.1 23NOV2013 Source Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/STREAMIO.cbl

Line Statement

Page: 14

```

=====
613             MOVE -3 TO L-SCB-Return-CD
614             PERFORM 099-ERROR-Return
615             END-IF
616             IF RETURN-CODE = 10
617                 GOBACK
618             END-IF
619             MOVE 0 TO WS-Tally-NUM
620             INSPECT WS-Buffer-TXT
621                 TALLYING WS-Tally-NUM FOR ALL X"OA"
622             IF WS-Tally-NUM = 0
623                 ADD 256 TO L-SCB-Offset-NUM
624             ELSE
625                 MOVE 0 TO WS-Tally-NUM
626                 INSPECT WS-Buffer-TXT
627                     TALLYING WS-Tally-NUM
628                     FOR CHARACTERS BEFORE INITIAL X"OA"
629                 ADD WS-Tally-NUM, 1 TO L-SCB-Offset-NUM
630                 GOBACK
631             END-IF
632             END-PERFORM
633             ELSE             *> There is (at least) one LF in the buffer
634             MOVE 0 TO WS-Tally-NUM
635             INSPECT L-Arg2-TXT(1:WS-Arg-Length-NUM)
636                 TALLYING WS-Tally-NUM
637                 FOR CHARACTERS BEFORE INITIAL X"OA"
638             ADD WS-Tally-NUM, 1 TO L-SCB-Offset-NUM
639             IF WS-Tally-NUM > 1
640                 IF L-Arg2-TXT(WS-Tally-NUM:1) = X"OD"
641                     COMPUTE WS-Arg-Length-NUM =
642                         WS-Arg-Length-NUM
643                         - WS-Tally-NUM
644                         + 1
645                 ELSE
646                     COMPUTE WS-Arg-Length-NUM =
647                         WS-Arg-Length-NUM
648                         - WS-Tally-NUM
649                     ADD 1 TO WS-Tally-NUM
650                 END-IF
651             MOVE SPACES
652                 TO L-Arg2-TXT(WS-Tally-NUM:WS-Arg-Length-NUM)
653             ELSE
654             MOVE SPACES
655                 TO L-Arg2-TXT(1:WS-Arg-Length-NUM)
656             END-IF
657             END-IF
658             .
=====

```

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 14

GNU COBOL 2.1 23NOV2013 Cross-Reference Listing

2014/03/27

C:/Users/tda010/Documents/Programs/Samples/STREAMIO.cbl

PROGRAM-ID	Identifier/Register/Function	Defn	Where Defined	References	Page: 15	
=====	=====	=====	=====	=====	=====	
STREAMIO	000-Main	383	PROCEDURE			
STREAMIO	020-Validate-Handle-Zero	432	PROCEDURE	392		
STREAMIO	030-Validate-Handle-NonZero	438	PROCEDURE	387	395	398
				401	406	411
STREAMIO	040-Check-WRITE-SCB-Return-CD	444	PROCEDURE	424	570	
STREAMIO	050-Check-READ-SCB-Return-CD	455	PROCEDURE	582	594	
STREAMIO	060-Identify-TEMP	466	PROCEDURE	493	508	
STREAMIO	099-ERROR-Return	478	PROCEDURE	417	428	435
				441	447	451
				458	489	535
				544	548	557
				614		
STREAMIO	100-OPEN	485	PROCEDURE	393		
STREAMIO	200-CLOSE	553	PROCEDURE	388		
STREAMIO	300-WRITE	562	PROCEDURE	402	407	412
STREAMIO	400-READ	573	PROCEDURE	396		
STREAMIO	500-READ-Delim	585	PROCEDURE	399		
STREAMIO	L-Arg2-TXT	380	LINKAGE	382	569C	576*
				581C	588*	593C
				599	600*	640
				652*	655*	
STREAMIO	L-SCB-DELIM-Unix-BOOL	379	[STREAMIOcb]	405		
STREAMIO	L-SCB-DELIM-Windows-BOOL	379	[STREAMIOcb]	410		
STREAMIO	L-SCB-Delimiter-Mode-CD	379	[STREAMIOcb]			
STREAMIO	L-SCB-Error-Routine-NUM	379	[STREAMIOcb]	479		
STREAMIO	L-SCB-Error-Routine-PTR	379	[STREAMIOcb]	379	480C	
STREAMIO	L-SCB-Filename-TXT	379	[STREAMIOcb]	390C	487	492
				494*	506*	507
				509	512	514*
				524*	537C	
STREAMIO	L-SCB-Func-CLOSE-BOOL	379	[STREAMIOcb]	386		
STREAMIO	L-SCB-Func-DELETE-BOOL	379	[STREAMIOcb]	389		
STREAMIO	L-SCB-Func-OPEN-BOOL	379	[STREAMIOcb]	391		
STREAMIO	L-SCB-Func-READ-BOOL	379	[STREAMIOcb]	394		
STREAMIO	L-SCB-Func-READ-Delim-BOOL	379	[STREAMIOcb]	397		
STREAMIO	L-SCB-Func-WRITE-BOOL	379	[STREAMIOcb]	400		
STREAMIO	L-SCB-Func-WRITE-Delim-BOOL	379	[STREAMIOcb]	403		
STREAMIO	L-SCB-Function-CD	379	[STREAMIOcb]			
STREAMIO	L-SCB-Handle-NUM	379	[STREAMIOcb]	419C	433	439
				541C	554C	560*
				565C	577C	589C
				607C		
STREAMIO	L-SCB-MODE-Both-BOOL	379	[STREAMIOcb]	486	531	
STREAMIO	L-SCB-Mode-CD	379	[STREAMIOcb]			
STREAMIO	L-SCB-MODE-Input-BOOL	379	[STREAMIOcb]	486	527	
STREAMIO	L-SCB-MODE-Output-BOOL	379	[STREAMIOcb]	529		
STREAMIO	L-SCB-Offset-NUM	379	[STREAMIOcb]	420C	425*	551*
				566C	571*	578C
				583*	590C	602*

GCic for Windows/MinGW Copyright (C) 2009-2014, Gary L. Cutler, GPL

Page: 15

GNU COBOL 2.1 23NOV2013 Cross-Reference Listing				2014/03/27		
C:/Users/tda010/Documents/Programs/Samples/STREAMIO.cbl				Page: 16		
PROGRAM-ID	Identifier/Register/Function	Defn	Where Defined	References		
				608C	623*	629*
				638*		
STREAMIO	L-SCB-Return-CD	379	[STREAMIOcb]	384*	416*	427*
				434*	440*	446*
				450*	453*	457*
				461*	464*	488*
				534*	543*	547*
				550*	556*	559*
				603*	613*	
STREAMIO	L-StreamIO-Control-Block-TXT	377	LINKAGE	381		
STREAMIO	RETURN-CODE		PROCEDURE	445	449	456
				460	542	546
				555	564	575
				587	612	616
STREAMIO	WS-256-Byte-TXT	375	WORKING-STORAGE	510*	512*	522
STREAMIO	WS-8-Digit-NUM	374	WORKING-STORAGE	496*	503	515*
				521		
STREAMIO	WS-Access-Mode-CD	367	WORKING-STORAGE	528*	530*	532*
				538C		
STREAMIO	WS-Arg-Length-NUM	368	WORKING-STORAGE	408*	413*	421C
				425	564*	567C
				571	575*	576
				579C	583	587*
				588	591C	596
				599	600	602
				604*	609C	635
				641*	642	646*
				647	652	655
STREAMIO	WS-Buffer-TXT	369	WORKING-STORAGE	606*	611C	
STREAMIO	WS-Delim-Buffer-TXT	370	WORKING-STORAGE	409*	414*	423C
STREAMIO	WS-Env-Temp-TXT	371	WORKING-STORAGE	467*	469	471
				474*	500	518
STREAMIO	WS-Slash-CHR	372	WORKING-STORAGE	470*	472*	475*
				501	519	
STREAMIO	WS-Tally-NUM	373	WORKING-STORAGE	595*	597*	598
				619*	621*	622
				625*	627*	629
				634*	636*	638
				639	640	643
				648	649*	652

7. GNU Free Documentation License

Version 1.3, 3 November 2008

Copyright © 2000, 2001, 2002, 2007, 2008 Free Software Foundation, Inc.
<http://fsf.org/>

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

0. PREAMBLE

The purpose of this License is to make a manual, textbook, or other functional and useful document *free* in the sense of freedom: to assure everyone the effective freedom to copy and redistribute it, with or without modifying it, either commercially or noncommercially. Secondly, this License preserves for the author and publisher a way to get credit for their work, while not being considered responsible for modifications made by others.

This License is a kind of “copyleft”, which means that derivative works of the document must themselves be free in the same sense. It complements the GNU General Public License, which is a copyleft license designed for free software.

We have designed this License in order to use it for manuals for free software, because free software needs free documentation: a free program should come with manuals providing the same freedoms that the software does. But this License is not limited to software manuals; it can be used for any textual work, regardless of subject matter or whether it is published as a printed book. We recommend this License principally for works whose purpose is instruction or reference.

1. APPLICABILITY AND DEFINITIONS

This License applies to any manual or other work, in any medium, that contains a notice placed by the copyright holder saying it can be distributed under the terms of this License. Such a notice grants a world-wide, royalty-free license, unlimited in duration, to use that work under the conditions stated herein. The “Document”, below, refers to any such manual or work. Any member of the public is a licensee, and is addressed as “you”. You accept the license if you copy, modify or distribute the work in a way requiring permission under copyright law.

A “Modified Version” of the Document means any work containing the Document or a portion of it, either copied verbatim, or with modifications and/or translated into another language.

A “Secondary Section” is a named appendix or a front-matter section of the Document that deals exclusively with the relationship of the publishers or authors of the Document to the Document’s overall subject (or to related matters) and contains nothing that could fall directly within that overall subject. (Thus, if the Document is in part a textbook of mathematics, a Secondary Section may not explain any mathematics.) The relationship could be a matter of historical connection with the subject or with related matters, or of legal, commercial, philosophical, ethical or political position regarding them.

The “Invariant Sections” are certain Secondary Sections whose titles are designated, as being those of Invariant Sections, in the notice that says that the Document is released under this License. If a section does not fit the above definition of Secondary then it is not allowed to be designated as Invariant. The Document may contain zero Invariant Sections. If the Document does not identify any Invariant Sections then there are none.

The “Cover Texts” are certain short passages of text that are listed, as Front-Cover Texts or Back-Cover Texts, in the notice that says that the Document is released under this License.

A Front-Cover Text may be at most 5 words, and a Back-Cover Text may be at most 25 words.

A “Transparent” copy of the Document means a machine-readable copy, represented in a format whose specification is available to the general public, that is suitable for revising the document straightforwardly with generic text editors or (for images composed of pixels) generic paint programs or (for drawings) some widely available drawing editor, and that is suitable for input to text formatters or for automatic translation to a variety of formats suitable for input to text formatters. A copy made in an otherwise Transparent file format whose markup, or absence of markup, has been arranged to thwart or discourage subsequent modification by readers is not Transparent. An image format is not Transparent if used for any substantial amount of text. A copy that is not “Transparent” is called “Opaque”.

Examples of suitable formats for Transparent copies include plain ASCII without markup, Texinfo input format, LaTeX input format, SGML or XML using a publicly available DTD, and standard-conforming simple HTML, PostScript or PDF designed for human modification. Examples of transparent image formats include PNG, XCF and JPG. Opaque formats include proprietary formats that can be read and edited only by proprietary word processors, SGML or XML for which the DTD and/or processing tools are not generally available, and the machine-generated HTML, PostScript or PDF produced by some word processors for output purposes only.

The “Title Page” means, for a printed book, the title page itself, plus such following pages as are needed to hold, legibly, the material this License requires to appear in the title page. For works in formats which do not have any title page as such, “Title Page” means the text near the most prominent appearance of the work’s title, preceding the beginning of the body of the text.

The “publisher” means any person or entity that distributes copies of the Document to the public.

A section “Entitled XYZ” means a named subunit of the Document whose title either is precisely XYZ or contains XYZ in parentheses following text that translates XYZ in another language. (Here XYZ stands for a specific section name mentioned below, such as “Acknowledgements”, “Dedications”, “Endorsements”, or “History”.) To “Preserve the Title” of such a section when you modify the Document means that it remains a section “Entitled XYZ” according to this definition.

The Document may include Warranty Disclaimers next to the notice which states that this License applies to the Document. These Warranty Disclaimers are considered to be included by reference in this License, but only as regards disclaiming warranties: any other implication that these Warranty Disclaimers may have is void and has no effect on the meaning of this License.

2. VERBATIM COPYING

You may copy and distribute the Document in any medium, either commercially or noncommercially, provided that this License, the copyright notices, and the license notice saying this License applies to the Document are reproduced in all copies, and that you add no other conditions whatsoever to those of this License. You may not use technical measures to obstruct or control the reading or further copying of the copies you make or distribute. However, you may accept compensation in exchange for copies. If you distribute a large enough number of copies you must also follow the conditions in section 3.

You may also lend copies, under the same conditions stated above, and you may publicly display copies.

3. COPYING IN QUANTITY

If you publish printed copies (or copies in media that commonly have printed covers) of the Document, numbering more than 100, and the Document's license notice requires Cover Texts, you must enclose the copies in covers that carry, clearly and legibly, all these Cover Texts: Front-Cover Texts on the front cover, and Back-Cover Texts on the back cover. Both covers must also clearly and legibly identify you as the publisher of these copies. The front cover must present the full title with all words of the title equally prominent and visible. You may add other material on the covers in addition. Copying with changes limited to the covers, as long as they preserve the title of the Document and satisfy these conditions, can be treated as verbatim copying in other respects.

If the required texts for either cover are too voluminous to fit legibly, you should put the first ones listed (as many as fit reasonably) on the actual cover, and continue the rest onto adjacent pages.

If you publish or distribute Opaque copies of the Document numbering more than 100, you must either include a machine-readable Transparent copy along with each Opaque copy, or state in or with each Opaque copy a computer-network location from which the general network-using public has access to download using public-standard network protocols a complete Transparent copy of the Document, free of added material. If you use the latter option, you must take reasonably prudent steps, when you begin distribution of Opaque copies in quantity, to ensure that this Transparent copy will remain thus accessible at the stated location until at least one year after the last time you distribute an Opaque copy (directly or through your agents or retailers) of that edition to the public.

It is requested, but not required, that you contact the authors of the Document well before redistributing any large number of copies, to give them a chance to provide you with an updated version of the Document.

4. MODIFICATIONS

You may copy and distribute a Modified Version of the Document under the conditions of sections 2 and 3 above, provided that you release the Modified Version under precisely this License, with the Modified Version filling the role of the Document, thus licensing distribution and modification of the Modified Version to whoever possesses a copy of it. In addition, you must do these things in the Modified Version:

- A. Use in the Title Page (and on the covers, if any) a title distinct from that of the Document, and from those of previous versions (which should, if there were any, be listed in the History section of the Document). You may use the same title as a previous version if the original publisher of that version gives permission.
- B. List on the Title Page, as authors, one or more persons or entities responsible for authorship of the modifications in the Modified Version, together with at least five of the principal authors of the Document (all of its principal authors, if it has fewer than five), unless they release you from this requirement.
- C. State on the Title page the name of the publisher of the Modified Version, as the publisher.
- D. Preserve all the copyright notices of the Document.
- E. Add an appropriate copyright notice for your modifications adjacent to the other copyright notices.
- F. Include, immediately after the copyright notices, a license notice giving the public permission to use the Modified Version under the terms of this License, in the form shown in the Addendum below.
- G. Preserve in that license notice the full lists of Invariant Sections and required Cover Texts given in the Document's license notice.

- H. Include an unaltered copy of this License.
- I. Preserve the section Entitled “History”, Preserve its Title, and add to it an item stating at least the title, year, new authors, and publisher of the Modified Version as given on the Title Page. If there is no section Entitled “History” in the Document, create one stating the title, year, authors, and publisher of the Document as given on its Title Page, then add an item describing the Modified Version as stated in the previous sentence.
- J. Preserve the network location, if any, given in the Document for public access to a Transparent copy of the Document, and likewise the network locations given in the Document for previous versions it was based on. These may be placed in the “History” section. You may omit a network location for a work that was published at least four years before the Document itself, or if the original publisher of the version it refers to gives permission.
- K. For any section Entitled “Acknowledgements” or “Dedications”, Preserve the Title of the section, and preserve in the section all the substance and tone of each of the contributor acknowledgements and/or dedications given therein.
- L. Preserve all the Invariant Sections of the Document, unaltered in their text and in their titles. Section numbers or the equivalent are not considered part of the section titles.
- M. Delete any section Entitled “Endorsements”. Such a section may not be included in the Modified Version.
- N. Do not retitle any existing section to be Entitled “Endorsements” or to conflict in title with any Invariant Section.
- O. Preserve any Warranty Disclaimers.

If the Modified Version includes new front-matter sections or appendices that qualify as Secondary Sections and contain no material copied from the Document, you may at your option designate some or all of these sections as invariant. To do this, add their titles to the list of Invariant Sections in the Modified Version’s license notice. These titles must be distinct from any other section titles.

You may add a section Entitled “Endorsements”, provided it contains nothing but endorsements of your Modified Version by various parties—for example, statements of peer review or that the text has been approved by an organization as the authoritative definition of a standard.

You may add a passage of up to five words as a Front-Cover Text, and a passage of up to 25 words as a Back-Cover Text, to the end of the list of Cover Texts in the Modified Version. Only one passage of Front-Cover Text and one of Back-Cover Text may be added by (or through arrangements made by) any one entity. If the Document already includes a cover text for the same cover, previously added by you or by arrangement made by the same entity you are acting on behalf of, you may not add another; but you may replace the old one, on explicit permission from the previous publisher that added the old one.

The author(s) and publisher(s) of the Document do not by this License give permission to use their names for publicity for or to assert or imply endorsement of any Modified Version.

5. COMBINING DOCUMENTS

You may combine the Document with other documents released under this License, under the terms defined in section 4 above for modified versions, provided that you include in the combination all of the Invariant Sections of all of the original documents, unmodified, and list them all as Invariant Sections of your combined work in its license notice, and that you preserve all their Warranty Disclaimers.

The combined work need only contain one copy of this License, and multiple identical Invariant Sections may be replaced with a single copy. If there are multiple Invariant Sections with the same name but different contents, make the title of each such section unique by adding at the end of it, in parentheses, the name of the original author or publisher of that section if known, or else a unique number. Make the same adjustment to the section titles in the list of Invariant Sections in the license notice of the combined work. In the combination, you must combine any sections Entitled “History” in the various original documents, forming one section Entitled “History”; likewise combine any sections Entitled “Acknowledgements”, and any sections Entitled “Dedications”. You must delete all sections Entitled “Endorsements.”

6. COLLECTIONS OF DOCUMENTS

You may make a collection consisting of the Document and other documents released under this License, and replace the individual copies of this License in the various documents with a single copy that is included in the collection, provided that you follow the rules of this License for verbatim copying of each of the documents in all other respects.

You may extract a single document from such a collection, and distribute it individually under this License, provided you insert a copy of this License into the extracted document, and follow this License in all other respects regarding verbatim copying of that document.

7. AGGREGATION WITH INDEPENDENT WORKS

A compilation of the Document or its derivatives with other separate and independent documents or works, in or on a volume of a storage or distribution medium, is called an “aggregate” if the copyright resulting from the compilation is not used to limit the legal rights of the compilation’s users beyond what the individual works permit. When the Document is included in an aggregate, this License does not apply to the other works in the aggregate which are not themselves derivative works of the Document.

If the Cover Text requirement of section 3 is applicable to these copies of the Document, then if the Document is less than one half of the entire aggregate, the Document’s Cover Texts may be placed on covers that bracket the Document within the aggregate, or the electronic equivalent of covers if the Document is in electronic form. Otherwise they must appear on printed covers that bracket the whole aggregate.

8. TRANSLATION

Translation is considered a kind of modification, so you may distribute translations of the Document under the terms of section 4. Replacing Invariant Sections with translations requires special permission from their copyright holders, but you may include translations of some or all Invariant Sections in addition to the original versions of these Invariant Sections. You may include a translation of this License, and all the license notices in the Document, and any Warranty Disclaimers, provided that you also include the original English version of this License and the original versions of those notices and disclaimers. In case of a disagreement between the translation and the original version of this License or a notice or disclaimer, the original version will prevail.

If a section in the Document is Entitled “Acknowledgements”, “Dedications”, or “History”, the requirement (section 4) to Preserve its Title (section 1) will typically require changing the actual title.

9. TERMINATION

You may not copy, modify, sublicense, or distribute the Document except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, or distribute it is void, and will automatically terminate your rights under this License.

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly

and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, receipt of a copy of some or all of the same material does not give you any rights to use it.

10. FUTURE REVISIONS OF THIS LICENSE

The Free Software Foundation may publish new, revised versions of the GNU Free Documentation License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns. See <http://www.gnu.org/copyleft/>.

Each version of the License is given a distinguishing version number. If the Document specifies that a particular numbered version of this License “or any later version” applies to it, you have the option of following the terms and conditions either of that specified version or of any later version that has been published (not as a draft) by the Free Software Foundation. If the Document does not specify a version number of this License, you may choose any version ever published (not as a draft) by the Free Software Foundation. If the Document specifies that a proxy can decide which future versions of this License can be used, that proxy’s public statement of acceptance of a version permanently authorizes you to choose that version for the Document.

11. RELICENSING

“Massive Multiauthor Collaboration Site” (or “MMC Site”) means any World Wide Web server that publishes copyrightable works and also provides prominent facilities for anybody to edit those works. A public wiki that anybody can edit is an example of such a server. A “Massive Multiauthor Collaboration” (or “MMC”) contained in the site means any set of copyrightable works thus published on the MMC site.

“CC-BY-SA” means the Creative Commons Attribution-Share Alike 3.0 license published by Creative Commons Corporation, a not-for-profit corporation with a principal place of business in San Francisco, California, as well as future copyleft versions of that license published by that same organization.

“Incorporate” means to publish or republish a Document, in whole or in part, as part of another Document.

An MMC is “eligible for relicensing” if it is licensed under this License, and if all works that were first published under this License somewhere other than this MMC, and subsequently incorporated in whole or in part into the MMC, (1) had no cover texts or invariant sections, and (2) were thus incorporated prior to November 1, 2008.

The operator of an MMC Site may republish an MMC contained in the site under CC-BY-SA on the same site at any time before August 1, 2009, provided the MMC is eligible for relicensing.

ADDENDUM: How to use this License for your documents

To use this License in a document you have written, include a copy of the License in the document and put the following copyright and license notices just after the title page:

```
Copyright (C)  year  your name.
Permission is granted to copy, distribute and/or modify this document
under the terms of the GNU Free Documentation License, Version 1.3
or any later version published by the Free Software Foundation;
with no Invariant Sections, no Front-Cover Texts, and no Back-Cover
Texts.  A copy of the license is included in the section entitled ‘‘GNU
Free Documentation License’’.
```

If you have Invariant Sections, Front-Cover Texts and Back-Cover Texts, replace the “with...Texts.” line with this:

```
with the Invariant Sections being list their titles, with
the Front-Cover Texts being list, and with the Back-Cover Texts
being list.
```

If you have Invariant Sections without Cover Texts, or some other combination of the three, merge those two alternatives to suit the situation.

If your document contains nontrivial examples of program code, we recommend releasing these examples in parallel under your choice of free software license, such as the GNU General Public License, to permit their use in free software.

