

B-BOX DASH parameters list
2026-07-01

Nos.	Field Indication(s)	標位顯示	Sub-Field Indication(s)	子標位顯示	Sensor/Input Type	Parameter Name	Unit of Measure	Update Interval	Payload	Range / Expected Values	Optimal value(s)	Formula(e)	IDs	V1.0	V1.5
1	WASTE PROCESSED	今日已處理廢棄物	TODAY'S INPUT	今日投入量	Load Cell (Disposal tray)	Waste Mass Input	kg	Every 1 minute	30 minutes (with 30 packs of data)	0 – 80 kg	N/A	Load Cell sensor (1)	weigh1	N	Y
2	BIOMASS PERFORMANCE	生物質表現	CURRENT BIOMASS	目前養殖容器累積	Load Cell (container)	Waste Mass BSF feeding container	kg	Every 30 minutes	30 minutes	0 – 250 kg	Less than 100 kg	Load Cell sensor (2)	weigh2	Y	Y
3	CONVERTED WASTE	已轉化有機質	WEEKLY WASTE VOLUME (KG) --> BIOMASS OUTPUT	每週廢棄物量 (公斤) --> 有機質產出	Waste Processed	Larval Biomass Generated	kg	24 hours	24 hours	0 – 200 kg	80 kg	Load Cell sensor (2) divided by 15	weigh2	Y	Y
4	ENVIRONMENTAL SENSORS	環境感測器	CHAMBER TEMP	容器溫度	Temperature Sensor	Internal Decomposition Chamber Temp	°C	Every 5 minutes	30 minutes (with 6 sets of data)	5°C – 65°C	Less than 37°C	Temperature sensor	Temperature	Y	Y
5	ENVIRONMENTAL SENSORS	環境感測器	CHAMBER HUMIDITY	容器濕度	Humidity Sensor	Chamber Relative Humidity	% RH	Every 5 minutes	30 minutes (with 6 sets of data)	20% – 99.9%	Less than 75%	Humidity sensor	Humidity	Y	Y
6	ENVIRONMENTAL SENSORS	環境感測器	CO2, NH3 LEVEL	CO ₂ 、NH ₃ 濃度	Gas Analysis Sensor	CO2 and NH4 levels	ppm	Every 30 minutes	30 minutes	0 – 1	CO2: Less than 5,000 ppm; NH4: Less than 1,000 ppm	CO2 sensor, NH4 sensor	CO2, NH3	Y	Y
7	ENERGY MONITORING	能源監控	SYSTEM USAGE	裝置用電量	Power Monitor	Energy Consumption	kWh	Every 60 minutes	60 minutes	0 – 5 kW	Less than 1.5KW	Current Meter	ACMotor	Y	N
8	ENERGY MONITORING	能源監控	SOLAR VOLTAGE	太陽能電壓	Power Monitor	Solar Energy Voltage	V	Every 60 minutes	60 minutes	0 - 36 V	24 +/-4V	DC/AC inverter from PV/ panel	BatVoltage	Y	N
9	BIOMASS PERFORMANCE	幼蟲健康度	LARVAL GROWTH STAGE	幼蟲生長階段	System Healthiness	Larvae Healthiness	ACTIVE / INACTIVE	Every 60 minutes	60 minutes	Baseline-specific	ACTIVE	ACTIVE : temperature sensor = expected values & humidity sensor = expected values	Temperature:15-45°C & Humidity:35-75%	Y	Y
10	SYSTEM STATUS	系統狀態	--	--	System Healthiness	System Status	Green (ACTIVE)/ Yellow (ACTIVE)/ Red dot (OFFLINE)	--	60 minutes	--	Green	Criteria (Green) : system online, self-check pass; Criteria (Yellow) : system online, self-check with parameters undetectable; self-check (Red) : self-check malfunction (system offline)	TiltDetect=undetected, RollMotor=value>0, CBoardPD=value>0, FanMotorN=value>0, FanMotorOUT=value>0, rssi>-90	N	Y
11	DEVICE LOCATION	裝置地理位置	UNIT LOCATION (MAP)	裝置位置 (地圖)	System Healthiness	Unit Location	(Map)	--	24 hours	--	--	GPS module	GPS	Y	Y
12	NEXT MAINTENANCE	距離下次維護	--	--	System Healthiness	Next Maintenance	days	--	24 hours	--	25 days	Countdown (25 days - 1 day) until 0	--	N	Y
13	DAILY REDUCTION	每日減排量	--	--	No. 1 + No. 3	--	kg CO2e Saved	--	24 hours	--	--	(Daily accumulated until 23:59 of No.1 * 1.5) + (No.3 * 0.9635)	--	Y	Y
14	WEEKLY REDUCTION	每週減排量	--	--	No. 1 + No. 3	--	kg CO2e Saved	--	24 hours	--	--	Accumulated No.13 historical 7 days record	--	Y	Y
15	60 DAYS REDUCTION	累計60天總減排量	--	--	No. 1 + No. 3	--	kg CO2e Saved	--	24 hours	--	--	Accumulated No. 14 record (Total)	--	Y	Y
	CONTAINER WEIGH TREND (7 days / 15 days / 30 days)	容器重量趨勢 (7天 / 15天 / 30天)	--	--	Load Cell (container)	Waste Mass BSF feeding container	kg	24 hours	Daily 23:59	0 - 150 kg	80 kg	Daily 23:59	weigh2	N	Y

About this Device	
fmVer	Firmware Version
devID	B-BOX ID

Admin Reference Only	
msgID	Payload ID

NO2	Cancel
CO	Cancel
weight3	Cancel
3Axis	Cancel