

mydb SQL Support Document

January 2, 2016

1 Keywords

(case not sensitive)					
DATABASE	DATABASES	TABLE	TABLES	SHOW	CREATE
DROP	USE	CHECK	PRIMARY	KEY	UNIQUE
NOT	NULL	AUTO_INCREMENT	INSERT	INTO	VALUES
DELETE	FROM	WHERE	UPDATE	SET	SELECT
GROUP	BY	IS	IN	BETWEEN	LIKE
AND	OR	SUM	AVG	MAX	MIN
INT	SMALLINT	BIGINT	FLOAT	REAL	DOUBLE
VARCHAR	STRING	CHAR	BOOLEAN	DATETIME	DESC
FOREIGN	REFERENCES	INDEX	DEFAULT	TRUE	FALSE

2 Syntax

$\langle \text{program} \rangle$::= $\langle \text{stmt} \rangle [\langle \text{stmt} \rangle]^*$
$\langle \text{ident} \rangle$::= $[A-Za-z_][A-Za-z0-9_]^*$
$\langle \text{integer} \rangle$::= $(+ -)?[0-9]^+$
$\langle \text{length} \rangle$::= $[0-9]^+$
$\langle \text{real} \rangle$::= $(+ -)?[0-9]^+.[0-9]^+$
$\langle \text{string} \rangle$::= $'.*'$
$\langle \text{bool} \rangle$::= $\text{TRUE} \mid \text{FALSE}$
$\langle \text{value} \rangle$::= $\langle \text{integer} \rangle \mid \langle \text{real} \rangle \mid \langle \text{string} \rangle \mid \langle \text{bool} \rangle \mid \text{NULL}$
$\langle \text{stmt} \rangle$::= $\langle \text{sysStmt} \rangle ;$ $\langle \text{dbStmt} \rangle ;$ $\langle \text{tbStmt} \rangle ;$ $\langle \text{idxStmt} \rangle ;$

$\langle sysStmt \rangle$::= SHOW DATABASES
$\langle dbStmt \rangle$::= CREATE DATABASE $\langle dbName \rangle$ DROP DATABASE $\langle dbName \rangle$ USE $\langle dbName \rangle$ SHOW TABLES
$\langle tbStmt \rangle$::= CREATE TABLE $\langle tbName \rangle$ ($\langle field \rangle$ [, $\langle field \rangle$]*) DROP TABLE $\langle tbName \rangle$ DESC $\langle tbName \rangle$ SHOW TABLE $\langle tbName \rangle$ INSERT INTO $\langle tbName \rangle$ [($\langle colName \rangle$ [, $\langle colName \rangle$]*)] VALUES ($\langle values \rangle$) [, ($\langle values \rangle$)]* DELETE FROM $\langle tbName \rangle$ WHERE $\langle boolExpr \rangle$ UPDATE $\langle tbName \rangle$ SET $\langle colName \rangle$ = $\langle expr \rangle$ [, $\langle colName \rangle$ = $\langle expr \rangle$]* WHERE $\langle boolExpr \rangle$ SELECT $\langle selectors \rangle$ FROM $\langle tbName \rangle$ [, $\langle tbName \rangle$]* [WHERE $\langle boolExpr \rangle$] [GROUP BY $\langle colName \rangle$]
$\langle tbName \rangle$::= $\langle ident \rangle$
$\langle colName \rangle$::= $\langle ident \rangle$
$\langle field \rangle$::= $\langle colName \rangle$ $\langle type \rangle$ [($\langle attr \rangle$)]* CHECK ($\langle boolExpr \rangle$) PRIMARY KEY ($\langle colName \rangle$) FOREIGN KEY ($\langle colName \rangle$) REFERENCES $\langle tbName \rangle$ ($\langle colName \rangle$)
$\langle type \rangle$::= INT [($\langle length \rangle$)] SMALLINT BIGINT FLOAT REAL DOUBLE VARCHAR ($\langle length \rangle$) STRING CHAR BOOLEAN DATETIME
$\langle attr \rangle$::= NOT NULL UNIQUE AUTO_INCREMENT DEFAULT $\langle value \rangle$
$\langle values \rangle$::= $\langle value \rangle$ [, $\langle value \rangle$]*
$\langle boolExpr \rangle$::= $\langle col \rangle$ $\langle boolOp \rangle$ $\langle expr \rangle$ $\langle col \rangle$ IS [NOT] NULL $\langle col \rangle$ [NOT] IN ($\langle value \rangle$ [, $\langle value \rangle$]*)

	$\langle col \rangle$ [NOT] BETWEEN $\langle value \rangle$ AND $\langle value \rangle$ $\langle col \rangle$ [NOT] LIKE $\langle string \rangle$ ($\langle boolExpr \rangle$) $\langle boolExpr \rangle$ AND $\langle boolExpr \rangle$ $\langle boolExpr \rangle$ OR $\langle boolExpr \rangle$
$\langle col \rangle$::= [$\langle tbName \rangle$.] $\langle colName \rangle$
$\langle boolOp \rangle$::= '=' '<>' '<=' '>=' '<' '>'
$\langle expr \rangle$::= $\langle value \rangle$ $\langle col \rangle$ $\langle expr \rangle$ $\langle op \rangle$ $\langle expr \rangle$ ($\langle expr \rangle$)
$\langle op \rangle$::= '+' '-' '*' '/' '%'
$\langle selectors \rangle$::= * $\langle selector \rangle$ [, $\langle selector \rangle$]*
$\langle selector \rangle$::= $\langle col \rangle$ $\langle func \rangle$ ($\langle col \rangle$)
$\langle func \rangle$::= SUM AVG MAX MIN
$\langle idxStmt \rangle$::= CREATE INDEX $\langle tbName \rangle$ ($\langle colName \rangle$) DROP INDEX $\langle tbName \rangle$ ($\langle colName \rangle$)

3 Priority

(from lowest to highest)

left or
left and
left + -
left * / %