



## Part 1: Diffusion MRI Analysis in Broad Strokes



Carl-Fredrik Westin, Ph.D.

Director, Laboratory of Mathematics in Imaging (LMI)

Brigham and Women's Hospital

Harvard Medical School

# Overview



1. Diffusion Tensor MRI
2. Structural connectivity from diffusion MRI
3. White matter anatomy from connectivity




# Diffusion-weighted MRI (DW-MRI)



Brownian motion of one material through another

Anisotropy: diffusion rate depends on direction


Magnetic gradients create spatial planar waves of proton **phase**



Destructive interference measures diffusion along gradient direction only



# Underlying Biology (Simplified!)



Gray matter (cortex + nuclei): cell bodies

White matter: axons

Myelin sheath speeds signal conduction


Axon + sheath = nerve fibers

Major white matter pathways aggregate many fibers into bundles

# Multiple DWI → Tensor Estimate

Single Tensor Model (Basser 1994)



$$S_i(b, \mathbf{g}_i) = S_0 e^{-b \mathbf{g}_i^T \mathbf{D} \mathbf{g}_i}$$



# Eigenvalues == Shape

$$\mathbf{D} = \mathbf{R}\mathbf{\Lambda}\mathbf{R}^{-1}$$


$$= \begin{bmatrix} | & | & | \\ \mathbf{v}_1 & \mathbf{v}_2 & \mathbf{v}_3 \\ | & | & | \end{bmatrix} \begin{bmatrix} \lambda_1 & 0 & 0 \\ 0 & \lambda_2 & 0 \\ 0 & 0 & \lambda_3 \end{bmatrix} \begin{bmatrix} -\mathbf{v}_1 \\ -\mathbf{v}_2 \\ -\mathbf{v}_3 \end{bmatrix}$$





# Tensor invariants as orthogonal shape parameterizations

Cylindrical or spherical coordinates  
(Ennis+Kindlmann 2005)




$$\text{tr}(\mathbf{D}) = D_{xx} + D_{yy} + D_{zz}$$


$$|\mathbf{D}| = \sqrt{\text{tr}(\mathbf{D}^T \mathbf{D})}$$

$$\mathbf{E} = \text{deviatoric}(\mathbf{D})$$


$$= \mathbf{D} - \text{trace}(\mathbf{D}) * \mathbf{I} / 3$$




$\text{tr}(\mathbf{D})$




$|\mathbf{E}|$



$|\mathbf{D}|$



$|\mathbf{E}|/|\mathbf{D}| \sim \text{FA}$   
**FA = Fractional Anisotropy**




$\text{mode}(\mathbf{E})$   
 $= \det(\mathbf{E}/|\mathbf{E}|)$   
 (Criscione '00)  
 Mode measures  
 Linear vs. planar  
 anisotropy

# Biological Meaning of Tensor Shape




Size: **bulk mean diffusivity** (“ADC”)




- ADC strictly speaking diffusivity along **one** direction
- Note: same across gray+white matter, high in CSF
- Indicator of acute ischemic stroke

Anisotropy (e.g. FA): directional microstructure



- High in white matter, low in gray matter and CSF
- Increases with myelination, decreases in some diseases (Multiple Sclerosis)


Mode: linear versus planar



- Partial voluming of adjacent orthogonal structures
- Fine-scale mixing of diverse fiber directions
- Tensor fitting error increases with planarity (Tuch 2002)



# Tensor shape on one slice




Trace

Fractional **A**nisotropy

FA & Mode

“Anisotropy” is a bivariate quantity



1. Diffusion Tensor MRI
2. Structural connectivity from diffusion MRI
3. White matter anatomy from connectivity

# “Connectivity” from dMRI



Examples of very different methods:

1. Principal Diffusion Direction (PDD) Tractography
2. Stochastic Methods, can model uncertainty
3. Geometric, Geodesic approaches




# Fiber Tractography (Basser 1999)

Path integration along principal eigenvector

Idea/Fantasy: follow paths of individual axons!


- Reality: 2-3 orders of magnitude too coarse

Essentially same as simplified hyperstreamlines (Delmarcelle 1993)





# Tractography



# Fiber Tractography Issues



- Tensor Field Interpolation/Filtering
- Integration quality, step size
  - Eigensolve at every sample non-trivial
- Seedpoint selection determines path
- Termination criteria
- Parameter space → Reproducibility, Validation





# “Connectivity” from dMRI



Examples of very different methods:

1. Principal Diffusion Direction (PDD) Tractography
2. Stochastic Methods, can model uncertainty
3. Geometric, Geodesic approaches



# Stochastic Tractography




Brun, Westin, **Regularized Stochastic White Matter Tractography Using Diffusion Tensor MRI: Monte Carlo, Sequential Importance Sampling and Resampling.** MICCAI 2002.

Lazar, Alexander, **White Matter Tractography using Random Vector (RAVE) Perturbation,** ISMRM 2002

D. Tuch, Diffusion MRI of complex tissue structure, Ph.D. dissertation, Harvard-MIT Division of Health Sciences and Technology, 2002



# Stochastic tractography: fiber distributions



# Non-parametric approaches: Bootstrap



Pajevic and Basser, JMR 2003

Jones and Pierpaoli, MRM 2005

Lazar and Alexander, Neuroimage 2005

A drawback with non-parametric approaches is that they require a lot of data, and thereby also scanning times that may be unacceptable.



# Parametric Approaches: Bayesian






Behrens, et al. *Characterization and propagation of uncertainty in diffusion-weighted MR imaging*, MRM 2003

Friman, Westin. *Uncertainty in white matter tractography*, MICCAI 2005


Friman, Farneback, Westin. *A Bayesian Approach for Stochastic White Matter Tractography*, IEEE Trans Med Imaging 2006

# Stochastic tractography

Friman, Westin MICCAI 2005, TMI 2006  
Behrens MRM 2003, Brun MICCAI 2002




Fractional anisotropy



A probability density function of the fiber orientation in each point.

Start point




In every step, draw a step direction from the pdf of the underlying fiber orientation.




# Bayesian Approach

Bayes' rule:  $p(\mathbf{v}_k \mid \text{diffusion data}, \mathbf{v}_{k-1}) \propto p(\text{diffusion data} \mid \mathbf{v}_k) p(\mathbf{v}_k \mid \mathbf{v}_{k-1})$


**Posterior distribution** of next step direction  $\mathbf{v}_k$  given the diffusion measurements and the previous step direction  $\mathbf{v}_{k-1}$



**Likelihood function** of the diffusion measurements given an underlying fiber orientation  $\mathbf{v}_k$ . Models the noise and water diffusion.



**Prior distribution** of next step direction  $\mathbf{v}_k$  given the previous step direction  $\mathbf{v}_{k-1}$ . Provides regularization of the fiber paths.



# Constrained tensor model

Tensor model of local water diffusion:



$$\mu_i = \mu_0 e^{-b_i \mathbf{g}_i^T \mathbf{D} \mathbf{g}_i}$$

Constrained tensor model where  $\lambda_2 = \lambda_3$  :

$$\mu_i = \mu_0 e^{-\alpha b_i} e^{-\beta b_i \left( \mathbf{g}_i^T \mathbf{v} \right)^2}$$

↑  
Isotropic

↑  
Anisotropic



Models the effect of a single underlying fiber bundle.

Multiple fiber orientations, and the oblate tensor case, will be reflected as increased uncertainty in the fiber orientation.

# Constrained tensor model estimation



**Constrained  
tensor model  
easy to estimate!**

Baseline  
intensity

Isotropic  
diffusion

Anisotropic  
diffusion

Fiber  
direction




$$\mu_i = \mu_0 e^{-\alpha b_i} e^{-\beta b_i (\mathbf{g}_i^T \mathbf{v})^2}$$

1. Estimate traditional tensor model which gives  $\mu_0$  and diffusion tensor

$$\mathbf{D} = \lambda_1 \mathbf{v}_1 \mathbf{v}_1^T + \lambda_2 \mathbf{v}_2 \mathbf{v}_2^T + \lambda_3 \mathbf{v}_3 \mathbf{v}_3^T, \quad \lambda_1 \geq \lambda_2 \geq \lambda_3$$

2. Set  $\alpha = \frac{\lambda_2 + \lambda_3}{2}$        $\beta = \lambda_1 - \alpha$        $\mathbf{v} = \mathbf{v}_1$

# Multiple fiber orientations




- a) A schematic image of the fiber crossing used as basis for simulating diffusion measurements.
- b) Assuming we are tracking the vertical fiber gives the prior above. The posterior is the produce of the prior and the likelihood.

The model miss-match results in increased uncertainty in the plane of crossing fibers.


# Probability of connection

Given a large number of fibers, the probability of a connection between two voxels can be estimated



Probability density function: 1) Add the contribution from all paths, and 2) normalize the total sum of all voxels

# Stochastic tracking results




3,000 fiber samples initiated in the splenium of Corpus callosum. The coloring indicates the probability along each path to end up in a specific area.




# Probability of connection

Corpus callosum



Inferior occipitofrontal fasciculi



# “Connectivity” from dMRI




Examples of very different methods:

1. Principal Diffusion Direction (PDD) Tractography
2. Stochastic Methods, can model uncertainty
3. Geometric, Geodesic approaches




# Geodesic Connectivity

Connectivity should be proportional to distance in some metric space.



Diffusion Tensor,  $D$

$$|v|^2 = v^T G v$$



Metric Tensor,  $G = D^{-1}$

O'Donnell, Haker, Westin, MICCAI 2002


# Riemannian Distance Map

Input: Riemannian metric tensor  $G$ .

Input: initial point

Output: geodesic paths.

Output: distances between points in the brain.




# Color-coded Connectivity

The length of the shortest (geodesic) path between two points indicates connectivity.

One measure of connectivity:


$$C = \frac{\text{Euclidean path length}}{\text{G-metric path length}}$$



# Color-coded Connectivity

Computed connectivity measure in 3D

PDD Tractography visualization passes through highest-connectivity region.





Geodesic connectivity based on the inverse diffusion tensor as Riemannian metric:

O'Donnell, Haker, Westin, MICCAI 2002

Lenglet, Deriche, Faugeras. Inferring White Matter Geometry from Diffusion Tensor MRI: Application to Connectivity Mapping, ECCV 2004

Fletcher, Tao, Jeong, Whitaker, A Volumetric Approach to Quantifying Region-to-Region White Matter Connectivity in Diffusion Tensor MRI, IPMI 2007

What happens if the metric cannot be described by a tensor?


High Angular Diffusion Imaging (HARDI) data can be used for estimation of more complex diffusion profiles and cost functions.

Finsler geometry is a metric extension of Riemannian geometry.


[Pichon05] Pichon, Westin, Tannenbaum “*A Hamilton-Jacobi-Bellman approach to high angular resolution diffusion tractography*”, MICCAI 2005

[Melanakis07] Melanakis, Mohan, Niethammer, Smith, Kubicki, Tannenbaum, “*Finsler Tractography for White Matter Connectivity Analysis of the Cingulum Bundle*”, MICCAI 2007


# Modeling crossing tracts



DTI: Single tensor model



Two-tensor model



# Overview





1. Diffusion Tensor MRI
2. Structural connectivity from diffusion MRI
3. White matter anatomy from connectivity






# Segmentation challenge

From DT-MRI tractography ...



... to white matter tract models  
using **clustering**

# Fibers to bundles



**Splenium of the corpus callosum** interconnecting different regions: occipital lobes (green), temporal lobes (red) and thalamus (blue).

Provided by Marek Kubicki

# Analysis by manifold learning




- Map data to a low-dimensional space
- Spectral methods to define manifold
- Try to preserve metric and topology

Provided by Anders Brun





# Spectral methods to define manifold



## Non-linear data reduction using locally linear embedding (LLE)

Images from Roweis and Saul, *Science* 2000

# Spectral methods to define manifold




Image from Roweis and Saul, *Science* 2000


Images of faces mapped into the embedding space described by the first two coordinates of LLE

# Spectral Method for Fiber Clustering



MICCAI

Fiber bundle clustering using spectral methods



- Pair-wise fiber affinities are inserted in a large matrix
- Eigenvectors of this matrix define manifold


Provided by A. Brun



# Fiber Clustering



Traced fibers



High-dimensional  
feature space




Colored bundles

A clustering algorithm takes a number of traced fibers (left), extracts features from these fibers (middle), and produces a segmentation based on the similarity of the fibers (right).

O'Donnell MICCAI 2005

# Defining fiber similarity



Hausdorff distance

Endpoint distance

Mean and covariance

Provided by L. O'Donnell





# Population Clustering



Five subject example

5,000-7,000 paths per subject


Automated generation of white matter ROIs

Work with L. O'Donnell

# Selected clusters



Cingulum bundles




Uncinate fasciculus

Work with L. O'Donnell



# Selected clusters



Corpus callosum

Work with L. O'Donnell

# High-dimensional Fiber Atlas

Created using many subjects

In **embedding space**


High-dimensional

- 20 dimensions
- Not a voxel atlas

Automatic segmentation

- Project new subject tractography data to embedded atlas space

Work with L. O'Donnell




# High-dimensional Fiber Atlas

## Method for atlas creation

- Learns clusters from multiple subjects
- Incorporates expert labels

## Automatic segmentation using atlas

- Label whole-brain tractography automatically



Work with L. O'Donnell

# Acknowledgements



Anders Brun, TechLic,  
Lauren O'Donnell, PhD  
Raul San-Jose Estepar, PhD  
Ola Friman, PhD  
Ron Kikinis, MD  
Gordon Kindlmann, PhD  
Marek Kubicki, MD, PhD  
Hans Knutsson, PhD  
Mahnaz Maddah, MSc  
Marc Niethammer, PhD  
Sharon Peled, PhD  
Steve Pieper, PhD  
Martha Shenton, PhD  
Ulas Ziyan, MSc

<http://lmi.bwh.harvard.edu>

