

- **Part Number:**

1926

- **Part Number Title:**

Safety and Health Regulations for Construction

- **Subpart:**

1926 Subpart E

- **Subpart Title:**

Personal Protective and Life Saving Equipment

- **Standard Number:**

1926.101

- **Title:**

Hearing protection.

- **GPO Source:**

e-CFR

1926.101(a)

Wherever it is not feasible to reduce the noise levels or duration of exposures to those specified in Table D-2, Permissible Noise Exposures, in § 1926.52, ear protective devices shall be provided and used.

1926.101(b)

Ear protective devices inserted in the ear shall be fitted or determined individually by competent persons.

1926.101(c)

- **Plain cotton is not an acceptable protective device.**

Part Number:

1926

- **Part Number Title:**

Safety and Health Regulations for Construction

- Subpart:

1926 Subpart E

- Subpart Title:

Personal Protective and Life Saving Equipment

- Standard Number:

[1926.103](#)

- Title:

Respiratory protection.

- GPO Source:

[e-CFR](#)

Note: The requirements applicable to construction work under this section are identical to those set forth at 29 CFR [1910.134](#) of this chapter.

- [58 FR 35160, June 30, 1993; 61 FR 5507, Feb. 13, 1996; 61 FR 9227, March 7, 1996; 63 FR 1152, Jan. 8, 1998]

Part Number:

1926

- Part Number Title:

Safety and Health Regulations for Construction

- Subpart:

1926 Subpart E

- Subpart Title:

Personal Protective and Life Saving Equipment

- Standard Number:

[1926.104](#)

- Title:

Safety belts, lifelines, and lanyards.

- **GPO Source:**

e-CFR

1926.104(a)

Lifelines, safety belts, and lanyards shall be used only for employee safeguarding. Any lifeline, safety belt, or lanyard actually subjected to in-service loading, as distinguished from static load testing, shall be immediately removed from service and shall not be used again for employee safeguarding.

1926.104(b)

Lifelines shall be secured above the point of operation to an anchorage or structural member capable of supporting a minimum dead weight of 5,400 pounds.

1926.104(c)

Lifelines used on rock-scaling operations, or in areas where the lifeline may be subjected to cutting or abrasion, shall be a minimum of 7/8 -inch wire core manila rope. For all other lifeline applications, a minimum of 3/4 -inch manila or equivalent, with a minimum breaking strength of 5,000 pounds, shall be used.

1926.104(d)

Safety belt lanyard shall be a minimum of 1/2 -inch nylon, or equivalent, with a maximum length to provide for a fall of no greater than 6 feet. The rope shall have a nominal breaking strength of 5,400 pounds.

1926.104(e)

All safety belt and lanyard hardware shall be drop forged or pressed steel, cadmium plated in accordance with type 1, Class B plating specified in Federal Specification QQ-P-416. Surface shall be smooth and free of sharp edges.

1926.104(f)

All safety belt and lanyard hardware, except rivets, shall be capable of withstanding a tensile loading of 4,000 pounds without cracking, breaking, or taking a permanent deformation.

[44 FR 8577, Feb. 9, 1979; 44 FR 20940, Apr. 6, 1979, as amended at 84 FR 21577, May 14, 2019]