

- **Part Number:**

1926

- **Part Number Title:**

Safety and Health Regulations for Construction

- **Subpart:**

1926 Subpart E

- **Subpart Title:**

Personal Protective and Life Saving Equipment

- **Standard Number:**

1926.106

- **Title:**

Working over or near water.

- **GPO Source:**

e-CFR

1926.106(a)

Employees working over or near water, where the danger of drowning exists, shall be provided with U.S. Coast Guard-approved life jacket or buoyant work vests.

1926.106(b)

Prior to and after each use, the buoyant work vests or life preservers shall be inspected for defects which would alter their strength or buoyancy. Defective units shall not be used.

1926.106(c)

Ring buoys with at least 90 feet of line shall be provided and readily available for emergency rescue operations. Distance between ring buoys shall not exceed 200 feet.

1926.106(d)

At least one lifesaving skiff shall be immediately available at locations where employees are working over or adjacent to water.

-

Part Number:

1926

- **Part Number Title:**

Safety and Health Regulations for Construction

- **Subpart:**

1926 Subpart E

- **Subpart Title:**

Personal Protective and Life Saving Equipment

- **Standard Number:**

[1926.107](#)

- **Title:**

Definitions applicable to this subpart.

- **GPO Source:**

[e-CFR](#)

1926.107(a)

Contaminant means any material which by reason of its action upon, within, or to a person is likely to cause physical harm.

1926.107(b)

Lanyard means a rope, suitable for supporting one person. One end is fastened to a safety belt or harness and the other end is secured to a substantial object or a safety line.

1926.107(c)

Lifeline means a rope, suitable for supporting one person, to which a lanyard or safety belt (or harness) is attached.

1926.107(d)

O.D. means optical density and refers to the light refractive characteristics of a lens.

1926.107(e)

Radiant energy means energy that travels outward in all directions from its sources.

1926.107(f)

Safetybelt means a device, usually worn around the waist which, by reason of its attachment to a lanyard and lifeline or a structure, will prevent a worker from falling.

[44 FR 8577, Feb. 9, 1979]

Related: [59 FR 40729, Aug. 9, 1994; 60 FR 5131, Jan. 26, 1995; 60 FR 39254, Aug. 2, 1995]