

## ▼ Activity 2: Regular Expressions

Those who are not able to make it to the class are required to provide explanations for the code part provided in the tutorial by adding a text below the code cell.

**Note:** your explanation must include how the code works and libraries used and why they are used.

Students who are present in the class need to complete the activity and answer the question given at the end of tutorial.

## ▼ Regular Expressions

a language for specifying text search regular expression strings. This practical language is used in every computer language, word processor, and text processing tools like the Unix tools grep or Emacs. Formally, a regular expression is an algebraic notation for characterizing a set of strings. Regular expressions are particularly useful for searching in texts, when we have a pattern to search corpus for and a corpus of texts to search through. A regular expression search function will search through the corpus, returning all texts that match the pattern. The corpus can be a single document or a collection. For example, the Unix command-line tool grep takes a regular expression and returns every line of the input document that matches the expression.

Python includes a builtin module called `re` which provides regular expression matching operations (Click [here](#) for the official module documentation). Once the module is imported into your code, you can use all of the available capabilities for performing pattern-based matching or searching using regular expressions.

```
##code block-1
import re

def apply_regex(data, pattern):
    for text in data:
        if re.fullmatch(pattern, text):
            print(f"Test string {text} accepted.")
        else:
            print(f"Test string {text} failed!")
```

Let's write a simple regular expression for matching binary strings.

```
##code block-2
# find binary strings
test_strings = ["0", "1", "dog", "hello, world", "123", "00", "10101010111"]
binary_pattern = r'[0-1]+'
apply_regex(test_strings, binary_pattern)

Test string 0 accepted.
Test string 1 accepted.
Test string dog failed!
Test string hello, world failed!
Test string 123 failed!
Test string 00 accepted.
Test string 10101010111 accepted.
```

In the code block - 2 first a set of test strings are defined to test a simple regular expression. The binary pattern is defined with 'r' to denote it's a regular expression. The format [0-1]+ is for the list of expressions that can be accepted for this case it would be numbers between 0 and 1.

Now, how about for matching 24-bit hexadecimal codes?

```
##code block-3
test_strings = ["#F0F8FF", "#FFF", "#0FFFFFF", "#2980BD", "#FAEBD7"]
hexcode_pattern = r'\#[0-9A-F]{5,6}'
apply_regex(test_strings, hexcode_pattern)

Test string #F0F8FF accepted.
Test string #FFF failed!
Test string #0FFFFFF failed!
Test string #2980BD accepted.
Test string #FAEBD7 accepted.
```

The code block -3 implementation follows the same methodology, since the code is trying to match hexadecimal the test strings are defined as such. The pattern to match the required hexadecimal code would be starting with # and all numbers between 0 - 9 and the alphabets between A and F, the length of the expression would be between 5 and 6 characters

## ▼ Evaluating a test\_string against a given re\_pattern.

```
##code block-4
```

```

re_pattern = r'(\([0-9][0-9][0-9]\)\s)?[0-9][0-9][0-9]-[0-9][0-9][0-9][0-9]'
test_strings = ["00", "999-999-9999", "(111) 111-1111", "(111)111-1111", "989-1830", '
apply_regex(test_strings, re_pattern)

Test string 00 failed!
Test string 999-999-9999 failed!
Test string (111) 111-1111 accepted.
Test string (111)111-1111 failed!
Test string 989-1830 accepted.
Test string 241/131/103 failed!
Test string (182).1903.1021 failed!
Test string (101).101.1001 failed!

```

The code block - 4 would test the strings in test strings which meet the requirements of the re\_pattern, which would be for (xxx) xxx-xxx and xxx-xxxx. The function apply\_regex is called by passing the test strings and the required RE patterns.

## ▼ Question 1

*Modify the regular expression in the code block -4 to also accept strings that follow the format xxx.xxx.xxxx and +1 xxx-xxx-xxxx where x is a digit between 0 to 9?*

Note: Use different Code blocks for each teststring given in the task

```
##your code here
```

## ▼ Basic Regular Expression Patterns

The simplest kind of regular expression is a sequence of simple characters; putting characters in sequence is called concatenation. To search for woodchuck, we type /woodchuck/. The expression /Buttercup/ matches any string containing the substring Buttercup; grep with that expression would return the line I'm called little Buttercup.

Regular expressions are case sensitive; lower case /s/ is distinct from upper case /S/ (/s/ matches a lower case s but not an upper case S). This means that the pattern /woodchucks/ will not match the string Woodchucks. We can solve this problem with the use of the square braces [ and ]. The string of characters inside the braces specifies a disjunction of characters to match

Regex	Match	Example Patterns
/[wW]oodchuck/	Woodchuck or woodchuck	“ <u>W</u> oodchuck”
/[abc]/	‘a’, ‘b’, <i>or</i> ‘c’	“In uomini, in soldat <u>i</u> ”
/[1234567890]/	any digit	“plenty of <u>7</u> to 5”

**Figure 2.2** The use of the brackets [] to specify a disjunction of characters.

The regular expression /[1234567890]/ specifies any single digit. While such classes of characters as digits or letters are important building blocks in expressions, they can get awkward (e.g., it's inconvenient to specify /[ABCDEFGHIJKLMNOPQRSTUVWXYZ]/ to mean “any capital letter”). In cases where there is a well-defined sequence associated with a set of characters, the brackets can be used with the dash (-) to specify any one character in a range. The pattern /[2-5]/ specifies any one of the characters 2, 3, 4, or 5. The pattern /[b-g]/ specifies one of the characters b, c, d, e, f, or g.

Regex	Match	Example Patterns Matched
/[A-Z]/	an upper case letter	“we should call it ‘ <u>D</u> renched Blossoms’ ”
/[a-z]/	a lower case letter	“ <u>m</u> y beans were impatient to be hoed!”
/[0-9]/	a single digit	“Chapter <u>1</u> : Down the Rabbit Hole”

**Figure 2.3** The use of the brackets [] plus the dash - to specify a range.

The following code block shows a regular expression that matches only those strings that:

1. are at the start of a line and
2. the string does not start with a number or a whitespace

`re.findall()` finds all matches of the pattern in the text under consideration. The output is a list of strings that matched.

```
text = """Here is the First Paragraph and this is the First Sentence. here is the Seco
Now, it is the Second Paragraph and its First Sentence. here is the Second Sentence."""
```

```
re_pattern1 = r'[A-Z][a-z]+ [A-Z][a-z]+'
print(re.findall(re_pattern1, text))
```

```
[]
```

"Now, let's find occurrences by using regular expressions."

```
##code block-4
import re
text = "cats are cute and dogs are loyal"
pattern = r"\b[a-z]*|\bd[a-z]*\b"
re.findall(pattern, text)

['cats', 'cute', 'dogs']
```

"In the provided code block -4, the given regular expression pattern attempts to identify words that begin with the letters 'c' and 'd'.". \b before c[a-z]\* ensures we match full words starting with c \b after d[a-z]\* ensures we match full words starting with d

## ▼ Question 2.

Now try to match words ending in 'ing' or 'ly' by using the given statement

```
##your code here
text = "amazing view lovely painting writing"
```

## ▼ Using regular expressions based pattern matching on real world text

For the purposes of demonstration, here's a dummy paragraph of text. A few observations here:

- The text has multiple paragraphs with each paragraph having more than one sentence.
- Some of the words are capitalized (first letter is in uppercase followed by lowercase letters).

```
##code block-5
text = """Here is the First Paragraph and this is the First Sentence. here is the Second Sentence. Now, it is the Second Paragraph and its First Sentence. here is the Second Sentence. Finally, this is the Third Paragraph and is the First Sentence of this paragraph. here is the 4th paragraph is not going to be detected by either of the regex patterns below.
"""

print(text)
```

```
Here is the First Paragraph and this is the First Sentence. here is the Second Sentence. Now, it is the Second Paragraph and its First Sentence. here is the Second Sentence. Finally, this is the Third Paragraph and is the First Sentence of this paragraph. here is the 4th paragraph is not going to be detected by either of the regex patterns below.
```

```
re_pattern2 = r'[A-Z][a-z]+ [A-Z][a-z]+'
print(re.findall(re_pattern2, text))
```

```
['First Paragraph', 'First Sentence', 'Second Sentence', 'Third Sentence', 'Four'
```

The RE pattern is defined to match the sentences for the contiguous capitalization of the words.

Following is a text excerpt on "Inaugural Address" taken from the website of the [Joint Congressional Committee on Inaugural Ceremonies](#):

```
inau_text="""The custom of delivering an address on Inauguration Day started with the
Every President since Washington has delivered an Inaugural address. While many of the
William Henry Harrison delivered the longest Inaugural address, at 8,445 words, on Mar
In 1921, Warren G. Harding became the first President to take his oath and deliver his
Most Presidents use their Inaugural address to present their vision of America and to
Today, Presidents deliver their Inaugural address on the West Front of the Capitol, bu
```

### ▼ Question-3

Identify all the capitalized words in the "Inaugural Address" excerpt and write a regular expression that finds all occurrences of such words in the text. Then, run the Python code snippet to automatically display the matched strings according to the pattern.

NOTE: You can use the *re.findall()* method as demonstrated in the example before this exercise.

```
##your code here
```

Explain briefly the changes you have made in the given Tasks in Today's activity (approximately 200 words)

-->

Your answer here

