


Community Detection Algorithms



Community Evolution

Network and Community Evolution

- How does a **network** change over time?
- How does a **community** change over time?
- What properties do you expect to remain roughly constant?
- What properties do you expect to change?

How Networks Evolve?


Network Growth Patterns

1. Network Segmentation
2. Graph Densification
3. Diameter Shrinkage

1. Network Segmentation

- Often, in evolving networks, segmentation takes place, where the large network is decomposed over time into three parts

1. **Giant Component:** As network connections stabilize, a giant component of nodes is formed, with a large proportion of network nodes and edges falling into this component.
2. **Stars:** These are isolated parts of the network that form star structures. A star is a tree with one internal node and n leaves.
3. **Singletons:** These are orphan nodes disconnected from all nodes in the network.



2. Graph Densification


- The density of the graph increases as the network grows
 - The number of edges increases faster than the number of nodes does

$$E(t) \propto V(t)^\alpha$$


- Densification exponent: $1 \leq \alpha \leq 2$:
 - $\alpha = 1$: linear growth – constant out-degree
 - $\alpha = 2$: quadratic growth – clique

$E(t)$ and $V(t)$ are numbers of edges and nodes respectively at time t

Densification in Real Networks




Physics Citations




Patent Citations

3. Diameter Shrinking

- In networks diameter shrinks over time



ArXiv citation graph




Affiliation Network

How Communities Evolve?

Community Evolution

- Communities also expand, shrink, or dissolve in dynamic networks




Community Evaluation

Evaluating the Communities

We are given objects of two different kinds (+, ×)

- **The perfect community:** all objects inside the community are of the same type



- **Evaluation with ground truth**
- **Evaluation without ground truth**

Evaluation with Ground Truth

- When ground truth is available
 - We have partial knowledge of what communities should look like
 - We are given the correct community (clustering) assignments
- **Measures**
 - Precision and Recall, or F-Measure
 - Purity
 - Normalized Mutual Information (NMI)

Precision and Recall

$$\text{Precision} = \frac{\text{Relevant and retrieved}}{\text{Retrieved}}$$

$$P = \frac{TP}{TP + FP}$$

$$\text{Recall} = \frac{\text{Relevant and retrieved}}{\text{Relevant}}$$

$$R = \frac{TP}{TP + FN}$$

True Positive (TP) :

- When similar members are assigned to the same communities
- A **correct** decision.

True Negative (TN) :

- When dissimilar members are assigned to different communities
- A **correct** decision


False Negative (FN) :

- When similar members are assigned to different communities
- An **incorrect** decision


False Positive (FP) :

- When dissimilar members are assigned to the same communities
- An **incorrect** decision

Precision and Recall: Example



Cluster 1



Cluster 2

$$TP = \binom{5}{2} + \binom{6}{2} + \binom{2}{2} = 26,$$

$$FP = (5 \times 1) + (6 \times 2) = 17,$$

$$FN = (5 \times 2) + (6 \times 1) = 16,$$

$$TN = (6 \times 5) + (2 \times 1) = 32.$$

$$P = \frac{26}{26+17} = 0.60$$

$$R = \frac{26}{26+16} = 0.61$$

F-Measure

Either P or R measures one aspect of the performance,

- To integrate them into one measure, we can use the harmonic mean of precision of recall

$$F = 2 \cdot \frac{P \cdot R}{P + R}$$

For the example earlier,

$$F = 2 \times \frac{0.6 \times 0.61}{0.6 + 0.61} = 0.60$$

We can assume the majority of a community represents the community


- We use the label of the majority against the label of each member to evaluate the communities

Purity can be easily **tampered** by

- Points being singleton communities (of size 1); or by
- Very large communities

$$Purity = \frac{1}{N} \sum_{i=1} \max_j |C_i \cap L_j|$$

- k : the number of communities
- N : total number of nodes,
- L_j : the set of instances with label j in all communities
- C_i : the set of members in community i



$$purity \text{ is: } \frac{6+5}{14} = 0.78$$

Mutual Information

- **Mutual information (MI).** The amount of information that two random variables share.
 - By knowing one of the variables, it measures the amount of uncertainty reduced regarding the others

$$MI = I(H, L) = \sum_{h \in H} \sum_{l \in L} \frac{n_{h,l}}{n} \log \frac{n \cdot n_{h,l}}{n_h n_l}$$

- L and H are labels and found communities;
- n_h and n_l are the number of data points in community h and with label l , respectively;
- $n_{h,l}$ is the number of nodes in community h and with label l ; and n is the number of nodes

Normalizing Mutual Information (NMI)

- Mutual information (MI) is unbounded
- To address this issue, we can normalize MI

- How? We know that

$$\begin{aligned} MI &\leq \min(H(L), H(H)), \\ (MI)^2 &\leq H(H)H(L). \\ MI &\leq \sqrt{H(H)} \sqrt{H(L)}. \end{aligned}$$

- $H(\cdot)$ is the entropy function

$$\begin{aligned} H(L) &= - \sum_{l \in L} \frac{n_l}{n} \log \frac{n_l}{n} \\ H(H) &= - \sum_{h \in H} \frac{n_h}{n} \log \frac{n_h}{n}. \end{aligned}$$

Normalized Mutual Information

Normalized Mutual Information

$$NMI = \frac{MI}{\sqrt{H(L)} \sqrt{H(H)}}.$$

$$NMI = \frac{\sum_{h \in H} \sum_{l \in L} n_{h,l} \log \frac{n \cdot n_{h,l}}{n_h n_l}}{\sqrt{(\sum_{h \in H} n_h \log \frac{n_h}{n})(\sum_{l \in L} n_l \log \frac{n_l}{n})}}.$$

We can also define it as

Note that $MI < 1/2(H(H) + H(L))$


$$NMI = \frac{I(H;L)}{\frac{1}{2}(H(L) + H(H))}$$

Normalized Mutual Information

$$NMI = \frac{\sum_{h,l} n_{h,l} \log \frac{n \cdot n_{h,l}}{n_h n_l}}{\sqrt{(\sum_h n_h \log \frac{n_h}{n})(\sum_l n_l \log \frac{n_l}{n})}}$$

- where l and h are known (with labels) and found communities, respectively
 - n_h and n_l are the number of members in the community h and l , respectively,
 - $n_{h,l}$ is the number of members in community h and labeled l ,
 - n is the size of the dataset
-
- **NMI** values close to **one** indicate **high** similarity between communities found and labels
 - Values close to zero indicate high dissimilarity between them

Normalized Mutual Information: Example



Found communities (H)

– [1,1,1,1,1,1, 2,2,2,2,2,2,2]

Actual Labels (L)

– [2,1,1,1,1,1, 2,2,2,2,2,2,1,1]

$n = 14$

	\mathbf{n}_h
h=1	6
h=2	8

	\mathbf{n}_l
l=1	7
l=2	7

$\mathbf{n}_{h,l}$	l=1	l=2
h=1	5	1
h=2	2	6

[illegible][illegible]

79