OFFICIAL TECHNICAL SPECIFICATION DATASHEET
MANUFACTURER: CANADIAN SOLAR
MODEL / SERIES: TOPBiHiKu6 CS6W-575TB-AG
DOCUMENT TITLE: Canadian Solar TOPBiHiKu6 CS6W-TB-AG N-type Bifacial Module Datasheet
REVISION / DATE: V1.2_EN_2023 | Published: 2023-06-20

---

1. PRODUCT IDENTIFICATION & ARCHITECTURE

Cell Technology:	N-type TOPCon
Module Construction:	Bifacial (Glass-Glass)
Number of Cells / Format:	144 [2x(12x6)] N-type TOPCon Half-cut Cells
Glass / Front Encapsulant:	2.0 mm Semi-tempered glass (Front & Rear Dual Glass)
Frame Material:	Anodized Aluminium Alloy (Silver)
Junction Box / Protection:	IP68 with 3 bypass diodes

2. ELECTRICAL CHARACTERISTICS AT STC (1000 W/m2, 25C, AM 1.5)

Nominal Maximum Power (Pmax / Pnom):	575.0 Wp
Module Aperture Efficiency:	22.30 %
Open Circuit Voltage (Voc):	52.00 V
Short Circuit Current (Isc):	13.88 A
Maximum Power Voltage (Vmp):	42.90 V
Maximum Power Current (Imp):	13.41 A
Maximum System Voltage:	1500.0 V DC
Maximum Series Fuse Rating:	30.0 A

3. TEMPERATURE CHARACTERISTICS & OPERATING LIMITS

Temp. Coefficient of Pmax (gamma):	-0.290 %/C
Temp. Coefficient of Voc (beta):	-0.250 %/C
Temp. Coefficient of Isc (alpha):	+0.050 %/C
Nominal Cell Temperature (NOCT/NMOT):	41 +/- 3 C (NMOT)
Operating Temperature Range:	-40 C to +85 C

4. MECHANICAL DIMENSIONS & RATINGS

Length:	2278.0 mm
Width:	1134.0 mm
Thickness (Height):	30.0 mm
Gross Aperture Area:	2.5833 m2
Module Weight:	32.3 kg
Mechanical Design Load (Front):	5400 Pa (Snow load)
Mechanical Design Load (Rear):	2400 Pa (Wind load)

5. WARRANTY & LIFETIME PERFORMANCE

Product Workmanship Warranty:	12.0 Years
Linear Power Output Warranty:	30.0 Years
Annual Linear Degradation:	0.40 % / year
End of Warranty Retained Output:	87.4 %

6. PROVENANCE & ARCHIVAL METADATA

Authoritative URL:	https://www.csisolar.com/wp-content/uploads/Canadian_Solar_Datasheet_TOP
Document Verification:	OFFICIAL_FAMILY_DOCUMENT
Installation Mapping:	BENCHMARK_REFERENCE_MODULE
Verification Date:	2026-11-10

SolarSelect MLOps Hardware Database Reference Standard IEC 61215 / IEC 61730