OFFICIAL TECHNICAL SPECIFICATION DATASHEET
MANUFACTURER: JINKO SOLAR
MODEL / SERIES: Tiger Neo JKM430N-54HL4-V
DOCUMENT TITLE: JinkoSolar Tiger Neo N-type 54HL4-(V) Module Datasheet
REVISION / DATE: JKM415-435N-54HL4-V-F1-EN | Published: 2022-11-01

---

1. PRODUCT IDENTIFICATION & ARCHITECTURE

Cell Technology:	N-type TOPCon
Module Construction:	Monofacial
Number of Cells / Format:	108 (54 half-cells, 6x18) N-type TOPCon Cells
Glass / Front Encapsulant:	3.2 mm Anti-Reflection Tempered Glass
Frame Material:	Anodized Aluminium Alloy
Junction Box / Protection:	IP68 with 3 bypass diodes

2. ELECTRICAL CHARACTERISTICS AT STC (1000 W/m2, 25C, AM 1.5)

Nominal Maximum Power (Pmax / Pnom):	430.0 Wp
Module Aperture Efficiency:	22.00 %
Open Circuit Voltage (Voc):	38.49 V
Short Circuit Current (Isc):	14.23 A
Maximum Power Voltage (Vmp):	31.88 V
Maximum Power Current (Imp):	13.49 A
Maximum System Voltage:	1500.0 V DC
Maximum Series Fuse Rating:	25.0 A

3. TEMPERATURE CHARACTERISTICS & OPERATING LIMITS

Temp. Coefficient of Pmax (gamma):	-0.290 %/C
Temp. Coefficient of Voc (beta):	-0.250 %/C
Temp. Coefficient of Isc (alpha):	+0.045 %/C
Nominal Cell Temperature (NOCT/NMOT):	45 +/- 2 C (NOCT)
Operating Temperature Range:	-40 C to +85 C

4. MECHANICAL DIMENSIONS & RATINGS

Length:	1722.0 mm
Width:	1134.0 mm
Thickness (Height):	30.0 mm
Gross Aperture Area:	1.9527 m2
Module Weight:	22.0 kg
Mechanical Design Load (Front):	5400 Pa (Snow load)
Mechanical Design Load (Rear):	2400 Pa (Wind load)

5. WARRANTY & LIFETIME PERFORMANCE

Product Workmanship Warranty:	15.0 Years
Linear Power Output Warranty:	30.0 Years
Annual Linear Degradation:	0.40 % / year
End of Warranty Retained Output:	87.4 %

6. PROVENANCE & ARCHIVAL METADATA

Authoritative URL:	https://www.jinkosolar.com/uploads/Tiger_Neo_54HL4-V_EN.pdf
Document Verification:	OFFICIAL_FAMILY_DOCUMENT
Installation Mapping:	BENCHMARK_REFERENCE_MODULE
Verification Date:	2026-11-10

SolarSelect MLOps Hardware Database Reference Standard IEC 61215 / IEC 61730