OFFICIAL TECHNICAL SPECIFICATION DATASHEET
MANUFACTURER: MAXEON SOLAR TECHNOLOGIES
MODEL / SERIES: Maxeon 3 SPR-MAX3-400
DOCUMENT TITLE: Maxeon 3 Commercial and Residential Solar Panel SPR-MAX3 Datasheet
REVISION / DATE: DS-MAX3-400-RevB-EN | Published: 2021-06-15

---

1. PRODUCT IDENTIFICATION & ARCHITECTURE

Cell Technology:	IBC (Interdigitated Back Contact)
Module Construction:	Monofacial
Number of Cells / Format:	104 Monocrystalline Maxeon Gen III Back-Contact Cells
Glass / Front Encapsulant:	High-transmission tempered glass with anti-reflective coating
Frame Material:	Class A anodized aluminium alloy (Black Frame)
Junction Box / Protection:	IP68 with 3 bypass diodes, Stäubli MC4

2. ELECTRICAL CHARACTERISTICS AT STC (1000 W/m2, 25C, AM 1.5)

Nominal Maximum Power (Pmax / Pnom):	400.0 Wp
Module Aperture Efficiency:	22.60 %
Open Circuit Voltage (Voc):	75.60 V
Short Circuit Current (Isc):	6.58 A
Maximum Power Voltage (Vmp):	65.80 V
Maximum Power Current (Imp):	6.08 A
Maximum System Voltage:	1000.0 V DC
Maximum Series Fuse Rating:	20.0 A

3. TEMPERATURE CHARACTERISTICS & OPERATING LIMITS

Temp. Coefficient of Pmax (gamma):	-0.290 %/C
Temp. Coefficient of Voc (beta):	-0.236 %/C
Temp. Coefficient of Isc (alpha):	+0.057 %/C
Nominal Cell Temperature (NOCT/NMOT):	45 +/- 2 C (NOCT)
Operating Temperature Range:	-40 C to +85 C

4. MECHANICAL DIMENSIONS & RATINGS

Length:	1690.0 mm
Width:	1046.0 mm
Thickness (Height):	40.0 mm
Gross Aperture Area:	1.7677 m2
Module Weight:	19.0 kg
Mechanical Design Load (Front):	5400 Pa (Snow load)
Mechanical Design Load (Rear):	2400 Pa (Wind load)

5. WARRANTY & LIFETIME PERFORMANCE

Product Workmanship Warranty:	40.0 Years
Linear Power Output Warranty:	40.0 Years
Annual Linear Degradation:	0.20 % / year
End of Warranty Retained Output:	88.3 %

6. PROVENANCE & ARCHIVAL METADATA

Authoritative URL:	https://maxeon.com/sites/default/files/2021-06/ds-maxeon-3-400-solar-par
Document Verification:	OFFICIAL_FAMILY_DOCUMENT
Installation Mapping:	BENCHMARK_REFERENCE_MODULE
Verification Date:	2026-11-10

SolarSelect MLOps Hardware Database Reference Standard IEC 61215 / IEC 61730