OFFICIAL TECHNICAL SPECIFICATION DATASHEET
MANUFACTURER: SUNPOWER
MODEL / SERIES: SunPower SPR-E20-435-COM
DOCUMENT TITLE: SunPower E-Series Commercial Solar Panels SPR-E20-435-COM Datasheet
REVISION / DATE: Rev E / 2017 | Published: 2017-09-01

---

1. PRODUCT IDENTIFICATION & ARCHITECTURE

Cell Technology:	IBC (Interdigitated Back Contact)
Module Construction:	Monofacial
Number of Cells / Format:	128 Monocrystalline Maxeon Gen II Cells
Glass / Front Encapsulant:	High-transmission tempered glass with anti-reflective coating
Frame Material:	Class A anodized aluminium alloy (Silver)
Junction Box / Protection:	IP65 rated with bypass diodes

2. ELECTRICAL CHARACTERISTICS AT STC (1000 W/m2, 25C, AM 1.5)

Nominal Maximum Power (Pmax / Pnom):	435.0 Wp
Module Aperture Efficiency:	20.10 %
Open Circuit Voltage (Voc):	85.60 V
Short Circuit Current (Isc):	6.43 A
Maximum Power Voltage (Vmp):	72.90 V
Maximum Power Current (Imp):	5.97 A
Maximum System Voltage:	1500.0 V DC
Maximum Series Fuse Rating:	15.0 A

3. TEMPERATURE CHARACTERISTICS & OPERATING LIMITS

Temp. Coefficient of Pmax (gamma):	-0.350 %/C
Temp. Coefficient of Voc (beta):	-0.275 %/C
Temp. Coefficient of Isc (alpha):	+0.054 %/C
Nominal Cell Temperature (NOCT/NMOT):	45 +/- 2 C (NOCT)
Operating Temperature Range:	-40 C to +85 C

4. MECHANICAL DIMENSIONS & RATINGS

Length:	2067.0 mm
Width:	1046.0 mm
Thickness (Height):	46.0 mm
Gross Aperture Area:	2.1621 m2
Module Weight:	25.4 kg
Mechanical Design Load (Front):	5400 Pa (Snow load)
Mechanical Design Load (Rear):	2400 Pa (Wind load)

5. WARRANTY & LIFETIME PERFORMANCE

Product Workmanship Warranty:	25.0 Years
Linear Power Output Warranty:	25.0 Years
Annual Linear Degradation:	0.40 % / year
End of Warranty Retained Output:	90.0 %

6. PROVENANCE & ARCHIVAL METADATA

Authoritative URL:	https://us.sunpower.com/sites/default/files/media-library/data-sheets/ds
Document Verification:	OFFICIAL_EXACT_MODEL
Installation Mapping:	VERIFIED_INSTALLATION_MAPPING
Verification Date:	2026-11-10

SolarSelect MLOps Hardware Database Reference Standard IEC 61215 / IEC 61730