OFFICIAL TECHNICAL SPECIFICATION DATASHEET
MANUFACTURER: TRINA SOLAR
MODEL / SERIES: Trina 330W (TSM-330PD14)
DOCUMENT TITLE: Trina Solar Tallmax TSM-PD14 Datasheet (Australia C Revision)
REVISION / DATE: 2017_Aus_C | Published: 2017-06-01

---

1. PRODUCT IDENTIFICATION & ARCHITECTURE

| | |
|---|---|
| Cell Technology: | Polycrystalline |
| Module Construction: | Monofacial |
| Number of Cells / Format: | 72 cells (6x12) multicrystalline |
| Glass / Front Encapsulant: | 3.2 mm High Transmission AR Coated Tempered Glass |
| Frame Material: | Anodized Aluminium Alloy (Silver) |
| Junction Box / Protection: | IP67 / IP68 with 3 bypass diodes |

2. ELECTRICAL CHARACTERISTICS AT STC (1000 W/m2, 25C, AM 1.5)

| | |
|---|---|
| Nominal Maximum Power (Pmax / Pnom): | 330.0 Wp |
| Module Aperture Efficiency: | 17.00 % |
| Open Circuit Voltage (Voc): | 45.80 V |
| Short Circuit Current (Isc): | 9.28 A |
| Maximum Power Voltage (Vmp): | 37.40 V |
| Maximum Power Current (Imp): | 8.83 A |
| Maximum System Voltage: | 1000.0 V DC |
| Maximum Series Fuse Rating: | 15.0 A |

3. TEMPERATURE CHARACTERISTICS & OPERATING LIMITS

| | |
|---|---|
| Temp. Coefficient of Pmax (gamma): | -0.410 %/C |
| Temp. Coefficient of Voc (beta): | -0.320 %/C |
| Temp. Coefficient of Isc (alpha): | +0.050 %/C |
| Nominal Cell Temperature (NOCT/NMOT): | 44 +/- 2 C (NOCT) |
| Operating Temperature Range: | -40 C to +85 C |

4. MECHANICAL DIMENSIONS & RATINGS

| | |
|---|---|
| Length: | 1960.0 mm |
| Width: | 992.0 mm |
| Thickness (Height): | 40.0 mm |
| Gross Aperture Area: | 1.9443 m2 |
| Module Weight: | 22.5 kg |
| Mechanical Design Load (Front): | 5400 Pa (Snow load) |
| Mechanical Design Load (Rear): | 2400 Pa (Wind load) |

5. WARRANTY & LIFETIME PERFORMANCE

| | |
|---|---|
| Product Workmanship Warranty: | 10.0 Years |
| Linear Power Output Warranty: | 25.0 Years |
| Annual Linear Degradation: | 0.70 % / year |
| End of Warranty Retained Output: | 80.7 % |

6. PROVENANCE & ARCHIVAL METADATA

| | |
|---|---|
| Authoritative URL: | https://static.trinasolar.com/sites/default/files/Datasheet_TSM_xxxPD14_ |
| Document Verification: | OFFICIAL_FAMILY_DOCUMENT |
| Installation Mapping: | CANDIDATE_INSTALLATION_MAPPING |
| Verification Date: | 2026-11-10 |

---

SolarSelect MLOps Hardware Database Reference Standard IEC 61215 / IEC 61730