
Cheat Sheet

Sets

Unordered collection of items.

Every set element is

- Unique (no duplicates)
- Must be immutable



Creating a Set

- Created by enclosing elements within {curly} brackets.
- Each item is separated by a comma.

Code

PYTHON

```
1  a = 2
2  set_a = {5, "Six", a, 8.2}
3  print(type(set_a))
4  print(set_a)
```

Need not be in the same order as defined.

No Duplicate Items

Sets contain unique elements

Code

PYTHON

```
1 set_a = {"a", "b", "c", "a"}
2 print(set_a)
```

Output

Immutable Items

Set items must be immutable.

As List is mutable, Set cannot have list as an item.

Code

PYTHON

```
1 set_a = {"a", ["c", "a"]}
2 print(set_a)
```

```
TypeError: unhashable type: 'list'
```

Creating Empty Set

We use

set() to create an empty set.

Code

PYTHON

```
1  set_a = set()
2  print(type(set_a))
3  print(set_a)
```

Output

```
<class 'set'>
set()
```

Converting to Set

set(sequence) takes any sequence as argument and converts to set, avoiding duplicates

List to Set

Code

PYTHON

```
1  set_a = set([1,2,1])
2  print(type(set_a))
3  print(set_a)
```

```
<class 'set'>
```

{1, 2}

String to Set

Code

PYTHON

```
1 set_a = set("apple")
2 print(set_a)
```

Output

Tuple to Set

Code

PYTHON

```
1  set_a = set((1, 2, 1))
2  print(set_a)
```

Output

Accessing Items

As sets are unordered, we cannot access or change an item of a set using

- Indexing
- Slicing

Code

PYTHON

```
1  set_a = {1, 2, 3}
2  print(set_a[1])
3  print(set_a[1:3])
```

Output

```
TypeError: 'set' object is not subscriptable
```

Adding Items

set.add(value) adds the item to the set, if the item is not present already.

Code

PYTHON

```
1  set_a = {1, 3, 6, 2, 9}
2  set_a.add(7)
3  print(set a)
```

Output

Adding Multiple Items

set.update(sequence) adds multiple items to the set, and duplicates are avoided.

Code

PYTHON

```
1 set_a = \{1, 3, 9\}
```

```
2 set_a.update([2, 3])
3 print(set_a)
```

Output

Removing Specific Item

set.discard(value) takes a single value and removes if present.

Code

PYTHON

```
1  set_a = {1, 3, 9}
2  set_a.discard(3)
3  print(set_a)
```

Output

set_a.remove(value) takes a value and remove if it present or raise an error.

Code

PYTHON

```
1  set_a = {1, 3, 9}
2  set_a.remove(5)
3  print(set_a)
```

KeyError: 5

Operations on Sets

You can perform the following operations on Sets

- clear()
- len()
- Iterating
- Membership Check

Submit Feedback