### www.PragimTech.com

Pragim@PragimTech.com

# **Part 34 – Temporary Tables**

Venkat
PRAGIM Technologies
<a href="mailto:kudvenkat@gmail.com">kudvenkat@gmail.com</a>
<a href="http://csharp-video-tutorials.blogspot.com">http://csharp-video-tutorials.blogspot.com</a>

PRAGIM Technologies | www.pragimtech.com | 9900113931





# In this session we will learn

- What are temporary tables
- Types of temporary tables Local and Global
- Difference between local and global temp tables

PRAGIM Technologies | www.pragimtech.com | 9900113931

http://csharp-video-tutorials.blogspot.com

2

## **Temporary Tables**

#### What are Temporary tables?

Temporary tables, are very similar to the permanent tables. Permanent tables get created in the database you specify, and remain in the database permanently, until you delete (drop) them. On the other hand, temporary tables get created in the TempDB and are automatically deleted, when they are no longer used.

#### **Different Types of Temporary tables**

- 1. Local Temporary Tables
- 2. Global Temporary tables.

```
--Create Local Temporary Table
Create Table #PersonDetails(Id int, Name nvarchar(20))

--Insert Data into the temporary table
Insert into #PersonDetails Values(1, 'Mike')
Insert into #PersonDetails Values(2, 'John')
Insert into #PersonDetails Values(3, 'Todd')

--Select data from the temporary table:
Select * from #PersonDetails
```

PRAGIM Technologies | www.pragimtech.com | 9900113931

### **Local Temporary Tables**

Check if the local temporary table is created:

Temporary tables are created in the TEMPDB. Query the sysobjects system table in TEMPDB. The name of the table, is suffixed with lot of underscores and a random number. For this reason you have to use the LIKE operator in the query.

```
Select name from tempdb..sysobjects where name like '#PersonDetails%'
```

A local temporary table is available, only for the connection that has created the table

A local temporary table is automatically dropped, when the connection that has created the it, is closed.

If the user wants to explicitly drop the temporary table, he can do so using DROP TABLE#PersonDetails

```
You can also check the existence of
temporary tables using object
explorer.

☐ (local) (SQL Server 10.0.1600 - sa)

       Databases
         System Databases
           ⊕ 🧻 msdb

☐ itempdb

             Tables
             Temporary Tables
                  dbo.#15702A09
                  dbo.#16644E42
                  dbo.#1758727B
                  dbo.#184C96B4
                  dbo.#395884C4
                  dbo.#3E723F9C
                  dbo.#4F47C5E3
                  dbo.#503BEA1C
                  dbo.#61BB7BD9
                  dbo.#62AFA012
                  dbo.#63A3C44B
                  dbo.#6774552F
                  dbo.#68687968
                  dbo.#695C9DA1
                  dbo.#70099B30
                 dbo.#PersonDetails
```



PRAGIM Technologies | www.pragimtech.com | 9900113931

## **Local Temporary Tables**

If the temporary table, is created inside the stored procedure, it get's dropped automatically upon the completion of stored procedure execution.

```
Create Procedure spCreateLocalTempTable
as
Begin
Create Table #PersonDetails(Id int, Name nvarchar(20))

Insert into #PersonDetails Values(1, 'Mike')
Insert into #PersonDetails Values(2, 'John')
Insert into #PersonDetails Values(3, 'Todd')

Select * from #PersonDetails
End
```

It is also possible for different connections, to create a local temporary table with the same name. For example User1 and User2, both can create a local temporary table with the same name #PersonDetails.

PRAGIM Technologies | www.pragimtech.com | 9900113931

## **Global Temporary Tables**

To create a Global Temporary Table, prefix the name of the table with 2 pound (##) symbols.

Create Table ##EmployeeDetails(Id int, Name nvarchar(20))

Global temporary tables are visible to all the connections of the sql server, and are only destroyed when the last connection referencing the table is closed.

Multiple users, across multiple connections can have local temporary tables with the same name, but, a global temporary table name has to be unique, and if you inspect the name of the global temp table, in the object explorer, there will be no random numbers suffixed at the end of the table name.

PRAGIM Technologies | www.pragimtech.com | 9900113931



### **Difference**

#### Difference Between Local and Global Temporary Tables:

- 1. Local Temp tables are prefixed with single pound (#) symbol, where as gloabl temp tables are prefixed with 2 pound (##) symbols.
- 2. SQL Server appends some random numbers at the end of the local temp table name, where this is not done for global temp table names.
- 3. Local temporary tables are only visible to that session of the SQL Server which has created it, where as Global temporary tables are visible to all the SQL server sessions
- **4. Local temporary tables are automatically dropped**, when the session that created the temporary tables is closed, where as Global temporary tables are destroyed when the last connection that is referencing the global temp table is closed.

PRAGIM Technologies | www.pragimtech.com | 9900113931

## **Additional Resources**

- PRAGIM Home Page:
  - http://www.PragimTech.com
- Resources:
  - ASP.NET Interview Questions
  - http://www.VenkatASPInterview.Blogspot.com
  - C# Interview Questions
  - http://www.VenkatCSharpInterview.Blogspot.com

PRAGIM Technologies | www.pragimtech.com | 9900113931

